

2005 Specifications

All brands: Trek, Fisher, Klein, LeMond

Fisher

Cake 1 DLX	1
Cake 1	2
Cake 2 DLX	3
Cake 2	4
Cake 3 DLX	5
Cake 3 DLX GS	6
Cake 3	7
Cake 3 GS	8
Cake 4 DLX	9
Cake 4	10
Bitter	11
Ged	12
Mullet	13
Opie	14
Sugar 292	15
Sugar 293	16
Sugar 4+	17
Paragon	18
Wahoo	19
Tassajara Disc	20
Tassajara	21
Tarpon	22
Marlin E	23
Marlin Disc E	24
Marlin	25
Mako	26
Hoo Koo E Koo	27
Cronus	28
Advance	29
Zebrano S	30
Zebrano	31
Tiburón S E	32
Tiburón S	33
Tiburón E	34
Nirvana S	35
Nirvana	36
X-Caliber	37
Napa	38
Capitola	39
Ziggurat	40
Big Sur Disc	41
Big Sur	42
Tassajara GS	43
Big Sur GS	44
Utopia	45
Montare	46
Dual Sport	47
Tyro	48
Cosmo	49
Gamma Ray	50
Astro	51
Sun Spot	52
Starfish	53
Freelader 241	54
Freelader 206	55
Freelader 201	56

Klein

Palomino XV	57
Attitude XX	58
Attitude XV	59
Attitude V Disc	60
Reve XX	61
Reve X	62
Reve V	63
Q-Pro XX	64
Q-Pro XV	65
Q-Pro V	66

LeMond

Tete de Course	67
Victoire	68
Victoire T	69
Maillot Jaune	70
Zurich	71
Zurich T	72
Buenos Aires	73
Buenos Aires T	74
Versailles	75
Versailles T	76

Versailles T, women's	77
Chambery	78
Chambery T	79
Alpe d'Huez	80
Alpe d'Huez T	81
Croix de Fer	82
Croix de Fer T	83
Croix de Fer T, wm's	84
Tourmalet	85
Tourmalet T	86
Big Sky SLT	87
Poprad	88
Fillmore	89

Trek

Elite 9.8	90
8500	91
8000	92
8000 Disc	93
6700	94
6700 Disc	95
6700E	96
6700 WSD	97
6700 WSD Disc	98
6500	99
4500	100
4500E	101
4500 Disc	102
4500 WSD	103
4500E WSD	104
4400	105
4300	106
4300 Disc	107
3900	108
3700	109
3500	110
820	111
Navigator 300E	112
Navigator 300	113
Navigator 200E	114
Navigator 200	115
Navigator 100	116
Bruiser 1	117
Bruiser 2	118
Fuel 110	119
Fuel 98	120
Fuel 98 Disc	121
Fuel 80	122
Fuel 70	123
Fuel EX 9	124
Fuel EX 9 WSD	125
Fuel EX 8	126
Fuel EX 7	127
Fuel EX 7 WSD	128
Liquid 65	129
Liquid 55	130
Liquid 25	131
Y 26	132
Session 77	133
Session 7	134
7700	135
7700FX	136
7500 FX	137
7500 FX Disc	138
7300 FXS	139
7300 FX Disc	140
7300	141
7300 FX	142
7200	143
7200 FX	144
7200 FXS	145
7100	146
7000	147
7100 FX	148
7100 E	149
7000 FXS	150
7000 FX	151
C350 Low-step	152
Rail 3	153
Rail 1	154
Town & Country	155
Calypso	156

Bonnie/Clyde	157
Cruiser Classic	158
Cruiser Classic Steel	159
Madone SSL	160
Madone 5.9 LTD	161
Madone 5.9	162
Madone SL 5.9 Com	163
Madone 5.9 Com	164
Madone SL 5.2 T	165
Madone SL 5.2 T	166
Madone SL 5.2	167
Madone 5.2 SL WSD T	168
Madone 5.2 T	169
Madone 5.2	170
5.9 SSL	171
5.9 Superlight	172
5200 T WSD	173
5000	174
5000 T	175
2300	176
2300T	177
2300 WSD T	178
2000	179
2000T	180
2100	181
2100T	182
2100 WSD T	183
1500	184
1500T	185
1500 WSD T	186
1400	187
1400T	188
1200 D	189
1200 T	190
1000 D	191
1000T	192
1000 WSD T	193
1000 KDR	194
Pilot 5.9	195
Pilot WSD 5.9	196
Pilot 5.2	197
Pilot WSD 5.2	198
Pilot 5.0	199
Pilot WSD 5.0	200
Pilot 2.1	201
Pilot WSD 2.1	202
2300C	203
2100C	204
2100 C WSD	205
1200C	206
Team Time Trial	207
Equinox 11	208
Equinox 9	209
Equinox 7	210
T2000	211
T1000	212
XO-1	213
520	214
Mt. Track 220	215
Mt. Track 200	216
Mt. Track 60	217
Jet 20	218
Mystic 20	219
Jet 16	220
Mystic 16	221
Jet 12	222
Mystic 12	223
Grommet 12	224
Surfer Girl 12	225
TR30	226
TR20	227
TR10	228
TR 5	229
Vert 2	230
Vert 1	231
Mt. Train 241	232
Mt. Train 206	233
Mt. Train 201	234
Trikester	235

Fisher Cake 1 DLX

2147600*25.124
Bike weight: 27.3 lb/12.39 kg

FRAMESET

Main tubes	Platinum series butted ZR9000	
Stays	Platinum series butted ZR9000	
Color	Matte Black/ Matte Blue • Multicolor decal • Matte Black fork	
Fork	Maverick SC 32, 85-125mm adjustable travel 470.9mm axle-crown length	100mm travel,
Rear shock	Manitou Swinger 3-Way, 40mm stroke, 7.5in length, 1.64in, 7/8in width, 8mm eyes	
Headset	Cane Creek S-6 Aheadset, alloy	25.4/34.0/30.0, 27.1mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Race Lite	31.8mm clamp diameter
Stem	Bontrager Race X Lite	40.0mm steerer clamp height
Shift levers	Shimano Deore XT	
Brake levers	Hydraulic, attached to brake	
Grips	Bontrager Earl	

DRIVETRAIN

Front derailleur . . .	Shimano Deore XT	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur	Shimano Deore XT SGS	
Crankset	Shimano Deore XT 44/32/22	64/104mm bolt hole circle
Bottom bracket	integral axle	73 (shell x axle,mm), Integral axle
Chain	Shimano HG-93	9 speed, 108 links
Cassette	Shimano Deore XT 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Race Lite Disc, tubeless compatible, 28°	537mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 266/267mm, 3x	
Tire	Bontrager ACX, folding, 26 x 2.2, Velox 22mm rim strip	
Rear wheel	Bontrager Race Lite Disc, tubeless compatible, 28°	537mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 266/267mm, 3x	
Tire	Bontrager ACX, folding, 26 x 2.2, Tubeless assymetric rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Race X Lite	31.6mm outer diameter
Saddle	Bontrager FS2000, CrMo rails, leather cover	
Seatpost binder	Alloy w/integral quick-release	36.4mm inner diameter
Brakes	Shimano Deore XT, hydraulic discs 8 in. DH front disc, 160mm rear disc, 44mm BCD	
Disc hose, mm	15.5 17.5 19 21	
Front	690 750 750 750	
Rear	1350 1350 1400 1400	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	15.5	17.5	19	21
Rider height, in.		66.1	69.6	72.7	74.6
	cm	168	177	185	190
Handlebar	width	630	630	630	630
Handlebar	rise	25	25	25	25
Stem	length	75	90	105	105
	angle	7	7	7	7
Headset spacers		30	30	30	30
Crank	length	170	175	175	175
Seatpost	length	330	400	400	400
Steerer	length	183.1	198.1	218.1	238.1

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.5	70.5	70.5
Fork offset	38.0	38.0	38.0	38.0
Trail	79	75	75	75
Seat tube angle	72.5	72.5	72.5	72.5
Effective top tube	582	607	628	648
Seat tube	406	445	483	533
Standover	743	744	767	806
Wheelbase	1070	1091	1112	1133
Bottom bracket height	320	320	320	321
Chainstay	417	417	417	417
Head tube	90	105	125	145

GEARING

	22 32 44
11	52 76 105
13	44 65 89
15	38 56 77
17	34 49 68
20	29 42 58
23	25 36 50
26	22 32 44
30	19 28 38
34	17 25 34

Fisher

Cake 1

2146600*25.124
Bike weight: 26.4 lb/11.99 kg

FRAMESET

Main tubes	Platinum series butted ZR9000
Stays	Platinum series butted ZR9000
Color	Metallic Green/ Metallic Silver • Multicolor decal • Metallic Silver fork
Fork	Fox FRL Air 100mm travel, 470.9mm axle-crown length
Rear shock	Manitou Swinger 3-Way, 40mm stroke, 7in length, 1.64in, 7/8in width, 8mm eyes
Headset	Cane Creek S-6 Aheadset, alloy 25.4/34.0/30.0, 27.1mm stack height

CONTROLS

Handlebar	Bontrager Race X Lite 31.8mm clamp diameter
Stem	Bontrager Race X Lite 40.0mm steerer clamp height
Shift levers	Shimano Deore XT
Brake levers	Hydraulic, attached to brake
Grips	Bontrager Race, dual density

DRIVETRAIN

Front derailleur	Shimano Deore XT	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur	Shimano XTR Low-Normal	
Crankset	Shimano Deore XT 44/32/22	64/104mm bolt hole circle
Bottom bracket	integral axle	73 (shell x axle,mm), Integral axle
Chain	Shimano HG-93	9 speed, 108 links
Cassette	Shimano Deore XT 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Race Lite Disc, tubeless compatible, 28°	537mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 266/267mm, 3x	
Tire	Bontrager ACX, folding, 26 x 2.2, Velox 22mm rim strip	
Rear wheel	Bontrager Race Lite Disc, tubeless compatible, 28°	537mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 266/267mm, 3x	
Tire	Bontrager ACX, folding, 26 x 2.2, Tubeless assymetric rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Race X Lite	31.6mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder	Alloy w/integral quick-release	36.4mm inner diameter
Brakes	Shimano Deore XT, hydraulic discs	
	160mm discs, 44mm BCD	
Disc hose, mm	15.5 17.5 19 21	
Front	690 750 750 750	
Rear	1350 1350 1400 1400	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional		

FIT dimensions in mm, unless specified

Frame	Size	15.5	17.5	19	21
Rider height, in.		66.8	70.1	73.7	75.6
	cm	170	178	187	192
Handlebar	width	650	650	650	650
Handlebar	rise	40	40	40	40
Stem	length	75	90	105	105
	angle	7	7	7	7
Headset spacers		30	30	30	30
Crank	length	170	175	175	175
Seatpost	length	330	400	400	400
Steerer	length	183.1	198.1	218.1	238.1

GEOMETRY dimensions in mm, unless specified

Head tube angle	70.0	70.5	70.5	70.5
Fork offset	38.0	38.0	38.0	38.0
Trail	79	75	75	75
Seat tube angle	72.5	72.5	72.5	72.5
Effective top tube	582	607	628	648
Seat tube	406	445	483	533
Standover	743	744	767	806
Wheelbase	1070	1091	1112	1133
Bottom bracket height	320	320	320	321
Chainstay	417	417	417	417
Head tube	90	105	125	145

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Fisher Cake 2 DLX

2145600*25.124
Bike weight: 29.2 lb/13.26 kg

FRAMESET

Main tubes	Platinum series butted ZR9000
Stays	Platinum series butted ZR9000
Color	Matte Warm Silver/Matte Silver • Multicolor decal • Matte Silver fork
Fork	Fox Float R Air 130mm travel, 470mm axle-crown length
Rear shock	Manitou Swinger 3-Way, 40mm stroke, 7.5in length, 1.64in, 7/8in width, 8mm eyes
Headset	Alloy aheadset, semi-cartridge 25.4/34.0/30.0, 27.2mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Race	40.0mm steerer clamp height
Shift levers	Shimano Deore LX	
Brake levers	Hydraulic, attached to brake	
Grips	Bontrager Earl	

DRIVETRAIN

Front derailleur	Shimano Deore LX	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur	Shimano Deore XT SGS	
Crankset	Bontrager Race 44/32/22	64/104mm bolt hole circle
Bottom bracket	TruVativ Giga-Pipe SL	73 x 116 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	SRAM PG970 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Race Disc, tubeless compatible, 28°	537mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 264/266mm, 3x	
Tire	Bontrager ACX, folding, 26 x 2.2, Tubeless assymetric rim strip	
Rear wheel	Bontrager Race Disc, tubeless compatible, 28°	542mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 264/265mm, 3x	
Tire	Bontrager ACX, folding, 26 x 2.2, Tubeless assymetric rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Select	31.6mm outer diameter
Saddle	Bontrager Select	
Seatpost binder	Alloy w/integral quick-release	36.4mm inner diameter
Brakes	Hayes HFX-9, hydraulic discs	
	6.3 in. discs, 44mm BCD	
Disc hose, mm	15.5 17.5 19 21	
Front	690 750 750 750	
Rear	1280 1350 1400 1400	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	15.5	17.5	19	21
Rider height, in.		65.9	69.3	72.5	74.4
	cm	167	176	184	189
Handlebar	width	630	630	630	630
Handlebar	rise	25	25	25	25
Stem	length	75	90	105	105
	angle	7	7	7	7
Headset spacers		30	30	30	30
Crank	length	170	175	175	175
Seatpost	length	330	400	400	400
Steerer	length	183.2	198.2	218.2	238.2

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.5	70.5	70.5
Fork offset	38.0	38.0	38.0	38.0
Trail	79	75	75	75
Seat tube angle	72.5	72.5	72.5	72.5
Effective top tube	582	607	628	648
Seat tube	406	445	483	533
Standover	743	744	767	806
Wheelbase	1070	1091	1112	1133
Bottom bracket height	320	320	320	321
Chainstay	417	417	417	417
Head tube	90	105	125	145

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Fisher

Cake 2

2144600*25.124
Bike weight: 27.8 lb/12.62 kg

FRAMESET

Main tubes	Platinum series butted ZR9000	
Stays	Platinum series butted ZR9000	
Color	Matte Black/Matte Khaki • Multicolor decal • Matte Black fork	
Fork	Manitou Black Super Air	100mm travel, 470mm axle-crown length
Rear shock	Manitou Swinger 3-Way, 40mm stroke, 7in length, 1.64in, 7/8in width, 8mm eyes	
Headset	Alloy aheadset, semi-cartridge	25.4/34.0/30.0, 27.2mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	Shimano Deore XT	
Brake levers	Hydraulic, attached to brake	
Grips	Bontrager Race, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Deore LX	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore XT SGS	
Crankset	Bontrager Race 44/32/22	64/104mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe SL	73 x 113 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Superstock, disc compatible, 28°	542mm ERD
Spokes	DT 14g, ProLock brass nipples, 267/267mm, 3x	
Tire	Bontrager ACX, folding, 26 x 2.2, Velox 22mm rim strip	
Rear wheel	Bontrager Superstock, disc compatible, 28°	542mm ERD
Spokes	DT 14g, ProLock brass nipples, 267/267mm, 3x	
Tire	Bontrager ACX, folding, 26 x 2.2, Velox 22mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Select	31.6mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .	Alloy w/integral quick-release	36.4mm inner diameter
Brakes	Hayes HFX-9, hydraulic discs	
	6.3 in. discs, 44mm BCD	
Disc hose, mm	15.5 17.5 19 21	
Front	690 750 750 750	
Rear	1350 1350 1400 1400	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	15.5	17.5	19	21
Rider height, in.		66.1	69.5	72.7	74.6
	cm	168	177	185	189
Handlebar	width	630	630	630	630
Handlebar	rise	25	25	25	25
Stem	length	75	90	105	105
	angle	7	7	7	7
Headset spacers		30	30	30	30
Crank	length	170	175	175	175
Seatpost	length	330	400	400	400
Steerer	length	184.2	199.2	219.2	239.2

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.5	70.5	70.5
Fork offset	38.0	38.0	38.0	38.0
Trail	79	75	75	75
Seat tube angle	72.5	72.5	72.5	72.5
Effective top tube	582	607	628	648
Seat tube	406	445	483	533
Standover	743	744	767	806
Wheelbase	1070	1091	1112	1133
Bottom bracket height	320	320	320	321
Chainstay	417	417	417	417
Head tube	90	105	125	145

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Fisher Cake 3 DLX

2142600*25.124
Bike weight: 30.6 lb/13.89 kg

FRAMESET

Main tubes	Platinum series butted ZR9000	
Stays	Platinum series butted ZR9000	
Color	Metallic Silver/Metallic Black • Multicolor decal • Matte Silver fork	
Fork	Manitou Black Elite	120mm travel, 490mm axle-crown length
Rear shock	Manitou Swinger 3-Way, 40mm stroke, 7.5in length, 1.64in, 7/8in width, 8mm eyes	
Headset	Alloy aheadset, semi-cartridge	25.4/34.0/30.0, 27.2mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	Shimano Deore LX	
Brake levers	Hydraulic, attached to brake	
Grips	Bontrager Race, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Deore LX	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore LX SGS	
Crankset	Bontrager Select 44/32/22	64/104mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe SL	73 x 116 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Select, disc compatible, 28°	541mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 268/268mm, 3x	
Tire	Bontrager ACX, folding, 26 x 2.2, Velox 22mm rim strip	
Rear wheel	Bontrager Select, disc compatible, 28°	541mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 268/267mm, 3x	
Tire	Bontrager ACX, folding, 26 x 2.2, Velox 22mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	31.6mm outer diameter
Saddle	Bontrager Select	
Seatpost binder . . .	Alloy w/integral quick-release	36.4mm inner diameter
Brakes	Hayes HFX-9, hydraulic discs	
	6.3 in. discs, 44mm BCD	
Disc hose, mm	15.5 17.5 19 21	
Front	750 750 750 750	
Rear	1280 1350 1400 1400	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	15.5	17.5	19	21
Rider height, in.		66.9	70.3	73.8	75.7
	cm	170	178	188	192
Handlebar	width	630	630	630	630
Handlebar	rise	25	25	25	25
Stem	length	75	90	105	105
	angle	7	7	7	7
Headset spacers		30	30	30	30
Crank	length	170	175	175	175
Seatpost	length	300	350	350	350
Steerer	length	184.2	199.2	219.2	239.2

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.5	70.5	70.5
Fork offset	38.0	38.0	38.0	38.0
Trail	79	75	75	75
Seat tube angle	72.5	72.5	72.5	72.5
Effective top tube	582	607	628	648
Seat tube	406	445	483	533
Standover	743	744	767	806
Wheelbase	1070	1091	1112	1133
Bottom bracket height	320	320	320	321
Chainstay	417	417	417	417
Head tube	90	105	125	145

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Fisher

Cake 3 DLX GS

2142603*25.124
Bike weight: 30.1 lb/13.67 kg

FRAMESET

Main tubes	Platinum series butted ZR9000	
Stays	Platinum series butted ZR9000	
Color	Metallic Black/Metallic Green • Multicolor decal • Matte Black fork	
Fork	Manitou Black Elite Diva	120mm travel, 490mm axle-crown length
Rear shock	Manitou Swinger 3-Way, stroke, 7.5in length, 1.64in, 7/8in width, 8mm eyes	
Headset	Alloy aheadset, semi-cartridge	25.4/34.0/30.0, 27.2mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	Shimano Deore LX	
Brake levers	Hydraulic, attached to brake	
Grips	Bontrager Race, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Deore LX	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore LX SGS	
Crankset	Bontrager Select 44/32/22	64/104mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe SL	73 x 116 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Select, disc compatible, 28°	541mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 268/268mm, 3x	
Tire	Bontrager ACX, folding, 26 x 2.2, Velox 22mm rim strip	
Rear wheel	Bontrager Select, disc compatible, 28°	541mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 268/267mm, 3x	
Tire	Bontrager ACX, folding, 26 x 2.2, Velox 22mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	31.6mm outer diameter
Saddle	Bontrager Select WSD	
Seatpost binder . . .	Alloy w/integral quick-release	36.4mm inner diameter
Brakes	Hayes HFX-9, hydraulic discs	
	6.3 in. discs, 44mm BCD	
Disc hose, mm	13 17.5	
Front	750 750	
Rear	1280 1350	
Pedals	Shimano SPD M505, clipless	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	13	17.5
Rider height, in.		64.4	68.5
	cm	164	174
Handlebar	width	630	630
Handlebar	rise	25	25
Stem	length	60	70
	angle	10	10
Headset spacers		30	30
Crank	length	170	175
Seatpost	length	300	350
Steerer	length	184.2	199.2

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.5
Fork offset	38.0	
Trail	79	75
Seat tube angle	72.5	72.5
Effective top tube	566	595
Seat tube	330	432
Standover	691	736
Wheelbase	1055	1079
Bottom bracket height	320	320
Chainstay	417	417
Head tube	90	105

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Fisher Cake 3

2141600*25.124
Bike weight: 28.4 lb/12.89 kg

FRAMESET

Main tubes	Platinum series butted ZR9000	
Stays	Platinum series butted ZR9000	
Color	Metallic Matte Black/Metallic Matte Silver • Multicolor decal •	
	Metallic Matte Black fork	
Fork	Manitou Skareb Comp	100mm travel, 470mm axle-crown length
Rear shock	Manitou Swinger 3-Way, 40mm stroke, 7.5in length, 1.64in, 7/8in width, 8mm eyes	
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	Shimano Deore LX	
Brake levers	Hydraulic, attached to brake	
Grips	Bontrager Race, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Deore LX	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore LX SGS	
Crankset	Bontrager Select 44/32/22	64/104mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe SL	73 x 116 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Superstock, disc compatible, 28°	542mm ERD
Spokes	DT 14g, ProLock brass nipples, 267/267mm, 3x	
Tire	Bontrager ACX, folding, 26 x 2.2, Velox 22mm rim strip	
Rear wheel	Bontrager Superstock, disc compatible, 28°	542mm ERD
Spokes	DT 14g, ProLock brass nipples, 267/267mm, 3x	
Tire	Bontrager ACX, folding, 26 x 2.2, Velox 22mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	31.6mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .	Alloy w/integral quick-release	36.4mm inner diameter
Brakes	Hayes HFX-9, hydraulic discs	
	6.3 in. discs, 44mm BCD	
Disc hose, mm	15.5 17.5 19 21	
Front	690 750 750 750	
Rear	1280 1350 1400 1400	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	15.5	17.5	19	21
Rider height, in.		66.0	69.5	72.6	74.6
	cm	168	177	185	189
Handlebar	width	630	630	630	630
Handlebar	rise	25	25	25	25
Stem	length	75	90	105	105
	angle	7°	7°	7°	7°
Headset spacers		30	30	30	30
Crank	length	170	175	175	175
Seatpost	length	300	350	350	350
Steerer	length	183.5	198.5	218.5	238.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.5	70.5	70.5
Fork offset	38.0	38.0	38.0	38.0
Trail	79	75	75	75
Seat tube angle	72.5	72.5	72.5	72.5
Effective top tube	582	607	628	648
Seat tube	406	445	483	533
Standover	743	744	767	806
Wheelbase	1070	1091	1112	1133
Bottom bracket height	320	320	320	321
Chainstay	417	417	417	417
Head tube	90	105	125	145

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Fisher

Cake 3 GS

2141603*25.124
Bike weight: 28.6 lb/12.98 kg

FRAMESET

Main tubes	Platinum series butted ZR9000	
Stays	Platinum series butted ZR9000	
Color	Metallic Light Blue/Metallic Silver • Multicolor decal • Metallic Silver fork	
Fork	Manitou Skareb Elite WSD	100mm travel, 490mm axle-crown length
Rear shock	Manitou Swinger 3-Way, stroke, 7.5in length, 1.64in, 7/8in width, 8mm eyes	
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Select	mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	Shimano Deore LX	
Brake levers	Hydraulic, attached to brake	
Grips	Bontrager Race, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Deore LX	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore LX SGS	
Crankset	Bontrager Select 44/32/22	64/104mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe SL	73 x 116 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Superstock, disc compatible, 28°	542mm ERD
Spokes	DT 14g, ProLock brass nipples, 267/267mm, 3x	
Tire	Bontrager ACX, folding, 26 x 2.2, Velox 22mm rim strip	
Rear wheel	Bontrager Superstock, disc compatible, 28°	542mm ERD
Spokes	DT 14g, ProLock brass nipples, 267/267mm, 3x	
Tire	Bontrager ACX, folding, 26 x 2.2, Velox 22mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	31.6mm outer diameter
Saddle	Bontrager Select WSD	
Seatpost binder . . .	Alloy w/integral quick-release	36.4mm inner diameter
Brakes	Hayes HFX-9, hydraulic discs, short reach levers	
	6.3 in. discs, 44mm BCD	
Disc hose, mm	13 17.5	
Front	690 690	
Rear	1280 1280	
Pedals	Shimano SPD M505, clipless	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	13	17.5
Rider height, in.		64.5	68.6
	cm	164	174
Handlebar	width	600	600
Handlebar	rise	25	25
Stem	length	60	70
	angle	10	10
Headset spacers		30	30
Crank	length	170	175
Seatpost	length	300	350
Steerer	length	183.5	198.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.5
Fork offset	38.0	
Trail	79	75
Seat tube angle	72.5	72.5
Effective top tube	566	595
Seat tube	330	432
Standover	691	736
Wheelbase	1055	1079
Bottom bracket height	320	320
Chainstay	417	417
Head tube	90	105

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Fisher Cake 4 DLX

2140600*25.124
Bike weight: 30.2 lb/13.71 kg

FRAMESET

Main tubes	Platinum series butted ZR9000	
Stays	Platinum series butted ZR9000	
Color	Black Metallic/Red Metallic • Multicolor decal • Black Metallic fork	
Fork	Manitou Black Comp	120mm travel, 490mm axle-crown length
Rear shock	Manitou Swinger 3-Way, 40mm stroke, 7.5in length, 1.64in, 7/8in width, 8mm eyes	
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	Shimano Deore	
Brake levers	Hydraulic, attached to brake	
Grips	Bontrager Earl	

DRIVETRAIN

Front derailleur . . .	Shimano Deore	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore SGS	
Crankset	Bontrager Select 44/32/22	64/104mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe SL	73 x 116 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Superstock, disc compatible, 28°	542mm ERD
Spokes	DT 14g, ProLock brass nipples, 267/267mm, 3x	
Tire	Bontrager ACX, folding, 26 x 2.2, Velox 22mm rim strip	
Rear wheel	Bontrager Superstock, disc compatible, 28°	542mm ERD
Spokes	DT 14g, ProLock brass nipples, 267/267mm, 3x	
Tire	Bontrager ACX, folding, 26 x 2.2, Velox 22mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	31.6mm outer diameter
Saddle	Bontrager Select	
Seatpost binder . . .	Alloy w/integral quick-release	36.4mm inner diameter
Brakes	Hayes HFX-9, hydraulic discs	
	6.3 in. discs, 44mm BCD	
Disc hose, mm	15.5 17.5 19 21	
Front	750 750 750 750	
Rear	1280 1350 1400 1400	
Pedals	Shimano SPD M505, clipless	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	15.5	17.5	19	21
Rider height, in.		66.9	70.2	73.8	75.7
	cm	170	178	187	192
Handlebar	width	630	630	630	630
Handlebar	rise	25	25	25	25
Stem	length	75	90	105	105
	angle	7	7	7	7
Headset spacers		30	30	30	30
Crank	length	170	175	175	175
Seatpost	length	300	350	350	350
Steerer	length	183.5	198.5	218.5	238.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.5	70.5	70.5
Fork offset	38.0	38.0	38.0	38.0
Trail	79	75	75	75
Seat tube angle	72.5	72.5	72.5	72.5
Effective top tube	582	607	628	648
Seat tube	406	445	483	533
Standover	743	744	767	806
Wheelbase	1070	1091	1112	1133
Bottom bracket height	320	320	320	321
Chainstay	417	417	417	417
Head tube	90	105	125	145

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Fisher Cake 4

2139600*25.124
Bike weight: 30.7 lb/13.94 kg

FRAMESET

Main tubes	Platinum series butted ZR9000
Stays	Platinum series butted ZR9000
Color	Metallic Silver/Metallic Blue • Multicolor decal • Metallic Silver fork
Fork	Manitou Splice Comp SL 100mm travel, 470mm axle-crown length
Rear shock	Manitou Swinger 3-Way, 40mm stroke, 7in length, 1.64in, 7/8in width, 8mm eyes
Headset	Aheadset, semi-cartridge 25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	Shimano Deore	
Brake levers	Avid AD 3L, long pull	
Grips	Bontrager Race, dual density	

DRIVETRAIN

Front derailleur	Shimano Deore	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur	Shimano Deore SGS	
Crankset	Bontrager Select 44/32/22	64/104mm bolt hole circle
Bottom bracket	TruVativ Giga-Pipe SL	73 x 116 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Superstock, disc compatible, 28°	542mm ERD
Spokes	DT 14g, ProLock brass nipples, 267/267mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, Velox 22mm rim strip	
Rear wheel	Bontrager Superstock, disc compatible, 28°	542mm ERD
Spokes	DT 14g, ProLock brass nipples, 267/267mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, Velox 22mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	31.6mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder	Alloy w/integral quick-release	36.4mm inner diameter
Brakes	Shimano M430, V type	
Pedals	Shimano SPD M505, clipless	9/16" axle
Additional		

FIT

dimensions in mm, unless specified

Frame	Size	15.5	17.5	19	21
Rider height, in.		66.0	69.5	72.6	74.6
	cm	168	177	185	189
Handlebar	width	630	630	630	630
Handlebar	rise	25	25	25	25
Stem	length	75	90	105	105
	angle	7	7	7	7
Headset spacers		30	30	30	30
Crank	length	170	175	175	175
Seatpost	length	300	350	350	350
Steerer	length	183.5	198.5	218.5	238.5

GEOMETRY

dimensions in mm, unless specified

Head tube angle	70.0	70.5	70.5	70.5
Fork offset	38.0	38.0	38.0	38.0
Trail	79	75	75	75
Seat tube angle	72.5	72.5	72.5	72.5
Effective top tube	582	607	628	648
Seat tube	406	445	483	533
Standover	743	744	767	806
Wheelbase	1070	1091	1112	1133
Bottom bracket height	320	320	320	321
Chainstay	417	417	417	417
Head tube	90	105	125	145

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Fisher Bitter

FRAMESET

Main tubes	Gold series aluminum	
Stays	Gold series aluminum	
Color	Metallic Silver	
Fork	Manitou Stance Static	100mm travel, 523.5mm axle-crown length
Headset	DC Tank, aheadset, semi-cartridge	25.4/34.0/30.0, 25.6mm stack height

CONTROLS

Handlebar	Bontrager Earl	31.8mm clamp diameter
Stem	Bontrager Earl	40.0mm steerer clamp height
Shift levers	Shimano Alivio	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano Alivio	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore SGS	
Crankset	Bontrager Big Earl 32/22	64/106mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe	73 x 113 (shell x axle,mm), ISIS splined axle
Chain	IG-51	9 speed, 102 links
Cassette	SRAM PG830 11-32, 8spd	

WHEELSET

Front wheel	Shimano M475, disc hub, 36°, Sun Ditchwitch rim	573.45mm ERD
Spokes	14G stainless, 260mm, 3x	
Tire	Bontrager Earl, 26 x 2.4, PVC rim strip	
Rear wheel	Shimano M475, disc hub, 36°, Sun Ditchwitch rim	573.45mm ERD
Spokes, 259/259mm, 3x		
Tire	Bontrager Earl, 26 x 2.4, PVC rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Bontrager Sport	31.6mm outer diameter
Saddle	Bontrager Big Earl	
Seatpost binder . . .		36.4mm inner diameter
Brakes	Hayes Sole XC, hydraulic discs	
	6.3 in. front disc, 8 in. DH rear disc, 44mm BCD	
Pedals	Platform, alloy 9/16" axle	
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	13	15.5	17.5	19	21
Rider height, in.		62.4	64.9	69.9	71.7	73.5
	cm	159	165	178	182	187
Handlebar	width	650	650	650	650	650
Handlebar	rise	50	50	50	50	50
Stem	length	50	50	70	70	70
	angle	10	10	10	10	10
Headset spacers		40	40	40	40	40
Crank	length	170	170	175	175	175
Seatpost	length	300	350	350	350	350
Steerer	length	193	208	220	233	248

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.0	70.0	70.0	70.0
Fork offset	44.5	44.5	44.5	44.5	44.5
Trail	81	81	81	81	81
Seat tube angle	71.0	71.0	71.0	71.0	71.0
Effective top tube	552	582	608	628	647
Seat tube	332	396	446	484	535
Standover	669	700	729	752	784
Wheelbase	1005	1035	1061	1081	1101
Bottom bracket height	305	305	305	305	305
Chainstay	413	413	413	413	413
Head tube	90	105	118	130	145

GEARING

	22 32
11	52 76
12	48 70
14	41 60
16	36 52
18	32 47
21	27 40
26	22 32
32	18 26

Fisher Ged

FRAMESET

Main tubes	Gold series aluminum	
Stays	Gold series aluminum	
Color	Metallic Black	
Fork	Marzocchi DropOff	130mm travel, 523.5mm axle-crown length
Headset	DC Tank, aheadset, semi-cartridge	25.4/34.0/30.0, 25.6mm stack height

CONTROLS

Handlebar	Bontrager Big Earl	31.8mm clamp diameter
Stem	Bontrager Big Earl	40.0mm steerer clamp height
Shift levers	Shimano Deore	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano Deore	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore LX SGS	
Crankset	Bontrager Big Earl 32/22	64/106mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe	73 x 113 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-73	9 speed, 102 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Shimano M525, disc hub, 36°, Sun Ryno Lite rim	573.45mm ERD
Spokes	14G stainless, 260mm, 3x	
Tire	Bontrager Big Earl, 26 x 2.5, PVC rim strip	
Rear wheel	Shimano M525, disc hub, 36°, Sun Ryno Lite rim	573.45mm ERD
Spokes, 259/259mm, 3x		
Tire	Bontrager Big Earl, 26 x 2.5, PVC rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Bontrager Select	31.6mm outer diameter
Saddle	Bontrager Big Earl	
Seatpost binder . . .		36.4mm inner diameter
Brakes	Hayes HFX-9, hydraulic discs	
	6.3 in. front disc, 8 in. DH rear disc, 44mm BCD	
Pedals	Platform, alloy 9/16" axle	
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	13	15.5	17.5	19	21
Rider height, in.		62.5	64.8	69.8	71.6	74.0
	cm	159	165	177	182	188
Handlebar	width	710	710	710	710	710
Handlebar	rise	50	50	50	50	50
Stem	length	50	50	70	70	70
	angle	10	10	10	10	10
Headset spacers		40	40	40	40	40
Crank	length	170	170	175	175	175
Seatpost	length	250	330	330	330	400
Steerer	length	193	208	220	233	248

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.0	70.0	70.0	70.0
Fork offset	44.5	44.5	44.5	44.5	44.5
Trail	81	81	81	81	81
Seat tube angle	71.0	71.0	71.0	71.0	71.0
Effective top tube	552	582	608	628	647
Seat tube	332	396	446	484	535
Standover	669	700	729	752	784
Wheelbase	1005	1035	1061	1081	1101
Bottom bracket height	305	305	305	305	305
Chainstay	413	413	413	413	413
Head tube	90	105	118	130	145

GEARING

	22 32
11	52 76
13	44 65
15	38 56
17	34 49
20	29 42
23	25 36
26	22 32
30	19 28
34	17 25 0

Fisher Mullet

FRAMESET

Main tubes	Gold series aluminum	
Stays	Gold series aluminum	
Color	Candy Blue	
Fork	Manitou Splice Comp	100mm travel, 523.5mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 25.6mm stack height

CONTROLS

Handlebar	Bontrager Earl	31.8mm clamp diameter
Stem	Bontrager Earl	40.0mm steerer clamp height
Shift levers	Shimano EF-29	
Brake levers	Alloy	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano Acera-X	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Alivio	
Crankset	Shimano MC20 42/32/22	64/106mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 110.5 (shell x axle,mm), Square axle
Chain	IG-51	3/32", 102 links
Cassette	SRAM PG830 11-32, 8spd	

WHEELSET

Front wheel	Shimano M475, disc hub, 36°, WTB Speed Disc rim	573.45mm ERD
Spokes	14G stainless, 255.5mm, 3x	
Tire	Bontrager Earl, 26 x 2.4, PVC rim strip	
Rear wheel	Shimano M475, disc hub, 36°, WTB Speed Disc rim	573.45mm ERD
Spokes, 256.5/256.5mm, 3x		
Tire	Bontrager Earl, 26 x 2.4, PVC rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Bontrager Sport	31.6mm outer diameter
Saddle	Bontrager Earl	
Seatpost binder . . .		36.4mm inner diameter
Brakes	Hayes Linx-2 mechanical discs	
	6.3 in. front disc, 8 in. DH rear disc, 44mm BCD	
Pedals	Platform, alloy 9/16" axle	
Additional		

FIT *dimensions in mm, unless specified*

Frame Size	13	15.5	17.5	19	21
Rider height, in.	62.4	64.9	69.9	71.7	73.5
cm	159	165	178	182	187
Handlebar width	650	650	650	650	650
Handlebar rise	50	50	50	50	50
Stem length	50	50	70	70	70
angle	10	10	10	10	10
Headset spacers	40	40	40	40	40
Crank length	170	170	175	175	175
Seatpost length	300	350	350	350	350
Steerer length	193	208	220	233	248

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.0	70.0	70.0	70.0
Fork offset	44.5	44.5	44.5	44.5	44.5
Trail	81	81	81	81	81
Seat tube angle	71.0	71.0	71.0	71.0	71.0
Effective top tube	552	582	608	628	647
Seat tube	332	396	446	484	535
Standover	669	700	729	752	784
Wheelbase	1005	1035	1061	1081	1101
Bottom bracket height	305	305	305	305	305
Chainstay	413	413	413	413	413
Head tube	90	105	118	130	145

GEARING

	22	32	42
11	52	76	100
12	48	70	92
14	41	60	79
16	36	52	69
18	32	47	61
21	27	40	52
26	22	32	42
32	18	26	34

Fisher Opie

FRAMESET

Main tubes	Gold series aluminum	
Stays	Gold series aluminum	
Color	Red	
Fork	InSync Edge 4	100mm travel, 490mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 25.7mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem	Bontrager	40.0mm steerer clamp height
Shift levers	Shimano EF-29	
Brake levers	Alloy	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano C050	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Acera-X	
Crankset	SR XCC-150 42/34/24	64/106mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 124.5 (shell x axle,mm), Square axle
Chain	IG-51	3/32", 108 links
Cassette	SRAM PG830 11-32, 8spd	

WHEELSET

Front wheel	Alloy, QR hub, 32°, WTB Dual Duty rim	573.45mm ERD
Spokes	14G stainless, 264mm, 3x	
Tire	Bontrager Earl, 26 x 2.4, PVC rim strip	
Rear wheel	Shimano RM-30 hub, 32°, WTB Dual Duty rim	573.45mm ERD
Spokes, 261/260.5mm, 3x		
Tire	Bontrager Earl, 26 x 2.4, PVC rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Bontrager	31.6mm outer diameter
Saddle	Bontrager Earl	
Seatpost binder . . .		36.4mm inner diameter
Brakes	Alloy direct pull	
	6.3 in. front disc, 8 in. DH rear disc, 44mm BCD	
Pedals	Platform	9/16" axle
Additional		

FIT

dimensions in mm, unless specified

Frame	Size	13	15.5	17.5	19	21
Rider height, in.		62.9	65.5	68.4	70.6	72.4
	cm	160	166	174	179	184
Handlebar	width	620	620	620	620	620
Handlebar	rise	30	30	30	30	30
Stem	length	75	75	75	75	75
	angle	15	15	15	15	15
Headset spacers		40	40	40	40	40
Crank	length	170	170	175	175	175
Seatpost	length	350	350	350	350	350
Steerer	length	193	208	220	233	248

GEOMETRY

dimensions in mm, unless specified

Head tube angle	70.0	70.0	70.0	70.0	70.0
Fork offset	38.0	38.0	38.0	38.0	38.0
Trail	81	81	81	81	81
Seat tube angle	71.0	71.0	71.0	71.0	71.0
Effective top tube	552	582	608	628	647
Seat tube	332	396	446	484	535
Standover	669	700	729	752	784
Wheelbase	1005	1035	1061	1081	1101
Bottom bracket height	305	305	305	305	305
Chainstay	413	413	413	413	413
Head tube	90	105	118	130	145

GEARING

	24	34	42
11	57	81	100
12	52	74	92
14	45	64	79
16	39	56	69
18	35	50	61
21	30	42	52
26	24	34	42
32	20	28	34

Fisher Sugar 292

2138600*15.104
Bike weight: 29.7 lb/13.48 kg

FRAMESET

Main tubes	Platinum series butted ZR9000	
Stays	Platinum series butted ZR9000	
Color	Red • Multicolor decal • Red fork	
Fork	RockShox Reba Race 29	100mm travel, 510mm axle-crown length
Rear shock	Manitou Q-RL, 2in stroke, 7.875 length, 7/8" width, 6mm eyes	
Headset	Cane Creek S-6 Aheadset, alloy	25.4/34.0/30.0, 32.0mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Race	31.8mm clamp diameter
Stem	Bontrager Race X Lite	40.0mm steerer clamp height
Shift levers	SRAM X.9 Triggers	
Brake levers	Avid FR-5	
Grips	Bontrager Race, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Deore XT	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	SRAM RD X.0 1:1 Alloy	
Crankset	Bontrager Race Lite 44/32/22	64/104mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe SL	73 x 113 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-73	9 speed, 116 links
Cassette	Shimano Deore XT 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Race Lite 29 Disc, 28°	596mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 295/296mm, 3x	
Tire	Bontrager ACX, folding, 29 x 2.2, Velox 22mm rim strip	
Rear wheel	Bontrager Race Lite 29 Disc, 28°	596mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 295/296mm, 3x	
Tire	Bontrager ACX, folding, 29 x 2.2, Velox 22mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Race X Lite	31.6mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .	Alloy w/integral bolt	36.4mm inner diameter
Brakes	Hayes HFX-9, hydraulic discs	
	6.3 in. discs, 44mm BCD	
Disc hose, mm	15.5 17.5 19 21	
Front	750 750 750 750	
Rear	1280 1350 1400 1400	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional	Seatpost bottle mount, RockShox PopLoc lever	

FIT *dimensions in mm, unless specified*

Frame	Size	15.5	17.5	19	21
Rider height, in.		69.7	73.2	75.9	77.2
	cm	177	186	193	196
Handlebar	width	630	630	630	630
Handlebar	rise	25	25	25	25
Stem	length	75	90	105	105
	angle	7	7	7	7
Headset spacers		30	30	30	30
Crank	length	170	175	175	175
Seatpost	length	330	400	400	400
Steerer	length	204.0	204.0	204.0	204.0

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	71.5	71.5	71.5
Fork offset	42.0	42.0	42.0	42.0
Trail	86	82	82	82
Seat tube angle	73.5	73.5	73.5	73.5
Effective top tube	590	608	628	647
Seat tube	394	446	484	535
Standover	714	737	754	772
Wheelbase	1100	1118	1132	1152
Bottom bracket height	322	322	322	322
Chainstay	467	467	467	467
Head tube	105	105	105	105

GEARING

	22	32	44
11	58	84	116
13	49	71	98
15	43	62	85
17	38	55	75
20	32	46	64
23	28	40	55
26	25	36	49
30	21	31	43
34	19	27	38

Fisher Sugar 293

2134600*15.084
Bike weight: 29.3 lb/13.30 kg

FRAMESET

Main tubes	Platinum series butted ZR9000	
Stays	Platinum series butted ZR9000	
Color	Black • Multicolor decal • Black fork	
Fork	RockShox Reba Race 29	100mm travel, 510mm axle-crown length
Rear shock	Fox Float R, 2 stroke, 7.875 length, 7/8" width, 6mm eyes	
Headset	Cane Creek S-6 Aheadset, alloy	25.4/34.0/30.0, 32.0mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	SRAM X.7 Triggers	
Brake levers	Avid FR-5	
Grips	Bontrager Race, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Deore	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	SRAM RD X.9	
Crankset	Bontrager Race 44/32/22	64/104mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe SL	73 x 113 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-53	9 speed, 116 links
Cassette	SRAM PG970 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Race 29 Disc, 28°	596mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 295/296mm, 3x	
Tire	Bontrager ACX, folding, 29 x 2.2, Velox 22mm rim strip	
Rear wheel	Bontrager Race 29 Disc, 28°	596mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 295/296mm, 3x	
Tire	Bontrager ACX, folding, 29 x 2.2, Velox 22mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Select	31.6mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .	Alloy w/integral quick-release	36.4mm inner diameter
Brakes	Avid BB-7, mechanical discs	
	160mm discs, 44mm BCD	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional	Seatpost bottle mount	

FIT *dimensions in mm, unless specified*

Frame	Size	15.5	17.5	19	21
Rider height, in.		69.7	73.2	75.9	77.2
	cm	177	186	193	196
Handlebar	width	630	630	630	630
Handlebar	rise	25	25	25	25
Stem	length	75	90	105	105
	angle	7	7	7	7
Headset spacers		30	30	30	30
Crank	length	170	175	175	175
Seatpost	length	330	400	400	400
Steerer	length	204.0	204.0	204.0	204.0

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	71.5	71.5	71.5
Fork offset	42.0	42.0	42.0	42.0
Trail	86	82	82	82
Seat tube angle	73.5	73.5	73.5	73.5
Effective top tube	590	608	628	647
Seat tube	394	446	484	535
Standover	714	737	754	772
Wheelbase	1100	1118	1132	1152
Bottom bracket height	322	322	322	322
Chainstay	467	467	467	467
Head tube	105	105	105	105

GEARING

	22	32	44
11	58	84	116
13	49	71	98
15	43	62	85
17	38	55	75
20	32	46	64
23	28	40	55
26	25	36	49
30	21	31	43
34	19	27	38

Fisher Sugar 4+

2120600*15.084
Bike weight: 31.7 lb/14.39 kg

FRAMESET

Main tubes	Gold series aluminum
Stays	Gold series aluminum
Color	Metallic Orange/Metallic Black • Multicolor decal • Black fork
Fork	Manitou Splice Super, Rapid Travel 70-100mm 80mm travel, 495mm axle-crown length
Rear shock	RockShox BAR Adjust, stroke, length, width, eyes
Headset	Aheadset, semi-cartridge 25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	Shimano Deore	
Brake levers	Avid AD 3L, long pull	
Grips	Bontrager, dual density	

DRIVETRAIN

Front derailleur	Shimano Deore LX	Top pull, 34.9 mm/ 1 3/8", high clamp only attachment
Rear derailleur	Shimano Deore LX SGS	
Crankset	Bontrager Select 44/32/22	64/104mm bolt hole circle
Bottom bracket	TruVativ Giga-Pipe SL	73 x 113 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Superstock, disc compatible, 28°	542mm ERD
Spokes	DT 14g, ProLock brass nipples, 267/267mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, Velox 22mm rim strip	
Rear wheel		542mm ERD
Spokes	DT 14g, ProLock brass nipples, 267/267mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, Velox 22mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	31.6mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder	Alloy w/integral quick-release	36.4mm inner diameter
Brakes	Shimano M420, V type	
Pedals	Shimano SPD M505, clipless	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	16	17.5	19	21
Rider height, in.		68.5	72.4	75.9	77.9
	cm	174	184	193	198
Handlebar	width	630	630	630	630
Handlebar	rise	25	25	25	25
Stem	length	75	90	105	105
	angle	7	7	7	7
Headset spacers		30	30	30	30
Crank	length	170	175	175	175
Seatpost	length	300	350	350	350
Steerer	length	183.5	198.5	218.5	238.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	71.5	71.5	71.5
Fork offset	38.1	38.0	38.0	38.0
Trail	73	70	70	70
Seat tube angle	73.5	73.5	73.5	73.5
Effective top tube	578	608	628	647
Seat tube	405	446	484	535
Standover	685	708	736	742
Wheelbase	1057	1083	1103	1123
Bottom bracket height	312	312	312	312
Chainstay	420	420	420	420
Head tube	90	105	125	145

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Fisher Paragon

2074600*15.084
Bike weight: 27.1 lb/12.30 kg

FRAMESET

Main tubes	Platinum series butted ZR9000	
Stays	Platinum series butted ZR9000	
Color	Ice Red • Multicolor decal • Red fork	
Fork	RockShox Reba Race 29	80mm travel, 490mm axle-crown length
Headset	Cane Creek S-2 Aheadset, alloy	25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Race	40.0mm steerer clamp height
Shift levers	SRAM X.9 Triggers	
Brake levers	Hydraulic, attached to brake	
Grips	Bontrager, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Deore LX	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	SRAM RD X.9	
Crankset	Bontrager Race 44/32/22	64/104mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe SL	73 x 113 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-73	9 speed, 112 links
Cassette	SRAM PG970 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Race 29 Disc, 28°	596mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 295/296mm, 3x	
Tire	Bontrager ACX, folding, 29 x 2.2, Velox 22mm rim strip	
Rear wheel	Bontrager Race 29 Disc, 28°	596mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 295/296mm, 3x	
Tire	Bontrager ACX, folding, 29 x 2.2, Velox 22mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Select	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .	Alloy w/integral bolt	32.1mm inner diameter
Brakes	Hayes HFX-9, hydraulic discs	
	6.3 in. discs, 44mm BCD	
Disc hose, mm	15.5 17.5 19 21	
Front	750 750 750 750	
Rear	1280 1350 1350 1350	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	15.5	17.5	19	21
Rider height, in.		70.2	73.2	75.9	77.0
	cm	178	186	193	196
Handlebar	width	630	630	630	630
Handlebar	rise	25	25	25	25
Stem	length	75	90	105	105
	angle	7	7	7	7
Headset spacers		30	30	30	30
Crank	length	170	175	175	175
Seatpost	length	330	400	400	400
Steerer	length	182.5	182.5	182.5	197.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	71.0	71.5	71.5
Fork offset	42.0	42.0	42.0	42.0
Trail	87	83	80	80
Seat tube angle	74.0	74.0	73.5	73.0
Effective top tube	590	608	628	647
Seat tube	394	442	479	529
Standover	695	729	757	799
Wheelbase	1081	1094	1103	1119
Bottom bracket height	292	292	292	297
Chainstay	440	440	440	440
Head tube	90	90	90	105

GEARING

	22	32	44
11	58	84	116
13	49	71	98
15	43	62	85
17	38	55	75
20	32	46	64
23	28	40	55
26	25	36	49
30	21	31	43
34	19	27	38

Fisher Wahoo

FRAMESET

Main tubes	Gold series aluminum	
Stays	Gold series aluminum	
Color	Black/Metallic Drak Gray	
Blue		
Fork	RockShox Judy TT	100mm travel, 454mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 25.7mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	25.4mm clamp diameter
Stem	Bontrager Sport	40.0mm steerer clamp height
Shift levers	Shimano EF-29	
Brake levers	Alloy, direct pull	
Grips	Bontrager, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Acera-X	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Alivio	
Crankset	Shimano MC08 42/32/22	64/106mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 122.5 (shell x axle,mm), Square axle
Chain	IG-51	3/32", 106 links
Cassette	SRAM PG830 11-32, 8spd	

WHEELSET

Front wheel	Alloy, QR hub, 32°, WTB Dual Duty rim	571mm ERD
Spokes	14G stainless, 264mm, 3x	
Tire	Bontrager Jones XR, 26 x 2.25, PVC rim strip	
Rear wheel	Alloy, QR hub, 32°, WTB Dual Duty rim	571mm ERD
Spokes	DT 14G stainless, 261.5/262.5mm, 3x	
Tire	Bontrager Jones XR, 26 x 2.2, PVC rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	27.2mm outer diameter
Saddle	Bontrager Select	
Seatpost binder . . .	Alloy w/integral quick-release	31.8mm inner diameter
Brakes	Alloy direct pull	
Pedals	Platform	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	13	15.5	17.5	19	21
Rider height, in.		63.9	67.9	71.1	73.6	75.8
	cm	162	172	180	187	193
Handlebar	width	600	600	620	620	620
Handlebar	rise	25	25	25	25	25
Stem	length	60	80	90	100	110
	angle	25	25	25	25	25
Headset spacers		40	40	40	40	40
Crank	length	170	170	175	175	175
Seatpost	length	300	300	350	350	350
Steerer	length	202	202	217	237	257

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.5	71.0	71.0	71.0
Fork offset	39.0	39.0	39.0	39.0	39.0
Trail	81	78	75	75	75
Seat tube angle	74.0	73.5	73.5	73.0	72.5
Effective top tube	552	582	608	628	647
Seat tube	332	396	446	484	535
Standover	675	706	737	765	802
Wheelbase	1033	1054	1076	1092	1108
Bottom bracket height	298	303	303	303	308
Chainstay	413	413	413	413	413
Head tube	90	90	105	125	145

GEARING

	22 32 42
11	52 76 100
12	48 70 92
14	41 60 79
16	36 52 69
18	32 47 61
21	27 40 52
26	22 32 42
32	18 26 34

Fisher Tassajara Disc

FRAMESET

Main tubes	Gold series aluminum	
Stays	Gold series aluminum	
Color	Metallic Black	
Fork	Manitou Axel Elite	100mm travel, 475mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 25.7mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	25.4mm clamp diameter
Stem	Bontrager Sport	40.0mm steerer clamp height
Shift levers	Shimano Deore	
Brake levers	Hydraulic, attached to brake	
Grips	Bontrager, dual density	

DRIVETRAIN

Front derailleur	Shimano Deore	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur	Shimano Deore LX SGS	
Crankset	Bontrager Select 44/32/22	64/106mm bolt hole circle
Bottom bracket	TruVativ Giga-Pipe	73 x 113 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-73	9 speed, 106 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Shimano M525, disc hub, 32°, WTB Dual Duty rim	571mm ERD
Spokes	14G stainless, 259.5mm, 3x	
Tire	Bontrager Jones XR, 26 x 2.25, PVC rim strip	
Rear wheel	Shimano M525, disc hub, 32°, WTB Dual Duty rim	571mm ERD
Spokes	DT 14G stainless, 258.5mm, 3x	
Tire	Bontrager Jones XR, 26 x 2.2, PVC rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	27.2mm outer diameter
Saddle	Bontrager Select	
Seatpost binder	Alloy w/integral quick-release	31.8mm inner diameter
Brakes	Hayes Sole XC, hydraulic discs	
Pedals	Shimano SPD M505, clipless	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	13	15.5	17.5	19	21
Rider height, in.		64.9	68.8	72.1	74.6	76.8
	cm	165	175	183	190	195
Handlebar	width	600	600	620	620	620
Handlebar	rise	25	25	25	25	25
Stem	length	60	80	90	100	110
	angle	10	10	10	10	10
Headset spacers		40	40	40	40	40
Crank	length	170	170	175	175	175
Seatpost	length	300	300	350	350	350
Steerer	length	202	202	217	237	257

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.5	71.0	71.0	71.0
Fork offset	39.0	39.0	39.0	39.0	39.0
Trail	81	78	75	75	75
Seat tube angle	74.0	73.5	73.5	73.0	72.5
Effective top tube	552	582	608	628	647
Seat tube	332	396	446	484	535
Standover	675	706	737	765	802
Wheelbase	1033	1054	1076	1092	1108
Bottom bracket height	298	303	303	303	308
Chainstay	413	413	413	413	413
Head tube	90	90	105	125	145

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Fisher Tassajara

FRAMESET

Main tubes	Gold series aluminum	
Stays	Gold series aluminum	
Color	Metallic Black	
	Metallic Red	
Fork	Manitou Axel Elite	100mm travel, 475mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 25.7mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	25.4mm clamp diameter
Stem	Bontrager Sport	40.0mm steerer clamp height
Shift levers	Shimano Deore	
Brake levers	Alloy, direct pull	
Grips	Bontrager, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Deore	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore LX SGS	
Crankset	Bontrager Select 44/32/22	64/106mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe	73 x 113 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-73	9 speed, 106 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Shimano M525, disc hub, 32°, WTB Dual Duty rim	571mm ERD
Spokes	14G stainless, 259.5mm, 3x	
Tire	Bontrager Jones XR, 26 x 2.25, PVC rim strip	
Rear wheel	Shimano M525, disc hub, 32°, WTB Dual Duty rim	571mm ERD
Spokes	DT 14G stainless, 258.5mm, 3x	
Tire	Bontrager Jones XR, 26 x 2.2, PVC rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	27.2mm outer diameter
Saddle	Bontrager Select	
Seatpost binder . . .	Alloy w/integral quick-release	31.8mm inner diameter
Brakes	ProMax direct pull	
Pedals	Platform, alloy 9/16" axle	
Additional		

FIT

dimensions in mm, unless specified

Frame	Size	13	15.5	17.5	19	21
Rider height, in.		64.9	68.8	72.1	74.6	76.8
	cm	165	175	183	190	195
Handlebar	width	600	600	620	620	620
Handlebar	rise	25	25	25	25	25
Stem	length	60	80	90	100	110
	angle	10	10	10	10	10
Headset spacers		40	40	40	40	40
Crank	length	170	170	175	175	175
Seatpost	length	300	300	350	350	350
Steerer	length	202	202	217	237	257

GEOMETRY

dimensions in mm, unless specified

Head tube angle	70.0	70.5	71.0	71.0	71.0
Fork offset	39.0	39.0	39.0	39.0	39.0
Trail	81	78	75	75	75
Seat tube angle	74.0	73.5	73.5	73.0	72.5
Effective top tube	552	582	608	628	647
Seat tube	332	396	446	484	535
Standover	675	706	737	765	802
Wheelbase	1033	1054	1076	1092	1108
Bottom bracket height	298	303	303	303	308
Chainstay	413	413	413	413	413
Head tube	90	90	105	125	145

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Fisher Tarpon

FRAMESET

Main tubes	Silver series aluminum	
Stays	Silver series aluminum	
Color	Metallic Light Silver/Metallic Medium Silver	
	Metallic Black	
Fork	RST 191 C5	63mm travel, 441.7mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 25.7mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem	Bontrager	40.0mm steerer clamp height
Shift levers	Shimano EF-29	
Brake levers	Alloy, direct pull	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano C051	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Acera-X	
Crankset	SR XCC-100 48/38/28	64/106mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 122.5 (shell x axle,mm), Square axle
Chain	KMC Z51	3/32", 110 links
Cassette	Sunrace 13-34, 7spd	

WHEELSET

Front wheel	Alloy, QR hub, 36°, Matrix 550 rim	522mm ERD
Spokes	14g, 264mm, 3x	
Tire	Bontrager Connection Trail, 26 x 2.0, Rubber rim strip	
Rear wheel	Alloy, QR hub, 36°, Matrix 550 rim	522mm ERD
Spokes, 261/262mm, 3x		
Tire	Bontrager Connection Trail, 26 x 2.0, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Bontrager	31.6mm outer diameter
Saddle	Bontrager Sport	
Seatpost binder . . .		36.4mm inner diameter
Brakes	Alloy direct pull	
Pedals	Platform	9/16" axle
Additional		

FIT

dimensions in mm, unless specified

Frame	Size	13	16	18	19.5	21.5	16W	18W
Rider height, in.		67.5	70.0	73.6	76.1	78.0	70.3	72.3
	cm	171	178	187	193	198	179	184
Handlebar	width	600	600	620	620	620	580	600
Handlebar	rise	30	30	30	30	30	30	30
Stem	length	90	90	110	120	120	110	110
	angle	25	25	25	25	25	40	40
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	170	175	175	175	170	170
Seatpost	length	300	300	350	350	350	350	350
Steerer	length	208	228	248	268	288	248	268

GEOMETRY

dimensions in mm, unless specified

Head tube angle	70.5	71.0	71.5	71.5	71.5	71.0	71.5
Fork offset	40.0	40.0	40.0	40.0	40.0	40.0	40.0
Trail	78	75	71	71	71	75	71
Seat tube angle	74.5	74.0	74.0	73.5	73.5	74.0	74.0
Effective top tube	545	568	586	604	622	567	585
Seat tube	324	401	451	490	540	401	451
Standover	646	701	743	772	811	602	608
Wheelbase	1022	1037	1053	1067	1085	1037	1053
Bottom bracket height	288	291	295	295	295	291	295
Chainstay	415	415	415	415	415	415	415
Head tube	105	125	145	165	185	145	165

GEARING

	28	38	48
13	56	77	97
15	49	66	84
17	43	59	74
19	39	52	66
22	33	45	57
26	28	38	48
34	22	29	37

Fisher Marlin E

FRAMESET

Main tubes	Gold series aluminum	
Stays	Gold series aluminum	
Color	Candy Blue/Silver	
	Green	
Fork	Manitou Axel Comp	100mm travel, 451mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 25.7mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	25.4mm clamp diameter
Stem	Bontrager Sport	40.0mm steerer clamp height
Shift levers	Shimano Deore	
Brake levers	Alloy, direct pull	
Grips	Bontrager Sport	

DRIVETRAIN

Front derailleur . . .	Shimano Alivio	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore SGS	
Crankset	Shimano MC20 42/32/22	64/106mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 110.5 (shell x axle,mm), Square axle
Chain	Shimano HG-73	9 speed, 106 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Alloy, QR hub, 32°, WTB Dual Duty rim	571mm ERD
Spokes	14G stainless, 264.5mm, 3x	
Tire	Bontrager Jones XR, 26 x 2.25, PVC rim strip	
Rear wheel	Shimano M470 hub, 32°, WTB Dual Duty rim	571mm ERD
Spokes	DT 14G stainless, 262/263mm, 3x	
Tire	Bontrager Jones XR, 26 x 2.2, PVC rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	27.2mm outer diameter
Saddle	Bontrager Select	
Seatpost binder . . .	Alloy w/integral quick-release	31.8mm inner diameter
Brakes	Alloy direct pull	
Pedals	Platform, alloy 9/16" axle	
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	13	15.5	17.5	19	21
Rider height, in.		64.0	67.7	71.0	73.5	75.7
	cm	163	172	180	187	192
Handlebar	width	600	600	620	620	620
Handlebar	rise	25	25	25	25	25
Stem	length	60	80	90	100	110
	angle	10	10	10	10	10
Headset spacers		40	40	40	40	40
Crank	length	170	170	175	175	175
Seatpost	length	300	300	350	350	350
Steerer	length	202	202	217	237	257

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.5	71.0	71.0	71.0
Fork offset	39.0	39.0	39.0	39.0	39.0
Trail	81	78	75	75	75
Seat tube angle	74.0	73.5	73.5	73.0	72.5
Effective top tube	552	582	608	628	647
Seat tube	332	396	446	484	535
Standover	675	706	737	765	802
Wheelbase	1033	1054	1076	1092	1108
Bottom bracket height	298	303	303	303	308
Chainstay	413	413	413	413	413
Head tube	90	90	105	125	145

GEARING

	22	32	42
11	52	76	100
13	44	65	85
15	38	56	73
17	34	49	65
20	29	42	55
23	25	36	48
26	22	32	42
30	19	28	37
34	17	25	32

Fisher Marlin Disc E

FRAMESET

Main tubes	Gold series aluminum	
Stays	Gold series aluminum	
Color	Candy Blue/Silver	
	Green	
Fork.	Manitou Axel Comp	100mm travel, 451mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 25.7mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	25.4mm clamp diameter
Stem	Bontrager Sport	40.0mm steerer clamp height
Shift levers	Shimano Deore	
Brake levers	Alloy	
Grips	Bontrager Sport	

DRIVETRAIN

Front derailleur . . .	Shimano Alivio	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore SGS	
Crankset	Shimano MC20 42/32/22	64/106mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 110.5 (shell x axle,mm), Square axle
Chain.	Shimano HG-73	9 speed, 106 links
Cassette.	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel.	Shimano M475, disc hub, 32°, WTB SpeedMaster rim	571mm ERD
Spokes	14G stainless, 260mm, 3x	
Tire	Bontrager Jones XR, 26 x 2.25, PVC rim strip	
Rear wheel	Shimano M475, disc hub, 32°, WTB SpeedMaster rim	571mm ERD
Spokes	DT 14G stainless, 259/259mm, 3x	
Tire	Bontrager Jones XR, 26 x 2.2, PVC rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost.	Bontrager Sport	27.2mm outer diameter
Saddle	Bontrager Select	
Seatpost binder. . .	Alloy w/integral quick-release	31.8mm inner diameter
Brakes	Hayes MX-2 mechanical discs	
Pedals	Platform, alloy 9/16" axle	
Additional		

FIT

dimensions in mm, unless specified

Frame	Size	13	15.5	17.5	19	21
Rider height, in.		64.0	67.7	71.0	73.5	75.7
	cm	163	172	180	187	192
Handlebar	width	600	600	620	620	620
Handlebar	rise	25	25	25	25	25
Stem	length	60	80	90	100	110
	angle	10	10	10	10	10
Headset spacers		40	40	40	40	40
Crank	length	170	170	175	175	175
Seatpost	length	300	300	350	350	350
Steerer	length	202	202	217	237	257

GEOMETRY

dimensions in mm, unless specified

Head tube angle	70.0	70.5	71.0	71.0	71.0
Fork offset	39.0	39.0	39.0	39.0	39.0
Trail	81	78	75	75	75
Seat tube angle	74.0	73.5	73.5	73.0	72.5
Effective top tube	552	582	608	628	647
Seat tube	332	396	446	484	535
Standover	675	706	737	765	802
Wheelbase	1033	1054	1076	1092	1108
Bottom bracket height	298	303	303	303	308
Chainstay	413	413	413	413	413
Head tube	90	90	105	125	145

GEARING

	22	32	42
11	52	76	100
13	44	65	85
15	38	56	73
17	34	49	65
20	29	42	55
23	25	36	48
26	22	32	42
30	19	28	37
34	17	25	32

Fisher Marlin

FRAMESET

Main tubes	Gold series aluminum	
Stays	Gold series aluminum	
Color	Candy Blue/Silver	
	Green	
Fork	Manitou Axel Comp	100mm travel, 451mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 25.7mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	25.4mm clamp diameter
Stem	Bontrager Sport	40.0mm steerer clamp height
Shift levers	Shimano Alivio	
Brake levers	Alloy, direct pull	
Grips	Bontrager, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Alivio	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore SGS	
Crankset	Bontrager Sport 44/32/22	64/106mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 110.5 (shell x axle,mm), Square axle
Chain	IG-51	3/32", 106 links
Cassette	SRAM PG830 11-32, 8spd	

WHEELSET

Front wheel	Alloy, QR hub, 32°, WTB Dual Duty rim	571mm ERD
Spokes	14G stainless, 264mm, 3x	
Tire	Bontrager Jones XR, 26 x 2.25, PVC rim strip	
Rear wheel	Alloy, QR hub, 32°, WTB Dual Duty rim	571mm ERD
Spokes	DT 14G stainless, 261.5/262.5mm, 3x	
Tire	Bontrager Jones XR, 26 x 2.2, PVC rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	27.2mm outer diameter
Saddle	Bontrager Select	
Seatpost binder . . .	Alloy w/integral quick-release	31.8mm inner diameter
Brakes	ProMax direct pull	
Pedals	Platform, alloy 9/16" axle	
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	13	15.5	17.5	19	21
Rider height, in.		63.7	67.7	71.1	73.4	75.9
	cm	162	172	181	186	193
Handlebar	width	600	600	620	620	620
Handlebar	rise	25	25	25	25	25
Stem	length	60	80	90	100	110
	angle	25	25	25	25	25
Headset spacers		40	40	40	40	40
Crank	length	170	170	175	175	175
Seatpost	length	300	300	350	350	350
Steerer	length	202	202	217	237	257

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.5	71.0	71.0	71.0
Fork offset	39.0	39.0	39.0	39.0	39.0
Trail	81	78	75	75	75
Seat tube angle	74.0	73.5	73.5	73.0	72.5
Effective top tube	552	582	608	628	647
Seat tube	332	396	446	484	535
Standover	675	706	737	765	802
Wheelbase	1033	1054	1076	1092	1108
Bottom bracket height	298	303	303	303	308
Chainstay	413	413	413	413	413
Head tube	90	90	105	125	145

GEARING

	22	32	44
11	52	76	105
12	48	70	96
14	41	60	82
16	36	52	72
18	32	47	64
21	27	40	55
26	22	32	44
32	18	26	36

Fisher Mako

FRAMESET

Main tubes	Silver series aluminum	
Stays	Silver series aluminum	
Color	Metallic Light Silver/Metallic Blue	
	Metallic Red	
Fork.	Hi-tensile steel, 452.7mm axle-crown length	
Headset	Semi-cartridge, threaded	25.4/34.0/30.0, 36mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem	Steel	
Shift levers	Shimano EF-29	
Brake levers	Alloy, direct pull	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano C051	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano TX-50	
Crankset	SR XCC-100 48/38/28	64/106mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 122.5 (shell x axle,mm), Square axle
Chain.	KMC Z51	3/32", 110 links
Cassette.	Sunrace 13-34, 7spd	

WHEELSET

Front wheel.	Alloy, QR hub, 36°, Matrix 550 rim	522mm ERD
Spokes	14g, 264mm, 3x	
Tire	Bontrager Connection Trail, 26 x 2.0, Rubber rim strip	
Rear wheel	Alloy, QR hub, 36°, Matrix 550 rim	522mm ERD
Spokes, 261/262mm, 3x		
Tire	Bontrager Connection Trail, 26 x 2.0, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost.	Bontrager	31.6mm outer diameter
Saddle	Bontrager Sport	
Seatpost binder. . . .		36.4mm inner diameter
Brakes	Alloy direct pull	
Pedals	Platform	9/16" axle
Additional		

FIT

dimensions in mm, unless specified

Frame	Size	13	16	18	19.5	21.5	16W	18W
Rider height, in.		68.2	70.2	74.6	77.1	79.0	71.1	73.1
	cm	173	178	189	196	201	181	186
Handlebar	width	600	600	620	620	620	580	600
Handlebar	rise	30	30	30	30	30	30	30
Stem	length	90	90	110	120	120	110	110
	angle	25	25	25	25	25	40	40
Headset spacers		6	6	6	6	6	6	6
Crank	length	170	170	175	175	175	170	170
Seatpost	length	300	300	350	350	350	350	350
Steerer	length	144	164	184	204	224	184	204

GEOMETRY

dimensions in mm, unless specified

Head tube angle	70.5	71.0	71.5	71.5	71.5	71.0	71.5
Fork offset	46.0	46.0	46.0	46.0	46.0	46.0	46.0
Trail	78	75	71	71	71	75	71
Seat tube angle	74.5	74.0	74.0	73.5	73.5	74.0	74.0
Effective top tube	545	568	586	604	622	567	585
Seat tube	324	401	451	490	540	401	451
Standover	646	701	743	772	811	602	608
Wheelbase	1022	1037	1053	1067	1085	1037	1053
Bottom bracket height	288	291	295	295	295	291	295
Chainstay	415	415	415	415	415	415	415
Head tube	105	125	145	165	185	145	165

GEARING

	28	38	48
13	56	77	97
15	49	66	84
17	43	59	74
19	39	52	66
22	33	45	57
26	28	38	48
34	22	29	37

Fisher Hoo Koo E Koo

2056600*15.084

FRAMESET

Main tubes	Platinum series butted ZR9000	
Stays	Platinum series butted ZR9000	
Color	Sapphire Blue • Multicolor decal • Blue fork	
Fork	RockShox Pilot SL	100mm travel, 471mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	Shimano Deore LX	
Brake levers	Avid AD 3L, long pull	
Grips	Bontrager, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Deore LX	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore LX SGS	
Crankset	Bontrager Select 44/32/22	64/104mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe SL	73 x 113 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-53	9 speed, 106 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Alloy, disc compatible, QR hub, 32°, Bontrager Maverick OSB rim	542mm ERD
Spokes	DT 14G stainless, 263/263mm, 3x	
Tire	Bontrager ACX, folding, 26 x 2.2, Velox 22mm rim strip	
Rear wheel	Alloy, disc compatible, QR hub, 32°, Bontrager Maverick OSB rim	542mm ERD
Spokes	DT 14G stainless, 262/263mm, 3x	
Tire	Bontrager ACX, folding, 26 x 2.2, Velox 22mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .	Alloy w/integral quick-release	32.1mm inner diameter
Brakes	Shimano M420, V type	
Pedals	Shimano SPD M505, clipless	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	13	15.5	17.5	19	21
Rider height, in.		64.8	68.0	71.7	74.6	76.0
	cm	165	173	182	189	193
Handlebar	width	630	630	630	630	630
Handlebar	rise	25	25	25	25	25
Stem	length	60	75	90	105	105
	angle	7	7	7	7	7
Headset	spacers	30	30	30	30	30
Crank	length	170	170	175	175	175
Seatpost	length	300	300	350	350	350
Steerer	length	183.5	183.5	198.5	218.5	238.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.5	71.0	71.0	71.0
Fork offset	38.1	38.1	38.1	38.1	38.1
Trail	81	78	75	75	75
Seat tube angle	74.0	73.5	73.5	73.0	72.5
Effective top tube	552	582	608	628	647
Seat tube	332	396	446	484	535
Standover	675	706	737	765	802
Wheelbase	1033	1054	1076	1092	1108
Bottom bracket height	298	303	303	303	308
Chainstay	413	413	413	413	413
Head tube	90	90	105	125	145

GEARING

	22 32 44
11	52 76 105
13	44 65 89
15	38 56 77
17	34 49 68
20	29 42 58
23	25 36 50
26	22 32 44
30	19 28 38
34	17 25 34

Fisher Cronus

FRAMESET

Main tubes	Gold series aluminum	
Stays	Gold series aluminum	
Color	Candy Blue/Silver	
	Green	
Fork.	Bontrager Switchblade	100mm travel, 451mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 25.7mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	25.4mm clamp diameter
Stem	Bontrager Sport	40.0mm steerer clamp height
Shift levers	SRAM X.7 Trigger, right only	
Brake levers	Avid FR-5	
Grips	Bontrager, dual density	

DRIVETRAIN

Rear derailleur	SRAM RD X.7	
Crankset	Bontrager Sport 42T	64/106mm bolt hole circle
Bottom bracket	Cartridge	73 x 110.5 (shell x axle,mm), Square axle
Chain.	HG-73	3/32", 106 links
Cassette.	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel.	Shimano M475, disc hub, 32°, WTB Speed Disc rim	571mm ERD
Spokes	14G stainless, 264mm, 3x	
Tire	Bontrager Hank, 26 x 2.2, PVC rim strip	
Rear wheel	Shimano M475, disc hub, 32°, WTB Speed Disc rim	571mm ERD
Spokes	DT 14G stainless, 261.5/262.5mm, 3x	
Tire	Bontrager Hank, 26 x 2.2, PVC rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost.	Bontrager Sport	27.2mm outer diameter
Saddle	Bontrager Select	
Seatpost binder. . . .	Alloy w/integral quick-release	31.8mm inner diameter
Brakes	Avid BB-7, mechanical discs	
Pedals	Platform, alloy 9/16" axle	
Additional		

FIT

dimensions in mm, unless specified

Frame	Size	13	15.5	17.5	19	21
Rider height, in.		63.7	67.7	71.1	73.4	75.9
	cm	162	172	181	186	193
Handlebar	width	600	600	620	620	620
Handlebar	rise	25	25	25	25	25
Stem	length	60	80	90	100	110
	angle	25	25	25	25	25
Headset spacers		40	40	40	40	40
Crank	length	170	170	175	175	175
Seatpost	length	300	300	350	350	350
Steerer	length	202	202	217	237	257

GEOMETRY

dimensions in mm, unless specified

Head tube angle	70.0	70.5	71.0	71.0	71.0
Fork offset	39.0	39.0	39.0	39.0	39.0
Trail	81	78	75	75	75
Seat tube angle	74.0	73.5	73.5	73.0	72.5
Effective top tube	552	582	608	628	647
Seat tube	332	396	446	484	535
Standover	675	706	737	765	802
Wheelbase	1033	1054	1076	1092	1108
Bottom bracket height	298	303	303	303	308
Chainstay	413	413	413	413	413
Head tube	90	90	105	125	145

GEARING

	22	32	44
11	52	76	105
12	48	70	96
14	41	60	82
16	36	52	72
18	32	47	64
21	27	40	55
26	22	32	44
32	18	26	36

Fisher Advance

FRAMESET

Main tubes	Silver series aluminum	
Stays	Silver series aluminum	
Color	Metallic Black/Metallic Blue	
	Metallic Orange	
Fork	RST Capa T5	75mm travel, 448mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 25.7mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem	Bontrager	40.0mm steerer clamp height
Shift levers	Shimano EF-29	
Brake levers	Alloy, direct pull	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano C050	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Alivio	
Crankset	SR XCC-150 42/34/24	64/106mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 122.5 (shell x axle,mm), Square axle
Chain	IG-51	3/32", 106 links
Cassette	SRAM PG830 11-32, 8spd	

WHEELSET

Front wheel	Alloy, QR hub, 36°, Matrix 550 rim	522mm ERD
Spokes	14G stainless, 264.5mm, 3x	
Tire	Bontrager Connection Trail, 26 x 2.0, Rubber rim strip	
Rear wheel	Shimano RM-30 hub, 36°, Matrix 550 rim	522mm ERD
Spokes, 261.5/262.5mm, 3x		
Tire	Bontrager Connection Trail, 26 x 2.0, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Bontrager	31.6mm outer diameter
Saddle	Bontrager Sport	
Seatpost binder . . .		36.4mm inner diameter
Brakes	Alloy direct pull	
Pedals	Platform	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	13	16	18	19.5	21.5	16W	18W
Rider height, in.		67.8	70.3	73.5	76.4	78.3	72.2	74.1
	cm	172	179	187	194	199	183	188
Handlebar	width	600	600	620	620	620	580	600
Handlebar	rise	30	30	30	30	30	30	30
Stem	length	90	90	105	120	120	110	110
	angle	25	25	25	25	25	25	25
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	170	175	175	175	170	170
Seatpost	length	300	300	350	350	350	350	350
Steerer	length	208	228	248	268	288	248	268

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	71.0	71.5	71.5	71.5	71.0	71.5
Fork offset	38.1	38.1	38.1	38.1	38.1	38.1	38.1
Trail	78	75	71	71	71	75	71
Seat tube angle	74.5	74.0	74.0	73.5	73.5	74.0	74.0
Effective top tube	545	568	586	604	622	567	585
Seat tube	324	401	451	490	540	401	451
Standover	646	701	743	772	811	602	608
Wheelbase	1022	1037	1053	1067	1085	1037	1053
Bottom bracket height	288	291	295	295	295	291	295
Chainstay	415	415	415	415	415	415	415
Head tube	105	125	145	165	185	145	165

GEARING

	24	34	42
11	57	81	100
12	52	74	92
14	45	64	79
16	39	56	69
18	35	50	61
21	30	42	52
26	24	34	42
32	20	28	34

Fisher Zebrano S

FRAMESET

Main tubes	Silver series aluminum	
Stays	Silver series aluminum	
Color	Metallic Warm Silver	
	Metallic Black	
Fork.	RST CT Free T5 50mm travel, 457mm axle-crown length	
Headset	Semi-cartridge, threaded	25.4/34.0/30.0, 36.0mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	25.4mm clamp diameter
Stem	Adjustable rise, quill type	
Shift levers	Shimano EF-29	
Brake levers	Alloy, direct pull	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano C102	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Alivio	
Crankset	Shimano TX71 48/38/28 w/chainguard	64/106mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 122.5 (shell x axle,mm), Square axle
Chain.	IG-51	3/32", 114 links
Cassette.	SRAM PG830 11-32, 8spd	

WHEELSET

Front wheel.	Alloy, QR hub, 32°, WTB Dual Duty rim	634mm ERD
Spokes	14G stainless, 295mm, 3x	
Tire	IRC Mythos XC Slick, 700 x 42c, PVC rim strip	
Rear wheel	Shimano RM-60 hub, 32°, WTB Dual Duty rim	534mm ERD
Spokes, 292/293.5mm, 3x		
Tire	IRC Mythos XC Slick, 700 x 42c, PVC rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost.	Suspension, alloy	27.2mm outer diameter
Saddle	Bontrager Webspring	
Seatpost binder. . . .		31.8mm inner diameter
Brakes	Alloy direct pull	
Pedals	Platform	9/16" axle
Additional		

FIT

dimensions in mm, unless specified

	Size	15	17.5	20	22.5	15W	17.5W	20W
Rider height, in.		65.4	68.4	68.9	71.2	65.7	68.7	68.4
	cm	166	174	175	181	167	174	174
Handlebar width		600	600	620	620	600	600	620
Handlebar rise		25	25	25	25	25	25	25
Stem length		85	105	105	105	85	105	105
Stem angle		35	35	35	35	35	35	35
Headset spacers		6	6	6	6	6	6	6
Crank length		170	170	170	170	170	170	170
Seatpost length		300	350	350	350	300	350	350
Steerer length		129	144	144	164	144	164	184

GEOMETRY

dimensions in mm, unless specified

Head tube angle	70.0	70.5	70.5	71.5	70.0	70.5	70.5
Fork offset	46.0	46.0	46.0	46.0	46.0	46.0	46.0
Trail	74	71	71	64	74	71	71
Seat tube angle	74.0	74.0	73.0	73.0	74.0	74.0	73.0
Effective top tube	544	548	565	581	543	547	553
Seat tube	381	445	508	572	381	445	508
Standover	685	731	769	817	598	603	605
Wheelbase	1056	1056	1062	1069	1056	1056	1052
Bottom bracket height	281	281	281	281	281	281	281
Chainstay	445	445	445	445	445	445	445
Head tube	90	105	105	125	105	125	145

GEARING

	28	38	48
11	69	94	119
12	64	86	109
14	54	74	93
16	48	65	82
18	42	58	73
21	36	49	62
26	29	40	50
32	24	32	41

Fisher Zebrano

FRAMESET

Main tubes	Silver series aluminum	
Stays	Silver series aluminum	
Color	Metallic Warm Silver	
	Metallic Black	
Fork	Cro-Moly, 428mm axle-crown length	
Headset	Semi-cartridge, threaded	25.4/34.0/30.0, 36.0mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	25.4mm clamp diameter
Stem	Adjustable rise, quill type	
Shift levers	Shimano EF-29	
Brake levers	Alloy, direct pull	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano C102	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Alivio	
Crankset	Shimano TX71 48/38/28 w/chainguard	64/106mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 122.5 (shell x axle,mm), Square axle
Chain	IG-51	3/32", 114 links
Cassette	SRAM PG830 11-32, 8spd	

WHEELSET

Front wheel	Alloy, QR hub, 32°, WTB Dual Duty rim	634mm ERD
Spokes	14G stainless, 295mm, 3x	
Tire	IRC Mythos XC Slick, 700 x 42c, PVC rim strip	
Rear wheel	Shimano RM-60 hub, 32°, WTB Dual Duty rim	534mm ERD
Spokes, 292/293.5mm, 3x		
Tire	IRC Mythos XC Slick, 700 x 42c, PVC rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Suspension, alloy	27.2mm outer diameter
Saddle	Bontrager Webspring	
Seatpost binder . . .		31.8mm inner diameter
Brakes	Alloy direct pull	
Pedals	Platform	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	15	17.5	20	22.5	15W	17.5W	20W
Rider height, in.		64.6	67.3	67.8	70.0	64.5	67.6	67.2
	cm	164	171	172	178	164	172	171
Handlebar	width	600	600	620	620	600	600	620
Handlebar	rise	25	25	25	25	25	25	25
Stem	length	85	105	105	105	85	105	105
	angle	35	35	35	35	35	35	35
Headset spacers		6	6	6	6	6	6	6
Crank	length	170	170	170	170	170	170	170
Seatpost	length	300	350	350	350	300	350	350
Steerer	length	129	144	144	164	144	164	184

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.5	70.5	71.5	70.0	70.5	70.5
Fork offset	46.0	46.0	46.0	46.0	46.0	46.0	46.0
Trail	74	71	71	64	74	71	71
Seat tube angle	74.0	74.0	73.0	73.0	74.0	74.0	73.0
Effective top tube	544	548	565	581	543	547	553
Seat tube	381	445	508	572	381	445	508
Standover	685	731	769	817	598	603	605
Wheelbase	1056	1056	1062	1069	1056	1056	1052
Bottom bracket height	281	281	281	281	281	281	281
Chainstay	445	445	445	445	445	445	445
Head tube	90	105	105	125	105	125	145

GEARING

	28 38 48
11	69 94 119
12	64 86 109
14	54 74 93
16	48 65 82
18	42 58 73
21	36 49 62
26	29 40 50
32	24 32 41

Fisher Tiburon S E

FRAMESET

Main tubes	Silver series aluminum	
Stays	Silver series aluminum	
Color	Metallic Warm Silver	
	Metallic Blue	
Fork.	RST CT Free C5	50mm travel, 457mm axle-crown length
Headset	Semi-cartridge, threaded	25.4/34.0/30.0, 36.0mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem	Adjustable rise, quill type	
Shift levers	Shimano EF-29	
Brake levers	Alloy, direct pull	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano C102	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Acera-X	
Crankset	SR XCC-100 48/38/28 w/chainguard	64/106mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 122.5 (shell x axle,mm), Square axle
Chain.	KMC Z51	3/32", 116 links
Cassette.	Sunrace 13-34, 7spd	

WHEELSET

Front wheel.	Alloy, QR hub, 36°, Matrix 750 rim	635mm ERD
Spokes	14G stainless, 289.5mm, 3x	
Tire	IRC Mythos XC Slick, 700 x 42c, PVC rim strip	
Rear wheel	Alloy, QR hub, 36°, Matrix 750 rim	635mm ERD
Spokes, 286/287mm, 3x		
Tire	IRC Mythos XC Slick, 700 x 42c, PVC rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost.	Suspension, alloy	27.2mm outer diameter
Saddle	Bontrager Webspring	
Seatpost binder. . . .		31.8mm inner diameter
Brakes	Alloy direct pull	
Pedals	Platform	9/16" axle
Additional		

FIT

dimensions in mm, unless specified

	Size	15	17.5	20	22.5	15W	17.5W	20W
Rider height, in.		65.7	68.7	69.2	71.4	65.9	68.9	68.6
	cm	167	174	176	181	167	175	174
Handlebar width		600	600	620	620	600	600	620
Handlebar rise		30	30	30	30	30	30	30
Stem length		85	105	105	105	85	105	105
Stem angle		35	35	35	35	35	35	35
Headset spacers		6	6	6	6	6	6	6
Crank length		170	170	175	175	170	170	170
Seatpost length		300	350	350	350	300	350	350
Steerer length		129	144	144	164	144	164	184

GEOMETRY

dimensions in mm, unless specified

Head tube angle	70.0	70.5	70.5	71.5	70.0	70.5	70.5
Fork offset	46.0	46.0	46.0	46.0	46.0	46.0	46.0
Trail	74	71	71	64	74	71	71
Seat tube angle	74.0	74.0	73.0	73.0	74.0	74.0	73.0
Effective top tube	544	548	565	581	543	547	553
Seat tube	381	445	508	572	381	445	508
Standover	685	731	769	817	598	603	605
Wheelbase	1056	1056	1062	1069	1056	1056	1052
Bottom bracket height	281	281	281	281	281	281	281
Chainstay	445	445	445	445	445	445	445
Head tube	90	105	105	125	105	125	145

GEARING

	28	38	48
13	59	80	101
15	51	69	87
17	45	61	77
19	40	54	69
22	35	47	59
26	29	40	50
34	22	30	38

Fisher Tiburon S

FRAMESET

Main tubes	Silver series aluminum	
Stays	Silver series aluminum	
Color	Metallic Warm Silver	
	Metallic Blue	
Fork	RST CT Free C5	50mm travel, 452.7mm axle-crown length
Headset	Semi-cartridge, threaded	25.4/34.0/30.0, 36.0mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem	Adjustable rise, quill type	
Shift levers	Shimano EF-29	
Brake levers	Alloy, direct pull	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano C102	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Acera-X	
Crankset	SR XCC-100 48/38/28 w/chainguard	64/106mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 122.5 (shell x axle,mm), Square axle
Chain	KMC Z51	3/32", 116 links
Cassette	Sunrace 13-34, 7spd	

WHEELSET

Front wheel	Alloy, QR hub, 36°, Matrix 750 rim	635mm ERD
Spokes	14G stainless, 289.5mm, 3x	
Tire	IRC Mythos XC Slick, 700 x 42c, PVC rim strip	
Rear wheel	Alloy, QR hub, 36°, Matrix 750 rim	635mm ERD
Spokes, 286/287mm, 3x		
Tire	IRC Mythos XC Slick, 700 x 42c, PVC rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Suspension, alloy	27.2mm outer diameter
Saddle	Bontrager Webspring	
Seatpost binder . . .		31.8mm inner diameter
Brakes	Alloy direct pull	
Pedals	Platform	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	15	17.5	20	22.5	15W	17.5W	20W
Rider height, in.		65.5	68.5	69.0	71.2	65.7	68.7	68.4
	cm	166	174	175	181	167	174	174
Handlebar	width	600	600	620	620	600	600	620
Handlebar	rise	30	30	30	30	30	30	30
Stem	length	85	105	105	105	85	105	105
	angle	35	35	35	35	35	35	35
Headset spacers		6	6	6	6	6	6	6
Crank	length	170	170	175	175	170	170	170
Seatpost	length	300	350	350	350	300	350	350
Steerer	length	129	144	144	164	144	164	184

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.5	70.5	71.5	70.0	70.5	70.5
Fork offset	46.0	46.0	46.0	46.0	46.0	46.0	46.0
Trail	74	71	71	64	74	71	71
Seat tube angle	74.0	74.0	73.0	73.0	74.0	74.0	73.0
Effective top tube	544	548	565	581	543	547	553
Seat tube	381	445	508	572	381	445	508
Standover	685	731	769	817	598	603	605
Wheelbase	1056	1056	1062	1069	1056	1056	1052
Bottom bracket height	281	281	281	281	281	281	281
Chainstay	445	445	445	445	445	445	445
Head tube	90	105	105	125	105	125	145

GEARING

	28 38 48
13	59 80 101
15	51 69 87
17	45 61 77
19	40 54 69
22	35 47 59
26	29 40 50
34	22 30 38

Fisher Tiburon E

FRAMESET

Main tubes	Silver series aluminum	
Stays	Silver series aluminum	
Color	Metallic Warm Silver	
	Metallic Blue	
Fork	Hi-tensile steel, 452.7mm axle-crown length	
Headset	Semi-cartridge, threaded	25.4/34.0/30.0, 36.0mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem	Adjustable rise, quill type	
Shift levers	Shimano EF-29	
Brake levers	Integrated brake/shift	
Grips	Fisher Comfort	

DRIVETRAIN

Front derailleur . . .	Shimano C102	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur	Shimano Acera-X	
Crankset	SR XCC-100 48/38/28 w/chainguard	64/106mm bolt hole circle
Bottom bracket	Cartridge	73 x 122.5 (shell x axle,mm), Square axle
Chain	KMC Z51	3/32", 116 links
Cassette	Sunrace 13-34, 7spd	

WHEELSET

Front wheel	Alloy, QR hub, 36°, Matrix 750 rim	635mm ERD
Spokes	14G stainless, 289.5mm, 3x	
Tire	IRC Mythos XC Slick, 700 x 42c, PVC rim strip	
Rear wheel	Alloy, QR hub, 36°, Matrix 750 rim	635mm ERD
Spokes, 286/287mm, 3x		
Tire	IRC Mythos XC Slick, 700 x 42c, PVC rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Suspension, alloy	27.2mm outer diameter
Saddle	Bontrager Sport	
Seatpost binder		31.8mm inner diameter
Brakes	Alloy direct pull	
Pedals	Platform	9/16" axle
Additional		

FIT

dimensions in mm, unless specified

	Size	15	17.5	20	22.5	15W	17.5W	20W
Frame		65.6	68.6	69.1	71.4	65.8	68.9	68.6
Rider height, in.								
	cm	167	174	176	181	167	175	174
Handlebar	width	600	600	620	620	600	600	620
Handlebar	rise	30	30	30	30	30	30	30
Stem	length	85	105	105	105	85	105	105
	angle	35	35	35	35	35	35	35
Headset spacers		6	6	6	6	6	6	6
Crank	length	170	170	175	175	170	170	170
Seatpost	length	300	350	350	350	300	350	350
Steerer	length	129	144	144	164	144	164	184

GEOMETRY

dimensions in mm, unless specified

Head tube angle	70.0	70.5	70.5	71.5	70.0	70.5	70.5
Fork offset	46.0	46.0	46.0	46.0	46.0	46.0	46.0
Trail	74	71	71	64	74	71	71
Seat tube angle	74.0	74.0	73.0	73.0	74.0	74.0	73.0
Effective top tube	544	548	565	581	543	547	553
Seat tube	381	445	508	572	381	445	508
Standover	685	731	769	817	598	603	605
Wheelbase	1056	1056	1062	1069	1056	1056	1052
Bottom bracket height	281	281	281	281	281	281	281
Chainstay	445	445	445	445	445	445	445
Head tube	90	105	105	125	105	125	145

GEARING

	28	38	48
13	59	80	101
15	51	69	87
17	45	61	77
19	40	54	69
22	35	47	59
26	29	40	50
34	22	30	38

Fisher Nirvana S

FRAMESET

Main tubes	Silver series aluminum	
Stays	Silver series aluminum	
Color	Metallic Light Silver	
	Metallic Red	
Fork	RockShox Metro GPS	50mm travel, 456mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 36.3mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	25.4mm clamp diameter
Stem	Alloy direct connect, adjustable rise	40.0mm steerer clamp height
Shift levers	Shimano Alivio	
Brake levers	Alloy, direct pull	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano C102	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore SGS	
Crankset	Shimano T303 48/38/28 w/chainguard	64/106mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 122.5 (shell x axle,mm), Square axle
Chain	IG-51	3/32", 114 links
Cassette	SRAM PG830 11-32, 8spd	

WHEELSET

Front wheel	Alloy, QR hub, 32°, WTB Dual Duty rim	634mm ERD
Spokes	14G stainless, 295mm, 3x	
Tire	IRC Mythos XC Slick, 700 x 42c, PVC rim strip	
Rear wheel	Shimano RM-60 hub, 32°, WTB Dual Duty rim	534mm ERD
Spokes, 292/293.5mm, 3x		
Tire	IRC Mythos XC Slick, 700 x 42c, PVC rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Suspension, alloy	27.2mm outer diameter
Saddle	Bontrager CRZ+	
Seatpost binder . . .		31.8mm inner diameter
Brakes	Shimano M420, V type	
Pedals	Platform, alloy 9/16" axle	
Additional		

FIT *dimensions in mm, unless specified*

	Size	15	17.5	20	22.5	15W	17.5W	20W
Frame								
Rider height, in.		67.2	68.2	68.6	72.5	67.2	68.2	68.2
	cm	171	173	174	184	171	173	173
Handlebar width		600	600	620	620	600	600	620
Handlebar rise		25	25	25	25	25	25	25
Stem length		105	105	105	125	105	105	105
	angle	35	35	35	35	35	35	35
Headset spacers		30	30	30	30	30	30	30
Crank length		170	170	170	170	170	170	170
Seatpost length		300	350	350	350	300	350	350
Steerer length		193	208	208	228	208	228	248

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.5	70.5	71.5	70.0	70.5	70.5
Fork offset	44.0	44.0	44.0	44.0	44.0	44.0	44.0
Trail	74	71	71	64	74	71	71
Seat tube angle	74.0	74.0	73.0	73.0	74.0	74.0	73.0
Effective top tube	544	548	565	581	543	547	553
Seat tube	381	445	508	572	381	445	508
Standover	685	731	769	817	598	603	605
Wheelbase	1056	1056	1062	1069	1056	1056	1052
Bottom bracket height	281	281	281	281	281	281	281
Chainstay	445	445	445	445	445	445	445
Head tube	90	105	105	125	105	125	145

GEARING

	28	38	48
11	69	94	119
12	64	86	109
14	54	74	93
16	48	65	82
18	42	58	73
21	36	49	62
26	29	40	50
32	24	32	41

Fisher Nirvana

FRAMESET

Main tubes	Silver series aluminum	
Stays	Silver series aluminum	
Color	Metallic Light Silver	
	Metallic Red	
Fork	Cro-Moly, 428mm axle-crown length	
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 36.3mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	25.4mm clamp diameter
Stem	Alloy direct connect, adjustable rise	40.0mm steerer clamp height
Shift levers	Shimano Alivio	
Brake levers	Alloy, direct pull	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano C102	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore SGS	
Crankset	Shimano T303 48/38/28 w/chainguard	64/106mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 122.5 (shell x axle,mm), Square axle
Chain	IG-51	3/32", 114 links
Cassette	SRAM PG830 11-32, 8spd	

WHEELSET

Front wheel	Alloy, QR hub, 32°, WTB Dual Duty rim	634mm ERD
Spokes	14G stainless, 295mm, 3x	
Tire	IRC Mythos XC Slick, 700 x 42c, PVC rim strip	
Rear wheel	Shimano RM-60 hub, 32°, WTB Dual Duty rim	534mm ERD
Spokes, 292/293.5mm, 3x		
Tire	IRC Mythos XC Slick, 700 x 42c, PVC rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Suspension, alloy	27.2mm outer diameter
Saddle	Bontrager CRZ+	
Seatpost binder . . .		31.8mm inner diameter
Brakes	Shimano M420, V type	
Pedals	Platform, alloy 9/16" axle	
Additional		

FIT

dimensions in mm, unless specified

	Size	15	17.5	20	22.5	15W	17.5W	20W
Frame		66.3	66.9	67.7	71.6	66.4	67.0	66.9
Rider height, in.								
	cm	169	170	172	182	169	170	170
Handlebar	width	600	600	620	620	600	600	620
Handlebar	rise	25	25	25	25	25	25	25
Stem	length	105	105	105	125	105	105	105
	angle	35	35	35	35	35	35	35
Headset spacers		30	30	30	30	30	30	30
Crank	length	170	170	170	170	170	170	170
Seatpost	length	300	350	350	350	300	350	350
Steerer	length	193	208	208	228	208	228	248

GEOMETRY

dimensions in mm, unless specified

Head tube angle	70.0	70.5	70.5	71.5	70.0	70.5	70.5
Fork offset	46.0	46.0	46.0	46.0	46.0	46.0	46.0
Trail	74	71	71	64	74	71	71
Seat tube angle	74.0	74.0	73.0	73.0	74.0	74.0	73.0
Effective top tube	544	548	565	581	543	547	553
Seat tube	381	445	508	572	381	445	508
Standover	685	731	769	817	598	603	605
Wheelbase	1056	1056	1062	1069	1056	1056	1052
Bottom bracket height	281	281	281	281	281	281	281
Chainstay	445	445	445	445	445	445	445
Head tube	90	105	105	125	105	125	145

GEARING

	28	38	48
11	69	94	119
12	64	86	109
14	54	74	93
16	48	65	82
18	42	58	73
21	36	49	62
26	29	40	50
32	24	32	41

Fisher X-Caliber

2058600*15.084
Bike weight: 28.0 lb/12.71 kg

FRAMESET

Main tubes	Platinum series butted ZR9000
Stays	Platinum series butted ZR9000
Color	Metallic Black • Multicolor decal • Black fork
Fork	RockShox Reba SL 29 80mm travel, 490mm axle-crown length
Headset	Aheadset, semi-cartridge 25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	SRAM X.7 Triggers	
Brake levers	Avid FR-5	
Grips	Bontrager, dual density	

DRIVETRAIN

Front derailleur	Shimano Deore	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur	SRAM RD X.7	
Crankset	Bontrager Select 44/32/22	64/104mm bolt hole circle
Bottom bracket	TruVativ Giga-Pipe SL	73 x 113 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-53	9 speed, 112 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Superstock 29" Disc, 28°	596mm ERD
Spokes	DT 14g, ProLock brass nipples, 294/294mm, 3x	
Tire	Bontrager ACX, folding, 29 x 2.2, Velox 22mm rim strip	
Rear wheel	Bontrager Superstock 29" Disc, 28°	596mm ERD
Spokes	DT 14g, ProLock brass nipples, 294/294mm, 3x	
Tire	Bontrager ACX, folding, 29 x 2.2, Velox 22mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Sport	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder	Alloy w/integral quick-release	32.1mm inner diameter
Brakes	Avid BB-7, mechanical discs	
	160mm discs, 44mm BCD	
Pedals	Shimano SPD M505, clipless	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	15.5	17.5	19	21
Rider height, in.		70.2	73.2	75.9	77.1
	cm	178	186	193	196
Handlebar	width	630	630	630	630
Handlebar	rise	25	25	25	25
Stem	length	75	90	105	105
	angle	7	7	7	7
Headset spacers		30	30	30	30
Crank	length	170	175	175	175
Seatpost	length	300	350	350	350
Steerer	length	183.5	183.5	183.5	198.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	71.0	71.5	71.5
Fork offset	42.0	42.0	42.0	42.0
Trail	87	83	80	80
Seat tube angle	74.0	74.0	73.5	73.0
Effective top tube	590	608	628	647
Seat tube	394	442	479	529
Standover	695	729	757	799
Wheelbase	1081	1094	1103	1119
Bottom bracket height	292	292	292	297
Chainstay	440	440	440	440
Head tube	90	90	90	105

GEARING

	22	32	44
11	58	84	116
13	49	71	98
15	43	62	85
17	38	55	75
20	32	46	64
23	28	40	55
26	25	36	49
30	21	31	43
34	19	27	38

Fisher Napa

FRAMESET

Main tubes	Silver series aluminum	
Stays	Silver series aluminum	
Color		
Fork	RST Gila T5	80mm travel, 456.5mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 26.3mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem	Alloy direct connect, adjustable rise	40.0mm steerer clamp height
Shift levers	Shimano EF-29	
Brake levers	Integrated brake/shift	
Grips	Fisher Comfort	

DRIVETRAIN

Front derailleur . . .	Shimano C102	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Alivio	
Crankset	Shimano TX71 48/38/28 w/chainguard	64/104mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 122.5 (shell x axle,mm), Square axle
Chain	IG-51	3/32", 112 links
Cassette	SRAM PG830 11-32, 8spd	

WHEELSET

Front wheel	Alloy, QR hub, 36°, Matrix 550 rim	559mm ERD
Spokes	14G stainless, 265mm, 3x	
Tire	Bontrager Hank, 26 x 2.2, Rubber rim strip	
Rear wheel	Shimano RM-60 hub, 36°, Matrix 550 rim	559mm ERD
Spokes	14G stainless, 262/263mm, 3x	
Tire	Bontrager Hank, 26 x 2.2, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Suspension, alloy	27.2mm outer diameter
Saddle	Bontrager Webspring	
Seatpost binder . . .		31.8mm inner diameter
Brakes	Tektro direct pull w/modulator front, Tektro direct pull rear	
Pedals	Platform	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	14.5	16.5	18.5	21	14.5W	16.5W	18.5W
Rider height, in.		63.8	68.0	71.3	73.5	63.8	66.2	71.3
	cm	162	173	181	187	162	168	181
Handlebar	width	600	600	620	620	600	600	620
Handlebar	rise	50	50	50	50	50	50	50
Stem	length	85	105	105	105	85	85	105
	angle	35	35	35	35	35	35	35
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	170	170	170	170	170	170
Seatpost	length	300	350	350	350	300	350	350
Steerer	length	238	258	298	338	238	258	298

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	70.5	70.5	70.5	70.5	70.5	70.5
Fork offset	38.6	38.6	38.6	38.6	38.6	38.6	38.6
Trail	74	74	74	74	74	74	74
Seat tube angle	72.5	72.5	72.5	72.5	72.5	72.5	72.5
Effective top tube	530	550	575	595	530	550	575
Seat tube	368	419	470	533	368	419	470
Standover	659	695	739	770	588	589	595
Wheelbase	1011	1032	1059	1080	1011	1032	1059
Bottom bracket height	287	287	287	287	287	287	287
Chainstay	435	435	435	435	435	435	435
Head tube	135	155	215	235	135	155	215

GEARING

	28 38 48
11	67 91 114
12	61 83 105
14	52 71 90
16	46 62 79
18	41 55 70
21	35 47 60
26	28 38 48
32	23 31 39

Fisher Capitola

FRAMESET

Main tubes	Silver series aluminum	
Stays	Silver series aluminum	
Color		
Fork	RST Capa C5	80mm travel, 451mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 26.3mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem	Alloy direct connect, adjustable rise	40.0mm steerer clamp height
Shift levers	SRAM MRX Plus	
Brake levers	Alloy, direct pull	
Grips	Fisher Comfort	

DRIVETRAIN

Front derailleur . . .	Shimano C051	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Acera-X	
Crankset	SR XCC-100 48/38/28 w/chainguard	64/104mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 122.5 (shell x axle,mm), Square axle
Chain	KMC Z51	3/32", 114 links
Cassette	Sunrace 13-34, 7spd	

WHEELSET

Front wheel	Alloy, QR hub, 36°, Matrix 550 rim	559mm ERD
Spokes	14g, 264mm, 3x	
Tire	Bontrager Hank, 26 x 2.2, Rubber rim strip	
Rear wheel	Alloy, QR hub, 36°, Matrix 550 rim	559mm ERD
Spokes	14g, 261/263mm, 3x	
Tire	Bontrager Hank, 26 x 2.2, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Suspension, alloy	27.2mm outer diameter
Saddle	Bontrager Webspring	
Seatpost binder . . .		34.9mm inner diameter
Brakes	Tektro direct pull w/modulator front, Tektro direct pull rear	
Pedals	Platform	9/16" axle
Additional	integral bell,	

FIT *dimensions in mm, unless specified*

Frame	Size	14.5	16.5	18.5	21	14.5W	16.5W	18.5W
Rider height, in.		65.9	69.9	73.2	75.3	65.9	69.9	73.2
	cm	167	178	186	191	167	178	186
Handlebar	width	600	600	620	620	600	600	620
Handlebar	rise	50	50	50	50	50	50	50
Stem	length	108	128	128	128	108	128	128
	angle	35	35	35	35	35	35	35
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	170	170	170	170	170	170
Seatpost	length	300	350	350	350	300	350	350
Steerer	length	238	258	298	338	238	258	298

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	70.5	70.5	70.5	70.5	70.5	70.5
Fork offset	38.6	38.6	38.6	38.6	38.6	38.6	38.6
Trail	74	74	74	74	74	74	74
Seat tube angle	72.5	72.5	72.5	72.5	72.5	72.5	72.5
Effective top tube	530	550	575	595	530	550	575
Seat tube	368	419	470	533	368	419	470
Standover	659	695	739	770	588	589	595
Wheelbase	1011	1032	1059	1080	1011	1032	1059
Bottom bracket height	287	287	287	287	287	287	287
Chainstay	435	435	435	435	435	435	435
Head tube	135	155	215	235	135	155	215

GEARING

28 38 48
? ? ?

Fisher Ziggurat

2072600*15.104
Bike weight: 25.5 lb/11.58 kg

FRAMESET

Main tubes		ZR9000	
Stays		Carbon fiber composite	
Color		Silver/Black Metallic • Multicolor decal • Silver fork	
Fork		Fox FRL Air	100mm travel, 470.9mm axle-crown length
Headset		Cane Creek S-2 Aheadset, alloy	25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar		Bontrager Crowbar Race Lite	31.8mm clamp diameter
Stem		Bontrager Race Lite	40.0mm steerer clamp height
Shift levers		SRAM X.9 Triggers	
Brake levers		Avid FR-1	
Grips		Bontrager Race, dual density	

DRIVETRAIN

Front derailleur	...	Shimano Deore XT	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur	...	SRAM RD X.0 1:1 Alloy	
Crankset		Bontrager Race Lite 44/32/22	64/104mm bolt hole circle
Bottom bracket		TruVativ Giga-Pipe SL	73 x 113 (shell x axle,mm), ISIS splined axle
Chain		Shimano HG-73	9 speed, 106 links
Cassette		SRAM PG970 11-34, 9spd	

WHEELSET

Front wheel		Bontrager Race, tubeless compatible, disc compatible, 28°	542mm ERD
Spokes		DT 14/15G butted stainless, ProLock alloy nipples, 267/268mm, 3x	
Tire		Bontrager Jones XR, folding, 127tpi, 26 x 2.25, Tubeless assymetric rim strip	
Rear wheel		Bontrager Race, tubeless compatible, disc compatible, 28°	542mm ERD
Spokes		DT 14/15G butted stainless, ProLock alloy nipples, 267/266mm, 3x	
Tire		Bontrager Jones XR, folding, 127tpi, 26 x 2.25, Tubeless assymetric rim strip	
Inner tubes		Presta valve	

OTHER

Seatpost		Bontrager Race X Lite	27.2mm outer diameter
Saddle		Bontrager Race Luxe	
Seatpost binder	...	Alloy w/integral bolt	32.1mm inner diameter
Brakes		Avid Single Digit SL, linear pull, Rim Wrangler pads	
Pedals		Shimano SPD M520, clipless	9/16" axle
Additional			

FIT *dimensions in mm, unless specified*

Frame	Size	15.5	17.5	19	21
Rider height, in.		68.1	71.2	74.4	75.8
	cm	173	181	189	192
Handlebar	width	630	630	630	630
Handlebar	rise	25	25	25	25
Stem	length	80	90	110	110
	angle	7	7	7	7
Headset spacers		30	30	30	30
Crank	length	170	175	175	175
Seatpost	length	330	400	400	400
Steerer	length	182.5	197.5	217.5	237.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle		70.5	71.0	71.0	71.0
Fork offset		38.0	38.0	38.0	38.0
Trail		78	75	75	75
Seat tube angle		73.5	73.5	73.0	72.5
Effective top tube		582	608	628	647
Seat tube		396	446	484	535
Standover		706	737	765	802
Wheelbase		1054	1076	1092	1108
Bottom bracket height		300	303	303	308
Chainstay		413	413	413	413
Head tube		90	105	125	145

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Fisher Big Sur Disc

2061600*15.084
Bike weight: 26.0 lb/11.80 kg

FRAMESET

Main tubes	ZR9000	
Stays	Carbon fiber composite	
Color	Ice Purple • Multicolor decal • Black fork	
Fork	Manitou Skareb Super	100mm travel, 490mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	Shimano Deore LX	
Brake levers	Hydraulic, attached to brake	
Grips	Bontrager Race, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Deore LX	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore XT SGS	
Crankset	Bontrager Race 44/32/22	64/104mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe SL	73 x 113 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-53	9 speed, 106 links
Cassette	SRAM PG970 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Superstock, disc compatible, 28°	542mm ERD
Spokes	DT 14g, ProLock brass nipples, 267/267mm, 3x	
Tire	Bontrager ACX, folding, 26 x 2.2, Velox 22mm rim strip	
Rear wheel	Bontrager Superstock, disc compatible, 28°	542mm ERD
Spokes	DT 14g, ProLock brass nipples, 267/267mm, 3x	
Tire	Bontrager ACX, folding, 26 x 2.2, Velox 22mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Select	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .	Alloy w/integral quick-release	32.1mm inner diameter
Brakes	Hayes HFX-9, hydraulic discs	
	6.3 in. discs, 44mm BCD	
Disc hose, mm	15.5 17.5 19 21	
Front	690 690 750 750	
Rear	1280 1280 1350 1350	
Pedals	Shimano SPD M505, clipless	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	15.5	17.5	19	21
Rider height, in.		68.6	72.0	74.8	76.2
	cm	174	183	190	194
Handlebar	width	630	630	630	630
Handlebar	rise	25	25	25	25
Stem	length	75	90	105	105
	angle	7	7	7	7
Headset spacers		30	30	30	30
Crank	length	170	175	175	175
Seatpost	length	330	400	400	400
Steerer	length	183.5	198.5	218.5	238.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	71.0	71.0	71.0
Fork offset	38.0	38.0	38.0	38.0
Trail	78	75	75	75
Seat tube angle	73.5	73.5	73.0	72.5
Effective top tube	582	608	628	647
Seat tube	396	446	484	535
Standover	706	737	765	802
Wheelbase	1054	1076	1092	1108
Bottom bracket height	300	303	303	308
Chainstay	413	413	413	413
Head tube	90	105	125	145

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Fisher Big Sur

2060600*15.084
Bike weight: 25.4 lb/11.53 kg

FRAMESET

Main tubes		ZR9000	
Stays		Carbon fiber composite	
Color		Ice Purple • Multicolor decal • Black fork	
Fork		Manitou Skareb Super	100mm travel, 490mm axle-crown length
Headset		Aheadset, semi-cartridge	25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar		Bontrager Select	31.8mm clamp diameter
Stem		Bontrager Select	41.0mm steerer clamp height
Shift levers		Shimano Deore LX	
Brake levers		Avid AD 3L, long pull	
Grips		Bontrager Race, dual density	

DRIVETRAIN

Front derailleur	...	Shimano Deore LX	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur		Shimano Deore XT SGS	
Crankset		Bontrager Race 44/32/22	64/104mm bolt hole circle
Bottom bracket		TruVativ Giga-Pipe SL	73 x 113 (shell x axle,mm), ISIS splined axle
Chain		Shimano HG-53	9 speed, 106 links
Cassette		SRAM PG970 11-34, 9spd	

WHEELSET

Front wheel		Bontrager Superstock, disc compatible, 28°	542mm ERD
Spokes		DT 14g, ProLock brass nipples, 267/267mm, 3x	
Tire		Bontrager ACX, folding, 26 x 2.2, Velox 22mm rim strip	
Rear wheel		Bontrager Superstock, disc compatible, 28°	542mm ERD
Spokes		DT 14g, ProLock brass nipples, 267/267mm, 3x	
Tire		Bontrager ACX, folding, 26 x 2.2, Velox 22mm rim strip	
Inner tubes		Presta valve	

OTHER

Seatpost		Bontrager Select	27.2mm outer diameter
Saddle		Bontrager Race Luxe	
Seatpost binder		Alloy w/integral quick-release	32.1mm inner diameter
Brakes		Avid Single Digit 5, linear pull	
Pedals		Shimano SPD M505, clipless	9/16" axle
Additional			

FIT *dimensions in mm, unless specified*

Frame	Size	15.5	17.5	19	21
Rider height, in.		68.6	72.0	74.8	76.2
	cm	174	183	190	194
Handlebar	width	630	630	630	630
Handlebar	rise	25	25	25	25
Stem	length	75	90	105	105
	angle	7	7	7	7
Headset spacers		30	30	30	30
Crank	length	170	175	175	175
Seatpost	length	330	400	400	400
Steerer	length	183.5	198.5	218.5	238.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle		70.5	71.0	71.0	71.0
Fork offset		38.0	38.0	38.0	38.0
Trail		78	75	75	75
Seat tube angle		73.5	73.5	73.0	72.5
Effective top tube		582	608	628	647
Seat tube		396	446	484	535
Standover		706	737	765	802
Wheelbase		1054	1076	1092	1108
Bottom bracket height		300	303	303	308
Chainstay		413	413	413	413
Head tube		90	105	125	145

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Fisher Tassajara GS

Bike weight: 25.6 lb/11.62 kg

FRAMESET

Main tubes	Gold series aluminum	
Stays	Gold series aluminum	
Color	Metallic Silver	
Fork	Manitou Axel Elite	100mm travel, 451mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 25.7mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	25.4mm clamp diameter
Stem	Bontrager Sport	40.0mm steerer clamp height
Shift levers	Shimano Deore	
Brake levers	Alloy, direct pull	
Grips	Bontrager Race, dual density	

DRIVETRAIN

Front derailleur	Shimano Deore	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur	Shimano Deore LX SGS	
Crankset	Bontrager Select 44/32/22	64/106mm bolt hole circle
Bottom bracket	TruVativ Giga-Pipe	73 x 113 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-73	9 speed, 106 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Shimano M525, disc hub, 32°, WTB Dual Duty rim	571mm ERD
Spokes	15g stainless, 259.5mm, 3x	
Tire	Bontrager Jones XR, 26 x 2.25, PVC rim strip	
Rear wheel	Shimano M525, disc hub, 32°, WTB Dual Duty rim	571mm ERD
Spokes	DT 14g, ProLock brass nipples, 258.5mm, 3x	
Tire	Bontrager Jones XR, 26 x 2.25, PVC rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	27.2mm outer diameter
Saddle	Bontrager Select WSD	
Seatpost binder	Alloy w/integral quick-release	31.8mm inner diameter
Brakes	ProMax direct pull	
Pedals	Platform, alloy 9/16" axle	
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	13	15.5	17.5
Rider height, in.		64.1	65.7	69.2
	cm	163	167	176
Handlebar	width	560	580	600
Handlebar	rise	25	25	25
Stem	length	60	70	80
	angle	10	10	10
Headset spacers		40	40	40
Crank	length	170	170	170
Seatpost	length	300	300	350
Steerer	length	202	202	217

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.5	71.0
Fork offset	39.0	39.0	39.0
Trail	81	78	75
Seat tube angle	74.0	73.5	73.5
Effective top tube	552	567	595
Seat tube	332	396	446
Standover	675	706	738
Wheelbase	1033	1039	1063
Bottom bracket height	298	303	303
Chainstay	413	413	413
Head tube	90	90	105

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Fisher Big Sur GS

2060603*15.084
Bike weight: 25.6 lb/11.62 kg

FRAMESET

Main tubes		ZR9000	
Stays		Carbon fiber composite	
Color		Moritz Sky Blue • Multicolor decal • Black fork	
Fork		Manitou Skareb Super	100mm travel, 490mm axle-crown length
Headset		Aheadset, semi-cartridge	25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar		Bontrager Select	31.8mm clamp diameter
Stem		Bontrager Select	41.0mm steerer clamp height
Shift levers		Shimano Deore LX	
Brake levers		Avid AD 3L, long pull	
Grips		Bontrager Race, dual density	

DRIVETRAIN

Front derailleur	...	Shimano Deore LX	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur		Shimano Deore XT SGS	
Crankset		Bontrager Race 44/32/22	64/104mm bolt hole circle
Bottom bracket		TruVativ Giga-Pipe SL	73 x 113 (shell x axle,mm), ISIS splined axle
Chain		Shimano HG-53	9 speed, 106 links
Cassette		SRAM PG970 11-34, 9spd	

WHEELSET

Front wheel		Bontrager Superstock, disc compatible, 28°	542mm ERD
Spokes		DT 14g, ProLock brass nipples, 267/267mm, 3x	
Tire		Bontrager ACX, folding, 26 x 2.2, Velox 22mm rim strip	
Rear wheel		Bontrager Superstock, disc compatible, 28°	542mm ERD
Spokes		DT 14g, ProLock brass nipples, 267/267mm, 3x	
Tire		Bontrager ACX, folding, 26 x 2.2, Velox 22mm rim strip	
Inner tubes		Presta valve	

OTHER

Seatpost		Bontrager Select	27.2mm outer diameter
Saddle		Bontrager Race Luxe	
Seatpost binder		Alloy w/integral quick-release	32.1mm inner diameter
Brakes		Avid Single Digit 5, linear pull	
Pedals		Shimano SPD M505, clipless	9/16" axle
Additional			

FIT *dimensions in mm, unless specified*

Frame	Size	13	15.5	17.5
Rider height, in.		65.4	67.6	70.4
	cm	166	172	179
Handlebar	width	630	630	630
Handlebar	rise	25	25	25
Stem	length	60	75	75
	angle	7	7	7
Headset spacers		30	30	30
Crank	length	170	170	175
Seatpost	length	330	330	400
Steerer	length	183.5	183.5	198.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle		70.0	70.5	71.0
Fork offset		38.2	38.0	38.0
Trail		81	78	75
Seat tube angle		74.0	73.5	73.5
Effective top tube		552	567	595
Seat tube		332	396	446
Standover		675	706	738
Wheelbase		1033	1039	1063
Bottom bracket height		298	303	303
Chainstay		413	413	413
Head tube		90	90	105

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Fisher Utopia

Bike weight: 29.0 lb/13.17 kg

FRAMESET

Main tubes	Gold series aluminum	
Stays	Gold series aluminum	
Color	Metallic Blue	
Fork	RockShox Metro GPS	50mm travel, 456mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 36.3mm stack height

CONTROLS

Handlebar	Bontrager Select	25.4mm clamp diameter
Stem	Bontrager Select	40.0mm steerer clamp height
Shift levers	Shimano Deore	
Brake levers	Alloy, direct pull	
Grips	Bontrager Select, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Deore	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore XT SGS	
Crankset	Bontrager Select Pavement 48/36/26	64/106mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe	73 x 113 (shell x axle,mm), Square axle
Chain	Shimano HG-73	9 speed, 112 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Shimano M525, disc hub, 32°, WTB Speed Disc rim	634mm ERD
Spokes	15g stainless, 291mm, 3x	
Tire	IRC Mythos XC Slick, folding, 700 x 42c, PVC rim strip	
Rear wheel	Shimano M525, disc hub, 32°, WTB Speed Disc rim	634mm ERD
Spokes	DT 14g, ProLock brass nipples, 290/290mm, 3x	
Tire	IRC Mythos XC Slick, folding, 700 x 42c, PVC rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Bontrager Select	31.6mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .	Alloy w/integral quick-release	36.4mm inner diameter
Brakes	Avid BB-7, mechanical discs	
	160mm discs, 44mm BCD	
Pedals	Platform, alloy 9/16" axle	
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	15.5	17.5	19	21
Rider height, in.		69.4	72.3	74.2	76.2
	cm	176	184	189	194
Handlebar	width	600	600	620	620
Handlebar	rise	25	25	25	25
Stem	length	80	90	100	110
	angle	10	10	10	10
Headset spacers		30	30	30	30
Crank	length	170	170	175	175
Seatpost	length	330	330	330	400
Steerer	length	194	194	194	209

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	71.0	71.5	71.5
Fork offset	44.0	44.0	44.0	44.0
Trail	87	83	80	80
Seat tube angle	74.0	74.0	73.5	73.0
Effective top tube	590	608	628	647
Seat tube	394	442	479	529
Standover	695	729	757	799
Wheelbase	1081	1094	1103	1119
Bottom bracket height	292	292	292	297
Chainstay	440	440	440	440
Head tube	90	90	90	105

GEARING

	26	36	48
11	69	95	127
13	58	80	107
15	50	70	93
17	44	61	82
20	38	52	70
23	33	45	61
26	29	40	54
30	25	35	46
34	22	31	41

Fisher Montare

2346600*15.084
Bike weight: 29.0 lb/13.17 kg

FRAMESET

Main tubes	Platinum series butted ZR9000
Stays	Platinum series butted ZR9000
Color	Metallic Silver • Multicolor decal • Silver fork
Fork	Manitou South Elite 75mm travel, 483mm axle-crown length
Headset	Aheadset, semi-cartridge 25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Select	25.4mm clamp diameter
Stem	Bontrager Sport	50.0mm steerer clamp height
Shift levers	Shimano Deore LX	
Brake levers	Avid AD 3L, long pull	
Grips	Bontrager Select, dual density	

DRIVETRAIN

Front derailleur	Shimano Deore	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur	Shimano Deore XT SGS	
Crankset	Bontrager Select Pavement 48/36/26	64/104mm bolt hole circle
Bottom bracket	TruVativ Giga-Pipe SL	73 x 113 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Superstock 29" Disc, 28°	596mm ERD
Spokes	DT 14g, ProLock brass nipples, 294/294mm, 3x	
Tire	IRC Mythos XC Slick, folding, 700 x 42c, Velox 22mm rim strip	
Rear wheel	Bontrager Superstock 29" Disc, 28°	596mm ERD
Spokes	DT 14g, ProLock brass nipples, 294/294mm, 3x	
Tire	IRC Mythos XC Slick, folding, 700 x 42c, Velox 22mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	31.6mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder	Alloy w/integral quick-release	36.4mm inner diameter
Brakes	Avid BB-7, mechanical discs	
	160mm discs, 44mm BCD	
Pedals	Shimano SPD M505, clipless	9/16" axle
Additional		

FIT

dimensions in mm, unless specified

Frame	Size	15.5	17.5	19	21
Rider height, in.		68.7	71.9	74.2	75.4
	cm	174	183	189	191
Handlebar	width	600	600	600	600
Stem	length	70	90	105	105
	angle	10	10	10	10
Headset spacers		25	25	25	25
Crank	length	170	175	175	175
Seatpost	length	330	400	400	400
Steerer	length	187.5	187.5	187.5	202.5

GEOMETRY

dimensions in mm, unless specified

Head tube angle	70.5	71.0	71.5	71.5
Fork offset	38.1	38.1	38.1	38.1
Trail	87	83	80	80
Seat tube angle	74.0	74.0	73.5	73.0
Effective top tube	590	608	628	647
Seat tube	394	442	479	529
Standover	695	729	757	799
Wheelbase	1081	1094	1103	1119
Bottom bracket height	292	292	292	297
Chainstay	440	440	440	440
Head tube	90	90	90	105

GEARING

	26	36	48
11	69	95	127
13	58	80	107
15	50	70	93
17	44	61	82
20	38	52	70
23	33	45	61
26	29	40	54
30	25	35	46
34	22	31	41

Fisher Dual Sport

2078600*15.064

FRAMESET

Main tubes	
Stays	
Color	
Fork	Manitou South Super 75mm travel, 483mm axle-crown length
Headset	Aheadset, semi-cartridge 25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Select	25.4mm clamp diameter
Stem	Bontrager Select	50.0mm steerer clamp height
Shift levers	Shimano Deore LX	
Grips	Bontrager Select, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Deore LX	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore XT SGS	
Crankset	Bontrager Select Pavement 48/36/26	64/104mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe SL	73 x 113 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Superstock 29, disc compatible, 32°	604mm ERD
Spokes	DT 14g, ProLock brass nipples, 294/293mm, 3x	
Tire	IRC Mythos XC Slick, folding, 700 x 42c, Velox 22mm rim strip	
Rear wheel	Bontrager Superstock 29, disc compatible, 32°	604mm ERD
Spokes	DT 14g, ProLock brass nipples, 293/294mm, 3x	
Tire	IRC Mythos XC Slick, folding, 700 x 42c, Velox 22mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Select	31.6mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .	Alloy w/integral bolt	36.4mm inner diameter
Brakes	Avid BB-7, mechanical discs	
	160mm discs, 44mm BCD	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	15	17.5	19	21
Rider height, in.		68.9	71.7	74.1	75.3
	cm	175	182	188	191
Handlebar	width	600	600	600	600
Stem	length	70	90	105	105
	angle	10	10	10	10
Headset spacers		25	25	25	25
Crank	length	170	175	175	175
Seatpost	length	330	400	400	400
Steerer	length	187.5	187.5	187.5	202.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	70.5	71.0	71.5
Fork offset	38.1	38.1	38.1	38.1
Trail	79	124	120	117
Seat tube angle	74.0	74.0	73.5	73.0
Effective top tube	590	607	628	647
Seat tube	432	478	503	567
Standover				
Wheelbase	1082	1094	1108	1119
Bottom bracket height	270	270	270	275
Chainstay	440	445	445	445
Head tube	90	90	90	105

GEARING

	26 36 48
11	64 89 119
13	54 75 101
15	47 65 87
17	42 58 77
20	35 49 65
23	31 43 57
26	27 38 50
30	24 33 44
34	21 29 38

Fisher Tyro

2580600
Bike weight: 31.9 lb/14.48 kg

FRAMESET

Main tubes	Silver series aluminum	
Stays	Silver series aluminum	
Color	Yellow/Black • Red decal (boys)	
	Blue/White • White decal (girls)	
Fork.	SR	80mm travel, 469.4mm axle-crown length
Headset	Steel	25.4/34.0/30.0, 36mm stack height

CONTROLS

Handlebar	Great Fit, 22.2mm diameter	25.4mm clamp diameter
Stem	Great Fit, adjustable rise	
Shift levers	SRAM MRX HalfPipe	
Brake levers	Alloy, direct pull, kid's reach	
Grips	Great Fit, 26mm grip size	

DRIVETRAIN

Front derailleur . . .	Shimano Altus	Down pull, 31.8 mm/ 1 1/4" attachment
Rear derailleur . . .	Shimano C050 MegaRange	
Crankset	Great Fit, adjustable 127 to 150mm, 40/32/22, w/chainguard	Riveted chainrings
Bottom bracket . . .	Cartridge	73 (shell x axle,mm), Square axle
Chain.	KMC Z-51	3/32", 104 links
Cassette.	Sun Race 14-34, 7spd	

WHEELSET

Front wheel.	Alloy, nuttet hub, 32°, Aluminum alloy rim	493.8mm ERD
Spokes	14G, 242mm, 2x	
Tire	Bontrager Connection, 24 x 2.0, Rubber rim strip	
Rear wheel	Alloy, nuttet hub, 32°, Aluminum alloy rim	493.8mm ERD
Spokes	14g, 239.5/241.5mm, 2x	
Tire	Bontrager Connection, 24 x 2.0, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost.	Alloy	27.2mm outer diameter
Saddle	Great Fit, sized	
Seatpost binder. . .	Quick release	31.8mm inner diameter
Brakes	Alloy direct pull w/modulator front, Alloy direct pull rear	
Pedals	Great Fit, sized 9/16" axle	
Additional	Derailleur guard	

FIT *dimensions in mm, unless specified*

Frame	Size	12B	12G
Rider height, in.		63.4	55.0
	cm	161	140
Handlebar	width	560	560
Handlebar	rise	30	
Stem	length	70	
	angle	15	
Headset spacers		2	2
Crank	length	127	150
Seatpost	length	300	300
Steerer	length	139.5	139.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.0
Fork offset	38.7	38.7
Trail	62	62
Seat tube angle	72.0	72.0
Effective top tube	523	523
Seat tube	290	290
Standover	565	565
Wheelbase	983	983
Bottom bracket height	262	262
Chainstay	409	409
Head tube	105	105

GEARING

	24	34	42
14	40	57	71
16	35	50	62
18	31	45	55
20	28	40	50
22	26	37	45
24	24	33	41
34	17	24	29

Fisher Cosmo

2578600
Bike weight: 26.0 lb/11.80 kg

FRAMESET

Main tubes	Hi Tensile steel	
Stays	Hi Tensile steel	
Color	Red/Silver • Silver decal (boys)	
	White/Purple • Purple decal (girls)	
Fork	RST 150E, 319mm axle-crown length	
Headset	Steel	25.4/34.0/30.0, 34mm stack height

CONTROLS

Handlebar	Great Fit, 22.2mm diameter	25.4mm clamp diameter
Stem	Great Fit, adjustable rise	
Shift levers	SRAM MRX, right only	
Brake levers	Alloy, direct pull	
Grips	Great Fit, 26mm grip size	

DRIVETRAIN

Rear derailleur	Shimano Tourney TY22	
Crankset	Great Fit, adjustable 120 to 140mm, 36T, w/chainguard	Riveted chainrings
Bottom bracket	One-piece type	68 (shell x axle,mm), One-piece axle
Chain	KMC Z-51	3/32", 96 links
Cassette	HG60 14-28, 6spd	

WHEELSET

Front wheel	Alloy, nuttled hub, 32°, Aluminum alloy rim	420mm ERD
Spokes	14G, 191.5mm, 2x	
Tire	Cross tread, 20 x 1.95, Rubber rim strip	
Rear wheel	Alloy, nuttled hub, 32°, Aluminum alloy rim	420mm ERD
Spokes	14g, 189/191mm, 2x	
Tire	Cross tread, 20 x 1.95, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Steel	29.2mm outer diameter
Saddle	Fisher Padded	
Seatpost binder	Quick release, 47mm	35.0mm inner diameter
Brakes	Alloy direct pull	
Pedals	Platform 1/2" axle	
Additional	Double chainring guards, kickstand, derailleur guard	

FIT *dimensions in mm, unless specified*

Frame	Size	12B	12G
Rider height, in.		57.9	57.9
	cm	147	147
Handlebar	width	540	540
Handlebar	rise	40	40
Stem	length	85	85
	angle	40	40
Headset spacers		2	
Crank	length	140	140
Seatpost	length	300	300
Steerer	length	124.5	124.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.0
Fork offset	38.0	38.0
Trail	49	49
Seat tube angle	72.0	72.0
Effective top tube	505	505
Seat tube	260	260
Standover	439	439
Wheelbase	918	918
Bottom bracket height	250	250
Chainstay	359	359
Head tube	100	100

GEARING

	32
14	46
16	40
18	36
21	31
24	27
28	23

Fisher Gamma Ray

2576000
Bike weight: 2.0 lb/.92 kg

FRAMESET

Main tubes	Hi Tensile steel	
Stays	Hi Tensile steel	
Color	Black • Silver decal (boys)	
	Purple • Pink decal (girls)	
Fork.	Hi Tensile steel, 235mm axle-crown length	
Headset	Steel	22.2/30.0/27.0, 36.5mm stack height

CONTROLS

Handlebar	Great Fit, 15.8mm diameter	22.2mm clamp diameter
Stem	Alloy BMX	
Grips	Great Fit, 17mm grip size	

DRIVETRAIN

Crankset	One-piece type, 28T	1 piecemm bolt hole circle
Bottom bracket	One-piece type	68 (shell x axle,mm), One-piece axle
Chain.	KMC 410	1/8", 70 links
Cassette.	20	

WHEELSET

Front wheel.	Steel hub, 28°, Steel rim	319mm ERD
Spokes	14G, 137mm, 2x	
Tire	Knobby, 16 x 2.125, Rubber rim strip	
Rear wheel	Coaster brake hub, 28°, Steel rim	319mm ERD
Spokes	14g, 137mm, 2x	
Tire	Knobby, 16 x 2.125, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost.	Steel	22.2mm outer diameter
Saddle	Great Fit, sized	
Seatpost binder. . . .	Bolt	25.4mm inner diameter
Brakes	Coaster brake rear	
Pedals	Great Fit, sized 1/2" axle	
Additional	Training wheels, fenders on boys', basket on girls'	

FIT *dimensions in mm, unless specified*

Frame	Size	9 Uni
Rider height, in.		43.2
	cm	110
Handlebar	width	500
Handlebar	rise	130
Stem	length	38
	angle	38
Headset spacers		2
Crank	length	92
Seatpost	length	225
Steerer	length	127

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0
Fork offset	34.0
Trail	33
Seat tube angle	69.5
Effective top tube	404
Seat tube	236
Standover	395
Wheelbase	735
Bottom bracket height	196
Chainstay	308
Head tube	95

GEARING

26
20 20

Fisher Astro

FRAMESET

Main tubes
 Stays
 Color
 Fork., mm axle-crown length
 Headset , mm stack height

CONTROLS

Handlebar mm clamp diameter
 Stem
 Grips

DRIVETRAIN

Crankset mm bolt hole circle
 Bottom bracket (shell x axle,mm), axle
 Chain., links
 Cassette.....

WHEELSET

Rear wheel mm ERD
 Spokes, mm, x
 Tire, , rim strip
 Inner tubes

OTHER

Seatpost..... mm outer diameter
 Saddle
 Seatpost binder... mm inner diameter
 Brakes none
 Pedals axle
 Additional

FIT *dimensions in mm, unless specified*

Frame	Size	
Rider height, in.		0.0
	cm	0
Handlebar	width	
Stem	length	
	angle	
Headset spacers		
Crank	length	
Seatpost	length	
Steerer	length	

GEOMETRY *dimensions in mm, unless specified*

Head tube angle
 Fork offset
 Trail
 Seat tube angle
 Effective top tube
 Seat tube
 Standover
 Wheelbase
 Bottom bracket height
 Chainstay
 Head tube

GEARING

Fisher Sun Spot

2572000114
Bike weight: 20.9 lb/9.49 kg

FRAMESET

Main tubes	Hi Tensile steel	
Stays	Hi Tensile steel	
Color	Blue • Silver decal (boys)	
	Pink • Purple decal (girls)	
Fork.	Hi Tensile steel, 185mm axle-crown length	
Headset	Steel	22.2/30.0/27.0, 36.5mm stack height

CONTROLS

Handlebar	Great Fit, 15.8mm diameter	22.2mm clamp diameter
Stem	Alloy BMX	
Grips	Great Fit, 17mm grip size	

DRIVETRAIN

Crankset	One-piece type, 22T	1 piecemm bolt hole circle
Bottom bracket	One-piece type	68 (shell x axle,mm), One-piece axle
Chain.	KMC 410	1/8", 58 links
Cassette.	20T	

WHEELSET

Front wheel.	Steel hub, 20°, Steel rim	218mm ERD
Spokes	14G, 74mm, 2x	
Tire	Knobby, 12.5 x 2.125, Rubber rim strip	
Rear wheel	Coaster brake hub, 20°, Steel rim	218mm ERD
Spokes	14g, 83.5mm, 2x	
Tire	Knobby, 12.5 x 2.125, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost.	Steel	22.2mm outer diameter
Saddle	Great Fit, sized	
Seatpost binder. . . .	Bolt, M6 x 30	25.4mm inner diameter
Brakes	Coaster brake rear	
Pedals	Great Fit, sized 1/2" axle	
Additional	Training wheels, chainguard, fenders on boys' and basket on girls', and pads	

FIT *dimensions in mm, unless specified*

Frame	Size	8 Uni
Rider height, in.		35.0
	cm	89
Handlebar	width	460
Handlebar	rise	120
Stem	length	50
	angle	38
Headset spacers		2
Crank	length	70
Seatpost	length	225
Steerer	length	125

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0
Fork offset	34.0
Trail	19
Seat tube angle	69.0
Effective top tube	336
Seat tube	200
Standover	331
Wheelbase	605
Bottom bracket height	146
Chainstay	235
Head tube	90

GEARING

22
20 13

Fisher Starfish

2570000114
Bike weight: 20.9 lb/9.49 kg

FRAMESET

Main tubes	Hi Tensile steel	
Stays	Hi Tensile steel	
Color	Ice Blue/Silver • White/Black/Silver decal • Ice Blue fork Light Metallic Blue/Silver • White/Black/Silver decal • Light Metallic Blue fork	
Fork.	Hi Tensile steel, 185mm axle-crown length	
Headset	Steel	22.2/30.0/27.0, 36.5mm stack height

CONTROLS

Handlebar	Dialed Child, 15.8mm diameter	mm clamp diameter
Stem	Cruiser	
Grips	Great Fit, 17mm grip size	

DRIVETRAIN

Crankset	One-piece type, 24T	1 piecemm bolt hole circle
Bottom bracket	One-piece type	68 (shell x axle,mm), One-piece axle
Chain.	KMC 410	1/8", 60 links
Cassette.	19	

WHEELSET

Front wheel.	Steel hub, 20°, Steel rim	218mm ERD
Spokes	14G, 74mm, 2x	
Tire	Cruiser Balloon, 12.5 x 2.125, Rubber rim strip	
Rear wheel	Coaster brake hub, 20°, Steel rim	218mm ERD
Spokes	14g, 83.5mm, 2x	
Tire	Cruiser Balloon, 12.5 x 2.125, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost.	Steel (one piece post and saddle)	25.4mm outer diameter
Saddle	Trek padded	
Seatpost binder. . . .	Bolt, M6 x 30	28.6mm inner diameter
Brakes	Coaster brake rear	
Pedals	Great Fit, sized 1/2" axle	
Additional	Training wheels	

FIT *dimensions in mm, unless specified*

Frame	Size	8B
Rider height, in.		32.8
	cm	83
Handlebar	width	470
Handlebar	rise	80
Stem	length	50
	angle	48
Headset spacers		2
Crank	length	70
Seatpost	length	225
Steerer	length	124

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0
Fork offset	9.0
Trail	44
Seat tube angle	73.3
Effective top tube	318
Seat tube	223
Standover	357
Wheelbase	585
Bottom bracket height	161
Chainstay	235
Head tube	90

GEARING

	24
19	15

Fisher Freeloader 241

FRAMESET

Main tubes Hi Tensile steel
 Stays Hi Tensile steel
 Color Silver/Metallic Black • Dark Silver/Black/White decals

CONTROLS

Handlebar BMX 25.4mm clamp diameter
 Stem Alloy adjustable rise, quick change, quill
 Grips Kraton

DRIVETRAIN

Crankset One-piece type, 42T mm bolt hole circle
 Bottom bracket One-piece type 68 (shell x axle,mm), axle
 Chain KMC Z-51 1/8", 88 links
 Cassette 16T

WHEELSET

Rear wheel Alloy, nitted hub, 36°, Aluminum alloy rim 524mm ERD
 Spokes 14g, 188.5mm, 2x
 Tire Cross tread, 20 x 1.75, Rubber rim strip
 Inner tubes Schraeder valve

OTHER

Seatpost Suspension 25.4mm outer diameter
 Saddle Trek padded
 Seatpost binder Alloy w/integral bolt 28.6mm inner diameter
 Brakes none
 Pedals Platform 1/2" axle
 Additional Handlebar pad, visibility flag

FIT *dimensions in mm, unless specified*

Frame	Size	
Rider height, in.		0.0
	cm	0
Handlebar	width	530
Handlebar	rise	150
Stem	length	85
	angle	5
Headset spacers		
Crank	length	127
Seatpost	length	300
Steerer	length	

GEOMETRY *dimensions in mm, unless specified*

Head tube angle
 Fork offset
 Trail
 Seat tube angle
 Effective top tube
 Seat tube 286
 Standover
 Wheelbase
 Bottom bracket height
 Chainstay
 Head tube

GEARING

42
16 62

Fisher Freeloader 206

FRAMESET

Main tubes Hi Tensile steel
 Stays Hi Tensile steel
 Color Silver/Metallic Champagne • Dark Silver/Black/White decals

CONTROLS

Handlebar BMX 25.4mm clamp diameter
 Stem Alloy adjustable rise, quick change, quill
 Shift levers SRAM MRX
 Grips Kraton

DRIVETRAIN

Rear derailleur Shimano Tourney TY-22
 Crankset One-piece type, 42T mm bolt hole circle
 Bottom bracket One-piece type 68 (shell x axle,mm), Square axle
 Chain 3/32", 104 links
 Cassette Sun Race 14-28, 6spd

WHEELSET

Rear wheel Alloy, nuttet hub, 36°, Aluminum alloy rim 420mm ERD
 Spokes 14g, 188.5/191mm, 2x
 Tire Cross tread, 20 x 1.75, Rubber rim strip
 Inner tubes Schraeder valve

OTHER

Seatpost Steel 25.4mm outer diameter
 Saddle Trek padded
 Seatpost binder Alloy w/integral bolt 28.6mm inner diameter
 Brakes none
 Pedals Platform 1/2" axle
 Additional Handlebar pad, visibility flag

FIT *dimensions in mm, unless specified*

Frame	Size	12
Rider height, in.		0.0
	cm	0
Handlebar	width	550
Handlebar	rise	150
Stem	length	85
	angle	5
Headset spacers		
Crank	length	127
Seatpost	length	300
Steerer	length	

GEOMETRY *dimensions in mm, unless specified*

Head tube angle
 Fork offset
 Trail
 Seat tube angle
 Effective top tube
 Seat tube 266
 Standover
 Wheelbase
 Bottom bracket height
 Chainstay
 Head tube

GEARING

	42
14	60
16	53
18	47
21	40
24	35
28	30

Fisher Freeloader 201

FRAMESET

Main tubes Hi Tensile steel
 Stays Hi Tensile steel
 Color Silver/Metallic Red • Black/White/Silver decals

CONTROLS

Handlebar BMX 25.4mm clamp diameter
 Stem Alloy adjustable rise, quick change, quill
 Grips Kraton

DRIVETRAIN

Crankset One-piece type, 42T mm bolt hole circle
 Bottom bracket One-piece type 68 (shell x axle,mm), Square axle
 Chain KMC Z-51 1/8", 88 links
 Cassette 16T

WHEELSET

Rear wheel Alloy, nitted hub, 36°, Aluminum alloy rim 420mm ERD
 Spokes 14g, 188.5/188.5mm, 2x
 Tire Cross tread, 20 x 1.75, Rubber rim strip
 Inner tubes Schraeder valve

OTHER

Seatpost Steel 25.4mm outer diameter
 Saddle Trek padded
 Seatpost binder Alloy w/integral bolt 28.6mm inner diameter
 Brakes none
 Pedals Platform 1/2" axle
 Additional Handlebar pad, visibility flag

FIT *dimensions in mm, unless specified*

Frame	Size	10.5
Rider height, in.		0.0
	cm	0
Handlebar	width	530
Handlebar	rise	150
Stem	length	85
	angle	5
Headset spacers		
Crank	length	127
Seatpost	length	300
Steerer	length	

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	
Fork offset	
Trail	?
Seat tube angle	
Effective top tube	
Seat tube	266
Standover	
Wheelbase	
Bottom bracket height	
Chainstay	
Head tube	

GEARING

	42
16	53

Klein Palomino XV

4157600*15.104
Bike weight: 27.5 lb/12.49 kg

FRAMESET

Main tubes	Klein Gradient ZR9000 aluminum	
Stays	Klein Gradient ZR9000 aluminum	
Color	Deep Blue	
Fork	Maverick SC 32, 85-125mm adjustable travel	100mm travel,
	470.9mm axle-crown length	
Rear shock	Palomino custom, 2.36 stroke, length, width, eyes	
Headset	Cane Creek S-6 Aheadset, alloy	25.4/34.0/30.0, 27.1mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Race Lite	31.8mm clamp diameter
Stem	Bontrager Race X Lite	40.0mm steerer clamp height
Shift levers	Shimano Deore XT	
Brake levers	Integrated brake/shift	
Grips	Klein Instinct	

DRIVETRAIN

Front derailleur	Shimano XTR	Down pull, Plate style attachment
Rear derailleur	Shimano Deore XT SGS	
Crankset	Shimano Deore XT 44/32/22	64/104mm bolt hole circle
Bottom bracket	integral axle	73 (shell x axle,mm), Integral axle
Chain	Shimano HG-73	9 speed, 108 links
Cassette	SRAM PG970 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Race Lite Disc, tubeless compatible, 28°	537mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 266/267mm, 3x	
Tire	Bontrager Super-X, tubeless ready, 127tpi, 52/52, Tubeless assymetric rim strip	
Rear wheel	Bontrager Race Lite Disc, tubeless compatible, 28°	537mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 266/267mm, 3x	
Tire	Bontrager Super-X, tubeless ready, 127tpi, 52/52, Tubeless assymetric rim strip	
Inner tubes	Presta valve, ultra light	

OTHER

Seatpost	Bontrager Race Lite	31.6mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder	Alloy w/integral bolt	38.3mm inner diameter
Brakes	Shimano Deore XT, hydraulic discs	
	160mm discs, 44mm BCD	
Disc hose, mm	16 17.5 19 21	
Front	650 650 750 750	
Rear	1350 1350 1400 1400	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional	Wrench Force pump,	

FIT *dimensions in mm, unless specified*

Frame	Size	16	17.5	19	21
Rider height, in.		71.1	72.9	74.3	77.0
	cm	181	185	189	196
Handlebar	width	630	630	630	630
Handlebar	rise	25	25	25	25
Stem	length	100	120	120	130
	angle	7	7	7	7
Headset spacers		30	30	30	30
Crank	length	175	175	175	175
Seatpost	length	330	330	400	400
Steerer	length	198.1	198.1	218.1	258.1

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	71.0	71.0	71.0
Fork offset	38.0	38.1	38.1	38.1
Trail	75	75	75	75
Seat tube angle	75.8	76.0	75.9	75.5
Effective top tube	568	575	584	594
Seat tube	404	445	483	533
Standover	749	760	776	825
Wheelbase	1088	1099	1108	1118
Bottom bracket height	310	310	310	310
Chainstay	439	439	439	439
Head tube	105	105	125	165

GEARING

	22 32 44
11	52 76 105
13	44 65 89
15	38 56 77
17	34 49 68
20	29 42 58
23	25 36 50
26	22 32 44
30	19 28 38
34	17 25 34

Klein Attitude XX

4028600*15.015
Bike weight: 24.4 lb/11.08 kg

FRAMESET

Main tubes	Klein Gradient ZR9000 aluminum	
Stays	Klein Gradient ZR9000 aluminum	
Color	Blazing Lupine	
Fork	Maverick SC 32, 85-125mm adjustable travel	100mm travel,
	470.9mm axle-crown length	
Headset	Cane Creek S-6 Aheadset, alloy	25.4/34.0/30.0, 27.1mm stack height

CONTROLS

Handlebar	Bontrager Race XXX Lite	31.8mm clamp diameter
Stem	Bontrager Race X Lite	41.0mm steerer clamp height
Shift levers	Shimano Deore XT	
Brake levers	Integrated brake/shift	
Grips	Klein Instinct	

DRIVETRAIN

Front derailleur . . .	Shimano XTR	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano XTR Low-Normal	
Crankset	Shimano XTR 44/32/22	64/104mm bolt hole circle
Bottom bracket . . .	integral axle	73 (shell x axle,mm), Integral axle
Chain	Shimano Dura-Ace	9 speed, 108 links
Cassette	Shimano XTR 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Race Lite Disc, tubeless compatible, 28°	537mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 266/267mm, 3x	
Tire	Bontrager Super-X, tubeless ready, 127tpi, 52/52, Tubeless assymetric rim strip	
Rear wheel	Bontrager Race Lite Disc, tubeless compatible, 28°	537mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 266/267mm, 3x	
Tire	Bontrager Super-X, tubeless ready, 127tpi, 52/52, Tubeless assymetric rim strip	
Inner tubes	Presta valve, ultra light	

OTHER

Seatpost	Bontrager Race XXX Lite	31.6mm outer diameter
Saddle	Fizik Arione, Ti rails	
Seatpost binder . . .	Alloy w/integral bolt	36.4mm inner diameter
Brakes	Shimano XTR, hydraulic discs	
	160mm discs, 44mm BCD	
Disc hose, mm	14 16 17.5 19 21	
Front	750 750 750 750 750	
Rear	1300 1300 1350 1350 1400	
Pedals	-not supplied- 9/16" axle	
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	14	16	17.5	19	21
Rider height, in.		65.9	68.6	71.4	73.1	76.5
	cm	167	174	181	186	194
Handlebar	width	600	600	600	600	600
Stem	length	90	100	120	120	130
	angle	7	7	7	7	7
Headset spacers		25	25	25	25	25
Crank	length	170	175	175	175	175
Seatpost	length	330	330	400	400	400
Steerer	length	193.1	193.1	193.1	213.1	253.1

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.2	70.7	71.3	71.4	71.4
Fork offset	38.0	38.1	38.1	38.1	38.1
Trail	80	77	73	73	73
Seat tube angle	72.7	72.7	72.8	72.8	72.8
Effective top tube	551	575	596	612	628
Seat tube	356	400	445	489	533
Standover	659	700	735	772	815
Wheelbase	1017	1038	1055	1072	1090
Bottom bracket height	290	295	300	303	305
Chainstay	417	417	417	417	417
Head tube	105	105	105	125	165

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Klein Attitude XV

4026600*15.084
Bike weight: 25.3 lb/11.49 kg

FRAMESET

Main tubes	Klein Gradient ZR9000 aluminum	
Stays	Klein Gradient ZR9000 aluminum	
Color	Ferrous Sunset	
Fork	Fox FR-LT	100mm travel, 470.9mm axle-crown length
Headset	Alloy aheadset, semi-cartridge	25.4/34.0/30.0, 27.2mm stack height

CONTROLS

Handlebar	Bontrager Race X Lite	31.8mm clamp diameter
Stem	Bontrager Race X Lite	41.0mm steerer clamp height
Shift levers	Shimano Deore XT	
Brake levers	Integrated brake/shift	
Grips	Klein Instinct	

DRIVETRAIN

Front derailleur . . .	Shimano Deore XT	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore XT SGS	
Crankset	Shimano Deore XT 44/32/22	64/104mm bolt hole circle
Bottom bracket . . .	integral axle	73 (shell x axle,mm), Integral axle
Chain	Shimano HG-73	9 speed, 108 links
Cassette	SRAM PG970 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Race Lite Disc, tubeless compatible, 28°	537mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 266/267mm, 3x	
Tire	Bontrager Super-X, tubeless ready, 127tpi, 52/52, Tubeless assymetric rim strip	
Rear wheel	Bontrager Race Lite Disc, tubeless compatible, 28°	537mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 266/267mm, 3x	
Tire	Bontrager Super-X, tubeless ready, 127tpi, 52/52, Tubeless assymetric rim strip	
Inner tubes	Presta valve, ultra light	

OTHER

Seatpost	Bontrager Race Lite	31.6mm outer diameter
Saddle	Bontrager FS2000, CrMo rails, leather cover	
Seatpost binder . . .	Alloy w/integral bolt	36.4mm inner diameter
Brakes	Shimano Deore XT, hydraulic discs	
	160mm discs, 44mm BCD	
Disc hose, mm	14 16 17.5 19 21	
Front	750 750 750 750 750	
Rear	1350 1350 1350 1400 1400	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	14	16	17.5	19	21
Rider height, in.		65.9	68.6	71.5	73.1	76.5
	cm	167	174	181	186	194
Handlebar	width	600	600	600	600	600
Stem	length	90	100	120	120	130
	angle	7	7	7	7	7
Headset spacers		25	25	25	25	25
Crank	length	170	175	175	175	175
Seatpost	length	330	330	400	400	400
Steerer	length	193.2	193.2	193.2	213.2	253.2

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.2	70.7	71.3	71.4	71.4
Fork offset	38.0	38.1	38.1	38.1	38.1
Trail	80	77	73	73	73
Seat tube angle	72.7	72.7	72.8	72.8	72.8
Effective top tube	551	575	596	612	628
Seat tube	356	400	445	489	533
Standover	659	700	735	772	815
Wheelbase	1017	1038	1055	1072	1090
Bottom bracket height	290	295	300	303	305
Chainstay	417	417	417	417	417
Head tube	105	105	105	125	165

GEARING

	22 32 44
11	52 76 105
13	44 65 89
15	38 56 77
17	34 49 68
20	29 42 58
23	25 36 50
26	22 32 44
30	19 28 38
34	17 25 34

Klein

Attitude V

Disc

4023600*25.124

Bike weight: 26.3 lb/11.94 kg

FRAMESET

Main tubes	Klein Gradient ZR9000 aluminum	
Stays	Klein Gradient ZR9000 aluminum	
Color	Deep Blue	
Fork	RockShox Duke Race	80mm travel, 451mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Select	25.4mm clamp diameter
Stem	Bontrager Race	41.0mm steerer clamp height
Shift levers	Shimano Deore	
Brake levers	Hydraulic, attached to brake	
Grips	Klein Instinct	

DRIVETRAIN

Front derailleur . . .	Shimano Deore LX	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur	Shimano Deore XT SGS	
Crankset	Bontrager Race 44/32/22	64/104mm bolt hole circle
Bottom bracket	TruVativ Giga-Pipe	73 x 113 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Race Disc, tubeless compatible, 28°	537mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 264/266mm, 3x	
Tire	Klein Deathgrip, folding, 26 x 2.35, Tubeless assymetric rim strip	
Rear wheel	Bontrager Race, tubeless compatible, disc compatible, 28°	542mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 264/265mm, 3x	
Tire	Klein Deathgrip, folding, 26 x 2.35, Tubeless assymetric rim strip	
Inner tubes	Presta valve, ultra light	

OTHER

Seatpost	Bontrager Select	31.6mm outer diameter
Saddle	Bontrager Select	
Seatpost binder	Alloy w/integral bolt	36.4mm inner diameter
Brakes	Hayes HFX-9, hydraulic discs	
	6.3 in. discs, 44mm BCD	
Disc hose, mm	14 16 17.5 19 21	
Front	690 690 690 750 750	
Rear	1280 1280 1350 1350 1350	
Pedals	Shimano SPD M505, clipless	9/16" axle
Additional		

FIT dimensions in mm, unless specified

Frame	Size	14	16	17.5	19	21
Rider height, in.		64.9	67.6	70.5	72.2	75.6
	cm	165	172	179	183	192
Handlebar	width	600	600	600	600	600
Stem	length	90	100	120	120	130
	angle	10	10	10	10	10
Headset spacers		25	25	25	25	25
Crank	length	170	175	175	175	175
Seatpost	length	330	330	400	400	400
Steerer	length	193.5	193.5	193.5	213.5	253.5

GEOMETRY dimensions in mm, unless specified

Head tube angle	70.2	70.7	71.3	71.4	71.4
Fork offset	38.0	38.1	38.1	38.1	38.1
Trail	80	77	73	73	73
Seat tube angle	72.7	72.7	72.8	72.8	72.8
Effective top tube	551	575	596	612	628
Seat tube	356	400	445	489	533
Standover	659	700	735	772	815
Wheelbase	1017	1038	1055	1072	1090
Bottom bracket height	290	295	300	303	305
Chainstay	417	417	417	417	417
Head tube	105	105	105	125	165

GEARING

	22 32 44
11	52 76 105
13	44 65 89
15	38 56 77
17	34 49 68
20	29 42 58
23	25 36 50
26	22 32 44
30	19 28 38
34	17 25 34

Klein

Reve XX

4428000*15.094
Bike weight: 18.3 lb/8.31 kg

FRAMESET

Main tubes	Klein Gradient ZR9000 aluminum	
Stays	OCLV 120 carbon fiber composite	
Color	Havana Citrus	
Fork	Bontrager Race, long, 379.9mm axle-crown length	
Rear shock	S.P.A.	
Headset	Cane Creek IS-2, integrated	25.4/34.0/30.0, 17.0mm stack height

CONTROLS

Handlebar	Bontrager Race Lite Flat Top	31.8mm clamp diameter
Stem	Bontrager Race X Lite	40.0mm steerer clamp height
Shift levers	Shimano Dura-Ace STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager	

DRIVETRAIN

Front derailleur . . .	Shimano Dura-Ace	Down pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Dura-Ace	
Crankset	Bontrager Race X Lite 50/36 w/Giga-X-Pipe	64/104mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano Dura-Ace	10 speed, 108 links
Cassette	Shimano Dura-Ace 12-27, 10spd	

WHEELSET

Front wheel	Bontrager Race Lite, 20°	592mm ERD
Spokes	DT New Aero, ProLock alloy nipples, 279mm, radial	
Tire	Bontrager Race Lite, folding, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Race Lite, 24°	595mm ERD
Spokes	DT New Aero, T-head drive side, ProLock alloy nipples, 291/293mm, 2x	
Tire	Bontrager Race Lite, folding, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race XXX Lite	31.6mm outer diameter
Saddle	Fizik Aliante Sport	
Seatpost binder . . .	Alloy w/integral bolt	36.4mm inner diameter
Brakes	Shimano Ultegra, long reach	
Pedals	-not supplied- 9/16" axle	
Additional	BuzzKill	

FIT *dimensions in mm, unless specified*

Frame Size	49	52	55	58	61
Rider height, in.	67.2	68.9	71.4	74.5	75.9
cm	171	175	181	189	193
Handlebar width	400	420	420	440	460
Handlebar rise	0	0	0	0	0
Stem length	80	90	100	110	110
angle	7	7	7	7	7
Headset spacers	33	33	33	33	33
Crank length	170	170	175	175	175
Seatpost length	330	330	330	330	330
Steerer length	189.0	209.5	237.5	264.5	295.0

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.5	71.8	73.0	73.5	73.5
Fork offset	45.0	45.0	45.0	45.0	45.0
Trail	67	65	58	54	54
Seat tube angle	74.3	74.0	73.5	73.5	72.5
Effective top tube	530	535	555	575	595
Seat tube	518	526	530	544	561
Standover	727	747	763	783	801
Wheelbase	997	999	1003	1018	1027
Bottom bracket height	267	268	269	269	271
Chainstay	424	424	424	424	424
Head tube	103	124	152	179	209

GEARING

	36 50
12	81 112
13	75 104
14	69 96
15	65 90
16	61 84
17	57 79
19	51 71
21	46 64
23	42 59 0
25	39 54 0

Klein Reve X

4426000*15.084
Bike weight: 19.5 lb/8.85 kg

FRAMESET

Main tubes	Klein Gradient ZR9000 aluminum
Stays	OCLV 120 carbon fiber composite
Color	Silver Thunder
Fork	Bontrager Race, long, 379.9mm axle-crown length
Rear shock	S.P.A.
Headset	Cane Creek IS-2, integrated 25.4/34.0/30.0, 17.0mm stack height

CONTROLS

Handlebar	Bontrager Race	26.0mm clamp diameter
Stem	Bontrager Race	40.0mm steerer clamp height
Shift levers	Campagnolo Veloce Ergopower	
Brake levers	Integrated brake/shift	
Grips	Bontrager	

DRIVETRAIN

Front derailleur	Campagnolo Veloce T	Down pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur	Campagnolo Veloce GS	
Crankset	Campagnolo Veloce 52/42/30	74/130mm bolt hole circle
Bottom bracket	Campagnolo Centaur	68 x 115 (shell x axle,mm), Square axle
Chain	Campagnolo	10 speed, 108 links
Cassette	Campagnolo Veloce 12-25, 10spd	

WHEELSET

Front wheel	Campagnolo Vento G3, 24°	mm ERD
Spokes	DT New Aero, ProLock brass nipples, 280mm, radial	
Tire	Bontrager Race Lite, folding, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Campagnolo Vento G3, 27°	mm ERD
Spokes	DT New Aero, ProLock brass nipples, mm, 3/radialx	
Tire	Bontrager Race Lite, folding, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race	31.6mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder	Alloy w/integral bolt	36.4mm inner diameter
Brakes	Shimano Ultegra, long reach	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional	BuzzKill	

FIT

dimensions in mm, unless specified

Frame	Size	49	52	55	58	61
Rider height, in.		67.7	68.1	71.0	74.1	75.5
	cm	172	173	180	188	192
Handlebar	width	400	420	420	440	460
Stem	length	90	90	100	110	110
	angle	7	7	7	7	7
Headset spacers		33	33	33	33	33
Crank	length	170	170	175	175	175
Seatpost	length	330	330	330	330	330
Steerer	length	189.0	209.5	237.5	264.5	295.0

GEOMETRY

dimensions in mm, unless specified

Head tube angle	71.5	71.8	73.0	73.5	73.5
Fork offset	45.0	45.0	45.0	45.0	45.0
Trail	67	65	58	54	54
Seat tube angle	74.3	74.0	73.5	73.5	72.5
Effective top tube	530	535	555	575	595
Seat tube	518	526	530	544	561
Standover	727	747	763	783	801
Wheelbase	997	999	1003	1018	1027
Bottom bracket height	267	268	269	269	271
Chainstay	424	424	424	424	424
Head tube	103	124	152	179	209

GEARING

	30	42	52
12	67	94	117
13	62	87	108
14	58	81	100
15	54	75	93
16	50	71	88
17	48	67	82
19	43	60	74
21	38	54	67
23	35	49	61
25	32	45	56

FRAMESET

Main tubes	Klein Gradient ZR9000 aluminum	
Stays	OCLV 120 carbon fiber composite	
Color	Deep Blue	
Fork	Bontrager Race, long, 379.9mm axle-crown length	
Rear shock	S.P.A.	
Headset	Cane Creek IS-2, integrated	25.4/34.0/30.0, 17.0mm stack height

CONTROLS

Handlebar	Bontrager Race	26.0mm clamp diameter
Stem	Bontrager Race	40.0mm steerer clamp height
Shift levers	Shimano 105 STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager	

DRIVETRAIN

Front derailleur . . .	Shimano 105 T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur . . .	Shimano 105 GS	
Crankset	Shimano 105 52/42/30	74/130mm bolt hole circle
Bottom bracket . . .	Shimano 105	68 x 118 (shell x axle,mm), Shimano splined axle
Chain	Shimano HG-73	9 speed, 110 links
Cassette	SRAM PG970 12-26, 9spd	

WHEELSET

Front wheel	Bontrager Race, 20°	593mm ERD
Spokes	DT New Aero, ProLock brass nipples, 280mm, radial	
Tire	Bontrager Race Lite, folding, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Race, 24°	603mm ERD
Spokes	DT New Aero, ProLock brass nipples, 294/294mm, 2x	
Tire	Bontrager Race Lite, folding, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race	31.6mm outer diameter
Saddle	Bontrager Race, hollow CrMo rails	
Seatpost binder . . .	Alloy w/integral bolt	36.4mm inner diameter
Brakes	Shimano Ultegra, long reach	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	49	52	55	58	61
Rider height, in.		66.9	67.3	71.0	74.1	75.5
	cm	170	171	180	188	192
Handlebar	width	400	420	420	440	460
Stem	length	80	80	100	110	110
	angle	7	7	7	7	7
Headset spacers		33	33	33	33	33
Crank	length	170	170	175	175	175
Seatpost	length	330	330	330	330	330
Steerer	length	189.0	209.5	237.5	264.5	295.0

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.5	71.8	73.0	73.5	73.5
Fork offset	45.0	45.0	45.0	45.0	45.0
Trail	67	65	58	54	54
Seat tube angle	74.3	74.0	73.5	73.5	72.5
Effective top tube	530	535	555	575	595
Seat tube	518	526	530	544	561
Standover	727	747	763	783	801
Wheelbase	997	999	1003	1018	1027
Bottom bracket height	267	268	269	269	271
Chainstay	424	424	424	424	424
Head tube	103	124	152	179	209

GEARING

	30 42 52
12	67 94 117
13	62 87 108
14	58 81 100
15	54 75 93
17	48 67 82
19	43 60 74
21	38 54 67
23	35 49 61
26	31 44 54

FRAMESET

Main tubes	Klein Gradient ZR9000 aluminum
Stays	OCLV 120 carbon fiber composite
Color	Vulcan Ember
Fork	Bontrager Race X Lite, OCLV 120 carbon, 379mm axle-crown length
Headset	Airheadset lower, Cane Creek integrated upper 25.4/34.0-1.75"/33.4, 6.5mm stack height

CONTROLS

Handlebar	Bontrager Race X Lite	31.8mm clamp diameter
Stem	Bontrager Race XXX Lite	40.0mm steerer clamp height
Shift levers	Campagnolo Record Ergopower	
Brake levers	Integrated brake/shift	
Grips	Bontrager	

DRIVETRAIN

Front derailleur . . .	Campagnolo Record	Down pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Campagnolo Record	
Crankset	Campagnolo Record Carbon 53/39	130mm bolt hole circle
Bottom bracket . . .	Campagnolo Record	68 x 102 (shell x axle,mm), Square axle
Chain	Campagnolo Record 10	9 speed, 108 links
Cassette	Campagnolo Record 12-25, 10 speed	

WHEELSET

Front wheel	Bontrager Race X Lite, 20°	592mm ERD
Spokes	DT Aerolite nail-head, internal alloy nipples, 286mm, radial	
Tire	Bontrager Race X Lite Pro, folding, 700 x 23c, Bontrager, 17.5mm rim strip	
Rear wheel	Bontrager Race X Lite, 24°	595mm ERD
Spokes	DT New Aero, Aerolite nail-head non-drive side, internal alloy nipples, 291/286mm, 2x/radial	
Tire	Bontrager Race X Lite Pro, folding, 700 x 23c, Bontrager, 17.5mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race XXX Lite	31.6mm outer diameter
Saddle	Fizik Arione, Ti rails	
Seatpost binder . . .	Alloy w/integral bolt	36.4mm inner diameter
Brakes	Campagnolo Record	
Pedals	-not supplied- 9/16" axle	
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	49	52	54	56	58	61
Rider height, in.		64.8	67.7	70.0	72.4	74.7	76.5
	cm	165	172	178	184	190	194
Handlebar	width	400	400	420	420	440	460
Stem	length	70	80	90	100	110	110
	angle	12	12	12	12	12	12
Headset spacers		40	40	40	40	40	40
Crank	length	170	170	172.5	172.5	175	175
Seatpost	length	250	250	330	330	330	330
Steerer	length	174.0	191.0	210.0	226.5	247.0	281.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.5	72.7	72.8	73.9	73.9	74.0
Fork offset	41.0	41.0	41.0	35.0	35.0	35.0
Trail	64	63	62	62	62	61
Seat tube angle	74.0	73.5	73.5	73.5	73.3	73.3
Effective top tube	524	547	560	572	587	606
Seat tube	444	500	567	587	608	638
Standover	691	734	786	819	828	860
Wheelbase	964	983	996	993	1006	1025
Bottom bracket height	260	263	265	267	269	272
Chainstay	414	414	414	414	414	414
Head tube	92	109	128	144	168	199

GEARING

	39 53
12	86 117
13	79 108
14	74 100
15	69 93
16	64 88
17	61 82
19	54 74
21	49 67
23	45 61 0
25	41 56 0

Klein

Q-Pro XV

4464000*15.114
Bike weight: 18.3 lb/8.31 kg

FRAMESET

Main tubes	Klein Gradient ZR9000 aluminum	
Stays	OCV 120 carbon fiber composite	
Color	Electric Lime	
Fork	Bontrager Race X Lite, OCLV 120 carbon, 379mm axle-crown length	
Headset	Airheadset lower, Cane Creek integrated upper	25.4/34.0-1.75"/33.4, 6.5mm stack height

CONTROLS

Handlebar	Bontrager Race Lite Flat Top	31.8mm clamp diameter
Stem	Bontrager Race Lite	40.0mm steerer clamp height
Shift levers	Campagnolo Centaur Ergopower	
Brake levers	Integrated brake/shift	
Grips	Bontrager	

DRIVETRAIN

Front derailleur . . .	Campagnolo Centaur	Down pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Campagnolo Centaur	
Crankset	Campagnolo Centaur 53/39	130mm bolt hole circle
Bottom bracket . . .	Campagnolo Centaur	68 x 118 (shell x axle,mm), Square axle
Chain	Campagnolo	10 speed, 108 links
Cassette	Campagnolo Veloce 12-25, 10spd	

WHEELSET

Front wheel	Bontrager Race Lite, 20°	592mm ERD
Spokes	DT New Aero, ProLock alloy nipples, 279mm, radial	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Velox 16mm rim strip	
Rear wheel	Bontrager Race Lite, 24°	595mm ERD
Spokes	DT New Aero, T-head drive side, ProLock alloy nipples, 291/293mm, 2x	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race X Lite	31.6mm outer diameter
Saddle	Fizik Arione, Ti rails	
Seatpost binder . . .	Alloy w/integral bolt	36.4mm inner diameter
Brakes	Campagnolo Centaur front, Campagnolo Centaur rear	
Pedals	-not supplied- 9/16" axle	
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	49	52	54	56	58	61
Rider height, in.		65.4	68.2	70.4	72.8	74.8	77.1
	cm	166	173	179	185	190	196
Handlebar	width	400	400	420	420	440	460
Handlebar	rise	0	0	0	0	0	0
Stem	length	70	80	90	100	110	110
	angle	7	7	7	7	7	7
Headset spacers		40	40	40	40	40	40
Crank	length	170	170	172.5	172.5	175	175
Seatpost	length	250	250	330	330	330	330
Steerer	length	174.0	191.0	210.0	226.5	250.0	281.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.5	72.7	72.8	73.9	73.9	74.0
Fork offset	41.0	41.0	41.0	35.0	35.0	35.0
Trail	64	63	62	62	62	61
Seat tube angle	74.0	73.5	73.5	73.5	73.3	73.3
Effective top tube	524	547	560	572	587	606
Seat tube	444	500	567	587	608	638
Standover	691	734	786	819	828	860
Wheelbase	964	983	996	993	1006	1025
Bottom bracket height	260	263	265	267	269	272
Chainstay	414	414	414	414	414	414
Head tube	92	109	128	144	168	199

GEARING

	39 53
12	86 117
13	79 108
14	74 100
15	69 93
16	64 88
17	61 82
19	54 74
21	49 67
23	45 61 0
25	41 56 0

FRAMESET

Main tubes	Klein Gradient ZR9000 aluminum	
Stays	OCV 120 carbon fiber composite	
Color	Blazing Lupine	
Fork	Bontrager Race X Lite, OCLV 120 carbon, 379mm axle-crown length	
Headset	Airheadset lower, Cane Creek integrated upper	25.4/34.0-1.75"/33.4,
	6.5mm stack height	

CONTROLS

Handlebar	Bontrager Race Lite	31.8mm clamp diameter
Stem	Bontrager Race Lite	40.0mm steerer clamp height
Shift levers	Shimano 105 STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager	

DRIVETRAIN

Front derailleur . . .	Shimano 105	Down pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano 105	
Crankset	Shimano 105 53/39	130mm bolt hole circle
Bottom bracket . . .	Shimano 105	68 x 109.5 (shell x axle,mm), Shimano splined axle
Chain	Shimano HG-73	9 speed, 108 links
Cassette	SRAM PG970 12-26, 9spd	

WHEELSET

Front wheel	Bontrager Race, 20°	593mm ERD
Spokes	DT New Aero, ProLock brass nipples, 280mm, radial	
Tire	Bontrager Race Lite, folding, 700 x 23c, Velox 16mm rim strip	
Rear wheel	Bontrager Race, 24°	603mm ERD
Spokes	DT New Aero, ProLock brass nipples, 294/294mm, 2x	
Tire	Bontrager Race Lite, folding, 700 x 23c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race Lite	31.6mm outer diameter
Saddle	Fizik Aliante Sport	
Seatpost binder . . .	Alloy w/integral bolt	36.4mm inner diameter
Brakes	Shimano 105	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	49	52	54	56	58	61
Rider height, in.		65.1	67.6	69.9	72.2	74.5	76.8
	cm	165	172	177	183	189	195
Handlebar	width	400	400	420	420	440	460
Stem	length	70	80	90	100	110	110
	angle	7	7	7	7	7	7
Headset spacers		40	40	40	40	40	40
Crank	length	170	170	172.5	172.5	175	175
Seatpost	length	250	250	330	330	330	330
Steerer	length	174.0	191.0	210.0	226.5	250.0	281.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.5	72.7	72.8	73.9	73.9	74.0
Fork offset	41.0	41.0	41.0	35.0	35.0	35.0
Trail	64	63	62	62	62	61
Seat tube angle	74.0	73.5	73.5	73.5	73.3	73.3
Effective top tube	524	547	560	572	587	606
Seat tube	444	500	567	587	608	638
Standover	691	734	786	819	828	860
Wheelbase	964	983	996	993	1006	1025
Bottom bracket height	260	263	265	267	269	272
Chainstay	414	414	414	414	414	414
Head tube	92	109	128	144	168	199

GEARING

	39 53
12	86 117
13	79 108
14	74 100
15	69 93
17	61 82
19	54 74
21	49 67
23	45 61
26	40 54 0

LeMond Tete de Course

3486000*15.104
Bike weight: 16.1 lb/7.31 kg

FRAMESET

Main tubes	True Temper T3 Ti/OCLV 110	
Stays	OCLV 110 carbon fiber composite	
Color	Raw Titanium/Silver/pearl nude carbon • Silver Taxalium panel	
Fork	Bontrager Race XXX Lite, OCLV 110 carbon, 379mm axle-crown length	
Headset	Cane Creek S-6 Aheadset, alloy	25.4/34.0/30.0, 27.1mm stack height

CONTROLS

Handlebar	Bontrager Race X Lite	31.8mm clamp diameter
Stem	Bontrager Race XXX Lite	40.0mm steerer clamp height
Shift levers	Shimano Dura-Ace STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano Dura-Ace	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur . . .	Shimano Dura-Ace	
Crankset	Shimano Dura-Ace 53/39	130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano Dura-Ace	10 speed, 108 links
Cassette	Shimano Dura-Ace 12-25, 10spd	

WHEELSET

Front wheel	Bontrager Race X Lite, 20°	592mm ERD
Spokes	DT Aerolite nail-head, internal alloy nipples, 286mm, radial	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Bontrager, 17.5mm rim strip	
Rear wheel	Bontrager Race X Lite, 24°	595mm ERD
Spokes	DT New Aero, Aerolite nail-head non-drive side, internal alloy nipples, 291/286mm, 2x/radial	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Bontrager, 17.5mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race X Lite	27.2mm outer diameter
Saddle	Bontrager Race X Lite	
Seatpost binder . . .	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano Dura-Ace	
Pedals	-not supplied- 9/16" axle	
Additional		

FIT dimensions in mm, unless specified

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		66.3	67.9	69.9	71.6	73.4	76.0	77.1
	cm	168	172	177	182	186	193	196
Handlebar	width	420	420	440	440	460	460	460
Stem	length	80	90	100	100	110	120	120
	angle	12	12	12	12	12	12	12
Headset spacers		30	30	30	30	30	30	30
Crank	length	170	172.5	172.5	175	175	175	175
Seatpost	length	330	330	330	330	330	330	330
Steerer	length	198.1	210.1	227.1	246.1	264.1	282.6	300.6

GEOMETRY dimensions in mm, unless specified

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	62	59	56	58	58	55	55
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	607
Seat tube	488	498	512	528	542	560	573
Standover	728	741	754	772	785	803	815
Wheelbase	968	969	975	984	989	600	1011
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	406	406	408	408	409	409	411
Head tube	105	117	134	153	171	190	208

GEARING

	39 53
12	86 117
13	79 108
14	74 100
15	69 93
16	64 88
17	61 82
19	54 74
21	49 67
23	45 61 0
25	41 56 0

LeMond Victoire

3484000*15.104
Bike weight: 18.3 lb/8.31 kg

FRAMESET

Main tubes	True Temper T3 Ti/OCV 110
Stays	OCV 110 carbon fiber composite
Color	Raw Titanium/Prime Blue/pearl nude carbon • Prime Blue panel
Fork	Bontrager Race Lite, 370mm axle-crown length
Headset	Cane Creek S-2 Aheadset, alloy 25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Race Lite	31.8mm clamp diameter
Stem	Bontrager Race Lite	40.0mm steerer clamp height
Shift levers	Shimano Ultegra STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano Ultegra	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur	Shimano Ultegra	
Crankset	Shimano Ultegra 53/39	130mm bolt hole circle
Bottom bracket	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano Ultegra	10 speed, 108 links
Cassette	Shimano Ultegra 12-25, 10spd	

WHEELSET

Front wheel	Bontrager Race Lite, 20°	592mm ERD
Spokes	DT New Aero, ProLock alloy nipples, 279mm, radial	
Tire	Bontrager Race X Lite, folding, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Race Lite, 24°	595mm ERD
Spokes	DT New Aero, T-head drive side, ProLock alloy nipples, 291/293mm, 2x	
Tire	Bontrager Race X Lite, folding, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race X Lite	27.2mm outer diameter
Saddle	Bontrager Race Lite Luxe	
Seatpost binder	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano Ultegra	
Pedals	-not supplied-	9/16" axle
Additional		

FIT dimensions in mm, unless specified

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		66.1	67.7	69.7	71.5	73.3	75.9	77.1
	cm	168	172	177	182	186	193	196
Handlebar	width	420	420	440	440	460	460	460
Stem	length	80	90	100	100	110	120	120
	angle	17	17	17	17	17	17	17
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	172.5	172.5	175	175	175	175
Seatpost	length	330	330	330	330	330	330	330
Steerer	length	207.5	219.5	236.5	255.5	273.5	292.0	310.0

GEOMETRY dimensions in mm, unless specified

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	62	59	56	58	58	55	55
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	607
Seat tube	488	498	512	528	542	560	573
Standover	728	741	754	772	785	803	815
Wheelbase	968	969	975	984	989	600	1011
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	406	406	408	408	409	409	411
Head tube	105	117	134	153	171	190	208

GEARING

	39 53
12	86 117
13	79 108
14	74 100
15	69 93
16	64 88
17	61 82
19	54 74
21	49 67
23	45 61 0
25	41 56 0

LeMond Victoire T

3485000*15.104
Bike weight: 18.6 lb/8.44 kg

FRAMESET

Main tubes	True Temper T3 Ti/OCLV 110	
Stays	OCLV 110 carbon fiber composite	
Color	Raw Titanium/Prime Blue/pearl nude carbon • Prime Blue panel	
Fork	Bontrager Race Lite, 370mm axle-crown length	
Headset	Cane Creek S-2 Aheadset, alloy	25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Race Lite	31.8mm clamp diameter
Stem	Bontrager Race Lite	40.0mm steerer clamp height
Shift levers	Shimano Ultegra STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano Ultegra T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur . . .	Shimano Ultegra GS	
Crankset	Shimano Ultegra 52/39/30	74/130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano Ultegra	10 speed, 108 links
Cassette	Shimano Ultegra 12-25, 10spd	

WHEELSET

Front wheel	Bontrager Race Lite, 20°	592mm ERD
Spokes	DT New Aero, ProLock alloy nipples, 279mm, radial	
Tire	Bontrager Race X Lite, folding, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Race Lite, 24°	595mm ERD
Spokes	DT New Aero, T-head drive side, ProLock alloy nipples, 291/293mm, 2x	
Tire	Bontrager Race X Lite, folding, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race X Lite	27.2mm outer diameter
Saddle	Bontrager Race Lite Luxe	
Seatpost binder . . .	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano Ultegra	
Pedals	-not supplied-	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		66.1	67.7	69.7	71.5	73.3	75.9	77.1
	cm	168	172	177	182	186	193	196
Handlebar	width	420	420	440	440	460	460	460
Stem	length	80	90	100	100	110	120	120
	angle	17	17	17	17	17	17	17
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	172.5	172.5	175	175	175	175
Seatpost	length	330	330	330	330	330	330	330
Steerer	length	207.5	219.5	236.5	255.5	273.5	292.0	310.0

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	62	59	56	58	58	55	55
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	607
Seat tube	488	498	512	528	542	560	573
Standover	728	741	754	772	785	803	815
Wheelbase	968	969	975	984	989	600	1011
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	406	406	408	408	409	409	411
Head tube	105	117	134	153	171	190	208

GEARING

	30 39 52
12	66 86 115
13	61 79 106
14	57 74 98
15	53 69 92
16	50 64 86
17	47 61 81
19	42 54 72
21	38 49 66
23	35 45 60
25	32 41 55

LeMond Maillot Jaune

3478000*15.084
Bike weight: 18.0 lb/8.17 kg

FRAMESET

Main tubes	True Temper OX Platinum/OCLV 120	
Stays	OCLV 120, carbon fiber composite	
Color	Ice Red/Saddle Red • Saddle Red panel	
Fork	Bontrager Race Lite, 370mm axle-crown length	
Headset	Cane Creek S-6 Aheadset, alloy	25.4/34.0/30.0, 27.1mm stack height

CONTROLS

Handlebar	Bontrager Race Lite	31.8mm clamp diameter
Stem	Bontrager Race X Lite	40.0mm steerer clamp height
Shift levers	Shimano Dura-Ace STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano Dura-Ace	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur	Shimano Dura-Ace	
Crankset	Shimano Dura-Ace 53/39	130mm bolt hole circle
Bottom bracket	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano Dura-Ace	10 speed, 108 links
Cassette	Shimano Dura-Ace 12-25, 10spd	

WHEELSET

Front wheel	Bontrager Race Lite, 20°	592mm ERD
Spokes	DT New Aero, ProLock alloy nipples, 279mm, radial	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Velox 16mm rim strip	
Rear wheel	Bontrager Race Lite, 24°	595mm ERD
Spokes	DT New Aero, T-head drive side, ProLock alloy nipples, 291/293mm, 2x	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race X Lite	27.2mm outer diameter
Saddle	Bontrager Race Lite Luxe	
Seatpost binder	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano Dura-Ace	
Pedals	-not supplied-	9/16" axle
Additional		

FIT dimensions in mm, unless specified

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		65.7	67.8	69.8	71.6	73.3	75.9	77.2
	cm	167	172	177	182	186	193	196
Handlebar	width	420	420	440	440	460	460	460
Stem	length	75	90	100	100	110	120	120
	angle	17	17	17	17	17	17	17
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	172.5	172.5	175	175	175	175
Seatpost	length	330	330	330	330	330	330	330
Steerer	length	208.1	220.1	237.1	256.1	274.1	293.1	313.1

GEOMETRY dimensions in mm, unless specified

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	63	60	57	59	59	56	56
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	606
Seat tube	488	498	512	528	542	560	574
Standover	728	741	754	772	785	803	815
Wheelbase	968	970	975	984	989	999	1010
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	406	406	408	408	409	409	411
Head tube	105	117	134	153	171	190	210

GEARING

	39 53
12	86 117
13	79 108
14	74 100
15	69 93
16	64 88
17	61 82
19	54 74
21	49 67
23	45 61 0
25	41 56 0

LeMond Zurich

3476000*15.104
Bike weight: 18.8 lb/8.54 kg

FRAMESET

Main tubes	True Temper OX Platinum/OCLV 120
Stays	OCLV 120, carbon fiber composite
Color	Ice Blue/ Transparent Blue • Transparent Blue panel
Fork	Bontrager Race Lite, 370mm axle-crown length
Headset	Cane Creek S-2 Aheadset, alloy 25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Race	31.8mm clamp diameter
Stem	Bontrager Race	40.0mm steerer clamp height
Shift levers	Shimano Ultegra STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano Ultegra	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur	Shimano Ultegra	
Crankset	Shimano Ultegra 53/39	130mm bolt hole circle
Bottom bracket	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano Ultegra	10 speed, 108 links
Cassette	Shimano Ultegra 12-25, 10spd	

WHEELSET

Front wheel	Bontrager Race Lite, 20°	592mm ERD
Spokes	DT New Aero, ProLock alloy nipples, 279mm, radial	
Tire	Bontrager Race X Lite, folding, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Race Lite, 24°	595mm ERD
Spokes	DT New Aero, T-head drive side, ProLock alloy nipples, 291/293mm, 2x	
Tire	Bontrager Race X Lite, folding, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race X Lite	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano Ultegra	
Pedals	-not supplied-	9/16" axle
Additional		

FIT dimensions in mm, unless specified

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		66.2	67.7	69.8	71.5	73.2	75.9	77.1
	cm	168	172	177	182	186	193	196
Handlebar	width	420	420	440	440	460	460	460
Stem	length	80	90	100	100	110	120	120
	angle	17	17	17	17	17	17	17
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	172.5	172.5	175	175	175	175
Seatpost	length	330	330	330	330	330	330	330
Steerer	length	207.5	219.5	236.5	255.5	273.5	292.5	312.5

GEOMETRY dimensions in mm, unless specified

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	63	60	57	59	59	56	56
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	606
Seat tube	488	498	512	528	542	560	574
Standover	728	741	754	772	785	803	815
Wheelbase	968	970	975	984	989	999	1010
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	406	406	408	408	409	409	411
Head tube	105	117	134	153	171	190	210

GEARING

	39 53
12	86 117
13	79 108
14	74 100
15	69 93
16	64 88
17	61 82
19	54 74
21	49 67
23	45 61 0
25	41 56 0

LeMond Zurich T

3477000*15.104
Bike weight: 19.1 lb/8.67 kg

FRAMESET

Main tubes	True Temper OX Platinum/OCLV 120
Stays	OCLV 120, carbon fiber composite
Color	Ice Blue/ Transparent Blue • Transparent Blue panel
Fork	Bontrager Race Lite, 370mm axle-crown length
Headset	Cane Creek S-2 Aheadset, alloy 25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Race	31.8mm clamp diameter
Stem	Bontrager Race	40.0mm steerer clamp height
Shift levers	Shimano Ultegra STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano Ultegra T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur	Shimano Ultegra GS	
Crankset	Shimano Ultegra 52/39/30	74/130mm bolt hole circle
Bottom bracket	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano Ultegra	10 speed, 108 links
Cassette	Shimano Ultegra 12-25, 10spd	

WHEELSET

Front wheel	Bontrager Race Lite, 20°	592mm ERD
Spokes	DT New Aero, ProLock alloy nipples, 279mm, radial	
Tire	Bontrager Race X Lite, folding, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Race Lite, 24°	595mm ERD
Spokes	DT New Aero, T-head drive side, ProLock alloy nipples, 291/293mm, 2x	
Tire	Bontrager Race X Lite, folding, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race X Lite	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano Ultegra	
Pedals	-not supplied-	9/16" axle
Additional		

FIT dimensions in mm, unless specified

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		66.2	67.7	69.8	71.5	73.2	75.9	77.1
	cm	168	172	177	182	186	193	196
Handlebar	width	420	420	440	440	460	460	460
Stem	length	80	90	100	100	110	120	120
	angle	17	17	17	17	17	17	17
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	172.5	172.5	175	175	175	175
Seatpost	length	330	330	330	330	330	330	330
Steerer	length	207.5	219.5	236.5	255.5	273.5	292.5	312.5

GEOMETRY dimensions in mm, unless specified

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	63	60	57	59	59	56	56
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	606
Seat tube	488	498	512	528	542	560	574
Standover	728	741	754	772	785	803	815
Wheelbase	968	970	975	984	989	999	1010
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	406	406	408	408	409	409	411
Head tube	105	117	134	153	171	190	210

GEARING

	30	39	52
12	66	86	115
13	61	79	106
14	57	74	98
15	53	69	92
16	50	64	86
17	47	61	81
19	42	54	72
21	38	49	66
23	35	45	60
25	32	41	55

LeMond Buenos Aires

3474000*15.084
Bike weight: 18.8 lb/8.54 kg

FRAMESET

Main tubes	True Temper OX Platinum/OCLV 120	
Stays	OCLV 120, carbon fiber composite	
Color	LeMond Yellow Metallic /pearl nude-carbon	Pearl nude-carbon panel
Fork	Bontrager Race, 370mm axle-crown length	
Headset	Cane Creek S-2 Aheadset, alloy	25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Race	31.8mm clamp diameter
Stem	Bontrager Race Lite	40.0mm steerer clamp height
Shift levers	Campagnolo Veloce Ergopower	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur	Campagnolo Veloce	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur	Campagnolo Centaur	
Crankset	Bontrager Race Lite 53/39 w/Giga-X-Pipe	130mm bolt hole circle
Bottom bracket	integral axle	68 (shell x axle,mm), Integral axle
Chain	Campagnolo	10 speed, 108 links
Cassette	Campagnolo Veloce 12-25, 10spd	

WHEELSET

Front wheel	Bontrager Race Lite, 20°	592mm ERD
Spokes	DT New Aero, ProLock alloy nipples, 279mm, radial	
Tire	Bontrager Race X Lite, folding, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Race Lite, 24°	595mm ERD
Spokes	DT New Aero, T-head drive side, ProLock alloy nipples, 291/293mm, 2x	
Tire	Bontrager Race X Lite, folding, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Select	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Campagnolo Veloce front, Campagnolo Veloce rear	
Pedals	-not supplied- 9/16" axle	
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		65.9	67.5	69.5	71.2	72.9	75.6	76.8
	cm	167	171	176	181	185	192	195
Handlebar	width	420	420	440	440	460	460	460
Stem	length	80	90	100	100	110	120	120
	angle	17	17	17	17	17	17	17
Headset spacers		30	30	30	30	30	30	30
Crank	length	170	172.5	172.5	175	175	175	175
Seatpost	length	330	330	330	330	330	330	330
Steerer	length	197.5	209.5	226.5	245.5	263.5	282.5	302.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	63	60	57	59	59	56	56
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	606
Seat tube	488	498	512	528	542	560	574
Standover	728	741	754	772	785	803	815
Wheelbase	968	970	975	984	989	999	1010
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	406	406	408	408	409	409	411
Head tube	105	117	134	153	171	190	210

GEARING

	39 53
12	86 117
13	79 108
14	74 100
15	69 93
16	64 88
17	61 82
19	54 74
21	49 67
23	45 61 0
25	41 56 0

LeMond Buenos Aires T

3475000*15.084
Bike weight: 19.1 lb/8.67 kg

FRAMESET

Main tubes	True Temper OX Platinum/OCLV 120	
Stays	OCLV 120, carbon fiber composite	
Color	LeMond Yellow Metallic /pearl nude-carbon • Pearl nude-carbon panel	
Fork	Bontrager Race, 370mm axle-crown length	
Headset	Cane Creek S-2 Aheadset, alloy	25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Race	31.8mm clamp diameter
Stem	Bontrager Race Lite	40.0mm steerer clamp height
Shift levers	Campagnolo Veloce Ergopower	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur	Campagnolo Veloce T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur	Campagnolo Centaur GS	
Crankset	Bontrager Race Lite 52/42/30 w/Giga-X-Pipe	74/130mm bolt hole circle
Bottom bracket	integral axle	68 (shell x axle,mm), Integral axle
Chain	Campagnolo	10 speed, 108 links
Cassette	Campagnolo Veloce 12-25, 10spd	

WHEELSET

Front wheel	Bontrager Race Lite, 20°	592mm ERD
Spokes	DT New Aero, ProLock alloy nipples, 279mm, radial	
Tire	Bontrager Race X Lite, folding, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Race Lite, 24°	595mm ERD
Spokes	DT New Aero, T-head drive side, ProLock alloy nipples, 291/293mm, 2x	
Tire	Bontrager Race X Lite, folding, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Select	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Campagnolo Veloce front, Campagnolo Veloce rear	
Pedals	-not supplied- 9/16" axle	
Additional		

FIT dimensions in mm, unless specified

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		65.9	67.5	69.5	71.2	72.9	75.6	76.8
	cm	167	171	176	181	185	192	195
Handlebar	width	420	420	440	440	460	460	460
Stem	length	80	90	100	100	110	120	120
	angle	17	17	17	17	17	17	17
Headset spacers		30	30	30	30	30	30	30
Crank	length	170	172.5	172.5	175	175	175	175
Seatpost	length	330	330	330	330	330	330	330
Steerer	length	197.5	209.5	226.5	245.5	263.5	282.5	302.5

GEOMETRY dimensions in mm, unless specified

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	63	60	57	59	59	56	56
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	606
Seat tube	488	498	512	528	542	560	574
Standover	728	741	754	772	785	803	815
Wheelbase	968	970	975	984	989	999	1010
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	406	406	408	408	409	409	411
Head tube	105	117	134	153	171	190	210

GEARING

	30	42	52
12	66	93	115
13	61	85	106
14	57	79	98
15	53	74	92
16	50	69	86
17	47	65	81
19	42	58	72
21	38	53	66
23	35	48	60
25	32	44	55

LeMond Versailles

3472000*15.064
Bike weight: 18.9 lb/8.58 kg

FRAMESET

Main tubes	True Temper OX Platinum/OCV 120	
Stays	OCV 120, carbon fiber composite	
Color	Black Metallic/ Pearl nude-carbon • Pearl nude-carbon panel	
Fork	Bontrager Race, 370mm axle-crown length	
Headset	Cane Creek BL	25.4/34.0/30.0, 30.1mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	Shimano 105 STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano 105	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur . . .	Shimano Ultegra	
Crankset	Bontrager Race Lite 53/39 w/Giga-X-Pipe	130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	SRAM PG970 12-26, 9spd	

WHEELSET

Front wheel	Bontrager Select, 20°	593mm ERD
Spokes	DT 14g, ProLock brass nipples, 281mm, radial	
Tire	Bontrager Race Lite, folding, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Select, 24°	603mm ERD
Spokes	DT 14g, ProLock brass nipples, 293/294mm, 2x	
Tire	Bontrager Race Lite, folding, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Select	27.2mm outer diameter
Saddle	SSM Era Luxe, CrMo/leather	
Seatpost binder . . .	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano 105	
Pedals	-not supplied- 9/16" axle	
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		66.3	67.9	69.9	71.7	73.4	75.7	76.6
	cm	168	172	178	182	186	192	195
Handlebar	width	420	420	440	440	460	460	460
Stem	length	80	90	100	100	110	120	120
	angle	17	17	17	17	17	17	17
Headset spacers		40	40	40	40	40	30	20
Crank	length	170	172.5	172.5	175	175	175	175
Seatpost	length	330	330	330	330	330	330	330
Steerer	length	210.6	224.1	241.1	260.1	278.1	287.1	297.1

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	63	60	57	59	59	56	56
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	606
Seat tube	488	498	512	528	542	560	574
Standover	728	741	754	772	785	803	815
Wheelbase	968	970	975	984	989	999	1010
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	406	406	408	408	409	409	411
Head tube	105	117	134	153	171	190	210

GEARING

	39 53
12	86 117
13	79 108
14	74 100
15	69 93
17	61 82
19	54 74
21	49 67
23	45 61
26	40 54 0

LeMond Versailles T

3473000*15.064
Bike weight: 19.9 lb/9.03 kg

FRAMESET

Main tubes	True Temper OX Platinum/OCLV 120	
Stays	OCLV 120, carbon fiber composite	
Color	Black Metallic/ Pearl nude-carbon • Pearl nude-carbon panel	
Fork	Bontrager Race, 370mm axle-crown length	
Headset	Cane Creek BL	25.4/34.0/30.0, 30.1mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	Shimano 105 STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano 105 T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur	Shimano Ultegra GS	
Crankset	Bontrager Race Lite 52/42/30 w/Giga-X-Pipe	74/130mm bolt hole circle
Bottom bracket	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	SRAM PG970 12-26, 9spd	

WHEELSET

Front wheel	Bontrager Select, 20°	593mm ERD
Spokes	DT 14g, ProLock brass nipples, 281mm, radial	
Tire	Bontrager Race Lite, folding, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Select, 24°	603mm ERD
Spokes	DT 14g, ProLock brass nipples, 293/294mm, 2x	
Tire	Bontrager Race Lite, folding, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Select	27.2mm outer diameter
Saddle	SSM Era Luxe, CrMo/leather	
Seatpost binder	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano 105	
Pedals	-not supplied-	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		66.3	67.9	69.9	71.7	73.4	75.7	76.6
	cm	168	172	178	182	186	192	195
Handlebar	width	420	420	440	440	460	460	460
Stem	length	80	90	100	100	110	120	120
	angle	17	17	17	17	17	17	17
Headset spacers		40	40	40	40	40	30	20
Crank	length	170	172.5	172.5	175	175	175	175
Seatpost	length	330	330	330	330	330	330	330
Steerer	length	210.6	224.1	241.1	260.1	278.1	287.1	297.1

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	63	60	57	59	59	56	56
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	606
Seat tube	488	498	512	528	542	560	574
Standover	728	741	754	772	785	803	815
Wheelbase	968	970	975	984	989	999	1010
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	406	406	408	408	409	409	411
Head tube	105	117	134	153	171	190	210

GEARING

	30 42 52
12	66 93 115
13	61 85 106
14	57 79 98
15	53 74 92
17	47 65 81
19	42 58 72
21	38 53 66
23	35 48 60
26	31 43 53

LeMond Versailles T, women's

3473003*15.064
Bike weight: 19.2 lb/8.72 kg

FRAMESET

Main tubes	True Temper OX Platinum/OCV 120	
Stays	OCV 120, carbon fiber composite	
Color	Metallic Silver/ Pearl nude-carbon • Pearl nude-carbon panel	
Fork	Bontrager Race, 370.0mm axle-crown length	
Headset	Cane Creek BL	25.4/34.0/30.0, 30.1mm stack height

CONTROLS

Handlebar	Bontrager Select Flat Top	26.0mm clamp diameter
Stem	Bontrager Race	40.0mm steerer clamp height
Shift levers	Shimano 105 STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano 105 T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur . . .	Shimano Ultegra GS	
Crankset	Bontrager Race Lite 52/42/30 w/Giga-X-Pipe	74/130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	SRAM PG970 12-26, 9spd	

WHEELSET

Front wheel	Bontrager Select, 20°	593mm ERD
Spokes	DT 14g, ProLock brass nipples, 281mm, radial	
Tire	Bontrager Race Lite, folding, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Select, 24°	603mm ERD
Spokes	DT 14g, ProLock brass nipples, 293/294mm, 2x	
Tire	Bontrager Race Lite, folding, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Select	27.2mm outer diameter
Saddle	Bontrager Select WSD	
Seatpost binder . . .	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano 105	
Pedals	-not supplied-	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	49	53
Rider height, in.		65.4	68.1
	cm	166	173
Handlebar	width	400	420
Handlebar	rise	0	0
Stem	length	80	90
	angle	17	17
Headset spacers		40	40
Crank	length	165	170
Seatpost	length	330	330
Steerer	length	211.1	240.1

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.3	72.0
Fork offset	45.0	45.0
Trail	67	62
Seat tube angle	74.0	73.3
Effective top tube	510	530
Seat tube	488	512
Standover	728	754
Wheelbase	960	970
Bottom bracket height	264	266
Chainstay	406	408
Head tube	105	134

GEARING

	30 42 52
12	66 93 115
13	61 85 106
14	57 79 98
15	53 74 92
17	47 65 81
19	42 58 72
21	38 53 66
23	35 48 60
26	31 43 53

LeMond Chambery

3446000*15.104
Bike weight: 18.5 lb/8.40 kg

FRAMESET

Main tubes	6066 butted aluminum	
Stays	Carbon fiber composite	
Color	Brushed Aluminum/Metallic Red • Metallic Red panel	
Fork	Bontrager Race, 370mm axle-crown length	
Headset	Cane Creek C-1 Aheadset	25.4/34.0/30.0, 26.7mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Race	40.0mm steerer clamp height
Shift levers	Shimano Ultegra STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano Ultegra	Down pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Ultegra	
Crankset	Shimano Ultegra 53/39	130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano Ultegra	10 speed, 108 links
Cassette	Shimano Ultegra 12-25, 10spd	

WHEELSET

Front wheel	Bontrager Race, 20°	593mm ERD
Spokes	DT New Aero, ProLock brass nipples, 280mm, radial	
Tire	Bontrager Race X Lite, folding, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Race, 24°	603mm ERD
Spokes	DT New Aero, ProLock brass nipples, 294/294mm, 2x	
Tire	Bontrager Race X Lite, folding, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Select	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .	Alloy w/integral bolt	31.9mm inner diameter
Brakes	Shimano Ultegra	
Pedals	-not supplied-	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		66.2	67.7	69.8	71.5	73.3	75.9	77.1
	cm	168	172	177	182	186	193	196
Handlebar	width	420	420	440	440	460	460	460
Stem	length	80	90	100	100	110	120	120
	angle	17	17	17	17	17	17	17
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	172.5	172.5	175	175	175	175
Seatpost	length	330	330	330	330	330	330	330
Steerer	length	207.7	219.7	236.7	255.7	273.7	292.7	312.7

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	62	59	56	58	58	55	55
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	606
Seat tube	491	498	512	528	542	560	574
Standover	731	741	754	772	785	803	815
Wheelbase	975	977	980	989	993	1003	1012
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	413	413	413	413	413	413	413
Head tube	105	117	134	153	171	190	210

GEARING

	39 53
12	86 117
13	79 108
14	74 100
15	69 93
16	64 88
17	61 82
19	54 74
21	49 67
23	45 61 0
25	41 56 0

LeMond Chambery T

3447000*15.104
Bike weight: 19.0 lb/8.63 kg

FRAMESET

Main tubes	6066 butted aluminum	
Stays	Carbon fiber composite	
Color	Brushed Aluminum/Metallic Red • Metallic Red panel	
Fork	Bontrager Race, 370mm axle-crown length	
Headset	Cane Creek C-1 Aheadset	25.4/34.0/30.0, 26.7mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Race	40.0mm steerer clamp height
Shift levers	Shimano Ultegra STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano Ultegra T	Down pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Ultegra GS	
Crankset	Shimano Ultegra 52/39/30	74/130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano Ultegra	10 speed, 108 links
Cassette	Shimano Ultegra 12-25, 10spd	

WHEELSET

Front wheel	Bontrager Race, 20°	593mm ERD
Spokes	DT New Aero, ProLock brass nipples, 280mm, radial	
Tire	Bontrager Race X Lite, folding, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Race, 24°	603mm ERD
Spokes	DT New Aero, ProLock brass nipples, 294/294mm, 2x	
Tire	Bontrager Race X Lite, folding, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Select	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .	Alloy w/integral bolt	31.9mm inner diameter
Brakes	Shimano Ultegra	
Pedals	-not supplied-	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		66.2	67.7	69.8	71.5	73.3	75.9	77.1
	cm	168	172	177	182	186	193	196
Handlebar	width	420	420	440	440	460	460	460
Stem	length	80	90	100	100	110	120	120
	angle	17	17	17	17	17	17	17
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	172.5	172.5	175	175	175	175
Seatpost	length	330	330	330	330	330	330	330
Steerer	length	207.7	219.7	236.7	255.7	273.7	292.7	312.7

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	62	59	56	58	58	55	55
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	606
Seat tube	491	498	512	528	542	560	574
Standover	731	741	754	772	785	803	815
Wheelbase	975	977	980	989	993	1003	1012
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	413	413	413	413	413	413	413
Head tube	105	117	134	153	171	190	210

GEARING

	30	39	52
12	66	86	115
13	61	79	106
14	57	74	98
15	53	69	92
16	50	64	86
17	47	61	81
19	42	54	72
21	38	49	66
23	35	45	60
25	32	41	55

LeMond Alpe d'Huez

3436000*15.084
Bike weight: 20.9 lb/9.49 kg

FRAMESET

Main tubes	6066 butted aluminum	
Stays	Carbon fiber composite	
Color	Brushed Aluminum/Metallic Blue • Metallic Blue panel	
Fork	Bontrager Race, 370mm axle-crown length	
Headset	Cane Creek SC-1	25.4/34.0/30.0, 30.1mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	Shimano 105 STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano 105	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur . . .	Shimano Ultegra	
Crankset	Bontrager Race Lite 53/39 w/Giga-X-Pipe	130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano HG-73	9 speed, 108 links
Cassette	SRAM PG970 12-26, 9spd	

WHEELSET

Front wheel	Bontrager Select, 20°	593mm ERD
Spokes	DT 14g, ProLock brass nipples, 281mm, radial	
Tire	Bontrager Race Lite, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Select, 24°	603mm ERD
Spokes	DT 14g, ProLock brass nipples, 293/294mm, 2x	
Tire	Bontrager Race Lite, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Select	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .	Alloy w/integral bolt	32.1mm inner diameter
Brakes	Shimano 105	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		66.1	67.6	69.6	71.4	73.1	75.7	77.0
	cm	168	172	177	181	186	192	195
Handlebar	width	420	420	440	440	460	460	460
Stem	length	80	90	100	100	110	120	120
	angle	17	17	17	17	17	17	17
Headset spacers		30	30	30	30	30	30	30
Crank	length	170	172.5	172.5	175	175	175	175
Seatpost	length	330	330	330	330	330	330	330
Steerer	length	202.1	214.1	231.1	250.1	268.1	287.1	307.1

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	63	60	57	59	59	56	56
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	606
Seat tube	488	498	512	528	542	560	574
Standover	728	741	754	772	785	803	815
Wheelbase	972	974	980	989	993	1007	1015
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	410	410	413	413	413	416	416
Head tube	105	117	134	153	171	190	210

GEARING

	39 53
12	86 117
13	79 108
14	74 100
15	69 93
17	61 82
19	54 74
21	49 67
23	45 61
26	40 54 0

LeMond Alpe d'Huez T

3437000*15.084
Bike weight: 20.6 lb/9.35 kg

FRAMESET

Main tubes	6066 butted aluminum	
Stays	Carbon fiber composite	
Color	Brushed Aluminum/Metallic Blue • Metallic Blue panel	
Fork	Bontrager Race, 370mm axle-crown length	
Headset	Cane Creek SC-1	25.4/34.0/30.0, 30.1mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	Shimano 105 STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano 105 T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur . . .	Shimano Ultegra GS	
Crankset	Bontrager Race Lite 52/42/30 w/Giga-X-Pipe	74/130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano HG-73	9 speed, 108 links
Cassette	SRAM PG970 12-26, 9spd	

WHEELSET

Front wheel	Bontrager Select, 20°	593mm ERD
Spokes	DT 14g, ProLock brass nipples, 281mm, radial	
Tire	Bontrager Race Lite, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Select, 24°	603mm ERD
Spokes	DT 14g, ProLock brass nipples, 293/294mm, 2x	
Tire	Bontrager Race Lite, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Select	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .	Alloy w/integral bolt	32.1mm inner diameter
Brakes	Shimano 105	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		66.1	67.6	69.6	71.4	73.1	75.7	77.0
	cm	168	172	177	181	186	192	195
Handlebar	width	420	420	440	440	460	460	460
Stem	length	80	90	100	100	110	120	120
	angle	17	17	17	17	17	17	17
Headset spacers		30	30	30	30	30	30	30
Crank	length	170	172.5	172.5	175	175	175	175
Seatpost	length	330	330	330	330	330	330	330
Steerer	length	202.1	214.1	231.1	250.1	268.1	287.1	307.1

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	63	60	57	59	59	56	56
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	606
Seat tube	488	498	512	528	542	560	574
Standover	728	741	754	772	785	803	815
Wheelbase	972	974	980	989	993	1007	1015
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	410	410	413	413	413	416	416
Head tube	105	117	134	153	171	190	210

GEARING

	30 42 52
12	66 93 115
13	61 85 106
14	57 79 98
15	53 74 92
17	47 65 81
19	42 58 72
21	38 53 66
23	35 48 60
26	31 43 53

LeMond Croix de Fer

3432000*15.054
Bike weight: 19.7 lb/8.94 kg

FRAMESET

Main tubes	True Temper OX Platinum	
Stays	True Temper OX Platinum	
Color	Prime Blue/Yellow Metallic • Yellow Metallic panel	
Fork	Bontrager Race, 370mm axle-crown length	
Headset	Slimstack	25.4/34.0/30.0, 36.3mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	Shimano 105 STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano 105	Down pull, 31.8 mm/ 1 1/4" attachment
Rear derailleur . . .	Shimano Ultegra	
Crankset	Bontrager Race 53/39	130mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe SL	68 x 108 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-73	9 speed, 108 links
Cassette	SRAM PG950 12-26, 9spd	

WHEELSET

Front wheel	Bontrager Select, 20°	593mm ERD
Spokes	DT 14g, ProLock brass nipples, 281mm, radial	
Tire	Bontrager Race Lite, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Select, 24°	603mm ERD
Spokes	DT 14g, ProLock brass nipples, 293/294mm, 2x	
Tire	Bontrager Race Lite, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Select	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .	Alloy w/integral bolt	31.9mm inner diameter
Brakes	Alloy dual pivot, cartridge pads	
Pedals	Shimano SPD M505, clipless	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		65.6	67.6	70.0	71.4	73.2	75.8	77.9
	cm	167	172	178	181	186	193	198
Handlebar	width	420	420	440	440	460	460	460
Stem	length	80	90	100	100	110	120	130
	angle	17	17	17	17	17	17	17
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	170	170	175	175	175	175
Seatpost	length	250	250	250	250	250	250	250
Steerer	length	196.8	213.3	229.3	245.8	264.3	288.3	307.3

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.5	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	57	57	54	53	53	52	52
Seat tube angle	74.0	73.8	73.8	73.0	72.5	72.5	72.0
Effective top tube	519	532	545	565	576	591	606
Seat tube	517	537	557	576	596	616	636
Standover	752	754	772	790	808	831	848
Wheelbase	967	980	984	995	1000	1013	1021
Bottom bracket height	266	266	266	266	266	270	270
Chainstay	412	415	415	415	415	418	418
Head tube	85	100	116	133	151	175	195

GEARING

	39 53
12	86 117
13	79 108
14	74 100
15	69 93
17	61 82
19	54 74
21	49 67
23	45 61
26	40 54 0

LeMond Croix de Fer T

3433000*15.054
Bike weight: 20.4 lb/9.26 kg

FRAMESET

Main tubes	True Temper OX Platinum	
Stays	True Temper OX Platinum	
Color	Prime Blue/Yellow Metallic • Yellow Metallic panel	
Fork	Bontrager Race, 370mm axle-crown length	
Headset	Slimstack	25.4/34.0/30.0, 36.3mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	Shimano 105 STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano 105 T	Down pull, 31.8 mm/ 1 1/4" attachment
Rear derailleur . . .	Shimano Ultegra GS	
Crankset	Bontrager Race 52/42/30	74/130mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe SL	68 x 118 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-73	9 speed, 108 links
Cassette	SRAM PG950 12-26, 9spd	

WHEELSET

Front wheel	Bontrager Select, 20°	593mm ERD
Spokes	DT 14g, ProLock brass nipples, 281mm, radial	
Tire	Bontrager Race Lite, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Select, 24°	603mm ERD
Spokes	DT 14g, ProLock brass nipples, 293/294mm, 2x	
Tire	Bontrager Race Lite, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Select	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .	Alloy w/integral bolt	31.9mm inner diameter
Brakes	Alloy dual pivot, cartridge pads	
Pedals	Shimano SPD M505, clipless	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		65.6	67.6	70.0	71.4	73.2	75.8	77.9
	cm	167	172	178	181	186	193	198
Handlebar	width	420	420	440	440	460	460	460
Stem	length	80	90	100	100	110	120	130
	angle	17	17	17	17	17	17	17
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	170	170	175	175	175	175
Seatpost	length	250	250	250	250	250	250	250
Steerer	length	196.8	213.3	229.3	245.8	264.3	288.3	307.3

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.5	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	57	57	54	53	53	52	52
Seat tube angle	74.0	73.8	73.8	73.0	72.5	72.5	72.0
Effective top tube	519	532	545	565	576	591	606
Seat tube	517	537	557	576	596	616	636
Standover	752	754	772	790	808	831	848
Wheelbase	967	980	984	995	1000	1013	1021
Bottom bracket height	266	266	266	266	266	270	270
Chainstay	412	415	415	415	415	418	418
Head tube	85	100	116	133	151	175	195

GEARING

	30 42 52
12	66 93 115
13	61 85 106
14	57 79 98
15	53 74 92
17	47 65 81
19	42 58 72
21	38 53 65
23	35 48 60
26	31 43 53

LeMond Croix de Fer T, women's

3433003*15.064
Bike weight: 20.5 lb/9.31 kg

FRAMESET

Main tubes	True Temper OX Platinum	
Stays	True Temper OX Platinum	
Color	Blue Metallic/Pearl White • Pearl White panel	
Fork	Bontrager Race, 370mm axle-crown length	
Headset	Slimstack	25.4/34.0/30.0, 36.3mm stack height

CONTROLS

Handlebar	Bontrager Select Flat Top	mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	Shimano 105 STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano 105 T	Down pull, 31.8 mm/ 1 1/4" attachment
Rear derailleur . . .	Shimano Ultegra GS	
Crankset	Bontrager Race 52/42/30	74/130mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe SL	68 x 118 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-73	9 speed, 108 links
Cassette	SRAM PG950 12-26, 9spd	

WHEELSET

Front wheel	Bontrager Select, 20°	593mm ERD
Spokes	DT 14g, ProLock brass nipples, 281mm, radial	
Tire	Bontrager Race Lite, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Select, 24°	603mm ERD
Spokes	DT 14g, ProLock brass nipples, 293/294mm, 2x	
Tire	Bontrager Race Lite, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Select	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .	Alloy w/integral bolt	31.9mm inner diameter
Brakes	Alloy dual pivot, cartridge pads	
Pedals	Shimano SPD M505, clipless	axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	45	49	53
Rider height, in.		64.8	65.9	68.3
	cm	164	167	173
Handlebar	width	380	400	420
Handlebar	rise	0	0	0
Stem	length	80	80	90
	angle	17	17	17
Headset spacers		40	40	40
Crank	length	165	165	170
Seatpost	length	250	250	250
Steerer	length	197.3	212.3	228.3

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	72.0	72.5
Fork offset	45.0	45.0	45.0
Trail	66	60	57
Seat tube angle	75.0	74.5	73.8
Effective top tube	498	510	530
Seat tube	477	517	554
Standover	725	756	784
Wheelbase	968	970	979
Bottom bracket height	266	266	266
Chainstay	412	415	415
Head tube	85	100	116

GEARING

	30	42	52
12	66	93	115
13	61	85	106
14	57	79	98
15	53	74	92
17	47	65	81
19	42	58	72
21	38	53	65
23	35	48	60
26	31	43	53

LeMond Tourmalet

3428000*15.054
Bike weight: 19.7 lb/8.94 kg

FRAMESET

Main tubes	6066 butted aluminum	
Stays	6066 butted aluminum	
Color	Viper Blue/Metallic Black • Metallic Black panel	
Fork	Bontrager Race, 370mm axle-crown length	
Headset	Slimstack	25.4/34.0/30.0, 36.3mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	Shimano 105 STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano 105	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur . . .	Shimano Ultegra	
Crankset	Bontrager Race 53/39	130mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe SL	68 x 108 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	SRAM PG950 12-26, 9spd	

WHEELSET

Front wheel	Bontrager Select, 20°	593mm ERD
Spokes	DT 14g, ProLock brass nipples, 281mm, radial	
Tire	Bontrager Race Lite, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Select, 24°	603mm ERD
Spokes	DT 14g, ProLock brass nipples, 293/294mm, 2x	
Tire	Bontrager Race Lite, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Select	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .	Alloy w/integral bolt	31.9mm inner diameter
Brakes	Alloy dual pivot, cartridge pads	
Pedals	Alloy w/clips and straps, clipless adaptable	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		66.5	68.1	70.2	71.9	73.7	76.3	76.9
	cm	169	173	178	183	187	194	195
Handlebar	width	420	420	440	440	460	460	460
Stem	length	80	90	100	100	110	120	120
	angle	17	17	17	17	17	17	17
Headset spacers		40	40	40	40	40	40	20
Crank	length	170	170	170	175	175	175	175
Seatpost	length	330	330	330	330	330	330	330
Steerer	length	216.8	230.3	247.3	266.3	284.3	303.3	303.3

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	63	60	57	59	59	56	56
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	606
Seat tube	488	498	512	528	542	560	574
Standover	728	741	754	772	785	803	815
Wheelbase	972	974	980	989	993	1007	1015
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	410	410	413	413	413	416	416
Head tube	105	117	134	153	171	190	210

GEARING

	39 53
12	86 117
13	79 108
14	74 100
15	69 93
17	61 82
19	54 74
21	49 67
23	45 61
26	40 54 0

LeMond Tourmalet T

3429000*15.054
Bike weight: 20.1 lb/9.13 kg

FRAMESET

Main tubes	6066 butted aluminum	
Stays	6066 butted aluminum	
Color	Viper Blue/Metallic Black • Metallic Black panel	
Fork	Bontrager Race, 370mm axle-crown length	
Headset	Slimstack	25.4/34.0/30.0, 36.3mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	Shimano 105 STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano 105 T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur . . .	Shimano Ultegra GS	
Crankset	Bontrager Race 52/42/30	74/130mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe SL	68 x 118 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	SRAM PG950 12-26, 9spd	

WHEELSET

Front wheel	Bontrager Select, 20°	593mm ERD
Spokes	DT 14g, ProLock brass nipples, 281mm, radial	
Tire	Bontrager Race Lite, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Select, 24°	603mm ERD
Spokes	DT 14g, ProLock brass nipples, 293/294mm, 2x	
Tire	Bontrager Race Lite, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Select	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .	Alloy w/integral bolt	31.9mm inner diameter
Brakes	Alloy dual pivot, cartridge pads	
Pedals	Alloy w/clips and straps, clipless adaptable	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	49	51	53	55	57	59	61
Rider height, in.		66.5	68.1	70.2	71.9	73.7	76.3	76.9
	cm	169	173	178	183	187	194	195
Handlebar	width	420	420	440	440	460	460	460
Stem	length	80	90	100	100	110	120	120
	angle	17	17	17	17	17	17	17
Headset spacers		40	40	40	40	40	40	20
Crank	length	170	170	170	175	175	175	175
Seatpost	length	330	330	330	330	330	330	330
Steerer	length	216.8	230.3	247.3	266.3	284.3	303.3	303.3

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.0	72.5	73.0	73.5	73.5	74.0	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	63	60	57	59	59	56	56
Seat tube angle	74.0	73.8	73.3	73.0	72.5	72.5	72.0
Effective top tube	525	532	545	565	575	591	606
Seat tube	488	498	512	528	542	560	574
Standover	728	741	754	772	785	803	815
Wheelbase	972	974	980	989	993	1007	1015
Bottom bracket height	264	266	266	269	269	269	269
Chainstay	410	410	413	413	413	416	416
Head tube	105	117	134	153	171	190	210

GEARING

	30 42 52
12	66 93 115
13	61 85 106
14	57 79 98
15	53 74 92
17	47 65 81
19	42 58 72
21	38 53 66
23	35 48 60
26	31 43 53

LeMond Big Sky SLT

3456000*15.074
Bike weight: 21.9 lb/9.94 kg

FRAMESET

Main tubes	6061 aluminum	
Stays	6061 aluminum	
Color	Brushed Aluminum/Metallic Blue • Metallic Blue panel	
Fork	Bontrager Satellite Plus, 381mm axle-crown length	
Headset	Slimstack	25.4/34.0/30.0, 36.3mm stack height

CONTROLS

Handlebar	Bontrager Flat Top	25.4mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	Shimano Ultegra STI, adjustable reach	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano 105 T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur . . .	Shimano 105 GS	
Crankset	Bontrager Race Lite 52/42/30 w/Giga-X-Pipe	74/130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	SRAM PG970 12-26, 9spd	

WHEELSET

Front wheel	Bontrager Select, 20°	593mm ERD
Spokes	DT 14g, ProLock brass nipples, 281mm, radial	
Tire	Bontrager Race Lite HardCase, 700 x 28c, Velox 16mm rim strip	
Rear wheel	Bontrager Select, 24°	603mm ERD
Spokes	DT 14g, ProLock brass nipples, 293/294mm, 2x	
Tire	Bontrager Race Lite HardCase, 700 x 28c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Select	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .	Alloy w/integral bolt	31.9mm inner diameter
Brakes	Alloy dual pivot, long reach, cartridge pads	
Pedals	Shimano SPD M505, clipless 9/16" axle	
Additional	Cane Creek CrossTop inline levers	

FIT *dimensions in mm, unless specified*

Frame	Size	47	52	55	57	61
Rider height, in.		67.0	68.7	70.6	73.6	76.0
	cm	170	175	179	187	193
Handlebar	width	400	420	440	440	460
Handlebar	rise	0	0	0	0	0
Stem	length	80	90	100	110	120
	angle	25	25	25	25	25
Headset spacers		30	30	30	25	25
Crank	length	170	172.5	172.5	175	175
Seatpost	length	330	330	330	330	330
Steerer	length	213.3	238.3	258.3	278.3	298.3

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.0	72.0	72.5	73.0	73.0
Fork offset	50.0	43.0	43.0	43.0	43.0
Trail	63	63	60	57	57
Seat tube angle	75.0	74.0	73.0	73.0	72.0
Effective top tube	515	530	545	565	590
Seat tube	331	398	434	469	510
Standover	654	704	732	762	792
Wheelbase	995	1000	1000	1015	1028
Bottom bracket height	267	267	267	267	267
Chainstay	430	430	430	430	430
Head tube	110	135	155	180	200

GEARING

	30 42 52
12	66 93 115
13	61 85 106
14	57 79 98
15	53 74 92
17	47 65 81
19	42 58 72
21	38 53 65
23	35 48 60
26	31 43 53

LeMond Poprad

346000*15.054
Bike weight: 21.6 lb/9.81 kg

FRAMESET

Main tubes	True Temper/Reynolds butted steel	
Stays	True Temper/Reynolds butted steel	
Color	White	
Fork	X-Lite aluminum, 414mm axle-crown length	
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 36.5mm stack height

CONTROLS

Handlebar	Bontrager Race CX	25.4mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	Shimano 105 STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano 105	Down pull, 31.8 mm/ 1 1/4" attachment
Rear derailleur . . .	Shimano 105	
Crankset	Bontrager Race 46/38	64/104mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe SL	68 x 108 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	SRAM PG950 12-26, 9spd	

WHEELSET

Front wheel	Bontrager Select, 20°	593mm ERD
Spokes	DT 14g, ProLock brass nipples, 281mm, radial	
Tire	Bontrager Jones CX, 127tpi, 700 x 32c, Velox 16mm rim strip	
Rear wheel	Bontrager Select, 24°	603mm ERD
Spokes	DT 14g, ProLock brass nipples, 293/294mm, 2x	
Tire	Bontrager Jones CX, 127tpi, 700 x 32c, Velox 16mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Select	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .	Alloy w/integral bolt, cable hanger	31.9mm inner diameter
Brakes	Avid Shorty 4, cantilevers	
Pedals	-not supplied- axle	
Additional	Front brake hanger	

FIT *dimensions in mm, unless specified*

Frame	Size	49	52	55	57	59
Rider height, in.		68.3	70.5	72.1	74.1	76.2
	cm	173	179	183	188	194
Handlebar	width	420	440	460	460	460
Stem	length	90	100	100	110	120
	angle	10	10	10	10	10
Headset spacers		40	40	40	40	30
Crank	length	170	170	175	175	175
Seatpost	length	330	330	330	330	330
Steerer	length	188.5	203.5	219.5	236.0	244.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.0	72.0	72.5	72.5	73.0
Fork offset	45.0	45.0	45.0	45.0	45.0
Trail	65	65	62	62	59
Seat tube angle	74.0	73.5	73.0	72.5	72.5
Effective top tube	525	542	562	578	590
Seat tube	519	549	578	598	618
Standover	776	795	817	833	852
Wheelbase	992	1004	1015	1025	1033
Bottom bracket height	269	269	269	269	269
Chainstay	430	430	430	430	430
Head tube	85	100	116	133	151

GEARING

	38 46
12	86 104
13	79 96
14	73 89
15	68 83
17	60 73
19	54 65
21	49 59
23	45 54
26	39 48 0

LeMond Fillmore

3464000*15.114
Bike weight: 17.9 lb/8.13 kg

FRAMESET

Main tubes	True Temper OX Platinum	
Stays	True Temper OX Platinum	
Color	Metallic Black/Cream • Cream panel	
Fork	Bontrager Race, 371mm axle-crown length	
Headset	Slimstack	25.4/34.0/30.0, 36.3mm stack height

CONTROLS

Handlebar	Bontrager Race Lite Flat Top	31.8mm clamp diameter
Stem	Bontrager Race Lite	40.0mm steerer clamp height
Brake levers	Shimano BL-R400	
Grips	Bontrager Gel	

DRIVETRAIN

Crankset	Bontrager Race 44T	64/104mm bolt hole circle
Bottom bracket	TruVativ Giga-Pipe SL	68 x 108 (shell x axle,mm), ISIS splined axle
Chain	SRAM PC-950	9 speed, 98 links
Cassette	Shimano MX30, 18T	

WHEELSET

Front wheel	Bontrager Select Track, 20°	593mm ERD
Spokes	DT 14g, ProLock brass nipples, 281mm, radial	
Tire	Bontrager Race Lite, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Select Track, 24°	593mm ERD
Spokes	DT 14g, ProLock brass nipples, 291/291mm, 2x	
Tire	Bontrager Race Lite, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder	Alloy w/integral bolt	31.9mm inner diameter
Brakes	Alloy dual pivot, cartridge pads front Alloy dual pivot, long reach, cartridge pads rear	
Pedals	-not supplied- 9/16" axle	
Additional	Shimano Dura-Ace Track cog, 16T	

FIT *dimensions in mm, unless specified*

Frame	Size	49	53	55	57	61
Rider height, in.		66.9	69.7	71.5	73.3	77.1
	cm	170	177	182	186	196
Handlebar	width	420	440	440	460	460
Handlebar	rise	0	0	0	0	0
Stem	length	90	100	100	110	120
	angle	17	17	17	17	17
Headset spacers		30	30	30	30	30
Crank	length	170	170	170	175	175
Seatpost	length	250	250	250	250	250
Steerer	length	187.3	218.3	234.8	253.3	297.3

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.0	73.0	73.5	73.5	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0
Trail	62	56	58	58	55
Seat tube angle	74.0	73.3	73.0	72.5	72.0
Effective top tube	519	545	565	576	606
Seat tube	517	557	576	596	636
Standover	750	786	805	822	863
Wheelbase	970	980	987	992	1013
Bottom bracket height	266	266	266	266	270
Chainstay	413	413	413	413	413
Head tube	85	116	133	151	195

GEARING

44
18 65

Trek Elite 9.8

1080600*15.104
Bike weight: 23.9 lb/10.85 kg

FRAMESET

Main tubes	OCV HC superlight carbon fiber composite
Stays	OCV 120 carbon fiber composite
Color	Platinum Silver/Baja Blue
Fork	RockShox SID Team w/PopLoc 80mm travel, 444mm axle-crown length
Headset	Alloy headset, semi-cartridge 25.4/34.0/30.0, 27.2mm stack height

CONTROLS

Handlebar	Bontrager Race X Lite	31.8mm clamp diameter
Stem	Bontrager Race Lite	40.0mm steerer clamp height
Shift levers	Shimano Deore XT	
Brake levers	Integrated brake/shift	
Grips	Bontrager Race, dual density	

DRIVETRAIN

Front derailleur	Shimano Deore XT	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur	Shimano Deore XT SGS	
Crankset	Shimano Deore XT 44/32/22	64/104mm bolt hole circle
Bottom bracket	integral axle	(shell x axle,mm), Integral axle
Chain	Shimano HG-93	9 speed, 108 links
Cassette	Shimano Deore XT 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Race Lite, tubeless compatible, 24"	539mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 252mm, radial	
Tire	Bontrager Super-X, tubeless ready, 127tpi, 49/48, Tubeless rim strip	
Rear wheel	Bontrager Race Lite, tubeless compatible, 28"	542mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 265/268mm, 3x	
Tire	Bontrager Super-X, tubeless ready, 127tpi, 49/48, Tubeless assymetric rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Race X Lite	31.6mm outer diameter
Saddle	Bontrager Race Lite Luxe	
Seatpost binder	Alloy w/integral bolt	39.85mm inner diameter
Brakes	Avid Single Digit 5, linear pull	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional	RockShox PopLoc lever	

FIT *dimensions in mm, unless specified*

Frame	Size	17.5	19.5	21.5
Rider height, in.		69.6	72.5	75.5
	cm	177	184	192
Handlebar	width	620	620	620
Stem	length	100	100	120
	angle	7	7	7
Headset spacers		30	30	30
Crank	length	175	175	175
Seatpost	length	400	400	400
Steerer	length	219.2	240.2	260.2

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	71.0	71.0
Fork offset	38.8	38.8	38.8
Trail	71	71	71
Seat tube angle	73.0	73.0	72.5
Effective top tube	588	625	641
Seat tube	445	495	545
Standover	744	782	821
Wheelbase	1064	1102	1113
Bottom bracket height	297	297	297
Chainstay	424	424	424
Head tube	126	147	167

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Trek 8500

1056600*15.084
Bike weight: 26.0 lb/11.80 kg

FRAMESET

Main tubes		ZR9000	
Stays		ZR9000	
Color		Matte Lava Black/Matte Black	
Fork		RockShox Reba Team w/PopLoc	85mm travel, 458mm axle-crown length
Headset		Alloy aheadset, semi-cartridge	25.4/34.0/30.0, 27.2mm stack height

CONTROLS

Handlebar		Bontrager Crowbar Race Lite	31.8mm clamp diameter
Stem		Bontrager Race Lite	40.0mm steerer clamp height
Shift levers		Shimano Deore XT	
Brake levers		Integrated brake/shift	
Grips		Bontrager Race, dual density	

DRIVETRAIN

Front derailleur	...	Shimano Deore XT	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur	...	Shimano Deore XT SGS	
Crankset		Shimano Deore XT 44/32/22	64/104mm bolt hole circle
Bottom bracket		integral axle	73 x 113 (shell x axle,mm), Integral axle
Chain		Shimano HG-73	9 speed, 108 links
Cassette		Shimano Deore XT 11-34, 9spd	

WHEELSET

Front wheel		Bontrager Race Lite Disc, tubeless compatible, 28°	537mm ERD
Spokes		DT 14/15G butted stainless, ProLock alloy nipples, 266/267mm, 3x	
Tire		Bontrager Super-X, tubeless ready, 127tpi, 52/52, Tubeless assymetric rim strip	
Rear wheel		Bontrager Race Lite Disc, tubeless compatible, 28°	537mm ERD
Spokes		DT 14/15G butted stainless, ProLock alloy nipples, 266/267mm, 3x	
Tire		Bontrager Super-X, tubeless ready, 127tpi, 52/52, Tubeless assymetric rim strip	
Inner tubes		Presta valve	

OTHER

Seatpost		Bontrager Race Lite	31.6mm outer diameter
Saddle		Bontrager Race Lite Luxe	
Seatpost binder		Alloy w/integral quick-release	36.4mm inner diameter
Brakes		Shimano Deore XT, hydraulic discs	
		160mm discs, 44mm BCD	
Disc hose, mm		15.5 17.5 19.5 21.5	
Front		750 750 750 750	
Rear		1350 1350 1400 1400	
Pedals		Shimano SPD M520, clipless	9/16" axle
Additional		RockShox PopLoc lever	

FIT dimensions in mm, unless specified

Frame	Size	15.5	17.5	19.5	21.5
Rider height, in.		67.4	71.4	74.5	77.1
	cm	171	181	189	196
Handlebar	width	630	630	630	630
Handlebar	rise	25	25	25	25
Stem	length	90	100	100	120
	angle	7	7	7	7
Headset spacers		30	30	30	30
Crank	length	170	175	175	175
Seatpost	length	330	400	400	400
Steerer	length	198.2	213.2	228.2	243.2

GEOMETRY

dimensions in mm, unless specified

Head tube angle	71.0	71.0	71.0	71.0
Fork offset	38.0	38.0	38.0	38.0
Trail				
Seat tube angle	73.5	73.0	73.0	72.5
Effective top tube	550	588	625	641
Seat tube	394	445	495	546
Standover	706	740	777	816
Wheelbase	1030	1064	1101	1114
Bottom bracket height	297	297	297	300
Chainstay	424	424	424	424
Head tube	105	120	135	150

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Trek 8000

1052600*15.084
Bike weight: 27.0 lb/12.26 kg

FRAMESET

Main tubes	Alpha SLR aluminum	
Stays	Alpha SLR aluminum	
Color	Matte Baja Blue/Matte Midnight Blue	
Fork	RockShox Duke Race	80mm travel, 451mm axle-crown length
Headset	Alloy aheadset, semi-cartridge	25.4/34.0/30.0, 27.2mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Race Lite	31.8mm clamp diameter
Stem	Bontrager Race	40.0mm steerer clamp height
Shift levers	Shimano Deore XT	
Brake levers	Integrated brake/shift	
Grips	Bontrager Race, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Deore LX	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore XT SGS	
Crankset	Shimano Deore LX 44/32/22	64/104mm bolt hole circle
Bottom bracket . . .		73 x 113 (shell x axle,mm), Integral axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	SRAM PG970 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Select, disc compatible, 28°	541mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 268/268mm, 3x	
Tire	Bontrager ACX, folding, 26 x 2.2, Velox 22mm rim strip	
Rear wheel	Bontrager Select, disc compatible, 28°	541mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 268/267mm, 3x	
Tire	Bontrager ACX, folding, 26 x 2.2, Velox 22mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Race	31.6mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .	Alloy w/quick release	36.4mm inner diameter
Brakes	Shimano Deore LX, hydraulic disc front, Shimano M420, V type rear	
	160mm discs, 44mm BCD	
Disc hose, mm	15.5 17.5 19.5 21.5	
Front	750 750 800 800	
Rear	1300 1300 1400 1400	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional		

FIT dimensions in mm, unless specified

Frame	Size	15.5	17.5	19.5	21.5
Rider height, in.		67.1	71.0	74.1	76.7
	cm	170	180	188	195
Handlebar	width	630	630	630	630
Handlebar	rise	25	25	25	25
Stem	length	90	100	100	120
	angle	7	7	7	7
Headset spacers		30	30	30	30
Crank	length	170	175	175	175
Seatpost	length	330	400	400	400
Steerer	length	198.2	213.2	228.2	243.2

GEOMETRY

dimensions in mm, unless specified

Head tube angle	71.0	71.0	71.0	71.0
Fork offset	38.0	38.0	38.0	38.0
Trail				
Seat tube angle	73.5	73.0	73.0	72.5
Effective top tube	550	588	625	641
Seat tube	394	445	495	546
Standover	706	740	777	816
Wheelbase	1030	1064	1101	1114
Bottom bracket height	297	297	297	300
Chainstay	424	424	424	424
Head tube	105	120	135	150

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Trek 8000 Disc

1052600*15.084
Bike weight: 25.7 lb/11.67 kg

FRAMESET

Main tubes		ZR9000	
Stays		ZR9000	
Color		Matte Baja Blue/Matte Midnight Blue	
Fork		RockShox Duke Race	80mm travel, 451mm axle-crown length
Headset		Alloy aheadset, semi-cartridge	25.4/34.0/30.0, 27.2mm stack height

CONTROLS

Handlebar		Bontrager Crowbar Race	31.8mm clamp diameter
Stem		Bontrager Race	40.0mm steerer clamp height
Shift levers		Shimano Deore XT	
Brake levers		Avid SD-5, long pull	
Grips		Bontrager Race, dual density	

DRIVETRAIN

Front derailleur	...	Shimano Deore LX	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur		Shimano Deore XT SGS	
Crankset		Shimano Deore LX 44/32/22	64/104mm bolt hole circle
Bottom bracket		integral axle	73 x 113 (shell x axle,mm), Integral axle
Chain		Shimano HG-53	9 speed, 108 links
Cassette		SRAM PG970 11-34, 9spd	

WHEELSET

Front wheel		Bontrager Select, disc compatible, 28°	541mm ERD
Spokes		DT 14/15G butted stainless, ProLock alloy nipples, 268/268mm, 3x	
Tire		Bontrager ACX, folding, 26 x 2.2, Velox 22mm rim strip	
Rear wheel		Bontrager Select, disc compatible, 28°	541mm ERD
Spokes		DT 14/15G butted stainless, ProLock alloy nipples, 268/267mm, 3x	
Tire		Bontrager ACX, folding, 26 x 2.2, Velox 22mm rim strip	
Inner tubes		Presta valve	

OTHER

Seatpost		Bontrager Race	31.6mm outer diameter
Saddle		Bontrager Race	
Seatpost binder		Alloy w/integral bolt	36.4mm inner diameter
Brakes		Shimano Deore LX, hydraulic disc front, Shimano Deore LX, hydraulic disc rear	
		160mm discs, 44mm BCD	
Pedals		Shimano SPD M520, clipless	9/16" axle
Additional			

FIT *dimensions in mm, unless specified*

Frame	Size	15.5	17.5	19.5	21.5
Rider height	in.	67.1	71.0	74.1	76.7
	cm	170	180	188	195
Handlebar	width	630	630	630	630
Handlebar	rise	25	25	25	25
Stem	length	90	100	100	120
	angle	7	7	7	7
Headset spacers		30	30	30	30
Crank	length	170	175	175	175
Seatpost	length	330	400	400	400
Steerer	length	198.2	218.2	238.2	258.2

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	71.0	71.0	71.0
Fork offset	38.0	38.0	38.0	38.0
Trail				
Seat tube angle	73.5	73.0	73.0	72.5
Effective top tube	550	588	625	641
Seat tube	394	445	495	546
Standover	706	740	777	816
Wheelbase	1030	1064	1101	1114
Bottom bracket height	297	297	297	300
Chainstay	424	424	424	424
Head tube	105	120	135	150

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Trek 6700

1044600*15.074
Bike weight: 28.7 lb/13.03 kg

FRAMESET

Main tubes	Alpha SLR aluminum	
Stays	Alpha SLR aluminum	
Color	Rally Blue/Liquid Silver	
Fork	RockShox Pilot SL	80mm travel, 451mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Sport	41.0mm steerer clamp height
Shift levers	Shimano Deore	
Brake levers	Alloy, direct pull	
Grips	Bontrager, dual density	

DRIVETRAIN

Front derailleur	Shimano Deore	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur	Shimano Deore LX SGS	
Crankset	Bontrager Select 44/32/22	64/104mm bolt hole circle
Bottom bracket	TruVativ Giga-Pipe	73 x 113 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	SRAM PG970 11-34, 9spd	

WHEELSET

Front wheel	Alloy, disc compatible, QR hub, 32°, Bontrager Maverick OSB rim	542mm ERD
Spokes	DT 14G stainless, 263/263mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, Velox 22mm rim strip	
Rear wheel	Alloy, disc compatible, QR hub, 32°, Bontrager Maverick OSB rim	542mm ERD
Spokes	DT 14G stainless, 263/263mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, Velox 22mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	31.6mm outer diameter
Saddle	Bontrager FS 2000	
Seatpost binder	Alloy w/integral quick-release	36.4mm inner diameter
Brakes	Shimano M420, V type	
Pedals	Shimano SPD M505, clipless	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	15.5	17.5	19.5	21.5
Rider height, in.		67.1	71.4	74.4	76.7
	cm	170	181	189	195
Handlebar	width	630	630	630	630
Handlebar	rise	25	25	25	25
Stem	length	90	105	105	120
	angle	7	7	7	7
Headset spacers		30	30	30	30
Crank	length	175	175	175	175
Seatpost	length	330	330	330	330
Steerer	length	198.5	213.5	228.5	243.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	71.0	71.0	71.0
Fork offset	38.0	38.0	38.0	38.0
Trail				
Seat tube angle	73.5	73.0	73.0	72.5
Effective top tube	550	588	625	641
Seat tube	394	445	495	546
Standover	706	740	777	816
Wheelbase	1030	1064	1101	1114
Bottom bracket height	297	297	297	300
Chainstay	424	424	424	424
Head tube	105	120	135	150

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Trek 6700 Disc

1045600*15.084
Bike weight: 29.0 lb/13.17 kg

FRAMESET

Main tubes	Alpha SLR aluminum	
Stays	Alpha SLR aluminum	
Color	Metallic Charcoal/Metallic Black	
Fork	RockShox Pilot SL	80mm travel, 451mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	Shimano Deore	
Brake levers	Hydraulic, attached to brake	
Grips	Bontrager, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Deore	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore LX SGS	
Crankset	Bontrager Select 44/32/22	64/104mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe	73 x 113 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	SRAM PG970 11-34, 9spd	

WHEELSET

Front wheel	Alloy, disc compatible, QR hub, 32°, Bontrager Maverick OSB rim	542mm ERD
Spokes	DT 14G stainless, 263/263mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, Velox 22mm rim strip	
Rear wheel	Alloy, disc compatible, QR hub, 32°, Bontrager Maverick OSB rim	542mm ERD
Spokes	DT 14G stainless, 263/263mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, Velox 22mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Select	31.6mm outer diameter
Saddle	Bontrager Select, hollow CrMo rails	
Seatpost binder . . .	Alloy w/integral quick-release	36.4mm inner diameter
Brakes	Hayes HFX-9, hydraulic discs	
	6.3 in. discs, 44mm BCD	
Disc hose, mm	15.5 17.5 19.5 21.5	
Front	690 690 690 750	
Rear	1220 1280 1350 1350	
Pedals	Shimano SPD M505, clipless	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	15.5	17.5	19.5	21.5
Rider height, in.		67.1	71.4	74.4	76.7
	cm	170	181	189	195
Handlebar	width	630	630	630	630
Handlebar	rise	25	25	25	25
Stem	length	90	105	105	120
	angle	7	7	7	7
Headset spacers		30	30	30	30
Crank	length	175	175	175	175
Seatpost	length	250	330	330	330
Steerer	length	198.5	213.5	228.5	243.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	71.0	71.0	71.0
Fork offset	38.0	38.0	38.0	38.0
Trail				
Seat tube angle	73.5	73.0	73.0	72.5
Effective top tube	550	588	625	641
Seat tube	394	445	495	546
Standover	706	740	777	816
Wheelbase	1030	1064	1101	1114
Bottom bracket height	297	297	297	300
Chainstay	424	424	424	424
Head tube	105	120	135	150

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Trek 6700E

Bike weight: 28.7 lb/13.03 kg

FRAMESET

Main tubes	Alpha SLR aluminum	
Stays	Alpha SLR aluminum	
Color	Rally Blue/Liquid Silver	
Fork	RockShox Pilot SL	80mm travel, 451mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 36mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Select	31.8mm clamp diameter
Stem	Bontrager Select	40.0mm steerer clamp height
Shift levers	Shimano Deore LX	
Brake levers	Alloy, direct pull	
Grips	Bontrager	

DRIVETRAIN

Front derailleur . . .	Shimano Deore LX	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore XT SGS	
Crankset	Shimano M540 44/32/22	64/104mm bolt hole circle
Bottom bracket . . .	Shimano ES-30	73 x 121 (shell x axle,mm), Square axle
Chain	Shimano HG-53	9 speed, 110 links
Cassette	SRAM PG970 11-34, 9spd	

WHEELSET

Front wheel	Shimano M525, disc hub, 32°, Bontrager Maverick OSB rim	571mm ERD
Spokes	15g stainless, 262mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, PVC rim strip	
Rear wheel	Shimano M525, disc hub, 32°, Bontrager Maverick OSB rim	571mm ERD
Spokes	DT 14G stainless, 261/261mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, PVC rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Select	31.6mm outer diameter
Saddle	Bontrager Select	
Seatpost binder . . .	Alloy w/integral quick-release	36.4mm inner diameter
Brakes	Shimano M430, V type	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	15.5	17.5	19.5	21.5
Rider height, in.		67.8	71.6	75.4	77.6
	cm	172	182	191	197
Handlebar	width	600	620	620	620
Handlebar	rise	25	25	25	25
Stem	length	90	100	110	120
	angle	7	7	7	7
Headset spacers		40	40	40	40
Crank	length	170	175	175	175
Seatpost	length	330	330	330	400
Steerer	length	208	223	238	253

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	71.0	71.0	71.0
Fork offset	39.0	39.0	39.0	39.0
Trail				
Seat tube angle	73.5	73.0	73.0	72.5
Effective top tube	550	588	625	641
Seat tube	394	445	495	546
Standover	706	740	777	816
Wheelbase	1030	1064	1101	1114
Bottom bracket height	297	297	297	300
Chainstay	424	424	424	424
Head tube	105	120	135	150

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Trek 6700 WSD

Bike weight: 28.6 lb/12.98 kg

FRAMESET

Main tubes	Alpha SLR aluminum	
Stays	Alpha SLR aluminum	
Color	Pearl White/Bright Silver	
Fork	RockShox Pilot SL, light springs	80mm travel, 451mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 36mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Select	25.4mm clamp diameter
Stem	Bontrager Select	40.0mm steerer clamp height
Shift levers	Shimano Deore LX	
Brake levers	Hydraulic, attached to brake	
Grips	Bontrager Race, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Deore LX	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore XT SGS	
Crankset	Shimano M540 44/32/22	64/104mm bolt hole circle
Bottom bracket . . .	Shimano ES-30	73 x 121 (shell x axle,mm), Square axle
Chain	Shimano HG-73	9 speed, 110 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Shimano M525, disc hub, 32°, WTB Speed Disc rim	571mm ERD
Spokes	DT 15g, 260mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, PVC rim strip	
Rear wheel	Shimano M525, disc hub, 32°, WTB Speed Disc rim	571mm ERD
Spokes	DT 15g, 259/259mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, PVC rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Select	31.6mm outer diameter
Saddle	Bontrager Select WSD	
Seatpost binder . . .	Alloy w/quick release	36.4mm inner diameter
Brakes	Hayes HFX-9, hydraulic discs, short reach levers	
	6.3 in. discs, 44mm BCD	
Disc hose, mm	14 16 18	
Front	690 690 690	
Rear	1220 1220 1280	
Pedals	Shimano SPD M520, clipless 9/16" axle	
Additional	2 water bottle mounts, rack mounts (1 bottle/no rack on 14, 16)	

FIT *dimensions in mm, unless specified*

Frame	Size	14	16	18
Rider height, in.		63.7	65.4	68.7
	cm	162	166	175
Handlebar	width	560	580	600
Handlebar	rise	25	25	25
Stem	length	70	80	90
	angle	7	7	7
Headset spacers		40	40	40
Crank	length	170	170	170
Seatpost	length	330	330	400
Steerer	length	193	193	208

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.0	70.0
Fork offset	39.0	39.0	39.0
Trail			
Seat tube angle	75.0	74.0	73.5
Effective top tube	518	532	563
Seat tube	356	406	457
Standover	670	701	741
Wheelbase	1018	1023	1051
Bottom bracket height	289	289	293
Chainstay	424	424	424
Head tube	90	90	105

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Trek 6700 WSD Disc

1044603*15.084
Bike weight: 28.6 lb/12.98 kg

FRAMESET

Main tubes	Alpha SLR aluminum	
Stays	Alpha SLR aluminum	
Color	Pearl White/Bright Silver	
Fork	RockShox Pilot SL, light springs	80mm travel, 451mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Select	25.4mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	Shimano Deore	
Brake levers	Hydraulic, attached to brake	
Grips	Bontrager Race, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Deore	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore LX SGS	
Crankset	Bontrager Select 44/32/22	64/104mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe	73 x 113 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Alloy, disc compatible, QR hub, 32°, Bontrager Maverick OSB rim	542mm ERD
Spokes	DT 14G stainless, 263/263mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, Velox 22mm rim strip	
Rear wheel	Alloy, disc compatible, QR hub, 32°, Bontrager Maverick OSB rim	542mm ERD
Spokes	DT 14G stainless, 262/263mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, Velox 22mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Select	31.6mm outer diameter
Saddle	Bontrager Select WSD	
Seatpost binder . . .	Alloy w/quick release	36.4mm inner diameter
Brakes	Hayes HFX-9, hydraulic discs	
	6.3 in. discs, 44mm BCD	
Disc hose, mm	14 16 18	
Front	690 690 690	
Rear	1220 1220 1280	
Pedals	Shimano SPD M505, clipless	9/16" axle
Additional	2 water bottle mounts, rack mounts (1 bottle/no rack on 14, 16)	

FIT dimensions in mm, unless specified

Frame	Size	14	16	18
Rider height, in.		62.7	64.0	68.4
	cm	159	162	174
Handlebar	width	600	600	600
Handlebar	rise	25	25	25
Stem	length	60	70	90
	angle	10	10	10
Headset spacers		30	30	30
Crank	length	170	170	175
Seatpost	length	250	250	330
Steerer	length	183.5	183.5	198.5

GEOMETRY dimensions in mm, unless specified

Head tube angle	70.0	70.0	70.0
Fork offset	38.2	38.2	38.2
Trail			
Seat tube angle	75.0	74.0	73.5
Effective top tube	518	532	563
Seat tube	356	406	457
Standover	670	701	741
Wheelbase	1018	1023	1051
Bottom bracket height	289	289	293
Chainstay	424	424	424
Head tube	90	90	105

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Trek 6500

Bike weight: 28.7 lb/13.03 kg

FRAMESET

Main tubes	Alpha SLR aluminum	
Stays	Alpha SLR aluminum	
Color	Matte Smooth Silver/Matte Black Chrome	
	Hot Orange/ Metallic Charcoal	
Fork	Manitou Axel Comp	80mm travel, 451mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 36mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	25.4mm clamp diameter
Stem	Bontrager Sport	40.0mm steerer clamp height
Shift levers	Shimano Alivio	
Brake levers	Alloy, direct pull	
Grips	Bontrager, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Alivio	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore SGS	
Crankset	Bontrager Sport 44/32/22	64/104mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe	73 x 113 (shell x axle,mm), Square axle
Chain	IG-51	9 speed, 108 links
Cassette	SRAM PG850 11-32, 8spd	

WHEELSET

Front wheel	Shimano M475, disc hub, 32°, WTB Speed Disc rim	571mm ERD
Spokes	15g stainless, 260mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, PVC rim strip	
Rear wheel	Shimano M475, disc hub, 32°, WTB Speed Disc rim	571mm ERD
Spokes	DT 14G stainless, 259/259mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, PVC rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	31.6mm outer diameter
Saddle	Bontrager Select	
Seatpost binder . . .	Alloy w/integral quick-release	36.4mm inner diameter
Brakes	Hayes Sole XC, hydraulic discs	
Pedals	Alloy platform, clipless adaptable	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	15.5	17.5	19.5	21.5
Rider height, in.		67.5	71.7	75.5	77.5
	cm	171	182	192	197
Handlebar	width	600	620	620	620
Handlebar	rise	25	25	25	25
Stem	length	90	100	110	120
	angle	10	10	10	10
Headset spacers		40	40	40	40
Crank	length	170	175	175	175
Seatpost	length	330	330	330	400
Steerer	length	217	232	247	262

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	71.0	71.0	71.0
Fork offset	39.0	39.0	39.0	39.0
Trail				
Seat tube angle	73.5	73.0	73.0	72.5
Effective top tube	550	588	625	641
Seat tube	394	445	495	546
Standover	706	740	777	816
Wheelbase	1030	1064	1101	1114
Bottom bracket height	297	297	297	300
Chainstay	424	424	424	424
Head tube	105	120	135	150

GEARING

	22 32 44
11	52 76 105
12	48 70 96
14	41 60 82
16	36 52 72
18	32 47 64
21	27 40 55
26	22 32 44
32	18 26 36

Trek 4500

FRAMESET

Main tubes	Alpha SL aluminum	
Stays	Alpha SL aluminum	
Color	Rally Blue/Metallic Black	
	Metallic Black/Rage Red	
Fork.	RockShox Judy TT	80mm travel, 432mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 25.7mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	25.4mm clamp diameter
Stem	Bontrager Sport	40.0mm steerer clamp height
Shift levers	Shimano Alivio	
Brake levers	Alloy, direct pull	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano Acera-X	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore SGS	
Crankset	Shimano MC08 42/32/22	64/104mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 110.5 (shell x axle,mm), Square axle
Chain.	IG-51	3/32", 108 links
Cassette.	SRAM PG850 11-32, 8spd	

WHEELSET

Front wheel.	Shimano M495, disc hub, 32°, WTB Speed Disc rim	571mm ERD
Spokes	14g stainless, 260mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, PVC rim strip	
Rear wheel	Shimano M495, disc hub, 32°, WTB Speed Disc rim	571mm ERD
Spokes	14g stainless, 259/259mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, PVC rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost.	Bontrager Sport	31.6mm outer diameter
Saddle	Bontrager Select	
Seatpost binder. . . .		36.4mm inner diameter
Brakes	Tektro direct pull	
Pedals	Alloy platform, clipless adaptable	9/16" axle
Additional		

FIT

dimensions in mm, unless specified

Frame	Size	13	16	18	19.5	21	22.5	24
Rider height, in.		63.1	65.5	68.6	70.2	73.2	74.1	74.9
	cm	160	166	174	178	186	188	190
Handlebar	width	600	600	620	620	620	620	620
Handlebar	rise	25	25	25	25	25	25	25
Stem	length	90	90	110	110	120	120	130
	angle	25	25	25	25	25	25	25
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	170	170	170	170	170	170
Seatpost	length	300	300	350	350	350	350	350
Steerer	length	217	217	237	257	277	297	317

GEOMETRY

dimensions in mm, unless specified

Head tube angle	70.0	70.5	70.5	70.5	70.5	70.5	70.5
Fork offset	39.0	39.0	39.0	39.0	39.0	39.0	39.0
Trail	82	79	79	79	79	79	82
Seat tube angle	74.0	73.5	73.5	73.0	73.0	72.5	72.0
Effective top tube	520	550	560	580	600	610	615
Seat tube	330	406	457	495	533	572	610
Standover	655	706	746	776	807	839	870
Wheelbase	1012	1035	1047	1063	1084	1089	1090
Bottom bracket height	287	291	293	293	293	295	297
Chainstay	430	430	430	430	430	430	430
Head tube	105	105	125	145	165	185	205

GEARING

	22 32 42
11	52 76 100
12	48 70 92
14	41 60 79
16	36 52 69
18	32 47 61
21	27 40 52
26	22 32 42
32	18 26 34

Trek 4500E

FRAMESET

Main tubes	Alpha SL aluminum	
Stays	Alpha SL aluminum	
Color	Rally Blue/Metallic Black	
	Metallic Black/Rage Red	
Fork	RockShox Judy TT	80mm travel, 432mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 25.7mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	25.4mm clamp diameter
Stem	Bontrager Sport	40.0mm steerer clamp height
Shift levers	Shimano Deore	
Brake levers	Alloy, direct pull	
Grips	Bontrager Sport	

DRIVETRAIN

Front derailleur . . .	Shimano Alivio	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore SGS	
Crankset	Shimano MC20 42/32/22	64/104mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 110.5 (shell x axle,mm), Square axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Shimano RM-60 hub, 32°, WTB Dual Duty rim	571mm ERD
Spokes	14g stainless, 264mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, PVC rim strip	
Rear wheel	Shimano RM-60 hub, 32°, Rigida ZAC-19R rim	571mm ERD
Spokes	14g stainless, 262.5/263.5mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, PVC rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Bontrager Sport	31.6mm outer diameter
Saddle	Bontrager Select	
Seatpost binder . . .		36.4mm inner diameter
Brakes	Tektro direct pull	
Pedals	Alloy platform, clipless adaptable	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame Size	13	16	18	19.5	21	22.5	24
Rider height, in.	62.8	66.3	69.3	71.0	73.8	74.8	75.8
cm	160	168	176	180	188	190	192
Handlebar width	600	600	620	620	620	620	620
Handlebar rise	25	25	25	25	25	25	25
Stem length	80	90	110	110	120	120	130
angle	10	10	10	10	10	10	10
Headset spacers	40	40	40	40	40	40	40
Crank length	170	170	175	175	175	175	175
Seatpost length	300	300	350	350	350	350	350
Steerer length	217	217	237	257	277	297	317

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.5	70.5	70.5	70.5	70.5	70.5
Fork offset	39.0	39.0	39.0	39.0	39.0	39.0	39.0
Trail	82	79	79	79	79	79	82
Seat tube angle	74.0	73.5	73.5	73.0	73.0	72.5	72.0
Effective top tube	520	550	560	580	600	610	615
Seat tube	330	406	457	495	533	572	610
Standover	655	706	746	776	807	839	870
Wheelbase	1012	1035	1047	1063	1084	1089	1090
Bottom bracket height	287	291	293	293	293	295	297
Chainstay	430	430	430	430	430	430	430
Head tube	105	105	125	145	165	185	205

GEARING

	22	32	42
11	52	76	100
13	44	65	85
15	38	56	73
17	34	49	65
20	29	42	55
23	25	36	48
26	22	32	42
30	19	28	37
34	17	25	32

Trek 4500 Disc

FRAMESET

Main tubes	Alpha SL aluminum	
Stays	Alpha SL aluminum	
Color	Rally Blue/Metallic Black	
	Metallic Black/Rage Red	
Fork.	RockShox Judy TT	80mm travel, 432mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 25.7mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	25.4mm clamp diameter
Stem	Bontrager Sport	40.0mm steerer clamp height
Shift levers	Shimano Alivio	
Brake levers	Alloy, direct pull	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano Acera-X	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore SGS	
Crankset	Shimano MC08 42/32/22	64/104mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 110.5 (shell x axle,mm), Square axle
Chain.	IG-51	3/32", 108 links
Cassette.	SRAM PG850 11-32, 8spd	

WHEELSET

Front wheel.	Shimano M495, disc hub, 32°, WTB Speed Disc rim	571mm ERD
Spokes	14g stainless, 260mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, PVC rim strip	
Rear wheel	Shimano M495, disc hub, 32°, WTB Speed Disc rim	571mm ERD
Spokes	14g stainless, 259/259mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, PVC rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost.	Bontrager Sport	31.6mm outer diameter
Saddle	Bontrager Select	
Seatpost binder. . . .		36.4mm inner diameter
Brakes	Shimano M495, mechanical discs	
Pedals	Alloy platform, clipless adaptable	9/16" axle
Additional		

FIT

dimensions in mm, unless specified

Frame	Size	13	16	18	19.5	21	22.5	24
Rider height, in.		63.1	65.5	68.6	70.2	73.2	74.1	74.9
	cm	160	166	174	178	186	188	190
Handlebar	width	600	600	620	620	620	620	620
Handlebar	rise	25	25	25	25	25	25	25
Stem	length	90	90	110	110	120	120	130
	angle	25	25	25	25	25	25	25
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	170	170	170	170	170	170
Seatpost	length	300	300	350	350	350	350	350
Steerer	length	217	217	237	257	277	297	317

GEOMETRY

dimensions in mm, unless specified

Head tube angle	70.0	70.5	70.5	70.5	70.5	70.5	70.5
Fork offset	39.0	39.0	39.0	39.0	39.0	39.0	39.0
Trail	82	79	79	79	79	79	82
Seat tube angle	74.0	73.5	73.5	73.0	73.0	72.5	72.0
Effective top tube	520	550	560	580	600	610	615
Seat tube	330	406	457	495	533	572	610
Standover	655	706	746	776	807	839	870
Wheelbase	1012	1035	1047	1063	1084	1089	1090
Bottom bracket height	287	291	293	293	293	295	297
Chainstay	430	430	430	430	430	430	430
Head tube	105	105	125	145	165	185	205

GEARING

	22	32	42
11	52	76	100
12	48	70	92
14	41	60	79
16	36	52	69
18	32	47	61
21	27	40	52
26	22	32	42
32	18	26	34

Trek 4500 WSD

FRAMESET

Main tubes	Alpha SL aluminum	
Stays	Alpha SL aluminum	
Color	Metallic Silver/Cool Blue	
Fork	RockShox Judy TT	80mm travel, 432mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 25.7mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	25.4mm clamp diameter
Stem	Bontrager Sport	40.0mm steerer clamp height
Shift levers	Shimano Deore	
Brake levers	Alloy, direct pull	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano Alivio	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore SGS	
Crankset	Shimano MC20 42/32/22	64/104mm bolt hole circle
Bottom bracket . . .		73 x 110.5 (shell x axle,mm), Square axle
Chain		9 speed, 108 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Shimano RM-60 hub, 21°, WTB Dual Duty rim	571mm ERD
Spokes	14g stainless, 260mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, PVC rim strip	
Rear wheel	Shimano RM-60 hub, 32°, WTB Dual Duty rim	571mm ERD
Spokes	14g stainless, 259/259mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, PVC rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Bontrager Sport	31.6mm outer diameter
Saddle	Bontrager Select WSD	
Seatpost binder . . .		36.4mm inner diameter
Brakes	none	
Pedals	Alloy platform, clipless adaptable	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	14	16	18
Rider height, in.		62.4	63.6	67.5
	cm	158	162	172
Handlebar	width	560	580	600
Handlebar	rise	25	25	25
Stem	length	70	80	90
	angle	25	25	25
Headset spacers		40	40	40
Crank	length	170	170	170
Seatpost	length	300	300	350
Steerer	length	202	202	217

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.0	70.0
Fork offset	38.2	38.1	38.1
Trail	78	78	78
Seat tube angle	75.0	74.0	73.5
Effective top tube	518	532	563
Seat tube	356	406	457
Standover	670	701	741
Wheelbase	1018	1023	1051
Bottom bracket height	289	289	293
Chainstay	424	424	424
Head tube	90	90	105

GEARING

	22	32	42
11	52	76	100
13	44	65	85
15	38	56	73
17	34	49	65
20	29	42	55
23	25	36	48
26	22	32	42
30	19	28	37
34	17	25	32

Trek 4500E WSD

FRAMESET

Main tubes	Alpha SL aluminum	
Stays	Alpha SL aluminum	
Color	Metallic Silver/Cool Blue	
Fork	RockShox Judy TT	80mm travel, 432mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 25.7mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	25.4mm clamp diameter
Stem	Bontrager Sport	40.0mm steerer clamp height
Shift levers	Shimano Deore	
Brake levers	Alloy, direct pull	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano Alivio	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore SGS	
Crankset	Shimano MC20 42/32/22	64/104mm bolt hole circle
Bottom bracket . . .		73 x 110.5 (shell x axle,mm), Square axle
Chain		9 speed, 108 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Alloy, QR hub, 21°, WTB Dual Duty rim	571mm ERD
Spokes	14g stainless, 264mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, PVC rim strip	
Rear wheel	Shimano RM-60 hub, 32°, WTB Dual Duty rim	571mm ERD
Spokes	14g stainless, 261.5/262.5mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, PVC rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Bontrager Sport	31.6mm outer diameter
Saddle	Bontrager Select WSD	
Seatpost binder . . .		36.4mm inner diameter
Brakes	none	
Pedals	Alloy platform, clipless adaptable	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	14	16	18
Rider height, in.		62.0	63.6	66.8
	cm	157	162	170
Handlebar	width	560	580	600
Handlebar	rise	25	25	25
Stem	length	60	70	80
	angle	10	10	10
Headset spacers		40	40	40
Crank	length	170	170	170
Seatpost	length	300	300	350
Steerer	length	202	202	217

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.0	70.0
Fork offset	39.0	39.0	39.0
Trail	78	78	78
Seat tube angle	75.0	74.0	73.5
Effective top tube	518	532	563
Seat tube	356	406	457
Standover	670	701	741
Wheelbase	1018	1023	1051
Bottom bracket height	289	289	293
Chainstay	424	424	424
Head tube	90	90	105

GEARING

	22	32	42
11	52	76	100
13	44	65	85
15	38	56	73
17	34	49	65
20	29	42	55
23	25	36	48
26	22	32	42
30	19	28	37
34	17	25	32

Trek 4400

FRAMESET

Main tubes	Alpha SL aluminum	
Stays	Alpha SL aluminum	
Color	Metallic Blue/Smooth Silver	
	Metallic Orange/Metallic Charcoal	
Fork	RST Omega T5 80mm travel, 456mm axle-crown length	
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 25.7mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	25.4mm clamp diameter
Stem	Bontrager Sport	40.0mm steerer clamp height
Shift levers	Shimano Alivio	
Brake levers	Alloy, direct pull	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano Acera-X	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore SGS	
Crankset	Shimano M340 42/32/22	64/104mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 113 (shell x axle,mm), Square axle
Chain	IG-51	3/32", 108 links
Cassette	SRAM PG850 11-32, 8spd	

WHEELSET

Front wheel	Alloy, QR hub, 32°, WTB Dual Duty rim	571mm ERD
Spokes	14g stainless, 264mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, PVC rim strip	
Rear wheel	Shimano RM-60 hub, 32°, WTB Dual Duty rim	571mm ERD
Spokes	14g stainless, 261/261.5mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, PVC rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	31.6mm outer diameter
Saddle	Bontrager Sport	
Seatpost binder . . .		36.4mm inner diameter
Brakes	Shimano M495, mechanical discs	
Pedals	Alloy platform, clipless adaptable	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame Size	13	16	18	19.5	21	22.5	24
Rider height, in.	63.4	67.1	70.1	71.8	75.1	75.6	76.5
cm	161	171	178	182	191	192	194
Handlebar width	600	600	620	620	620	620	620
Handlebar rise	25	25	25	25	25	25	25
Stem length	80	90	110	110	120	120	130
angle	10	10	10	10	10	10	10
Headset spacers	40	40	40	40	40	40	40
Crank length	170	170	175	175	175	175	175
Seatpost length	300	350	350	350	350	350	350
Steerer length	217	217	237	257	277	297	317

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.5	70.5	70.5	70.5	70.5	70.5
Fork offset	43.0	43.0	43.0	43.0	43.0	43.0	43.0
Trail	82	79	79	79	79	79	82
Seat tube angle	74.0	73.5	73.5	73.0	73.0	72.5	72.0
Effective top tube	520	550	560	580	600	610	615
Seat tube	330	406	457	495	533	572	610
Standover	655	706	746	776	807	839	870
Wheelbase	1012	1035	1047	1063	1084	1089	1090
Bottom bracket height	287	291	293	293	293	295	297
Chainstay	430	430	430	430	430	430	430
Head tube	105	105	125	145	165	185	205

GEARING

	22	32	42
11	52	76	100
12	48	70	92
14	41	60	79
16	36	52	69
18	32	47	61
21	27	40	52
26	22	32	42
32	18	26	34

Trek 4300

FRAMESET

Main tubes	Alpha SL aluminum	
Stays	Alpha SL aluminum	
Color	Metallic Blue/Smooth Silver	
	Metallic Orange/Metallic Charcoal	
Fork.	RST Gila T5	80mm travel, 451mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 25.7mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	25.4mm clamp diameter
Stem	Bontrager Sport	40.0mm steerer clamp height
Shift levers	Shimano EF-29	
Brake levers	Integrated brake/shift	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano C050	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Alivio	
Crankset	SR 42/34/24	64/105mm bolt hole circle
Bottom bracket . . .		73 x 122.5 (shell x axle,mm), Square axle
Chain		3/32", 108 links
Cassette	SRAM PG850 11-32, 8spd	

WHEELSET

Front wheel.	Shimano M495, disc hub, 32°, WTB Speed Disc rim	571mm ERD
Spokes	14g stainless, 264mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, PVC rim strip	
Rear wheel	Shimano M495, disc hub, 32°, WTB Speed Disc rim	571mm ERD
Spokes	14g stainless, 260.5/261.5mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, PVC rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost.	Bontrager Sport	31.6mm outer diameter
Saddle	Bontrager Sport	
Seatpost binder. . . .		36.4mm inner diameter
Brakes	Shimano M465, mechanical discs	
Pedals	Alloy platform, clipless adaptable	9/16" axle
Additional		

FIT

dimensions in mm, unless specified

Frame	Size	13	16	18	19.5	21	22.5	24
Rider height, in.		63.6	66.4	69.5	71.2	74.1	74.4	75.8
	cm	162	169	177	181	188	189	192
Handlebar	width	600	600	620	620	620	620	620
Handlebar	rise	25	25	25	25	25	25	25
Stem	length	90	90	110	110	120	120	130
	angle	25	25	25	25	25	25	25
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	170	175	175	175	175	175
Seatpost	length	300	300	350	350	350	350	350
Steerer	length	217	217	237	257	277	297	317

GEOMETRY

dimensions in mm, unless specified

Head tube angle	70.0	70.5	70.5	70.5	70.5	70.5	70.5
Fork offset	43.0	43.0	43.0	43.0	43.0	43.0	43.0
Trail	82	79	79	79	79	79	82
Seat tube angle	74.0	73.5	73.5	73.0	73.0	72.5	72.0
Effective top tube	520	550	560	580	600	610	615
Seat tube	330	406	457	495	533	572	610
Standover	655	706	746	776	807	839	870
Wheelbase	1012	1035	1047	1063	1084	1089	1090
Bottom bracket height	287	291	293	293	293	295	297
Chainstay	430	430	430	430	430	430	430
Head tube	105	105	125	145	165	185	205

GEARING

	24 34 42
11	57 81 100
12	52 74 92
14	45 64 79
16	39 56 69
18	35 50 61
21	30 42 52
26	24 34 42
32	20 28 34

Trek 4300 Disc

FRAMESET

Main tubes	Alpha SL aluminum	
Stays	Alpha SL aluminum	
Color	Metallic Blue/Smooth Silver	
Fork	RST Gila T5	80mm travel, 451mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 25.7mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	25.4mm clamp diameter
Stem	Bontrager Sport	40.0mm steerer clamp height
Shift levers	Shimano EF-29	
Brake levers	Integrated brake/shift	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano C050	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Alivio	
Crankset	SR 42/34/24	64/105mm bolt hole circle
Bottom bracket . . .		73 x 122.5 (shell x axle,mm), Square axle
Chain		3/32", 108 links
Cassette	SRAM PG850 11-32, 8spd	

WHEELSET

Front wheel	Shimano M495, disc hub, 32°, WTB Speed Disc rim	571mm ERD
Spokes	14g stainless, 263/262mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, PVC rim strip	
Rear wheel	Shimano M495, disc hub, 32°, WTB Speed Disc rim	571mm ERD
Spokes	14g stainless, 262/261mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, PVC rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	31.6mm outer diameter
Saddle	Bontrager Sport	
Seatpost binder . . .		36.4mm inner diameter
Brakes	Shimano M465, mechanical discs	
Pedals	Alloy platform, clipless adaptable	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	13	16	18	19.5	21	22.5	24
Rider height, in.		63.6	66.4	69.5	71.2	74.1	74.4	75.8
	cm	162	169	177	181	188	189	192
Handlebar	width	600	600	620	620	620	620	620
Handlebar	rise	25	25	25	25	25	25	25
Stem	length	90	90	110	110	120	120	130
	angle	25	25	25	25	25	25	25
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	170	175	175	175	175	170
Seatpost	length	300	300	350	350	350	350	350
Steerer	length	217	217	237	257	277	297	317

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.5	70.5	70.5	70.5	70.5	70.5
Fork offset	43.0	43.0	43.0	43.0	43.0	43.0	43.0
Trail	82	79	79	79	79	79	82
Seat tube angle	74.0	73.5	73.5	73.0	73.0	72.5	72.0
Effective top tube	520	550	560	580	600	610	615
Seat tube	330	406	457	495	533	572	610
Standover	655	706	746	776	807	839	870
Wheelbase	1012	1035	1047	1063	1084	1089	1090
Bottom bracket height	287	291	293	293	293	295	297
Chainstay	430	430	430	430	430	430	430
Head tube	105	105	125	145	165	185	205

GEARING

	24	34	42
11	57	81	100
12	52	74	92
14	45	64	79
16	39	56	69
18	35	50	61
21	30	42	52
26	24	34	42
32	20	28	34

Trek 3900

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color	Metallic Yellow/Rally Blue	
	Metallic Black/Rally Blue	
	Lava Black/Matte Black	
Fork	InSync Grind 1	80mm travel, 451mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 25.7mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem	Bontrager	40.0mm steerer clamp height
Shift levers	Shimano EF-29	
Brake levers	Integrated brake/shift	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano C050	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Acera-X	
Crankset	SR 42/34/24	64/105mm bolt hole circle
Bottom bracket . . .		73 x 124.5 (shell x axle,mm), Square axle
Chain		3/32", 108 links
Cassette	SRAM PG850 11-32, 8spd	

WHEELSET

Front wheel	Alloy, QR hub, 36°, Matrix 550 rim	573mm ERD
Spokes	14g stainless, 264.5mm, 3x	
Tire	Bontrager Connection Trail, 26 x 2.0, Rubber rim strip	
Rear wheel	Shimano RM30 hub, 36°, Matrix 550 rim	573mm ERD
Spokes	14g stainless, 261/262mm, 3x	
Tire	Bontrager Connection Trail, 26 x 2.0, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Bontrager	31.6mm outer diameter
Saddle	Bontrager Sport	
Seatpost binder . . .		36.4mm inner diameter
Brakes	Tektro direct pull	
Pedals	Platform	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	13	16	18	19.5	21	22.5	13W	16W	19.5W
Rider height, in.		63.9	66.7	69.4	70.4	74.4	74.7	62.1	66.6	69.4
	cm	162	169	176	179	189	190	158	169	176
Handlebar	width	600	600	620	620	620	620	580	600	600
Handlebar	rise	30	30	30	30	30	30	30	30	30
Stem	length	90	90	105	105	120	120	90	110	110
	angle	25	25	25	25	25	25	40	40	40
Headset spacers		40	40	40	40	40	40	40	40	40
Crank	length	170	170	175	175	175	175	170	170	175
Seatpost	length	300	300	350	350	350	350	300	300	350
Steerer	length	209	209	229	249	269	289	209	229	269

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.5	70.5	70.5	70.5	70.5	70.0	70.5	70.5
Fork offset	41.0	41.0	41.0	41.0	41.0	41.0	41.0	41.0	41.0
Trail	82	79	79	79	79	79	82	79	79
Seat tube angle	74.0	73.5	73.5	73.0	73.0	72.5	74.0	73.5	73.0
Effective top tube	520	550	560	580	600	610	515	545	575
Seat tube	330	406	457	495	533	572	330	406	495
Standover	655	706	746	776	807	839	586	592	596
Wheelbase	1012	1035	1047	1063	1084	1089	1007	1030	1058
Bottom bracket height	287	291	293	293	293	295	287	291	293
Chainstay	430	430	430	430	430	430	430	430	430
Head tube	105	105	125	145	165	185	105	125	165

GEARING

	24	34	42
11	57	81	100
12	52	74	92
14	45	64	79
16	39	56	69
18	35	50	61
21	30	42	52
26	24	34	42
32	20	28	34

Trek 3700

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color	Metallic Silver/Midnight Blue	
	Metallic Green/Metallic Charcoal	
	Metallic Silver/Metallic Purple	
Fork	RST 80mm travel, 412mm axle-crown length	
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 25.7mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem	Bontrager	40.0mm steerer clamp height
Shift levers	Shimano EF-29	
Brake levers	Integrated brake/shift	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano C051	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Acera-X	
Crankset	SR 48/38/28	64/105mm bolt hole circle
Bottom bracket . . .		73 x 124.5 (shell x axle,mm), Square axle
Chain		3/32", 112 links
Cassette	Sunrace 13-34, 7spd	

WHEELSET

Front wheel	Alloy, QR hub, 36°, Matrix 550 rim	573mm ERD
Spokes	14g stainless, 264.5mm, 3x	
Tire	Bontrager Connection Trail, 26 x 2.0, Rubber rim strip	
Rear wheel	Alloy, QR hub, 36°, Matrix 550 rim	573mm ERD
Spokes	14g stainless, 261/262mm, 3x	
Tire	Bontrager Connection Trail, 26 x 2.0, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Bontrager	31.6mm outer diameter
Saddle	Bontrager Sport	
Seatpost binder . . .		36.4mm inner diameter
Brakes	Tektro direct pull	
Pedals	Platform 9/16" axle	
Additional		

FIT *dimensions in mm, unless specified*

	Size	13	16	18	19.5	21	22.5	13W	16W	19.5W
Rider height, in.		62.3	65.2	67.8	69.5	72.8	73.2	60.4	65.1	68.1
	cm	158	166	172	177	185	186	153	165	173
Handlebar width		600	600	620	620	620	620	580	600	600
Handlebar rise		30	30	30	30	30	30	30	30	30
Stem length		90	90	105	105	120	120	90	110	110
	angle	25	25	25	25	25	25	40	40	40
Headset spacers		40	40	40	40	40	40	40	40	40
Crank length		170	170	175	175	175	175	170	170	175
Seatpost length		300	300	350	350	350	350	300	300	350
Steerer length		208	208	228	248	268	288	208	228	268

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.5	70.5	70.5	70.5	70.5	70.0	70.5	70.5
Fork offset	40.1	40.1	40.1	40.1	40.1	40.1	40.1	40.1	40.1
Trail	82	79	79	79	79	79	82	79	79
Seat tube angle	74.0	73.5	73.5	73.0	73.0	72.5	74.0	73.5	73.0
Effective top tube	520	550	560	580	600	610	515	545	575
Seat tube	330	406	457	495	533	572	330	406	495
Standover	655	706	746	776	807	839	586	592	596
Wheelbase	1012	1035	1047	1063	1084	1089	1007	1030	1058
Bottom bracket height	287	291	293	293	293	295	287	291	293
Chainstay	430	430	430	430	430	430	430	430	430
Head tube	105	105	125	145	165	185	105	125	165

GEARING

	28 38 48
13	56 77 97
15	49 66 84
17	43 59 74
19	39 52 66
22	33 45 57
26	28 38 48
34	22 29 37

Trek 3500

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color	Metallic Silver/Metallic Black	
	Metallic Silver/Rage Red	
Fork	Hi-tensile steel, 405mm axle-crown length	
Headset	Semi-cartridge, threaded	25.4/34.0/30.0, 36mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem	Alloy direct connect	
Shift levers	Shimano EF-29	
Brake levers	Integrated brake/shift	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano C051	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano TX-50	
Crankset	SR 48/38/28	105mm bolt hole circle
Bottom bracket . . .		73 x 124.5 (shell x axle,mm), Square axle
Chain		3/32", 112 links
Cassette	Sunrace 13-34, 7spd	

WHEELSET

Front wheel	Alloy, QR hub, 36°, Matrix 550 rim	573mm ERD
Spokes	14g stainless, 264.5mm, 3x	
Tire	Bontrager Connection Trail, 26 x 2.0, Rubber rim strip	
Rear wheel	Alloy, QR hub, 36°, Matrix 550 rim	573mm ERD
Spokes	14g stainless, 261/262mm, 3x	
Tire	Bontrager Connection Trail, 26 x 2.0, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Bontrager	31.6mm outer diameter
Saddle	Bontrager Sport	
Seatpost binder . . .		36.4mm inner diameter
Brakes	Tektro direct pull	
Pedals	Platform	9/16" axle
Additional		

FIT

dimensions in mm, unless specified

Frame	Size	13	16	18	19.5	21	22.5	13W	16W	19.5W
Rider height, in.		62.6	65.3	66.4	69.3	71.5	73.6	61.8	66.4	69.2
	cm	159	166	169	176	182	187	157	169	176
Handlebar	width	600	600	620	620	620	620	580	600	600
Handlebar	rise	30	30	30	30	30	30	30	30	30
Stem	length	105	105	105	120	120	135	103	120	120
	angle	40	40	40	40	40	40	40	40	40
Headset spacers		4	4	4	4	4	4	4	4	4
Crank	length	170	170	175	175	175	175	170	170	175
Seatpost	length	300	300	350	350	350	350	300	300	350
Steerer	length	144	144	164	184	204	224	144	164	204

GEOMETRY

dimensions in mm, unless specified

Head tube angle	70.0	70.5	70.5	70.5	70.5	70.5	70.0	70.5	70.5
Fork offset	40.1	40.1	40.1	40.1	40.1	40.1	40.1	40.1	40.1
Trail	82	79	79	79	79	79	82	79	79
Seat tube angle	74.0	73.5	73.5	73.0	73.0	72.5	74.0	73.5	73.0
Effective top tube	520	550	560	580	600	610	515	545	575
Seat tube	330	406	457	495	533	572	330	406	495
Standover	655	706	746	776	807	839	586	592	596
Wheelbase	1012	1035	1047	1063	1084	1089	1007	1030	1058
Bottom bracket height	287	291	293	293	293	295	287	291	293
Chainstay	430	430	430	430	430	430	430	430	430
Head tube	105	105	125	145	165	185	105	125	165

GEARING

	28	38	48
13	56	77	97
15	49	66	84
17	43	59	74
19	39	52	66
22	33	45	57
26	28	38	48
34	22	29	37

Trek 820

FRAMESET

Main tubes	Hi-tensile steel	
Stays	Hi-tensile steel	
Color	Rally Blue/Metallic Silver	
	Metallic Yellow/Metallic Black	
Fork	RST 80mm travel, 412mm axle-crown length	
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 25.7mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem	Bontrager	40.0mm steerer clamp height
Shift levers	Shimano EF-29	
Brake levers	Integrated brake/shift	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano C050	Top pull, 31.8 mm/ 1 1/4" attachment
Rear derailleur . . .	Shimano Acera-X	
Crankset	SR 42/34/24	105mm bolt hole circle
Bottom bracket . . .		68 x 121.5 (shell x axle,mm), Square axle
Chain		3/32", 114 links
Cassette	Sunrace 13-34, 7spd	

WHEELSET

Front wheel	Alloy, QR hub, 36°, Matrix 550 rim	573mm ERD
Spokes	14g stainless, 264.5mm, 3x	
Tire	Bontrager Connection Trail, 26 x 2.0, Rubber rim strip	
Rear wheel	Alloy, QR hub, 36°, Matrix 550 rim	573mm ERD
Spokes	14g stainless, 261/262mm, 3x	
Tire	Bontrager Connection Trail, 26 x 2.0, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Bontrager	29.2mm outer diameter
Saddle	Bontrager Sport	
Seatpost binder . . .		31.8mm inner diameter
Brakes	Tektro direct pull	
Pedals	Platform 9/16" axle	
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	13	15.5	17.5	19.5	21.5	13W	17.5W
Rider height, in.		63.5	64.3	66.3	67.5	69.7	62.8	66.1
	cm	161	163	169	171	177	159	168
Handlebar	width	600	600	620	520	520	580	600
Handlebar	rise	30	30	30	30	30	30	30
Stem	length	90	90	105	105	120	90	110
	angle	25	25	25	25	25	25	25
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	170	175	175	175	170	175
Seatpost	length	300	300	350	350	350	300	300
Steerer	length	208	208	228	248	268	208	228

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.5	70.5	70.5	71.0	70.0	70.5
Fork offset	43.0	43.0	43.0	43.0	43.0	43.0	43.0
Trail	82	79	79	79	76	82	79
Seat tube angle	74.0	73.5	73.0	73.0	72.5	74.0	73.0
Effective top tube	528	545	555	565	575	525	546
Seat tube	330	394	445	495	546	330	445
Standover	658	699	731	769	813	599	600
Wheelbase	1026	1034	1039	1051	1052	1022	1028
Bottom bracket height	288	291	291	293	293	283	283
Chainstay	435	435	435	435	435	435	435
Head tube	90	90	90	105	145	105	125

GEARING

	24	34	42
13	48	69	85
15	42	59	73
17	37	52	65
19	33	47	58
22	29	41	50
26	24	34	42
34	19	26	32

Trek Navigator 300E

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color		
Fork	RST CT COM 1 T5	50mm travel, 433mm axle-crown length
Headset	Sealed, semi-cartridge	25.4/34.0/30.0, 33.0mm stack height

CONTROLS

Handlebar	Alloy riser	25.4mm clamp diameter
Stem	Adjustable rise, quill type	
Shift levers	SRAM MRX Pro	
Brake levers	Alloy, direct pull	
Grips	SRAM	

DRIVETRAIN

Front derailleur . . .	Shimano C102	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	SRAM RD X.7	
Crankset	Bontrager Sport 48/38/28 w/chainguard	64/104mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 115 (shell x axle,mm), Square axle
Chain	IG-51	3/32", 112 links
Cassette	SRAM PG830 11-32, 8spd	

WHEELSET

Front wheel	Alloy, QR hub, 36°, Alex TA-19 rim	559mm ERD
Spokes	14G stainless, 265mm, 3x	
Tire	Bontrager Comfort HardCase, 26 x 1.95, Rubber rim strip	
Rear wheel	Shimano RM-60 hub, 36°, Alex TA-19 rim	559mm ERD
Spokes	14G stainless, 261/263mm, 3x	
Tire	Bontrager Comfort HardCase, 26 x 1.95, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Suspension, alloy	27.2mm outer diameter
Saddle	Bontrager Webspring w/elastomers	
Seatpost binder . . .		34.9mm inner diameter
Brakes	Tektro direct pull w/modulator front, Tektro direct pull rear	
Pedals	Platform 9/16" axle	
Additional	integral bell, Alloy kickstand, Rack strap, Alloy rear rack, Trek cruiser fenders,	

FIT *dimensions in mm, unless specified*

	Size	14.5	16.5	18.5	21	14.5W	16.5W	18.5W
Rider height, in.		63.3	68.0	71.7	74.0	63.3	66.1	71.7
	cm	161	173	182	188	161	168	182
Handlebar width		600	620	620	620	600	600	620
Handlebar rise		50	50	50	50	50	50	50
Stem length		85	105	105	105	85	85	105
	angle	35	35	35	35	35	35	35
Headset spacers		6	6	6	6	6	6	6
Crank length		170	170	170	170	170	170	170
Seatpost length		300	300	350	350	300	300	350
Steerer length		168	188	228	268	168	188	233

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	70.5	70.5	70.5	70.5	70.5	70.5
Fork offset	43.0	43.0	43.0	43.0	43.0	43.0	43.0
Trail	74	74	74	74	74	74	74
Seat tube angle	72.5	72.5	72.5	72.5	72.5	72.5	72.5
Effective top tube	530	550	575	595	530	550	575
Seat tube	368	419	470	533	368	419	470
Standover	659	695	739	770	588	589	595
Wheelbase	1011	1032	1059	1080	1011	1032	1059
Bottom bracket height	287	287	287	287	287	287	287
Chainstay	435	435	435	435	435	435	435
Head tube	135	155	215	235	135	155	215

GEARING

	28	38	48
11	67	91	114
12	61	83	105
14	52	71	90
16	46	62	79
18	41	55	70
21	35	47	60
26	28	38	48
32	23	31	39

Trek Navigator 300

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color		
Fork	RST CT COM 1 T5	50mm travel, 433mm axle-crown length
Headset	Sealed, semi-cartridge	25.4/34.0/30.0, 33.0mm stack height

CONTROLS

Handlebar	Alloy riser	25.4mm clamp diameter
Stem	Adjustable rise, quill type	
Shift levers	SRAM MRX Pro	
Brake levers	Alloy, direct pull	
Grips	SRAM	

DRIVETRAIN

Front derailleur . . .	Shimano C102	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	SRAM RD X.7	
Crankset	Bontrager Sport 48/38/28 w/chainguard	64/104mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 115 (shell x axle,mm), Square axle
Chain	IG-51	3/32", 112 links
Cassette	SRAM PG830 11-32, 8spd	

WHEELSET

Front wheel	Alloy, QR hub, 36°, Alex TA-19 rim	559mm ERD
Spokes	14G stainless, 265mm, 3x	
Tire	Bontrager Comfort HardCase, 26 x 1.95, Rubber rim strip	
Rear wheel	Shimano RM-60 hub, 36°, Alex TA-19 rim	559mm ERD
Spokes	14G stainless, 261/263mm, 3x	
Tire	Bontrager Comfort HardCase, 26 x 1.95, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Suspension, alloy	27.2mm outer diameter
Saddle	Bontrager Webspring w/elastomers	
Seatpost binder . . .		34.9mm inner diameter
Brakes	Tektro direct pull w/modulator front, Tektro direct pull rear	
Pedals	Platform 9/16" axle	
Additional	integral bell,	

FIT *dimensions in mm, unless specified*

	Size	14.5	16.5	18.5	21	14.5W	16.5W	18.5W
Frame								
Rider height, in.		63.3	68.0	71.7	74.0	63.3	66.1	71.7
	cm	161	173	182	188	161	168	182
Handlebar	width	600	620	620	620	600	600	620
Handlebar	rise	50	50	50	50	50	50	50
Stem	length	85	105	105	105	85	85	105
	angle	35	35	35	35	35	35	35
Headset spacers		6	6	6	6	6	6	6
Crank	length	170	170	175	175	170	170	175
Seatpost	length	300	300	350	350	300	300	350
Steerer	length	168	188	228	268	168	188	233

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	70.5	70.5	70.5	70.5	70.5	70.5
Fork offset	43.0	43.0	43.0	43.0	43.0	43.0	43.0
Trail	74	74	74	74	74	74	74
Seat tube angle	72.5	72.5	72.5	72.5	72.5	72.5	72.5
Effective top tube	530	550	575	595	530	550	575
Seat tube	368	419	470	533	368	419	470
Standover	659	695	739	770	588	589	595
Wheelbase	1011	1032	1059	1080	1011	1032	1059
Bottom bracket height	287	287	287	287	287	287	287
Chainstay	435	435	435	435	435	435	435
Head tube	135	155	215	235	135	155	215

GEARING

	28	38	48
11	67	91	114
12	61	83	105
14	52	71	90
16	46	62	79
18	41	55	70
21	35	47	60
26	28	38	48
32	23	31	39

Trek Navigator 200E

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color		
Fork	RST CT COM 1 C5	50mm travel, 433mm axle-crown length
Headset	Sealed, semi-cartridge	25.4/34.0/30.0, 33.0mm stack height

CONTROLS

Handlebar	Alloy riser	25.4mm clamp diameter
Stem	Adjustable rise, quill type	
Shift levers	SRAM MRX Pro	
Brake levers	Alloy, direct pull	
Grips	SRAM	

DRIVETRAIN

Front derailleur . . .	Shimano C102	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	SRAM RD X.7	
Crankset	Bontrager Sport 48/38/28 w/chainguard	64/104mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 124.5 (shell x axle,mm), Square axle
Chain	IG-51	3/32", 112 links
Cassette	SRAM PG830 11-32, 8spd	

WHEELSET

Front wheel	Alloy, QR hub, 36°, Alex TA-19 rim	559mm ERD
Spokes	14G stainless, 265mm, 3x	
Tire	Bontrager Comfort HardCase, 26 x 1.95, Rubber rim strip	
Rear wheel	Shimano RM-60 hub, 36°, Alex TA-19 rim	559mm ERD
Spokes	14G stainless, 261/263mm, 3x	
Tire	Bontrager Comfort HardCase, 26 x 1.95, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Suspension, alloy	27.2mm outer diameter
Saddle	Bontrager Webspring w/elastomers	
Seatpost binder . . .		34.9mm inner diameter
Brakes	Tektro direct pull w/modulator front, Tektro direct pull rear	
Pedals	Platform 9/16" axle	
Additional	integral bell, Alloy kickstand, Rack strap, Alloy rear rack, Trek cruiser fenders,	

FIT *dimensions in mm, unless specified*

	Size	14.5	16.5	18.5	21	14.5W	16.5W	18.5W
Rider height, in.		63.3	68.0	71.7	74.0	63.3	66.1	71.7
	cm	161	173	182	188	161	168	182
Handlebar width		600	620	620	620	600	600	620
Handlebar rise		50	50	50	50	50	50	50
Stem length		85	105	105	105	85	85	105
Stem angle		35	35	35	35	35	35	35
Headset spacers		6	6	6	6	6	6	6
Crank length		170	170	170	170	170	170	170
Seatpost length		300	300	350	350	300	300	350
Steerer length		168	188	228	268	168	188	233

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	70.5	70.5	70.5	70.5	70.5	70.5
Fork offset	43.0	43.0	43.0	43.0	43.0	43.0	43.0
Trail	74	74	74	74	74	74	74
Seat tube angle	72.5	72.5	72.5	72.5	72.5	72.5	72.5
Effective top tube	530	550	575	595	530	550	575
Seat tube	368	419	470	533	368	419	470
Standover	659	695	739	770	588	589	595
Wheelbase	1011	1032	1059	1080	1011	1032	1059
Bottom bracket height	287	287	287	287	287	287	287
Chainstay	435	435	435	435	435	435	435
Head tube	135	155	215	235	135	155	215

GEARING

	28	38	48
11	67	91	114
12	61	83	105
14	52	71	90
16	46	62	79
18	41	55	70
21	35	47	60
26	28	38	48
32	23	31	39

Trek Navigator 200

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color		
Fork	RST CT COM 1 C5	50mm travel, 433mm axle-crown length
Headset	Sealed, semi-cartridge	25.4/34.0/30.0, 33.0mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem	Adjustable rise, quill type	
Shift levers	SRAM MRX Plus	
Brake levers	Alloy, direct pull	
Grips	SRAM	

DRIVETRAIN

Front derailleur . . .	Shimano C102	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Alivio	
Crankset	Shimano TX71 48/38/28 w/chainguard	64/104mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 124.5 (shell x axle,mm), Square axle
Chain	IG-51	3/32", 112 links
Cassette	SRAM PG830 11-32, 8spd	

WHEELSET

Front wheel	Alloy, QR hub, 36°, Matrix 550 rim	559mm ERD
Spokes	14G stainless, 265mm, 3x	
Tire	Bontrager Comfort HardCase, 26 x 1.95, Rubber rim strip	
Rear wheel	Shimano RM-60 hub, 36°, Matrix 550 rim	559mm ERD
Spokes	14G stainless, 261/263mm, 3x	
Tire	Bontrager Comfort HardCase, 26 x 1.95, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Suspension, alloy	27.2mm outer diameter
Saddle	Bontrager Webspring	
Seatpost binder . . .		34.9mm inner diameter
Brakes	Tektro direct pull w/modulator front, Tektro direct pull rear	
Pedals	Platform	9/16" axle
Additional	integral bell,	

FIT *dimensions in mm, unless specified*

	Size	14.5	16.5	18.5	21	14.5W	16.5W	18.5W
Frame								
Rider height, in.		63.3	68.0	71.7	74.0	63.3	66.1	71.7
	cm	161	173	182	188	161	168	182
Handlebar	width	600	620	620	620	600	600	620
Handlebar	rise	50	50	50	50	50	50	50
Stem	length	85	105	105	105	85	85	105
	angle	35	35	35	35	35	35	35
Headset spacers		6	6	6	6	6	6	6
Crank	length	170	170	170	170	170	170	170
Seatpost	length	300	300	350	350	300	300	350
Steerer	length	168	188	228	268	168	188	233

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	70.5	70.5	70.5	70.5	70.5	70.5
Fork offset	43.0	43.0	43.0	43.0	43.0	43.0	43.0
Trail	74	74	74	74	74	74	74
Seat tube angle	72.5	72.5	72.5	72.5	72.5	72.5	72.5
Effective top tube	530	550	575	595	530	550	575
Seat tube	368	419	470	533	368	419	470
Standover	659	695	739	770	588	589	595
Wheelbase	1011	1032	1059	1080	1011	1032	1059
Bottom bracket height	287	287	287	287	287	287	287
Chainstay	435	435	435	435	435	435	435
Head tube	135	155	215	235	135	155	215

GEARING

	28	38	48
11	67	91	114
12	61	83	105
14	52	71	90
16	46	62	79
18	41	55	70
21	35	47	60
26	28	38	48
32	23	31	39

Trek Navigator 100

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color		
Fork	RST CT COM 1 C5	50mm travel, 433mm axle-crown length
Headset	Sealed, semi-cartridge	25.4/34.0/30.0, 33.0mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem	Adjustable rise, quill type	
Shift levers	SRAM ESP 3.0 Plus	
Brake levers	Alloy, direct pull	
Grips	SRAM	

DRIVETRAIN

Front derailleur . . .	SR XCR-328	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	SRAM ESP 3.0	
Crankset	SR NEX200 48/38/28 w/chainguard	64/104mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 112.5 (shell x axle,mm), Square axle
Chain	KMC Z51	3/32", 116 links
Cassette	Sunrace 13-34, 7spd	

WHEELSET

Front wheel	Alloy, QR hub, 36°, Matrix 550 rim	559mm ERD
Spokes	14g, 265mm, 3x	
Tire	Bontrager Comfort, 26 x 1.95, Rubber rim strip	
Rear wheel	Alloy, QR hub, 36°, Matrix 550 rim	559mm ERD
Spokes	14g, 261/263mm, 3x	
Tire	Bontrager Comfort, 26 x 1.95, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Suspension, alloy	27.2mm outer diameter
Saddle	Bontrager Webspring	
Seatpost binder . . .		34.9mm inner diameter
Brakes	Tektro direct pull w/modulator front, Tektro direct pull rear	
Pedals	Platform	9/16" axle
Additional	integral bell,	

FIT *dimensions in mm, unless specified*

	Size	14.5	16.5	18.5	21	14.5W	16.5W	18.5W
Rider height, in.		63.3	68.0	71.7	74.0	63.3	66.1	71.7
	cm	161	173	182	188	161	168	182
Handlebar width		600	620	620	620	600	600	620
Handlebar rise		50	50	50	50	50	50	50
Stem length		85	105	105	105	85	85	105
	angle	35	35	35	35	35	35	35
Headset spacers		6	6	6	6	6	6	6
Crank length		170	170	175	175	170	170	175
Seatpost length		300	300	350	350	300	300	350
Steerer length		168	188	228	268	168	188	233

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	70.5	70.5	70.5	70.5	70.5	70.5
Fork offset	43.0	43.0	43.0	43.0	43.0	43.0	43.0
Trail	74	74	74	74	74	74	74
Seat tube angle	72.5	72.5	72.5	72.5	72.5	72.5	72.5
Effective top tube	530	550	575	595	530	550	575
Seat tube	368	419	470	533	368	419	470
Standover	659	695	739	770	588	589	595
Wheelbase	1011	1032	1059	1080	1011	1032	1059
Bottom bracket height	287	287	287	287	287	287	287
Chainstay	435	435	435	435	435	435	435
Head tube	135	155	215	235	135	155	215

GEARING

	28	38	48
13	56	77	97
15	49	66	84
17	43	59	74
19	39	52	66
21	35	47	60
24	31	42	52
34	22	29	37

Trek Bruiser 1

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color	Matte Charcoal	
Fork	RST Gila T5	120mm travel, 490mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 25.6mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Big Earl	40.0mm steerer clamp height
Shift levers	Shimano Alivio	
Grips	Bontrager Earl	

DRIVETRAIN

Front derailleur . . .	Shimano Acera-X	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore SGS	
Crankset	Shimano MC08 42/34/24	64/105mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 121.5 (shell x axle,mm), Square axle
Chain	IG-51	3/32", 106 links
Cassette	SRAM PG850 11-32, 8spd	

WHEELSET

Front wheel	Alloy, disc compatible, QR hub, 36°, WTB Dual Duty rim	573mm ERD
Spokes	14g, 257/258mm, 3x	
Tire	Bontrager Big Earl, 26 x 2.4, Rubber rim strip	
Rear wheel	Alloy, disc compatible, QR hub, 36°, WTB Dual Duty rim	573mm ERD
Spokes	14g, 256/257mm, 3x	
Tire	Bontrager Big Earl, 26 x 2.4, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Bontrager Sport	29.2mm outer diameter
Saddle	Bontrager Big Earl	
Seatpost binder . . .		35.0mm inner diameter
Brakes	Alloy direct pull	
Pedals	Platform, alloy 9/16" axle	
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	14.5	16
Rider height, in.		62.7	64.5
	cm	159	164
Handlebar	width	600	600
Handlebar	rise	25	25
Stem	length	50	50
	angle	10	10
Headset spacers		15	15
Crank	length	170	175
Seatpost	length	400	
Steerer	length	188	188

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.0
Fork offset	45.0	45.0
Trail	79	79
Seat tube angle	71.0	71.0
Effective top tube	570	592
Seat tube	368	406
Standover	700	716
Wheelbase	1032	1054
Bottom bracket height	323	323
Chainstay	420	420
Head tube	112	112

GEARING

	24	34	42
11	57	81	100
12	52	74	92
14	45	64	79
16	39	56	69
18	35	50	61
21	30	42	52
26	24	34	42
32	20	28	34

Trek Bruiser 2

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color	Matte Navy	
Fork	Marzocchi MZ Comp	130mm travel, 490mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 28mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Big Earl	40.0mm steerer clamp height
Shift levers	Shimano Alivio	
Grips	Bontrager Earl	

DRIVETRAIN

Front derailleur . . .	Shimano Alivio	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore LX SGS	
Crankset	Bontrager Big Earl 32/22	64/105mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 113 (shell x axle,mm), ISIS splined axle
Chain	IG-51	3/32", 102 links
Cassette	SRAM PG850 11-32, 8spd	

WHEELSET

Front wheel	Alloy, disc compatible, QR hub, 36°, Alloy rim	573mm ERD
Spokes	14g, 257/258mm, 3x	
Tire	Bontrager Big Earl, 26 x 2.4, Rubber rim strip	
Rear wheel	Alloy, disc compatible, QR hub, 36°, Alloy rim	573mm ERD
Spokes	14g, 256/257mm, 3x	
Tire	Bontrager Big Earl, 26 x 2.4, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Bontrager Select	29.2mm outer diameter
Saddle	Bontrager Big Earl	
Seatpost binder . . .		35.0mm inner diameter
Brakes	Hayes MX-1 XC mechanical discs	
	6.3 in. front disc, 8 in. DH rear disc, 44mm BCD	
Pedals	Platform, alloy 9/16" axle	
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	14.5	16
Rider height, in.		62.8	64.7
	cm	160	164
Handlebar	width	600	600
Handlebar	rise	25	25
Stem	length	50	50
	angle	10	10
Headset spacers		15	15
Crank	length	170	175
Seatpost	length	400	
Steerer	length	188	188

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.0
Fork offset	39.0	39.0
Trail	79	79
Seat tube angle	71.0	71.0
Effective top tube	570	592
Seat tube	368	406
Standover	700	716
Wheelbase	1032	1054
Bottom bracket height	323	323
Chainstay	420	420
Head tube	112	112

GEARING

	22 32
11	52 76
12	48 70
14	41 60
16	36 52
18	32 47
21	27 40
26	22 32
32	18 26

Trek Fuel 110

1168600*15.094
Bike weight: 24.8 lb/11.26 kg

FRAMESET

Main tubes	OCLV 120 carbon fiber composite	
Stays	OCLV 120 carbon fiber composite	
Color	Silver/Satin Silver	
Fork	RockShox SID World Cup w/PopLoc	80mm travel, 444mm axle-crown length
Rear shock	RockShox Motion Control 3 w/PopLoc, 1.5in stroke, 6.5 length, 0.860" width, 6mm eyes	
Headset	Cane Creek S-6 Aheadset, alloy	25.4/34.0/30.0, 27.1mm stack height

CONTROLS

Handlebar	Bontrager Race XXX Lite	31.8mm clamp diameter
Stem	Bontrager Race XXX Lite	40.0mm steerer clamp height
Shift levers	Shimano XTR	
Brake levers	Integrated brake/shift	
Grips	Bontrager Race, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano XTR	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur	Shimano XTR Low-Normal	
Crankset	Shimano XTR 44/32/22	64/104mm bolt hole circle
Bottom bracket	integral axle	73 (shell x axle,mm), Integral axle
Chain	Shimano Dura-Ace	9 speed, 108 links
Cassette	Shimano XTR 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Race Lite, tubeless compatible, 24°	539mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 252mm, radial	
Tire	Bontrager Super-X, tubeless ready, 127tpi, 26 x 2.1, Tubeless rim strip	
Rear wheel	Bontrager Race Lite, tubeless compatible, 28°	542mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 265/268mm, 3x	
Tire	Bontrager Super-X, tubeless ready, 127tpi, 26 x 2.1, Tubeless assymetric rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Race XXX Lite	31.6mm outer diameter
Saddle	Bontrager Race X Lite	
Seatpost binder	Alloy w/integral quick-release	39.85mm inner diameter
Brakes	Avid Single Digit SL, linear pull, Rim Wrangler pads	
Pedals	Shimano SPD M520, clipless 9/16" axle	
Additional	RockShox PopLoc dual leverWrench Force pump,	

FIT *dimensions in mm, unless specified*

Frame	Size	15.5	17.5	19.5	21.5
Rider height, in.		65.2	69.1	71.7	74.8
	cm	166	175	182	190
Handlebar	width	600	600	600	600
Handlebar	rise	0			
Stem	length	90	100	100	120
	angle	12	12	12	12
Headset spacers		30	30	30	30
Crank	length	170	175	175	175
Seatpost	length	330	400	400	400
Steerer	length	198.1	218.1	238.1	258.1

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	71.0	71.0	71.0
Fork offset	38.0	38.0	38.0	38.0
Trail				
Seat tube angle	73.5	73.5	73.5	73.5
Effective top tube	550	588	625	642
Seat tube	394	445	495	546
Standover	701	737	773	818
Wheelbase	1032	1071	1109	1126
Bottom bracket height	312	312	312	312
Chainstay	423	423	423	423
Head tube	105	120	135	150

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Trek Fuel 98

1167600*15.084
Bike weight: 26.3 lb/11.94 kg

FRAMESET

Main tubes	OCV 120 carbon fiber composite	
Stays	OCV 120 carbon fiber composite	
Color	Baja Blue/Satin Silver	
Fork	RockShox SID Team w/PopLoc	80mm travel, 444mm axle-crown length
Rear shock	RockShox Motion Control 3, 1.5in stroke, 6.5 length, 0.860" width, 6mm eyes	
Headset	Alloy aheadset, semi-cartridge	25.4/34.0/30.0, 27.2mm stack height

CONTROLS

Handlebar	Bontrager Race X Lite	25.4mm clamp diameter
Stem	Bontrager Race X Lite	40.0mm steerer clamp height
Shift levers	Shimano Deore XT	
Brake levers	Integrated brake/shift	
Grips	Bontrager Race, dual density	

DRIVETRAIN

Front derailleur	Shimano Deore XT	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur	Shimano Deore XT SGS	
Crankset	Shimano Deore XT 44/32/22	64/104mm bolt hole circle
Bottom bracket	integral axle	73 (shell x axle,mm), Integral axle
Chain	Shimano HG-73	9 speed, 108 links
Cassette	Shimano Deore XT 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Race Lite, tubeless compatible, 24°	539mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 252mm, radial	
Tire	Bontrager Super-X, tubeless ready, 127tpi, 26 x 2.1, Tubeless rim strip	
Rear wheel	Bontrager Race Lite, tubeless compatible, 28°	542mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 265/268mm, 3x	
Tire	Bontrager Super-X, tubeless ready, 127tpi, 26 x 2.1, Tubeless assymetric rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Race X Lite	31.6mm outer diameter
Saddle	Bontrager Race Lite Luxe	
Seatpost binder	Alloy w/integral quick-release	39.85mm inner diameter
Brakes	Avid Single Digit 5, linear pull	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional	RockShox PopLoc leverWrench Force pump,	

FIT

dimensions in mm, unless specified

Frame	Size	15.5	17.5	19.5	21.5
Rider height, in.		67.1	71.3	73.9	77.0
	cm	170	181	188	196
Handlebar	width	650	650	650	650
Handlebar	rise	40	40	40	40
Stem	length	90	100	100	120
	angle	7	7	7	7
Headset spacers		30	30	30	30
Crank	length	170	175	175	175
Seatpost	length	330	400	400	400
Steerer	length	198.2	213.2	228.2	243.2

GEOMETRY

dimensions in mm, unless specified

Head tube angle	71.0	71.0	71.0	71.0
Fork offset	38.0	38.0	38.0	38.0
Trail				
Seat tube angle	73.5	73.5	73.5	73.5
Effective top tube	550	588	625	642
Seat tube	394	445	495	546
Standover	701	737	773	818
Wheelbase	1032	1071	1109	1126
Bottom bracket height	312	312	312	312
Chainstay	423	423	423	423
Head tube	105	120	135	150

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Trek

Fuel 98 Disc

1167610*15.104
Bike weight: 25.3 lb/11.49 kg

FRAMESET

Main tubes	OCV 120 carbon fiber composite	
Stays	OCV 120 carbon fiber composite	
Color	Baja Blue/Satin Silver	
Fork	RockShox SID Team w/PopLoc	80mm travel, 444mm axle-crown length
Rear shock	RockShox Motion Control 3, 1.5in stroke, 6.5 length, 0.860" width, 6mm eyes	
Headset	Alloy aheadset, semi-cartridge	25.4/34.0/30.0, 27.2mm stack height

CONTROLS

Handlebar	Bontrager Race X Lite	25.4mm clamp diameter
Stem	Bontrager Race Lite	40.0mm steerer clamp height
Shift levers	Shimano Deore XT	
Brake levers	Integrated brake/shift	
Grips	Bontrager Race, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Deore XT	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore XT SGS	
Crankset	Shimano Deore XT 44/32/22	64/104mm bolt hole circle
Bottom bracket . . .	integral axle	73 (shell x axle,mm), Integral axle
Chain	Shimano HG-73	9 speed, 108 links
Cassette	Shimano Deore XT 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Race Lite Disc, tubeless compatible, 28°	537mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 266/267mm, 3x	
Tire	Bontrager Super-X, tubeless ready, 127tpi, 26 x 2.1, Tubeless assymetric rim strip	
Rear wheel	Bontrager Race Lite Disc, tubeless compatible, 28°	537mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 266/267mm, 3x	
Tire	Bontrager Super-X, tubeless ready, 127tpi, 26 x 2.1, Tubeless assymetric rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Race X Lite	31.6mm outer diameter
Saddle	Bontrager Race Lite Luxe	
Seatpost binder . . .	Alloy w/integral quick-release	39.85mm inner diameter
Brakes	Shimano Deore XT, hydraulic discs	
	160mm discs, 44mm BCD	
Disc hose, mm	15.5 17.5 19.5 21.5	
Front	750 750 750 750	
Rear	1350 1350 1400 1400	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional	RockShox PopLoc dual leverWrench Force pump,	

FIT *dimensions in mm, unless specified*

Frame	Size	15.5	17.5	19.5	21.5
Rider height, in.		67.1	71.3	73.9	77.0
	cm	170	181	188	196
Handlebar	width	650	650	650	650
Handlebar	rise	40	40	40	40
Stem	length	90	100	100	120
	angle	7	7	7	7
Headset spacers		30	30	30	30
Crank	length	170	175	175	175
Seatpost	length	330	400	400	400
Steerer	length	198.2	218.2	238.2	258.2

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	71.0	71.0	71.0
Fork offset	38.0	38.0	38.0	38.0
Trail				
Seat tube angle	73.5	73.5	73.5	73.5
Effective top tube	550	588	625	642
Seat tube	394	445	495	546
Standover	701	737	773	818
Wheelbase	1032	1071	1109	1126
Bottom bracket height	312	312	312	312
Chainstay	423	423	423	423
Head tube	105	120	135	150

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Trek Fuel 80

1162600*15.054
Bike weight: 30.3 lb/13.76 kg

FRAMESET

Main tubes	Alpha SL aluminum	
Stays	Alpha SL aluminum	
Color	Matte Metallic Charcoal	
Fork	Manitou Splice Comp, w/lockout	100mm travel, 470mm axle-crown length
Rear shock	RockShox BAR Adjust, 1.5in stroke, 6.5 length, 0.860" width, 6mm eyes	
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	25.4mm clamp diameter
Stem	Bontrager Sport	50.0mm steerer clamp height
Shift levers	Shimano Deore	
Brake levers	Hydraulic, attached to brake	
Grips	Oasis, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Deore	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur	Shimano Deore XT SGS	
Crankset	Bontrager Select 44/32/22	64/104mm bolt hole circle
Bottom bracket	TruVativ Giga-Pipe	73 x 113 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	SRAM PG970 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Superstock, disc compatible, 28°	542mm ERD
Spokes	DT 14g, ProLock brass nipples, 267/267mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, Velox 22mm rim strip	
Rear wheel	Bontrager Superstock, disc compatible, 28°	542mm ERD
Spokes	DT 14g, ProLock brass nipples, 267/267mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, Velox 22mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	31.6mm outer diameter
Saddle	Bontrager FS 2000	
Seatpost binder	Alloy w/integral quick-release	36.4mm inner diameter
Brakes	Hayes HFX-9, hydraulic discs	
	6.3 in. discs, 44mm BCD	
Disc hose, mm	15.5 17.5 19.5 21.5	
Front	690 690 750 750	
Rear	1280 1280 1350 1400	
Pedals	Shimano SPD M505, clipless	9/16" axle
Additional	Wrench Force pump,	

FIT *dimensions in mm, unless specified*

Frame	Size	15.5	17.5	19.5	21.5
Rider height, in.		68.4	72.2	75.3	78.0
	cm	174	183	191	198
Handlebar	width	620	620	620	620
Handlebar	rise	25	25	25	25
Stem	length	100	105	105	120
	angle	10	10	10	10
Headset spacers		30	30	30	30
Crank	length	170	175	175	175
Seatpost	length	300	350	350	350
Steerer	length	207.5	222.5	237.5	252.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	71.0	71.0	71.0
Fork offset	38.0	38.0	38.0	38.0
Trail				
Seat tube angle	73.5	73.5	73.5	73.5
Effective top tube	550	588	625	642
Seat tube	394	445	495	546
Standover	701	737	773	818
Wheelbase	1032	1071	1109	1126
Bottom bracket height	312	312	312	312
Chainstay	423	423	423	423
Head tube	105	120	135	150

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

FRAMESET

Main tubes	Alpha SL aluminum	
Stays	Alpha SL aluminum	
Color	Matte Blue	
Fork	Manitou Axel Comp	100mm travel, 470mm axle-crown length
Rear shock	RockShox BAR, 1.5in stroke, 6.5 length, 0.860" width, 6mm eyes	
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	25.4mm clamp diameter
Stem	Bontrager Sport	41.0mm steerer clamp height
Shift levers	Shimano Alivio	
Brake levers	Alloy, direct pull	
Grips	Bontrager, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Alivio	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur	Shimano Deore LX SGS	
Crankset	Bontrager Sport 44/32/22	64/104mm bolt hole circle
Bottom bracket	Shimano BB-LP28	73 x 113 (shell x axle,mm), Square axle
Chain	IG-31	3/32", 108 links
Cassette	SRAM 5.0 11-32, 8spd	

WHEELSET

Front wheel	Alloy, disc compatible, QR hub, 32°, Bontrager Maverick rim	542mm ERD
Spokes	DT 14G stainless, 263/263mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, Velox 22mm rim strip	
Rear wheel	Alloy, disc compatible, QR hub, 32°, Bontrager Maverick OSB rim	542mm ERD
Spokes	DT 14G stainless, 263/263mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, Velox 22mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	31.6mm outer diameter
Saddle	Bontrager Select, hollow CrMo rails	
Seatpost binder	Alloy w/integral quick-release	36.4mm inner diameter
Brakes	Hayes MX-1 XC mechanical discs	
	6.3 in. discs, 44mm BCD	
Pedals	Alloy/alloy cage, clipless adaptable	9/16" axle
Additional	Wrench Force pump,	

FIT *dimensions in mm, unless specified*

Frame	Size	15.5	17.5	19.5	21.5
Rider height, in.		68.5	72.0	75.0	77.8
	cm	174	183	191	198
Handlebar	width	620	620	620	620
Handlebar	rise	25	25	25	25
Stem	length	100	105	105	120
	angle	10	10	10	10
Headset spacers		30	30	30	30
Crank	length	170	175	175	175
Seatpost	length	300	350	350	350
Steerer	length	207.5	222.5	237.5	252.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	71.0	71.0	71.0
Fork offset	38.0	38.0	38.0	38.0
Trail				
Seat tube angle	73.5	73.5	73.5	73.5
Effective top tube	550	588	625	642
Seat tube	394	445	495	546
Standover	701	737	773	818
Wheelbase	1032	1071	1109	1126
Bottom bracket height	312	312	312	312
Chainstay	423	423	423	423
Head tube	105	120	135	150

GEARING

	22	32	44
11	52	76	105
12	48	70	96
14	41	60	82
16	36	52	72
18	32	47	64
21	27	40	55
26	22	32	44
32	18	26	36

Trek

Fuel EX 9

1166600*15.114
Bike weight: 29.0 lb/13.17 kg

FRAMESET

Main tubes	ZR9000	
Stays	OCLV 120 carbon fiber composite	
Color	Blue Anodized	
Fork	RockShox Reba Team w/PopLoc	100mm travel, 473mm axle-crown length
Rear shock	RockShox Motion Control 3 w/PopLoc, 1.5in stroke, 6.5 length,	
	40.0mm/ 0.86in width, 6mm eyes	
Headset	Alloy aheadset, semi-cartridge	25.4/34.0/30.0, 27.2mm stack height

CONTROLS

Handlebar	Bontrager Race X Lite	31.8mm clamp diameter
Stem	Bontrager Race Lite	40.0mm steerer clamp height
Shift levers	Shimano Deore XT	
Brake levers	Integrated brake/shift	
Grips	Bontrager, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Deore XT	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur	Shimano Deore XT SGS	
Crankset	Shimano Deore XT 44/32/22	64/104mm bolt hole circle
Bottom bracket	integral axle	73 (shell x axle,mm), Integral axle
Chain	Shimano HG-73	9 speed, 110 links
Cassette	Shimano Deore XT 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Race Lite Disc, tubeless compatible, 28°	537mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 266/267mm, 3x	
Tire	Bontrager Jones ACX, tubeless ready, 120tpi, 26 x 2.2, Tubeless asym rim strip	
Rear wheel	Bontrager Race Lite Disc, tubeless compatible, 28°	537mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 266/267mm, 3x	
Tire	Bontrager Jones ACX, tubeless ready, 120tpi, 26 x 2.2, Tubeless asym rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Race X Lite	31.6mm outer diameter
Saddle	Bontrager Race Lite Luxe	
Seatpost binder	Alloy w/integral quick-release	36.4mm inner diameter
Brakes	Shimano Deore XT, hydraulic discs	
	160mm discs, 44mm BCD	
Disc hose, mm	15.5 17.5 19.5 21.5	
Front	750 750 750 750	
Rear	1350 1350 1400 1400	
Pedals	Shimano SPD M520, clipless axle	
Additional	RockShox PopLoc dual leverWrench Force pump,	

FIT *dimensions in mm, unless specified*

Frame	Size	15.5	17.5	19.5	21.5
Rider height, in.		66.7	70.9	74.3	77.4
	cm	169	180	189	197
Handlebar	width	650	650	650	650
Handlebar	rise	40	40	40	40
Stem	length	90	100	100	120
	angle	7	7	7	7
Headset spacers		30	30	30	30
Crank	length	170	175	175	175
Seatpost	length	330	400	400	400
Steerer	length	183.2	198.2	213.2	228.2

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	71.0	71.0	71.0
Fork offset	38.0	38.0	38.0	38.0
Trail	73	73	73	73
Seat tube angle	73.5	73.5	73.5	73.5
Effective top tube	550	588	625	642
Seat tube	394	445	495	546
Standover	706	722	760	790
Wheelbase	1032	1071	1109	1126
Bottom bracket height	327	327	312	312
Chainstay	423	423	423	423
Head tube	90	105	120	135

GEARING

	22 32 44
11	52 76 105
13	44 65 89
15	38 56 77
17	34 49 68
20	29 42 58
23	25 36 50
26	22 32 44
30	19 28 38
34	17 25 34

Trek

Fuel EX 9 WSD

1166603*15.114
Bike weight: 28.5 lb/12.94 kg

FRAMESET

Main tubes	ZR9000	
Stays	OCLV 120 carbon fiber composite	
Color	Blue Anodized	
Fork	RockShox Reba Team w/PopLoc	100mm travel, 473mm axle-crown length
Rear shock	RockShox Motion Control 3 w/PopLoc, 1.5in stroke, 6.5 length,	
	40.0mm/ 0.86in width, 6mm eyes	
Headset	Alloy headset, semi-cartridge	25.4/34.0/30.0, 27.2mm stack height

CONTROLS

Handlebar	Bontrager Race X Lite	25.4mm clamp diameter
Stem	Bontrager Race Lite	40.0mm steerer clamp height
Shift levers	Shimano Deore XT	
Brake levers	Integrated brake/shift	
Grips	Bontrager Race, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Deore XT	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur	Shimano Deore XT SGS	
Crankset	Shimano Deore XT 44/32/22	64/104mm bolt hole circle
Bottom bracket	integral axle	73 (shell x axle,mm), Integral axle
Chain	Shimano HG-73	9 speed, 110 links
Cassette	Shimano Deore XT 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Race Lite Disc, tubeless compatible, 28°	537mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 266/267mm, 3x	
Tire	Bontrager Jones ACX, tubeless ready, 120tpi, 26 x 2.2, Tubeless asym rim strip	
Rear wheel	Bontrager Race Lite Disc, tubeless compatible, 28°	537mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 266/267mm, 3x	
Tire	Bontrager Jones ACX, tubeless ready, 120tpi, 26 x 2.2, Tubeless asym rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Race X Lite	31.6mm outer diameter
Saddle	Bontrager Race Lite WSD	
Seatpost binder	Alloy w/integral quick-release	36.4mm inner diameter
Brakes	Shimano Deore XT, hydraulic discs	
	160mm discs, 44mm BCD	
Disc hose, mm	14 16 18	
Front	690 690 690	
Rear	1220 1280 1280	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional	RockShox PopLoc dual leverWrench Force pump,	

FIT *dimensions in mm, unless specified*

Frame Size	14	16	18
Rider height, in.	61.3	63.0	68.0
cm	156	160	173
Handlebar width	650	650	650
Handlebar rise	40	40	40
Stem length	70	70	90
angle	10	10	10
Headset spacers	30	30	30
Crank length	170	170	175
Seatpost length	250	330	400
Steerer length	183.2	183.2	183.2

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.0	71.0
Fork offset	38.0	38.0	38.0
Trail	80	80	73
Seat tube angle	73.5	73.5	73.5
Effective top tube	515	532	565
Seat tube	356	406	457
Standover	681	717	755
Wheelbase	1018	1023	1053
Bottom bracket height	327	327	327
Chainstay	423	423	423
Head tube	90	90	90

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Trek Fuel EX 8

1164600*35.124
Bike weight: 29.4 lb/13.35 kg

FRAMESET

Main tubes		ZR9000	
Stays		OCLV 120 carbon fiber composite	
Color		Bright Silver/Pewter	
Fork		RockShox Reba Race	100mm travel, 473mm axle-crown length
Rear shock		RockShox Motion Control 3 w/PopLoc, 1.5in stroke, 6.5 length,	
		40.0mm/ 0.86in width, 6mm eyes	
Headset		Alloy aheadset, semi-cartridge	25.4/34.0/30.0, 27.2mm stack height

CONTROLS

Handlebar		Bontrager Crowbar Race Lite	31.8mm clamp diameter
Stem		Bontrager Race	40.0mm steerer clamp height
Shift levers		SRAM X.9 Triggers	
Brake levers		Hydraulic, attached to brake	
Grips		Bontrager, dual density	

DRIVETRAIN

Front derailleur	...	Shimano Deore LX	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur		SRAM RD X.9	
Crankset		Shimano Deore LX 44/32/22	64/104mm bolt hole circle
Bottom bracket		integral axle	73 (shell x axle,mm), Integral axle
Chain		Shimano HG-73	9 speed, 110 links
Cassette		SRAM PG970 11-34, 9spd	

WHEELSET

Front wheel		Bontrager Race Disc, tubeless compatible, 28°	537mm ERD
Spokes		DT 14/15G butted stainless, ProLock alloy nipples, 264/266mm, 3x	
Tire		Bontrager ACX, folding, 26 x 2.2, Tubeless asym rim strip	
Rear wheel		Bontrager Race Disc, tubeless compatible, 28°	542mm ERD
Spokes		DT 14/15G butted stainless, ProLock alloy nipples, 264/265mm, 3x	
Tire		Bontrager ACX, folding, 26 x 2.2, Tubeless asym rim strip	
Inner tubes		Presta valve	

OTHER

Seatpost		Bontrager Race	31.6mm outer diameter
Saddle		Bontrager Race Luxe	
Seatpost binder		Alloy w/integral quick-release	36.4mm inner diameter
Brakes		Hayes HFX-Mag HD, hydraulic disc front, Hayes HFX-Mag HD, hydraulic disc rear	
		6.3 in. discs, 44mm BCD	
Disc hose, mm		15.5 17.5 19.5 21.5	
Front		750 750 750 750	
Rear		1280 1350 1350 1400	
Pedals		Shimano SPD M520, clipless axle	
Additional		RockShox PopLoc dual leverWrench Force pump,	

FIT *dimensions in mm, unless specified*

Frame	Size	15.5	17.5	19.5	21.5
Rider height, in.		66.1	70.0	73.4	76.5
	cm	168	178	186	194
Handlebar	width	630	630	630	630
Handlebar	rise	25	25	25	25
Stem	length	90	100	100	120
	angle	7	7	7	7
Headset spacers		30	30	30	30
Crank	length	170	175	175	175
Seatpost	length	330	400	400	400
Steerer	length	183.2	198.2	213.2	228.2

GEOMETRY *dimensions in mm, unless specified*

Head tube angle		71.0	71.0	71.0	71.0
Fork offset		38.0	38.0	38.0	38.0
Trail		73	73	73	73
Seat tube angle		73.5	73.5	73.5	73.5
Effective top tube		550	588	625	642
Seat tube		394	445	495	546
Standover		706	722	760	790
Wheelbase		1032	1071	1109	1126
Bottom bracket height		327	327	312	312
Chainstay		423	423	423	423
Head tube		90	105	120	135

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Trek Fuel EX 7

1163600*35.124
Bike weight: 31.0 lb/14.07 kg

FRAMESET

Main tubes	ZR9000	
Stays	OCLV 120 carbon fiber composite	
Color	Titanite Black	
Fork	RockShox Reba SL	100mm travel, 473mm axle-crown length
Rear shock	RockShox Motion Control 3, 1.5in stroke, 6.5 length, 40.0mm/ 0.86in width, 6mm eyes	
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	Shimano Deore	
Brake levers	Hydraulic, attached to brake	
Grips	Bontrager, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Deore	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore XT SGS	
Crankset	Shimano Deore LX 44/32/22	64/104mm bolt hole circle
Bottom bracket . . .	integral axle	73 (shell x axle,mm), Integral axle
Chain	Shimano HG-53	9 speed, 112 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Select, disc compatible, 28°	541mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 268/268mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, Velox 22mm rim strip	
Rear wheel	Bontrager Select, disc compatible, 28°	541mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 268/267mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, Velox 22mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Select	31.6mm outer diameter
Saddle	Bontrager Select	
Seatpost binder . . .	Alloy w/integral quick-release	36.4mm inner diameter
Brakes	Hayes HFX-Mag HD, hydraulic disc front, Hayes HFX-Mag HD, hydraulic disc rear	
	6.3 in. discs, 44mm BCD	
Disc hose, mm	15.5 17.5 19.5 21.5	
Front	750 750 750 750	
Rear	1280 1350 1350 1400	
Pedals	Shimano SPD M505, clipless	axle
Additional	Wrench Force pump,	

FIT *dimensions in mm, unless specified*

Frame Size	15.5	17.5	19.5	21.5
Rider height, in.	66.1	70.0	73.4	76.5
cm	168	178	186	194
Handlebar width	630	630	630	630
Handlebar rise	25	25	25	25
Stem length	90	100	100	120
angle	7°	7°	7°	7°
Headset spacers	30	30	30	30
Crank length	170	175	175	175
Seatpost length	330	400	400	400
Steerer length	183.5	198.5	213.5	228.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	71.0	71.0	71.0
Fork offset	38.0	38.0	38.0	38.0
Trail	73	73	73	73
Seat tube angle	73.5	73.5	73.5	73.5
Effective top tube	550	588	625	642
Seat tube	394	445	495	546
Standover	706	722	760	790
Wheelbase	1032	1071	1109	1126
Bottom bracket height	327	327	312	312
Chainstay	423	423	423	423
Head tube	90	105	120	135

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Trek Fuel EX 7 WSD

1163603*15.104
Bike weight: 30.6 lb/13.89 kg

FRAMESET

Main tubes	ZR9000	
Stays	OCLV 120 carbon fiber composite	
Color	Mist Bluegray/Neptune Blue	
Fork	RockShox Reba SL	100mm travel, 473mm axle-crown length
Rear shock	RockShox Motion Control 3, 1.5in stroke, 6.5 length, 40.0mm/ 0.86in width, 6mm eyes	
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Select	25.4mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	Shimano Deore	
Brake levers	Hydraulic, attached to brake	
Grips	Bontrager Race, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Deore	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore XT SGS	
Crankset	Shimano Deore LX 44/32/22	64/104mm bolt hole circle
Bottom bracket . . .	integral axle	73 (shell x axle,mm), Integral axle
Chain	Shimano HG-53	9 speed, 112 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Select, disc compatible, 28°	541mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 268/268mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, Velox 22mm rim strip	
Rear wheel	Bontrager Select, disc compatible, 28°	541mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 268/267mm, 3x	
Tire	Bontrager ACX, 26 x 2.2, Velox 22mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Select	31.6mm outer diameter
Saddle		
Seatpost binder . . .	Alloy w/integral quick-release	36.4mm inner diameter
Brakes	Hayes HFX-9, hydraulic discs	
	6.3 in. discs, 44mm BCD	
Disc hose, mm	14 16 18	
Front	690 690 690	
Rear	1220 1280 1280	
Pedals	Shimano SPD M505, clipless	9/16" axle
Additional	Wrench Force pump,	

FIT *dimensions in mm, unless specified*

Frame Size	14	16	18
Rider height, in.	59.6	62.6	67.1
cm	151	159	170
Handlebar width	600	600	600
Handlebar rise	25	25	25
Stem length	60	70	90
angle	10	10	10
Headset spacers	30	30	30
Crank length	170	170	175
Seatpost length	250	330	400
Steerer length	183.5	183.5	183.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.0	71.0
Fork offset	38.0	38.0	38.0
Trail	80	80	73
Seat tube angle	73.5	73.5	73.5
Effective top tube	515	532	565
Seat tube	356	406	457
Standover	681	717	755
Wheelbase	1018	1023	1053
Bottom bracket height	327	327	327
Chainstay	423	423	423
Head tube	90	90	90

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Trek Liquid 65

1190600*15.104
Bike weight: 36.0 lb/16.34 kg

FRAMESET

Main tubes	ZR9000	
Stays	ZR9000	
Color	Black Anodized	
Fork	Manitou Nixon Super	145mm travel, 510mm axle-crown length
Rear shock	Manitou Swinger coil 3-way, 2in stroke, 7.5 length, 0.860" / 30mm width, 8mm eyes	
Headset	Alloy aheadset, semi-cartridge	25.4/34.0/30.0, 27.2mm stack height

CONTROLS

Handlebar	Bontrager Big Earl	31.8mm clamp diameter
Stem	Bontrager Big Earl	50.0mm steerer clamp height
Shift levers	SRAM X.9 Triggers	
Brake levers	Hydraulic, attached to brake	
Grips	Bontrager Earl	

DRIVETRAIN

Front derailleur . . .	Shimano Deore XT	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	SRAM RD X.9	
Crankset	Bontrager Big Earl 32/22	64/104mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe DH-LT	73 x 113 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-73	9 speed, 106 links
Cassette	SRAM PG970 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Big Earl, 32°	537mm ERD
Spokes	DT 14g, ProLock brass nipples, 251mm, 2x	
Tire	Bontrager Big Earl, 26 x 2.5, Schwalbe 25mm rim strip	
Rear wheel	Bontrager Big Earl, 32°	537mm ERD
Spokes	DT 14g, ProLock brass nipples, 251/251mm, 2x	
Tire	Bontrager Big Earl, 26 x 2.5, Schwalbe 25mm rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Bontrager Big Earl	31.6mm outer diameter
Saddle	Bontrager Big Earl	
Seatpost binder . . .	Alloy w/integral quick-release	36.4mm inner diameter
Brakes	Hayes HFX-Mag HD hydraulic discs	
	8 in. DH front disc, 6.3 in. rear disc, 44mm BCD	
Disc hose, mm	15.5 17.5 19.5 21.5	
Front	750 750 750 850	
Rear	1350 1350 1400 1400	
Pedals	Freeride platform	9/16" axle
Additional	Trek chainstay guardWrench Force pump,	

FIT *dimensions in mm, unless specified*

Frame	Size	15.5	17.5	19.5	21.5
Rider height, in.		55.9	65.6	64.3	66.0
	cm	142	167	163	168
Handlebar	width	710	710	710	710
Handlebar	rise	50	50	50	50
Stem	length		50		
	angle		10		
Headset spacers		25	25	25	25
Crank	length	165	170	170	170
Seatpost	length	330	400	400	400
Steerer	length	194.2	214.2	234.2	254.2

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	68.5	68.5	68.5	68.5
Fork offset	39.0			
Trail	89	89	89	89
Seat tube angle	71.5	71.5	71.5	71.5
Effective top tube	554	592	629	645
Seat tube	394	450	495	521
Standover	744	745	780	801
Wheelbase	1066	1105	1143	1160
Bottom bracket height	339	339	339	339
Chainstay	435	435	435	435
Head tube	105	125	145	165

GEARING

	22 32
11	52 76
13	44 65
15	38 56
17	34 49
20	29 42
23	25 36
26	22 32
30	19 28
34	17 25 0

Trek Liquid 55

1189600*15.084
Bike weight: 29.6 lb/13.44 kg

FRAMESET

Main tubes	ZR9000	
Stays	ZR9000	
Color	Pewter Anodized	
Fork	Manitou Minute II	130mm travel, 505mm axle-crown length
Rear shock	Manitou Swinger 3-Way, 2in stroke, 7.5 length, 7/8" width, 8mm eyes	
Headset	Alloy aheadset, semi-cartridge	25.4/34.0/30.0, 27.2mm stack height

CONTROLS

Handlebar	Bontrager Race X Lite	31.8mm clamp diameter
Stem	Bontrager Race Lite	40.0mm steerer clamp height
Shift levers	SRAM X.9 Triggers	
Brake levers	Hydraulic, attached to brake	
Grips	Bontrager Race, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Deore XT	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	SRAM RD X.9	
Crankset	Shimano Deore XT 44/32/22	64/104mm bolt hole circle
Bottom bracket . . .	integral axle	73 (shell x axle,mm), Integral axle
Chain	Shimano HG-73	9 speed, 112 links
Cassette	SRAM PG970 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Race Lite Disc, tubeless compatible, 28°	537mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 266/267mm, 3x	
Tire	Bontrager Jones ACX, tubeless ready, 120tpi, 26 x 2.2, Tubeless asym rim strip	
Rear wheel	Bontrager Race Lite Disc, tubeless compatible, 28°	537mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 266/267mm, 3x	
Tire	Bontrager Jones ACX, tubeless ready, 120tpi, 26 x 2.2, Tubeless asym rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Race Lite	31.6mm outer diameter
Saddle	Bontrager Race Lite Luxe	
Seatpost binder . . .	Alloy w/integral quick-release	36.4mm inner diameter
Brakes	Hayes HFX-Mag HD hydraulic discs	
	8 in. DH front disc, 6.3 in. rear disc, 44mm BCD	
Disc hose, mm	15.5 17.5 19.5 21.5	
Front	750 750 750 750	
Rear	1350 1350 1400 1400	
Pedals	Shimano SPD M520, clipless axle	
Additional	Trek chainstay guardWrench Force pump,	

FIT *dimensions in mm, unless specified*

Frame Size	15.5	17.5	19.5	21.5
Rider height, in.	67.7	72.2	75.7	77.5
cm	172	183	192	197
Handlebar width	650	650	650	650
Handlebar rise	40	40	40	40
Stem length	90	90	90	90
angle	7	7	7	7
Headset spacers	30	30	30	30
Crank length	170	175	175	175
Seatpost length	330	400	400	400
Steerer length	198.2	218.2	238.2	258.2

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	69.3	69.3	69.3	69.3
Fork offset	39.0			
Trail	85	85	85	85
Seat tube angle	72.3	72.3	72.3	72.3
Effective top tube	554	592	629	645
Seat tube	394	445	495	546
Standover	710	745	782	822
Wheelbase	1053	1092	1130	1147
Bottom bracket height	308	308	308	308
Chainstay	439	439	439	439
Head tube	105	125	145	165

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Trek Liquid 25

1186600*35.124
Bike weight: 31.8 lb/14.44 kg

FRAMESET

Main tubes	ZR9000	
Stays	ZR9000	
Color	Matte Navy	
Fork	Manitou Black Super	120mm travel, 490mm axle-crown length
Rear shock	Manitou Swinger 3-Way, 2in stroke, 7.5 length, 7/8" width, 8mm eyes	
Headset	Alloy aheadset, semi-cartridge	25.4/34.0/30.0, 27.2mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Race Lite	31.8mm clamp diameter
Stem	Bontrager Race	40.0mm steerer clamp height
Shift levers	Shimano Deore	
Brake levers	Hydraulic, attached to brake	
Grips	Bontrager Earl	

DRIVETRAIN

Front derailleur . . .	Shimano Deore LX	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore XT SGS	
Crankset	Bontrager Race 44/32/22	64/104mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe	73 x 116 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-53	9 speed, 112 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Race Disc, tubeless compatible, 28°	537mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 264/266mm, 3x	
Tire	Bontrager ACX, folding, 26 x 2.2, Tubeless asym rim strip	
Rear wheel	Bontrager Race Disc, tubeless compatible, 28°	542mm ERD
Spokes	DT 14/15G butted stainless, ProLock alloy nipples, 264/265mm, 3x	
Tire	Bontrager ACX, folding, 26 x 2.2, Tubeless asym rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Race	31.6mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .	Alloy w/integral quick-release	36.4mm inner diameter
Brakes	Hayes HFX-Mag HD hydraulic discs	
	8 in. DH front disc, 6.3 in. rear disc, 44mm BCD	
Disc hose, mm	15.5 17.5 19.5 21.5	
Front	750 750 750 750	
Rear	1350 1350 1400 1400	
Pedals	Shimano SPD M520, clipless	axle
Additional	Trek chainstay guardWrench Force pump,	

FIT *dimensions in mm, unless specified*

Frame	Size	15.5	17.5	19.5	21.5
Rider height, in.		66.7	71.1	74.4	76.2
	cm	169	180	189	193
Handlebar	width	630	630	630	630
Handlebar	rise	25	25	25	25
Stem	length	90	90	90	90
	angle	7	7	7	7
Headset spacers		30	30	30	30
Crank	length	170	175	175	175
Seatpost	length	330	400	400	400
Steerer	length	198.2	218.2	238.2	258.2

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	69.3	69.3	69.3	69.3
Fork offset	39.0			
Trail	85	85	85	85
Seat tube angle	72.3	72.3	72.3	72.3
Effective top tube	554	592	629	645
Seat tube	394	445	495	546
Standover	710	745	782	822
Wheelbase	1053	1092	1130	1147
Bottom bracket height	308	308	308	308
Chainstay	439	439	439	439
Head tube	105	125	145	165

GEARING

	22	32	44
11	52	76	105
13	44	65	89
15	38	56	77
17	34	49	68
20	29	42	58
23	25	36	50
26	22	32	44
30	19	28	38
34	17	25	34

Trek Y 26

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color	Rage Red/Metallic Black	
Fork	InSync Grind 2	70mm travel, 443mm axle-crown length
Rear shock	Mozo USA, stroke, 165mm length, 24mm width, 8mm eyes	
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 25.7mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem	Bontrager	41.0mm steerer clamp height
Shift levers	Shimano EF-29	
Brake levers	Integrated brake/shift	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano C050	Top pull, 31.8 mm/ 1 1/4" attachment
Rear derailleur . . .	Shimano Acera-X	
Crankset	SR 42/34/24	64/104mm bolt hole circle
Bottom bracket . . .		73 x 122.5 (shell x axle,mm), Square axle
Chain		3/32", 108 links
Cassette	SRAM 732 12-32, 7spd	

WHEELSET

Front wheel	Alloy, QR hub, 36°, WTB Dual Duty rim	559mm ERD
Spokes	14g stainless, 262mm, 3x	
Tire	Bontrager Connection Trail, 26 x 2.0, PVC rim strip	
Rear wheel	Shimano RM-40 hub, 36°, WTB Dual Duty rim	559mm ERD
Spokes	14g stainless, 259/261mm, 3x	
Tire	Bontrager Connection Trail, 26 x 2.0, PVC rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Bontrager	31.6mm outer diameter
Saddle	Bontrager Sport	
Seatpost binder . . .	Alloy w/integral bolt	36.4mm inner diameter
Brakes	Tektro direct pull	
Pedals	Alloy platform, clipless adaptable	9/16" axle
Additional		

FIT

dimensions in mm, unless specified

Frame	Size	16	17.5	19
Rider height, in.		68.4	73.2	76.0
	cm	174	186	193
Handlebar	width	600	620	620
Handlebar	rise	30	30	30
Stem	length	90	105	120
	angle	25	25	25
Headset spacers		40	40	40
Crank	length	170	175	175
Seatpost	length	300	300	350
Steerer	length	232	232	232

GEOMETRY

dimensions in mm, unless specified

Head tube angle	71.0	71.0	71.0
Fork offset	41.7	41.7	41.7
Trail	71	71	71
Seat tube angle	74.0	73.0	72.0
Effective top tube	564	612	644
Seat tube	432	483	533
Standover	710	740	739
Wheelbase	1047	1087	1109
Bottom bracket height	302	302	302
Chainstay	425	425	425
Head tube	115	125	125

GEARING

	24 34 42
12	52 74 92
14	45 64 79
16	39 56 69
19	33 47 58
22	29 41 50
26	24 34 42
32	20 28 34

Trek Session 77

1176600*15.114

FRAMESET

Main tubes	ZR9000	
Stays	ZR9000	
Color	Black Anodized	
Fork	Manitou Sherman Breakout Plus	170mm travel, 540mm axle-crown length
Rear shock	Manitou Swinger SPV coil 4-way, 2.5in stroke, 8.5 length, 7/8 in, 40mm width, 8mm eyes	
Headset	Cane Creek Double-X 1.5	38.1/49.6/29.8, 0mm stack height

CONTROLS

Handlebar	Bontrager Big Earl	31.8mm clamp diameter
Stem	Bontrager Big Earl	44.5mm steerer clamp height
Shift levers	SRAM X.9 Triggers	
Brake levers	Hydraulic, attached to brake	
Grips	Bontrager Earl	

DRIVETRAIN

Front derailleur . . .	Shimano Deore XT	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	SRAM RD X.9	
Crankset	Shimano Saint 32/22	64/104mm bolt hole circle
Bottom bracket . . .	integral axle	73 (shell x axle,mm), Integral axle
Chain	Shimano HG-73	9 speed, 114 links
Cassette	SRAM PG970 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Big Earl, 32°	537mm ERD
Spokes	DT 14g, ProLock brass nipples, 251mm, 2x	
Tire	Bontrager Big Earl, 26 x 2.5, Schwalbe 25mm rim strip	
Rear wheel	Bontrager Big Earl, 32°	537mm ERD
Spokes	DT 14g, ProLock brass nipples, 251/251mm, 2x	
Tire	Bontrager Big Earl, 26 x 2.7, Schwalbe 25mm rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Bontrager Big Earl	31.6mm outer diameter
Saddle	Bontrager Big Earl	
Seatpost binder . . .	Alloy w/integral bolt	36.4mm inner diameter
Brakes	Hayes HFX-Mag HD hydraulic discs	
	8 in. DH front disc, 8 in. DH rear disc, 44mm BCD	
Disc hose, mm	15.5 17.5 19	
Front	850 850 850	
Rear	1350 1350 1400	
Pedals	Freeride platform	9/16" axle
Additional	Trek chainstay protector	Wrench Force pump,

FIT *dimensions in mm, unless specified*

Frame	Size	15.5	17.5	19
Rider height, in.		52.2	53.4	56.9
	cm	133	136	145
Handlebar	width	710	710	710
Handlebar	rise	50	50	50
Stem	length	50	50	70
	angle	10	10	10
Headset spacers		0		
Crank	length	165	170	170
Seatpost	length	330	330	330
Steerer	length	155.5	155.5	155.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	66.5	66.5	66.5
Fork offset			
Trail	104	104	104
Seat tube angle	72.0	72.0	72.0
Effective top tube	565	584	610
Seat tube	394	445	483
Standover	775	792	815
Wheelbase	1123	1143	1170
Bottom bracket height	368	368	368
Chainstay	438	438	438
Head tube			

GEARING

	22 32
11	52 76
13	44 65
15	38 56
17	34 49
20	29 42
23	25 36
26	22 32
30	19 28
34	17 25 0

Trek Session 7

1174600*15.114
Bike weight: 43.2 lb/19.61 kg

FRAMESET

Main tubes	ZR9000	
Stays	ZR9000	
Color	Matte Silver	
Fork	Manitou Stance Flow	170mm travel, 540mm axle-crown length
Rear shock	Manitou Swinger SPV coil 4-way, 2.5in stroke, 8.5 length, 7/8 in,	
	40mm width, 8mm eyes	
Headset	Cane Creek Double-X 1.5	38.1/49.6/29.8, 0mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Earl	31.8mm clamp diameter
Stem	Bontrager Big Earl	44.5mm steerer clamp height
Shift levers	SRAM X.7 Triggers	
Brake levers	Hydraulic, attached to brake	
Grips	Bontrager Earl	

DRIVETRAIN

Front derailleur . . .	Shimano Deore	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	SRAM RD X.7	
Crankset	Bontrager Big Earl 32/22	64/104mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe Team DH	73 x 113 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-73	9 speed, 114 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Big Earl, 32°	537mm ERD
Spokes	DT 14g, ProLock brass nipples, 251mm, 2x	
Tire	Bontrager Big Earl, 26 x 2.5, Schwalbe 25mm rim strip	
Rear wheel	Bontrager Big Earl, 32°	537mm ERD
Spokes	DT 14g, ProLock brass nipples, 251/251mm, 2x	
Tire	Bontrager Big Earl, 26 x 2.7, Schwalbe 25mm rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Bontrager Big Earl	31.6mm outer diameter
Saddle	Bontrager Earl Kevlar	
Seatpost binder . . .	Alloy w/integral bolt	36.4mm inner diameter
Brakes	Hayes HFX-Mag HD hydraulic discs	
	8 in. DH front disc, 8 in. DH rear disc, 44mm BCD	
Disc hose, mm	15.5 17.5 19	
Front	850 850 850	
Rear	1350 1350 1400	
Pedals	Freeride platform	9/16" axle
Additional	Wrench Force pump,	

FIT dimensions in mm, unless specified

Frame Size	15.5	17.5	19
Rider height, in.	52.2	53.4	56.9
cm	133	136	145
Handlebar width	690	690	690
Handlebar rise	25	25	25
Stem length	50	50	70
angle	10	10	10
Headset spacers			
Crank length	165	170	170
Seatpost length	330	330	330
Steerer length	155.5	155.5	155.5

GEOMETRY dimensions in mm, unless specified

Head tube angle	66.5	66.5	66.5
Fork offset			
Trail	104	104	104
Seat tube angle	72.0	72.0	72.0
Effective top tube	565	584	610
Seat tube	394	445	483
Standover	775	792	815
Wheelbase	1123	1143	1170
Bottom bracket height	368	368	368
Chainstay	438	438	438
Head tube			

GEARING

	22 32
11	52 76
13	44 65
15	38 56
17	34 49
20	29 42
23	25 36
26	22 32
30	19 28
34	17 25 0

Trek 7700

1344600*15.084
Bike weight: 28.0 lb/12.71 kg

FRAMESET

Main tubes	Alpha SL aluminum	
Stays	Alpha SL aluminum	
Color	Brushed Aluminum	
Fork	Manitou Luxe Super	60mm travel, 499mm axle-crown length
Headset	Slimstack	25.4/34.0/30.0, 36.3mm stack height

CONTROLS

Handlebar	Alloy riser	25.4mm clamp diameter
Stem	Bontrager Satellite Plus, adjustable rise	40.0mm steerer clamp height
Shift levers	Shimano Deore XT	
Brake levers	Integrated brake/shift	
Grips	Oasis, dual density	

DRIVETRAIN

Front derailleur . . .	Shimano Deore XT	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore XT SGS	
Crankset	Bontrager Select Pavement 48/36/26	64/104mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe	73 x 113 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-73	9 speed, 114 links
Cassette	SRAM PG970 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Select Hybrid, 20°	593mm ERD
Spokes	DT 14g, ProLock brass nipples, 281mm, radial	
Tire	Bontrager Select Invert HardCase, 700 x 35c, Velox 16mm rim strip	
Rear wheel	Bontrager Select Hybrid, 24°	603mm ERD
Spokes	DT 14g, ProLock brass nipples, 293/294mm, 2x	
Tire	Bontrager Select Invert HardCase, 700 x 35c, Velox 16mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Suspension, alloy	27.2mm outer diameter
Saddle	Bontrager	
Seatpost binder . . .	Alloy w/integral quick-release	35.0mm inner diameter
Brakes	Shimano M420, V type, w/modulator front, Shimano M420, V type rear	
Pedals	Shimano SPD M324, clipless	9/16" axle
Additional	2 water bottle mounts (1 on 15, 15W), rack mounts (not 15)	

FIT *dimensions in mm, unless specified*

Frame	Size	15	17.5	20	22.5
Rider height, in.		69.5	70.6	70.9	73.1
	cm	176	179	180	186
Handlebar	width	620	620	620	620
Handlebar	rise	38	38	38	38
Stem	length	110	110	110	110
	angle	40	40	40	40
Headset spacers		30	30	30	30
Crank	length	170	170	175	175
Seatpost	length	300	350	350	350
Steerer	length	183.2	198.2	198.2	218.2

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.5	70.5	71.5
Fork offset	43.6	43.6	43.6	43.6
Trail				
Seat tube angle	74.0	74.0	73.0	73.0
Effective top tube	544	550	565	581
Seat tube	381	445	508	572
Standover	690	732	774	822
Wheelbase	1056	1056	1062	1069
Bottom bracket height	281	281	281	281
Chainstay	445	445	445	445
Head tube	90	105	105	125

GEARING

	26	36	48
11	64	89	119
13	54	75	101
15	47	65	87
17	42	58	77
20	35	49	65
23	31	43	57
26	27	38	50
30	24	33	44
34	21	29	38

Trek 7700FX

1345000*15.104

FRAMESET

Main tubes	ZR9000	
Stays	ZR9000	
Color	Brushed Aluminum	
Fork	Bontrager Satellite Plus, 381mm axle-crown length	
Headset	Slimstack	25.4/34.0/30.0, 36.3mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Race	mm clamp diameter
Stem	Bontrager Race	41.0mm steerer clamp height
Shift levers	Shimano Deore XT	
Brake levers	Integrated brake/shift	
Grips	Bontrager Race, triple density	

DRIVETRAIN

Front derailleur . . .	Shimano Deore XT	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur	Shimano Deore XT SGS	
Crankset	Bontrager Select Pavement 48/36/26	64/104mm bolt hole circle
Bottom bracket	TruVativ Giga-Pipe	73 x 113 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-73	9 speed, 114 links
Cassette	SRAM PG970 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Select Hybrid, 20°	593mm ERD
Spokes	DT 14g, ProLock brass nipples, 281mm, radial	
Tire	Bontrager Race Lite HardCase, 700 x 32c, Velox 16mm rim strip	
Rear wheel	Bontrager Select Hybrid, 24°	603mm ERD
Spokes	DT 14g, ProLock brass nipples, 293/294mm, 2x	
Tire	Bontrager Race Lite HardCase, 700 x 32c, Velox 16mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Race X Lite	27.2mm outer diameter
Saddle	Bontrager Race CRZ+	
Seatpost binder	Alloy w/integral bolt	32.1mm inner diameter
Brakes	Avid Single Digit 5, linear pull	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	15	17.5	20	22.5
Rider height, in.		64.0	66.8	67.4	71.3
	cm	162	170	171	181
Handlebar	width	630	630	630	630
Handlebar	rise	25	25	25	25
Stem	length	90	110	110	130
	angle	25	25	25	25
Headset spacers		30	30	30	30
Crank	length	170	175	175	175
Seatpost	length	250	330	330	330
Steerer	length	218.3	233.3	233.3	253.3

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.5	70.5	71.5
Fork offset	50.0	50.0	50.0	45.0
Trail	74	70	70	64
Seat tube angle	74.0	74.0	73.0	73.0
Effective top tube	544	550	565	581
Seat tube	381	445	508	572
Standover	690	732	774	822
Wheelbase	1056	1056	1062	1069
Bottom bracket height	281	281	281	281
Chainstay	445	445	445	445
Head tube	90	105	105	125

GEARING

	26	36	48
11	64	89	119
13	54	75	101
15	47	65	87
17	42	58	77
20	35	49	65
23	31	43	57
26	27	38	50
30	24	33	44
34	21	29	38

Trek 7500 FX

FRAMESET

Main tubes	Alpha SL aluminum	
Stays	Alpha SL aluminum	
Color	Metallic Black/Rage Red	
Fork	Aluminum, 412mm axle-crown length	
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 36.0mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	25.4mm clamp diameter
Stem	Bontrager Sport	50.0mm steerer clamp height
Shift levers	Shimano Deore	
Brake levers	Alloy, direct pull	
Grips	Bontrager Sport	

DRIVETRAIN

Front derailleur . . .	Shimano Deore	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore LX SGS	
Crankset	Bontrager Select Pavement 48/36/26	64/104mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe	73 x 113 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-73	9 speed, 114 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Select Hybrid, 20°	593mm ERD
Spokes	DT 14g, ProLock brass nipples, mm, radial	
Tire	Bontrager Race Lite HardCase, 700 x 28c, Velox 16mm rim strip	
Rear wheel	Bontrager Select Hybrid, 24°	635mm ERD
Spokes	DT 14g, ProLock brass nipples, 293/294mm, 2x	
Tire	Bontrager Race Lite HardCase, 700 x 28c, Velox 16mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .		31.8mm inner diameter
Brakes	Shimano M420, V type, w/modulator front, Shimano M420, V type rear	
Pedals	Alloy platform, clipless adaptable	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	15	17.5	20	22.5
Rider height, in.		65.2	67.0	69.1	71.6
	cm	166	170	176	182
Handlebar	width	580	580	600	600
Handlebar	rise	25	25	25	25
Stem	length	80	100	110	120
	angle	10	10	10	10
Headset spacers		30	30	30	30
Crank	length	170	170	175	175
Seatpost	length	300	350	350	350
Steerer	length	154	169	169	189

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	70.5	71.5	72.5
Fork offset	50.0	50.0	50.0	50.0
Trail	78	78	72	65
Seat tube angle	74.5	74.0	73.5	73.0
Effective top tube	548	552	568	584
Seat tube	381	445	508	572
Standover	693	737	778	825
Wheelbase	1058	1057	1057	1058
Bottom bracket height	288	288	288	288
Chainstay	445	445	445	445
Head tube	90	105	105	125

GEARING

	26	36	48
11	65	90	120
13	55	76	101
15	47	66	88
17	42	58	77
20	36	49	66
23	31	43	57
26	27	38	51
30	24	33	44
34	21	29	39

Trek 7500 FX Disc

FRAMESET

Main tubes	Alpha SL aluminum	
Stays	Alpha SL aluminum	
Color	Metallic Black/Rage Red	
Fork	Aluminum, 412mm axle-crown length	
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 36.0mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	25.4mm clamp diameter
Stem	Bontrager Sport	50.0mm steerer clamp height
Shift levers	Shimano Deore	
Brake levers	Hydraulic, attached to brake	
Grips	Bontrager Sport	

DRIVETRAIN

Front derailleur . . .	Shimano Deore	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore LX SGS	
Crankset	Bontrager Select Pavement 48/36/26	64/104mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe	73 x 113 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-73	9 speed, 114 links
Cassette	SRAM PG950 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Select Hybrid, 32°Alloy, disc compatible, QR hub, 32°, WTB Speed Disc rim	635mm ERD
Spokes	14g stainless, 294.5mm, 3x	
Tire	Bontrager Race Lite HardCase, 700 x 28c, PVC rim strip	
Rear wheel	Bontrager Select Hybrid, 32°Alloy, disc compatible, QR hub, 32°, WTB Speed Disc rim	635mm ERD
Spokes	14g stainless, 292/293mm, 3x	
Tire	Bontrager Race Lite HardCase, 700 x 28c, PVC rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .		31.8mm inner diameter
Brakes	Hayes Sole XC, hydraulic discs	
Pedals	Alloy platform, clipless adaptable	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	15	17.5	20	22.5	25	17W	20W
Rider height, in.		65.2	67.0	69.1	71.6	72.7	67.0	69.5
	cm	166	170	176	182	185	170	177
Handlebar	width	580	580	600	600	620	580	600
Handlebar	rise	25	25	25	25	25	25	25
Stem	length	80	100	110	120	130	100	110
	angle	10	10	10	10	10	10	10
Headset spacers		30	30	30	30	30	30	30
Crank	length	170	170	175	175	175	170	175
Seatpost	length	300	350	350	350	350	300	350
Steerer	length	154	169	169	189	209	189	209

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	70.5	71.5	72.5	72.5	70.5	71.5
Fork offset	50.0	50.0	50.0	50.0	50.0	50.0	50.0
Trail	78	78	72	65			
Seat tube angle	74.5	74.0	73.5	73.0	72.0	74.0	73.5
Effective top tube	548	552	568	584	596	550	566
Seat tube	381	445	508	572	635	432	508
Standover	693	737	778	825	872	589	574
Wheelbase	1058	1057	1057	1058	1058	1057	1057
Bottom bracket height	288	288	288	288	288	288	288
Chainstay	445	445	445	445	445	445	445
Head tube	90	105	105	125	145	125	145

GEARING

	26	36	48
11	65	90	120
13	55	76	101
15	47	66	88
17	42	58	77
20	36	49	66
23	31	43	57
26	27	38	51
30	24	33	44
34	21	29	39

Trek 7300 FXS

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color	Matte Lava Black	
Fork	Hi-tensile steel	50mm travel, 457mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 36.3mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	25.4mm clamp diameter
Stem	Alloy direct connect	40.0mm steerer clamp height
Shift levers	Shimano EF-29	
Brake levers	Integrated brake/shift	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano C102	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Alivio	
Crankset	Shimano TX71 48/38/28 w/chainguard	64/104mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 120 (shell x axle,mm), Square axle
Chain	IG-51	3/32", 114 links
Cassette	SRAM PG850 11-32, 8spd	

WHEELSET

Front wheel	Alloy, QR hub, 36°, Matrix 750 rim	622mm ERD
Spokes	14g stainless, 296mm, 3x	
Tire	Bontrager Invert Hard Case, 700 x 35c, PVC rim strip	
Rear wheel	Shimano RM-60 hub, 36°, Matrix 750 rim	622mm ERD
Spokes	14g stainless, 294/295mm, 3x	
Tire	Bontrager Invert Hard Case, 700 x 35c, PVC rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Suspension, alloy	27.2mm outer diameter
Saddle	Bontrager Sport	
Seatpost binder . . .		31.8mm inner diameter
Brakes	Tektro direct pull w/modulator front, Tektro direct pull rear	
Pedals	Platform	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

	Size	15	17.5	20	22.5	25	15W	17W	20W	22.5W
Frame										
Rider height, in.		67.0	68.6	70.9	73.4	75.4	65.9	65.9	69.4	72.9
	cm	170	174	180	186	191	167	167	176	185
Handlebar	width	580	580	600	600	620	580	580	600	600
Handlebar	rise	25	25	25	25	25	25	25	25	25
Stem	length	80	100	110	120	135	80	80	100	120
	angle	10	10	10	10	10	25	25	25	25
Headset spacers		30	30	30	30	30	30	30	30	30
Crank	length	170	170	175	175	175	170	170	175	175
Seatpost	length	300	300	350	350	350	300	300	350	350
Steerer	length	203	218	218	238	258	218	238	258	278

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	70.5	71.5	72.5	72.5	70.5	70.5	71.5	72.5
Fork offset	43.0	43.0	43.0	43.0	43.0	43.0	43.0	43.0	43.0
Trail	78	78	72	65	65	77	77	71	64
Seat tube angle	74.5	74.0	73.5	73.0	72.0	74.5	74.0	73.5	73.0
Effective top tube	548	552	568	584	596	546	550	566	583
Seat tube	381	445	508	572	635	381	432	508	572
Standover	693	737	778	825	872	596	589	574	558
Wheelbase	1058	1057	1057	1058	1058	1057	1057	1057	1057
Bottom bracket height	288	288	288	288	288	288	288	288	288
Chainstay	445	445	445	445	445	445	445	445	445
Head tube	90	105	105	125	145	105	125	145	165

GEARING

	28	38	48
11	70	95	120
12	64	87	110
14	55	74	94
16	48	65	82
18	43	58	73
21	37	50	63
26	30	40	51
32	24	33	41

Trek 7300 FX Disc

FRAMESET

Main tubes	Alpha SL aluminum	
Stays	Alpha SL aluminum	
Color	Matte Smooth Silver	
Fork	Cro-Moly, triple butted, 412mm axle-crown length	
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 36.0mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	22.2mm clamp diameter
Stem	Bontrager Sport	40.0mm steerer clamp height
Shift levers	Shimano Alivio	
Brake levers	Integrated brake/shift	
Grips	Bontrager Sport	

DRIVETRAIN

Front derailleur . . .	Shimano C102	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore SGS	
Crankset	Shimano T303 48/38/28 w/chainguard	64/104mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 122.5 (shell x axle,mm), Square axle
Chain	IG-51	3/32", 116 links
Cassette	SRAM PG850 11-32, 8spd	

WHEELSET

Front wheel	Alloy, disc compatible, QR hub, 36°, WTB Speed Disc rim	635mm ERD
Spokes	14g stainless, 294.5mm, 3x	
Tire	Bontrager Invert Hard Case, 700 x 35c, PVC rim strip	
Rear wheel	Alloy, disc compatible, QR hub, 36°, WTB Speed Disc rim	635mm ERD
Spokes	14g stainless, 292/293mm, 3x	
Tire	Bontrager Invert Hard Case, 700 x 35c, PVC rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	27.2mm outer diameter
Saddle	Bontrager Sport	
Seatpost binder . . .		31.8mm inner diameter
Brakes	Hayes MX-2 mechanical discs	
Pedals	Alloy platform, clipless adaptable	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	15	17.5	20	22.5	25	17W	20W
Rider height, in.		65.9	67.1	69.9	71.1	73.1	65.6	66.9
	cm	167	170	178	181	186	167	170
Handlebar	width	580	580	600	600	620	580	600
Handlebar	rise	30	30	30	30	30	30	30
Stem	length	90	105	120	120	135	90	90
	angle	25	25	25	25	25	25	25
Headset spacers		30	30	30	30	30	30	30
Crank	length	170	170	175	175	175	170	175
Seatpost	length	300	350	350	350	350	300	350
Steerer	length	154	169	169	189	209	189	209

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	70.5	71.5	72.5	72.5	70.5	71.5
Fork offset	50.0	50.0	50.0	50.0	50.0	50.0	50.0
Trail	78	78	72	65	65	78	72
Seat tube angle	74.5	74.0	73.5	73.0	72.0	74.0	73.5
Effective top tube	548	552	568	584	596	550	566
Seat tube	381	445	508	572	635	432	508
Standover	693	737	778	825	872	589	574
Wheelbase	1058	1057	1057	1058	1058	1057	1057
Bottom bracket height	288	288	288	288	288	288	288
Chainstay	445	445	445	445	445	445	445
Head tube	90	105	105	125	145	125	145

GEARING

	28 38 48
11	70 95 120
12	64 87 110
14	55 74 94
16	48 65 82
18	43 58 73
21	37 50 63
26	30 40 51
32	24 33 41

Trek 7300

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color	Midnight Blue/Ball Burnished	
Matte Latte/Matte Parchment Gold		
Fork	RST C5 50mm travel, 428.1mm axle-crown length	
Headset	Semi-cartridge, threaded	25.4/34.0/30.0, 36mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem	Adjustable rise	
Shift levers	SRAM ESP 4.0 Pro	
Brake levers	Alloy, direct pull	
Grips	SRAM	

DRIVETRAIN

Front derailleur . . .	Shimano C102	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	SRAM RD X.7	
Crankset	Bontrager Sport 48/38/28 w/chainguard	64/104mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 113 (shell x axle,mm), Square axle
Chain	IG-51	3/32", 114 links
Cassette	SRAM PG850 11-32, 8spd	

WHEELSET

Front wheel	Alloy, QR hub, 36°, Alex Ace rim	635mm ERD
Spokes	14g stainless, 294.5mm, 3x	
Tire	Bontrager Invert Hard Case, 700 x 35c, Rubber rim strip	
Rear wheel	Shimano RM-60 hub, 36°, Alex Ace rim	635mm ERD
Spokes	14g stainless, 292.5/293mm, 3x	
Tire	Bontrager Invert Hard Case, 700 x 35c, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Suspension, alloy	27.2mm outer diameter
Saddle	Bontrager Webspring w/elastomers	
Seatpost binder . . .		31.8mm inner diameter
Brakes	ProMax direct pull w/modulator front, ProMax direct pull rear	
Pedals	Platform w/flashing lights	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame Size	15	17.5	20	22.5	25	15W	20W
Rider height, in.	67.0	66.8	70.5	71.8	72.0	66.8	70.7
cm	170	170	179	182	183	170	180
Handlebar width	600	600	620	620	620	600	620
Handlebar rise	50	50	50	50	50	50	50
Stem length	85	85	105	105	105	85	105
angle	15	15	15	15	15	15	15
Headset spacers	4	4	4	4	4	4	4
Crank length	170	170	175	175	175	170	175
Seatpost length	300	350	350	350	350	300	350
Steerer length	129	144	144	164	184	144	184

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	70.5	71.5	72.5	72.5	70.5	71.5
Fork offset	50.0	50.0	50.0	50.0	50.0	50.0	50.0
Trail	78	78	72	65	78	65	72
Seat tube angle	74.5	74.0	73.5	73.0	72.0	74.5	73.5
Effective top tube	548	552	568	584	596	546	566
Seat tube	381	445	508	572	635	381	508
Standover	693	737	778	825	872	596	574
Wheelbase	1058	1057	1057	1058	1058	1057	1057
Bottom bracket height	288	288	288	288	288	288	288
Chainstay	445	445	445	445	445	445	445
Head tube	90	105	105	125	145	105	145

GEARING

	28 38 48
11	70 95 120
12	64 87 110
14	55 74 94
16	48 65 82
18	43 58 73
21	37 50 63
26	30 40 51
32	24 33 41

Trek 7300 FX

FRAMESET

Main tubes	Alpha SL aluminum	
Stays	Alpha SL aluminum	
Color	Matte Smooth Silver	
Fork	Cro-Moly, triple butted, 412mm axle-crown length	
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 36.0mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	22.2mm clamp diameter
Stem	Bontrager Sport	40.0mm steerer clamp height
Shift levers	Shimano Alivio	
Brake levers	Integrated brake/shift	
Grips	Bontrager Sport	

DRIVETRAIN

Front derailleur . . .	Shimano C102	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Deore SGS	
Crankset	Shimano T303 48/38/28 w/chainguard	64/104mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 122.5 (shell x axle,mm), Square axle
Chain	IG-51	3/32", 116 links
Cassette	SRAM PG850 11-32, 8spd	

WHEELSET

Front wheel	Alloy, QR hub, 36°, WTB Dual Duty rim	635mm ERD
Spokes	14g stainless, 294.5mm, 3x	
Tire	Bontrager Invert Hard Case, 700 x 35c, PVC rim strip	
Rear wheel	Shimano Deore hub, 36°, WTB Dual Duty rim	635mm ERD
Spokes	14g stainless, 292/293mm, 3x	
Tire	Bontrager Invert Hard Case, 700 x 35c, PVC rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	27.2mm outer diameter
Saddle	Bontrager Sport	
Seatpost binder . . .		31.8mm inner diameter
Brakes	ProMax direct pull w/modulator front, ProMax direct pull rear	
Pedals	Alloy platform, clipless adaptable	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	15	17.5	20	22.5	25	17W	20W
Rider height, in.		65.9	67.1	69.9	71.1	73.1	65.6	66.9
	cm	167	170	178	181	186	167	170
Handlebar	width	580	580	600	600	620	580	600
Handlebar	rise	30	30	30	30	30	30	30
Stem	length	90	105	120	120	135	90	90
	angle	25	25	25	25	25	25	25
Headset spacers		30	30	30	30	30	30	30
Crank	length	170	170	175	175	175	170	175
Seatpost	length	300	350	350	350	350	300	350
Steerer	length	154	169	169	189	209	189	209

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	70.5	71.5	72.5	72.5	70.5	71.5
Fork offset	50.0	50.0	50.0	50.0	50.0	50.0	50.0
Trail	78	78	72	65	65	78	72
Seat tube angle	74.5	74.0	73.5	73.0	72.0	74.0	73.5
Effective top tube	548	552	568	584	596	550	566
Seat tube	381	445	508	572	635	432	508
Standover	693	737	778	825	872	589	574
Wheelbase	1058	1057	1057	1058	1058	1057	1057
Bottom bracket height	288	288	288	288	288	288	288
Chainstay	445	445	445	445	445	445	445
Head tube	90	105	105	125	145	125	145

GEARING

	28	38	48
11	70	95	120
12	64	87	110
14	55	74	94
16	48	65	82
18	43	58	73
21	37	50	63
26	30	40	51
32	24	33	41

Trek 7200

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color	Black Chrome/ Smooth Silver	
	Matte Cool Silver/ Matte Wedgewood Blue	
Fork	RST C5 50mm travel, 452.9mm axle-crown length	
Headset	Semi-cartridge, threaded	25.4/34.0/30.0, 36mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem	Adjustable rise	
Shift levers	SRAM MRX Plus	
Brake levers	Alloy, direct pull	
Grips	SRAM	

DRIVETRAIN

Front derailleur . . .	Shimano C102	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Alivio	
Crankset	Shimano TX71 48/38/28 w/chainguard	64/105mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 122.5 (shell x axle,mm), Square axle
Chain	IG-51	3/32", 114 links
Cassette	SRAM PG850 11-32, 8spd	

WHEELSET

Front wheel	Alloy, QR hub, 36°, Matrix 550 rim	635mm ERD
Spokes	14g stainless, 294.5mm, 3x	
Tire	Bontrager Invert Hard Case, 700 x 35c, Rubber rim strip	
Rear wheel	Shimano RM-60 hub, 36°, Matrix 550 rim	635mm ERD
Spokes	14g stainless, 292.5/293mm, 3x	
Tire	Bontrager Invert Hard Case, 700 x 35c, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Suspension, alloy	27.2mm outer diameter
Saddle	Bontrager Webspring	
Seatpost binder . . .		31.8mm inner diameter
Brakes	Tektro direct pull w/modulator front, Tektro direct pull rear	
Pedals	Platform 9/16" axle	
Additional	integral bell,	

FIT *dimensions in mm, unless specified*

Frame	Size	15	17.5	20	22.5	25	15W	20W
Rider height, in.		67.8	67.8	71.5	72.8	73.3	67.7	71.9
	cm	172	172	182	185	186	172	183
Handlebar	width	600	600	620	620	620	600	620
Handlebar	rise	50	50	50	50	50	50	50
Stem	length	85	85	105	105	105	85	105
	angle	15	15	15	15	15	15	15
Headset spacers		4	4	4	4	4	4	4
Crank	length	170	170	170	170	170	170	170
Seatpost	length	300	350	350	350	350	300	350
Steerer	length	129	144	144	164	184	144	184

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	70.5	71.5	72.5	72.5	70.5	71.5
Fork offset	46.0	46.0	46.0	46.0	46.0	46.0	46.0
Trail	78	78	72	65	78	65	72
Seat tube angle	74.5	74.0	73.5	73.0	72.0	74.5	73.5
Effective top tube	548	552	568	584	596	546	566
Seat tube	381	445	508	572	635	381	508
Standover	693	737	778	825	872	596	574
Wheelbase	1058	1057	1057	1058	1058	1057	1057
Bottom bracket height	288	288	288	288	288	288	288
Chainstay	445	445	445	445	445	445	445
Head tube	90	105	105	125	145	105	145

GEARING

	28 38 48
11	70 95 120
12	64 87 110
14	55 74 94
16	48 65 82
18	43 58 73
21	37 50 63
26	30 40 51
32	24 33 41

Trek 7200 FX

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color	Matte Lava Black	
Fork	Hi-tensile steel, 445mm axle-crown length	
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 36.0mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	22.2mm clamp diameter
Stem	Alloy direct connect, adjustable rise	40.0mm steerer clamp height
Shift levers	Shimano EF-29	
Brake levers	Integrated brake/shift	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano C102	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Alivio	
Crankset	Shimano TX71 48/38/28 w/chainguard	64/104mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 122.5 (shell x axle,mm), Square axle
Chain	IG-51	3/32", 116 links
Cassette	SRAM PG850 11-32, 8spd	

WHEELSET

Front wheel	Alloy, QR hub, 36°, Matrix 750 rim	635mm ERD
Spokes	14g stainless, 289.5mm, 3x	
Tire	Bontrager Invert Hard Case, 700 x 35c, PVC rim strip	
Rear wheel	Shimano RM-60 hub, 36°, Matrix 750 rim	635mm ERD
Spokes	14g stainless, 286/287mm, 3x	
Tire	Bontrager Invert Hard Case, 700 x 35c, PVC rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Suspension, alloy	27.2mm outer diameter
Saddle	Bontrager Sport	
Seatpost binder . . .		31.8mm inner diameter
Brakes	Tektro direct pull w/modulator front, Tektro direct pull rear	
Pedals	Platform	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	15	17.5	20	22.5	25	15W	17W	20W
Rider height, in.		67.6	69.3	71.8	73.4	75.0	67.4	67.4	70.3
	cm	172	176	182	187	190	171	171	179
Handlebar	width	580	580	600	600	620	580	580	600
Handlebar	rise	30	30	30	30	30	30	30	30
Stem	length	90	105	120	120	135	90	90	105
	angle	6	6	6	6	6	6	6	6
Headset spacers		30	30	30	30	30	30	30	30
Crank	length	170	170	175	175	175	170	170	175
Seatpost	length	300	350	350	350	350	300	300	350
Steerer	length	154	169	169	189	209	169	189	209

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	70.5	71.5	72.5	72.5	70.5	70.5	71.5
Fork offset	43.0	43.0	43.0	43.0	43.0	43.0	43.0	43.0
Trail	78	78	72	65	65	78	78	72
Seat tube angle	74.5	74.0	73.5	73.0	72.0	74.5	74.0	73.5
Effective top tube	548	552	568	584	596	546	550	566
Seat tube	381	445	508	572	635	381	432	508
Standover	693	737	778	825	872	596	589	574
Wheelbase	1058	1057	1057	1058	1058	1057	1057	1057
Bottom bracket height	288	288	288	288	288	288	288	288
Chainstay	445	445	445	445	445	445	445	445
Head tube	90	105	105	125	145	105	125	145

GEARING

	28	38	48
11	70	95	120
12	64	87	110
14	55	74	94
16	48	65	82
18	43	58	73
21	37	50	63
26	30	40	51
32	24	33	41

Trek 7200 FXS

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color	Matte Lava Black	
Fork	Hi-tensile steel	50mm travel, 457mm axle-crown length
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 36.3mm stack height

CONTROLS

Handlebar	Bontrager Crowbar Sport	22.2mm clamp diameter
Stem	Alloy direct connect, adjustable rise	40.0mm steerer clamp height
Shift levers	Shimano EF-29	
Brake levers	Integrated brake/shift	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano C102	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Alivio	
Crankset	Shimano TX71 48/38/28 w/chainguard	64/104mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 122.5 (shell x axle,mm), Square axle
Chain	IG-51	3/32", 114 links
Cassette	SRAM PG850 11-32, 8spd	

WHEELSET

Front wheel	Alloy, QR hub, 36°, Matrix 750 rim	622mm ERD
Spokes	14g stainless, 293mm, 3x	
Tire	Bontrager Invert Hard Case, 700 x 35c, PVC rim strip	
Rear wheel	Shimano RM-60 hub, 36°, Matrix 750 rim	622mm ERD
Spokes	14g stainless, 289/291mm, 3x	
Tire	Bontrager Invert Hard Case, 700 x 35c, PVC rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Suspension, alloy	27.2mm outer diameter
Saddle	Bontrager Sport	
Seatpost binder . . .		31.8mm inner diameter
Brakes	Tektro direct pull w/modulator front, Tektro direct pull rear	
Pedals	Platform	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

	Size	15	17.5	20	22.5	25	15W	17W	20W	22.5W
Frame										
Rider height, in.		67.7	68.0	70.9	72.5	72.7	67.9	67.9	71.3	73.7
	cm	172	173	180	184	185	173	173	181	187
Handlebar width		580	580	600	600	620	580	580	600	600
Handlebar rise		30	30	30	30	30	30	30	30	30
Stem length		105	105	125	125	125	105	105	125	125
Stem angle		35	35	35	35	35	35	35	35	35
Headset spacers		30	30	30	30	30	30	30	30	30
Crank length		170	170	170	170	170	170	170	170	
Seatpost length		300	300	350	350	350	300	300	350	350
Steerer length		193	208	208	228	248	208	228	248	268

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	70.5	71.5	72.5	72.5	70.5	70.5	71.5	72.5
Fork offset	43.0	43.0	43.0	43.0	43.0	43.0	43.0	43.0	
Trail	78	78	72	65	65	77	77	71	64
Seat tube angle	74.5	74.0	73.5	73.0	72.0	74.5	74.0	73.5	73.0
Effective top tube	548	552	568	584	596	546	550	566	583
Seat tube	381	445	508	572	635	381	432	508	572
Standover	693	737	778	825	872	596	589	574	558
Wheelbase	1058	1057	1057	1058	1058	1057	1057	1057	1057
Bottom bracket height	288	288	288	288	288	288	288	288	288
Chainstay	445	445	445	445	445	445	445	445	445
Head tube	90	105	105	125	145	105	125	145	165

GEARING

	28	38	48
11	70	95	120
12	64	87	110
14	55	74	94
16	48	65	82
18	43	58	73
21	37	50	63
26	30	40	51
32	24	33	41

Trek 7100

FRAMESET

Main tubes	Alpha aluminum
Stays	Alpha aluminum
Color	Metallic Red/Wheat Silver
	Matte Green/Matte Parchment Gold
Fork.	RST C5 50mm travel, 452.9mm axle-crown length
Headset	Semi-cartridge, threaded 25.4/34.0/30.0, 36mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem	Adjustable rise	
Shift levers	SRAM ESP 3.0 Plus	
Grips	SRAM	

DRIVETRAIN

Front derailleur . . .	SR CR-238	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	SRAM ESP 3.0	
Crankset	SR NEX200 48/38/28	64/105mm bolt hole circle
Bottom bracket . . .		73 x 122.5 (shell x axle,mm), Square axle
Chain.	KMC Z51	3/32", 114 links
Cassette.	Sunrace 13-34, 7spd	

WHEELSET

Front wheel.	Alloy, QR hub, 36°, Matrix 550 rim	635mm ERD
Spokes	14g stainless, 294.5mm, 3x	
Tire	Bontrager Invert, 700 x 35c, Rubber rim strip	
Rear wheel	Alloy, QR hub, 36°, Matrix 550 rim	635mm ERD
Spokes	14g stainless, 292.5/293mm, 3x	
Tire	Bontrager Invert, 700 x 35c, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost.	Suspension, alloy	27.2mm outer diameter
Saddle	Bontrager Webspring	
Seatpost binder. . .		31.8mm inner diameter
Brakes	Tektro direct pull w/modulator front, Tektro direct pull rear	
Pedals	Platform 9/16" axle	
Additional	integral bell,	

FIT *dimensions in mm, unless specified*

	Size	15	17.5	20	22.5	25	15W	20W
Rider height, in.		67.8	67.8	71.0	72.6	72.9	67.7	71.3
	cm	172	172	180	184	185	172	181
Handlebar width		580	580	600	600	600	580	600
Handlebar rise		50	50	50	50	50	50	50
Stem length		85	85	105	105	105	85	105
	angle	15	15	15	15	15	15	15
Headset spacers		4	4	4	4	4	4	4
Crank length		170	170	175	175	175	170	175
Seatpost length		300	350	350	350	350	300	350
Steerer length		129	144	144	164	184	144	184

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	70.5	71.5	72.5	72.5	70.5	71.5
Fork offset	46.0	46.0	46.0	46.0	46.0	46.0	46.0
Trail	78	78	72	65	78	65	72
Seat tube angle	74.5	74.0	73.5	73.0	72.0	74.5	73.5
Effective top tube	548	552	568	584	596	546	566
Seat tube	381	445	508	572	635	381	508
Standover	693	737	778	825	872	596	574
Wheelbase	1058	1057	1057	1058	1058	1057	1057
Bottom bracket height	288	288	288	288	288	288	288
Chainstay	445	445	445	445	445	445	445
Head tube	90	105	105	125	145	105	145

GEARING

	28	38	48
13	59	80	101
15	51	69	88
17	45	61	77
19	40	55	69
22	35	47	60
26	30	40	51
34	23	31	39

Trek 7000

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color	Matte Navy Blue/ Matte Silver	
	Silver/ Pearl White	
Fork	Hi-tensile steel, 452.7mm axle-crown length	
Headset	Semi-cartridge, threaded	25.4/34.0/30.0, 36mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem	Adjustable rise	
Shift levers	SRAM MRX Plus	
Grips	SRAM	

DRIVETRAIN

Front derailleur . . .	SR CR-238	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano TX-50	
Crankset	SR NEX200 48/38/28	64/105mm bolt hole circle
Bottom bracket . . .		73 x 122.5 (shell x axle,mm), Square axle
Chain	KMC Z51	3/32", 114 links
Cassette	Sunrace 13-34, 7spd	

WHEELSET

Front wheel	Alloy, QR hub, 36°, Matrix 550 rim	635mm ERD
Spokes	14g stainless, 294.5mm, 3x	
Tire	Bontrager Invert, 700 x 35c, Rubber rim strip	
Rear wheel	Alloy, QR hub, 36°, Matrix 550 rim	635mm ERD
Spokes	14g stainless, 292.5/293mm, 3x	
Tire	Bontrager Invert, 700 x 35c, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Suspension, alloy	27.2mm outer diameter
Saddle	Bontrager Webspring	
Seatpost binder . . .		31.8mm inner diameter
Brakes	Tektro direct pull w/modulator front, Tektro direct pull rear	
Pedals	Platform 9/16" axle	
Additional	integral bell,	

FIT *dimensions in mm, unless specified*

Frame	Size	15	17.5	20	22.5	15W	20W
Rider height, in.		68.0	68.0	71.2	72.8	67.9	59.4
	cm	173	173	181	185	173	151
Handlebar	width	580	580	600	600	580	600
Handlebar	rise	50	50	50	50	50	50
Stem	length	85	85	105	105	85	105
	angle	15	15	15	15	15	15
Headset spacers		4	4	4	4	4	4
Crank	length	170	170	175	175	170	175
Seatpost	length	300	350	350	350	300	350
Steerer	length	129	144	144	164	144	184

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	70.5	71.5	72.5	70.5	71.5
Fork offset	46.0	46.0	46.0	46.0	46.0	43/46.0
Trail	78	78	72	65	78	72
Seat tube angle	74.5	74.0	73.5	73.0	74.5	73.5
Effective top tube	548	552	568	584	546	566
Seat tube	381	445	508	572	381	508
Standover	693	737	778	825	596	574
Wheelbase	1058	1057	1057	1058	1057	1057
Bottom bracket height	288	288	288	288	288	288
Chainstay	445	445	445	445	445	445
Head tube	90	105	105	125	105	145

GEARING

	28 38 48
13	59 80 101
15	51 69 88
17	45 61 77
19	40 55 69
22	35 47 60
26	30 40 51
34	23 31 39

Trek 7100 FX

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color		
Fork	Hi-tensile steel, 412mm axle-crown length	
Headset	Semi-cartridge, threaded	25.4/34.0/30.0, 36.0mm stack height

CONTROLS

Handlebar	Steel	22.2mm clamp diameter
Stem	Alloy direct connect, adjustable rise	40.0mm steerer clamp height
Shift levers	Shimano EF-29	
Brake levers	Integrated brake/shift	
Grips	Bontrager	

DRIVETRAIN

Front derailleur . . .	Shimano C102	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur	Shimano Acera-X	
Crankset	SR XCC-100 48/38/28 w/chainguard	64/104mm bolt hole circle
Bottom bracket	Cartridge	73 x 122.5 (shell x axle,mm), Square axle
Chain	KMC Z51	3/32", 116 links
Cassette	Sunrace 13-34, 7spd	

WHEELSET

Front wheel	Alloy, QR hub, 36°, Matrix 750 rim	635mm ERD
Spokes	14g, 294.5mm, 3x	
Tire	Bontrager Invert, 700 x 35c, Rubber rim strip	
Rear wheel	Alloy, QR hub, 36°, Matrix 750 rim	635mm ERD
Spokes	14g, 292/293mm, 3x	
Tire	Bontrager Invert, 700 x 35c, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Suspension, alloy	27.2mm outer diameter
Saddle	Bontrager Sport	
Seatpost binder		31.8mm inner diameter
Brakes	Tektro direct pull w/modulator front, Tektro direct pull rear	
Pedals	Platform	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

	Size	15	17.5	20	22.5	25	15W	17W	20W	22.5W
Rider height, in.		66.1	67.2	70.2	71.3	73.2	65.9	66.1	69.0	72.1
	cm	168	171	178	181	186	168	168	175	183
Handlebar width		580	580	600	600	620	580	580	600	600
Handlebar rise		30	30	30	30	30	30	30	30	30
Stem length		90	105	120	120	135	90	90	105	120
Stem angle		35	35	35	35	35	35	35	35	35
Headset spacers		6	6	6	6	6	6	6	6	6
Crank length		170	170	175	175	175	170	170	175	175
Seatpost length		300	350	350	350	350	300	300	350	350
Steerer length		154	169	169	189	209	169	189	209	229

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	70.5	71.5	72.5	72.5	70.5	70.5	71.5	72.5
Fork offset	50.0	50.0	50.0	50.0	50.0	50.0	50.0	50.0	50.0
Trail	71	71	65	58	58	71	71	65	58
Seat tube angle	74.5	74.0	73.5	73.0	72.0	74.5	74.0	73.5	73.0
Effective top tube	544	548	565	581	592	546	547	563	580
Seat tube	381	445	508	572	635	381	432	508	572
Standover	681	725	766	814	861	596	579	564	550
Wheelbase	1056	1056	1058	1059	1058	1057	1057	1057	1059
Bottom bracket height	283	283	283	283	283	283	283	283	283
Chainstay	445	445	445	445	445	445	445	445	445
Head tube	115	130	130	150	170	105	150	170	190

GEARING

	28	38	48
13	59	80	101
15	51	69	88
17	45	61	77
19	40	55	69
22	35	47	60
26	30	40	51
34	23	31	39

Trek 7100 E

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color		
Fork	Hi-tensile steel, 454mm axle-crown length	
Headset	Semi-cartridge, threaded	25.4/34.0/30.0, 36.0mm stack height

CONTROLS

Handlebar	Steel	22.2mm clamp diameter
Stem	Alloy direct connect, adjustable rise	
Shift levers	Shimano EF-29	
Brake levers	Integrated brake/shift	
Grips	Bontrager	

DRIVETRAIN

Front derailleur . . .	Shimano C102	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Acera-X	
Crankset	SR XCC-100 48/38/28 w/chainguard	64/104mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 122.5 (shell x axle,mm), Square axle
Chain	KMC Z51	3/32", 116 links
Cassette	Sunrace 13-34, 7spd	

WHEELSET

Front wheel	Alloy, QR hub, 36°, Matrix 750 rim	635mm ERD
Spokes	14g, 289.5mm, 3x	
Tire	Bontrager Invert, 700 x 35c, PVC rim strip	
Rear wheel	Alloy, QR hub, 36°, Matrix 750 rim	635mm ERD
Spokes	14g, 286/287mm, 3x	
Tire	Bontrager Invert, 700 x 35c, PVC rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Suspension, alloy	27.2mm outer diameter
Saddle	Bontrager Sport	
Seatpost binder . . .		31.8mm inner diameter
Brakes	Tektro direct pull w/modulator front, Tektro direct pull rear	
Pedals	Platform	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

	Size	15	17.5	20	22.5	25	15W	17W	20W	22.5W
Frame										
Rider height, in.		69.4	71.2	74.0	75.4	77.3	69.3	69.5	72.8	76.1
	cm	176	181	188	192	196	176	177	185	193
Handlebar width		580	580	600	600	620	580	580	600	600
Handlebar rise		30	30	30	30	30	30	30	30	30
Stem length		90	105	120	120	135	90	90	105	120
Stem angle		6	6	6	6	6	6	6	6	6
Headset spacers		4	4	4	4	4	4	4	4	4
Crank length		170	170	175	175	175	170	170	175	175
Seatpost length		300	350	350	350	350	300	300	350	350
Steerer length		154	169	169	189	209	169	189	209	229

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	70.5	71.5	72.5	72.5	70.5	70.5	71.5	72.5
Fork offset	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0
Trail	71	71	65	58	58	71	71	65	58
Seat tube angle	74.5	74.0	73.5	73.0	72.0	74.5	74.0	73.5	73.0
Effective top tube	544	548	565	581	592	546	547	563	580
Seat tube	381	445	508	572	635	381	432	508	572
Standover	681	725	766	814	861	596	579	564	550
Wheelbase	1056	1056	1058	1059	1058	1057	1057	1057	1059
Bottom bracket height	283	283	283	283	283	283	283	283	283
Chainstay	445	445	445	445	445	445	445	445	445
Head tube	115	130	130	150	170	105	150	170	190

GEARING

	28	38	48
13	59	80	101
15	51	69	88
17	45	61	77
19	40	55	69
22	35	47	60
26	30	40	51
34	23	31	39

Trek 7000 FXS

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color		
Fork	Hi-tensile steel	50mm travel, 454mm axle-crown length
Headset	Semi-cartridge, threaded	25.4/34.0/30.0, 36.0mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem	Steel	
Shift levers	Shimano EF-29	
Brake levers	Integrated brake/shift	
Grips	Bontrager	

DRIVETRAIN

Front derailleur . . .	Shimano C102	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano TX-50	
Crankset	SR XCC-100 48/38/28 w/chainguard	64/104mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 122.5 (shell x axle,mm), Square axle
Chain	KMC Z51	3/32", 114 links
Cassette	Sunrace 13-34, 7spd	

WHEELSET

Front wheel	Alloy, QR hub, 36°, Matrix 550 rim	622mm ERD
Spokes	14g, 295mm, 3x	
Tire	Bontrager Invert, 700 x 35c, Rubber rim strip	
Rear wheel	Alloy, QR hub, 36°, Matrix 550 rim	622mm ERD
Spokes	14g, 292/294mm, 3x	
Tire	Bontrager Invert, 700 x 35c, Rubber rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager	27.2mm outer diameter
Saddle	Bontrager Sport	
Seatpost binder . . .		31.8mm inner diameter
Brakes	Tektro direct pull w/modulator front, Tektro direct pull rear	
Pedals	Platform	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

	Size	15	17.5	20	22.5	25	15W	17W	20W	22.5W
Frame										
Rider height, in.		69.3	70.8	74.2	76.1	77.7	69.2	69.3	72.9	76.4
	cm	176	180	188	193	197	176	176	185	194
Handlebar	width	580	580	600	600	620	580	580	600	600
Handlebar	rise	30	30	30	30	30	30	30	30	30
Stem	length	90	105	120	120	135	90	90	105	120
	angle	25	25	25	25	25	25	25	25	25
Headset spacers		6	6	6	6	6	6	6	6	6
Crank	length	170	170	175	175	175	170	170	175	175
Seatpost	length	300	300	350	350	350	300	300	350	350
Steerer	length	130	145	145	165	185	145	165	185	205

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	70.5	71.5	72.5	72.5	70.5	70.5	71.5	72.5
Fork offset	43.0	43.0	43.0	43.0	43.0	43.0	43.0	43.0	43.0
Trail	71	71	65	58	58	71	71	65	58
Seat tube angle	74.5	74.0	73.5	73.0	72.0	74.5	74.0	73.5	73.0
Effective top tube	544	548	565	581	592	546	547	563	580
Seat tube	381	445	508	572	635	381	432	508	572
Standover	681	725	766	814	861	596	579	564	550
Wheelbase	1056	1056	1058	1059	1058	1057	1057	1057	1059
Bottom bracket height	283	283	283	283	283	283	283	283	283
Chainstay	445	445	445	445	445	445	445	445	445
Head tube	115	130	130	150	170	105	150	170	190

GEARING

	28	38	48
13	59	80	101
15	51	69	88
17	45	61	77
19	40	55	69
22	35	47	60
26	30	40	51
34	23	31	39

Trek 7000 FX

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color		
Fork	Hi-tensile steel, 412mm axle-crown length	
Headset	Semi-cartridge, threaded	25.4/34.0/30.0, 36.0mm stack height

CONTROLS

Handlebar	Steel	22.2mm clamp diameter
Stem	Steel	
Shift levers	Shimano EF-29	
Brake levers	Integrated brake/shift	
Grips	Bontrager	

DRIVETRAIN

Front derailleur . . .	Shimano C102	Top pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano TX-50	
Crankset	SR XCC-100 48/38/28 w/chainguard	64/104mm bolt hole circle
Bottom bracket . . .	Cartridge	73 x 122.5 (shell x axle,mm), Square axle
Chain	KMC Z51	3/32", 116 links
Cassette	Sunrace 13-34, 7spd	

WHEELSET

Front wheel	Alloy, QR hub, 36°, Matrix 550 rim	635mm ERD
Spokes	14g, 294.5mm, 3x	
Tire	Bontrager Invert, 700 x 35c, Rubber rim strip	
Rear wheel	Alloy, QR hub, 36°, Matrix 550 rim	635mm ERD
Spokes	14g, 292/293mm, 3x	
Tire	Bontrager Invert, 700 x 35c, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Bontrager	27.2mm outer diameter
Saddle	Bontrager Sport	
Seatpost binder . . .		31.8mm inner diameter
Brakes	Tektro direct pull w/modulator front, Tektro direct pull rear	
Pedals	Platform	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

	Size	15	17.5	20	22.5	25	15W	17W	20W	22.5W
Frame										
Rider height, in.		67.2	68.8	71.9	73.7	75.6	67.1	67.6	70.9	74.5
	cm	171	175	183	187	192	170	172	180	189
Handlebar	width	580	580	600	600	620	580	580	600	600
Handlebar	rise	30	30	30	30	30	30	30	30	30
Stem	length	90	105	120	120	135	90	90	105	120
	angle	25	25	25	25	25	25	25	25	25
Headset spacers		6	6	6	6	6	6	6	6	6
Crank	length	170	170	175	175	175	170	170	175	175
Seatpost	length	300	350	350	350	350	300	300	350	350
Steerer	length	154	169	169	189	209	169	189	209	229

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	70.5	71.5	72.5	72.5	70.5	70.5	71.5	72.5
Fork offset	50.0	50.0	50.0	50.0	50.0	50.0	50.0	50.0	50.0
Trail	71	71	65	58	58	71	71	65	58
Seat tube angle	74.5	74.0	73.5	73.0	72.0	74.5	74.0	73.5	73.0
Effective top tube	544	548	565	581	592	546	547	563	580
Seat tube	381	445	508	572	635	381	432	508	572
Standover	681	725	766	814	861	596	579	564	550
Wheelbase	1056	1056	1058	1059	1058	1057	1057	1057	1059
Bottom bracket height	283	283	283	283	283	283	283	283	283
Chainstay	445	445	445	445	445	445	445	445	445
Head tube	115	130	130	150	170	105	150	170	190

GEARING

	28	38	48
13	59	80	101
15	51	69	88
17	45	61	77
19	40	55	69
22	35	47	60
26	30	40	51
34	23	31	39

Trek C350 Low-step

1834631*15.084

FRAMESET

Main tubes		
Stays		
Color		
Fork	SR CR880W	50mm travel, 464mm axle-crown length
Headset	Steel	25.4/44.0/30.0, 35.0mm stack height

CONTROLS

Handlebar	Humpert City Liner	25.4mm clamp diameter
Stem	Bontrager Satellite Plus, adjustable rise	
Shift levers	Shimano Nexus Revo	
Brake levers	Alloy, direct pull	
Grips	Trek Ergo	

DRIVETRAIN

Crankset	Stronglight Twin-IC, 38T	mm bolt hole circle
Bottom bracket	Sealed	68 x 122.5 (shell x axle,mm), Square axle
Chain	SRAM PC10	1/8", 100 links
Cassette	Shimano 20T	

WHEELSET

Front wheel	Shimano NX-32, dynamo hub, 36°, Rigida ZAC-19R rim	606mm ERD
Spokes	DT 14G stainless, 285mm, 3x	
Tire	Bontrager Satellite Plus, reflective strip, 700 x 35c, rim strip	
Rear wheel	Shimano Nexus 7spd, coaster brake hub, 36°, Rigida ZAC-19R rim	mm ERD
Spokes	DT 14G stainless, 283mm, 3x	
Tire	Bontrager Satellite Plus, reflective strip, 700 x 35c, rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Suspension, alloy	31.6mm outer diameter
Saddle	Trek, womens	
Seatpost binder	Alloy w/integral bolt	36.4mm inner diameter
Brakes	Shimano M420, V type	
Pedals	Platform 9/16" axle	
Additional	seatpost shim, DeciBell II bell, Alloy kickstand, Massload, w/springclip rear rack, Spanninga Radius w/dynamo headlight, Spanninga taillight, Easy Clip fenders, Scoop chainguard, SKS Rookie pump,	

FIT *dimensions in mm, unless specified*

Frame	Size	45LL	50LL	55LL
Rider height, in.		70.1	71.0	71.9
	cm	178	180	183
Handlebar	width	590	590	590
Handlebar	rise	30	30	30
Stem	length	110	110	110
	angle	35	35	35
Headset spacers				
Crank	length			
Seatpost	length	350	350	350
Steerer	length	193.0	193.0	193.0

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	70.5	70.5
Fork offset	42.0	42.0	42.0
Trail	75	75	75
Seat tube angle	75.5	73.5	73.5
Effective top tube	529	561	571
Seat tube	450	500	550
Standover	459	452	
Wheelbase	1059	1070	1082
Bottom bracket height	291	291	291
Chainstay	450	450	450
Head tube	160	160	160

GEARING

38
20 52

Trek Rail 3

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color	Matte Smooth Silver (men's)	
	Pearl White (women's)	
Fork	Hi-tensile steel, Switchblade style, 396mm axle-crown length	
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 25.7mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem	Alloy direct connect	
Shift levers	Shimano Nexus Revo	
Grips	Dual density	

DRIVETRAIN

Crankset	Alloy 3-piece, 38T	65mm bolt hole circle
Bottom bracket	Cartridge	68 x 124.5 (shell x axle,mm), Square axle
Chain	Z410	1/8", 106 links
Cassette	20T	

WHEELSET

Front wheel	Alloy, nuttled hub, 36°, Alloy rim	573mm ERD
Spokes	14g stainless, 259mm, 3x	
Tire	Bontrager Hank, 26 x 2.2, Rubber rim strip	
Rear wheel	Shimano Nexus 3-speed hub, 36°, Alloy rim	573mm ERD
Spokes	14g stainless, 255/255mm, 3x	
Tire	Bontrager Hank, 26 x 2.2, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Alloy	27.2mm outer diameter
Saddle	Cruiser webspring	
Seatpost binder	Alloy w/integral bolt	31.8mm inner diameter
Brakes	no front, Shimano Nexus, coaster type rear	
Pedals	Platform, alloy 9/16" axle	
Additional	Alloy kickstand, Trek cruiser fenders, Trek cruiser chainguard,	

FIT *dimensions in mm, unless specified*

Frame	Size	19	17W
Rider height, in.		63.3	63.3
	cm	161	161
Handlebar	width	698	698
Handlebar	rise	132	132
Stem	length	80	80
	angle	25	25
Headset spacers		40	40
Crank	length	165	165
Seatpost	length	350	350
Steerer	length	219	219

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	69.5	69.5
Fork offset	58.0	58.0
Trail	63	63
Seat tube angle	72.8	72.8
Effective top tube	609	609
Seat tube	449	397
Standover	658	501
Wheelbase	1105	1080
Bottom bracket height	275	275
Chainstay	450	450
Head tube	130	130

GEARING

	38
20	50

Trek Rail 1

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color	Matte Black (men's)	
	Silver (women's)	
Fork.	Hi-tensile steel, 396mm axle-crown length	
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 25.7mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem	Alloy direct connect	
Grips	Dual density	

DRIVETRAIN

Crankset	Alloy 3-piece, 38T	65mm bolt hole circle
Bottom bracket	Cartridge	68 x 124.5 (shell x axle,mm), Square axle
Chain.	Z410	1/8", 106 links
Cassette.	18T	

WHEELSET

Front wheel.	Alloy, nuttled hub, 36°, Alloy rim	573mm ERD
Spokes	14g stainless, 259mm, 3x	
Tire	Bontrager Hank, 26 x 2.2, Rubber rim strip	
Rear wheel	Coaster brake, nuttled hub, 36°, Alloy rim	573mm ERD
Spokes	14g stainless, 255/255mm, 3x	
Tire	Bontrager Hank, 26 x 2.2, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost.	Alloy	27.2mm outer diameter
Saddle	Cruiser webspring	
Seatpost binder. . . .	Alloy w/integral bolt	31.8mm inner diameter
Brakes	no front, Coaster type rear	
Pedals	Platform, alloy 9/16" axle	
Additional	Alloy kickstand, Trek cruiser fenders, Trek cruiser chainguard,	

FIT *dimensions in mm, unless specified*

Frame	Size	19	17W
Rider height, in.		63.3	63.3
	cm	161	161
Handlebar	width	698	698
Handlebar	rise	132	132
Stem	length	80	80
	angle	25	25
Headset spacers		40	40
Crank	length	165	165
Seatpost	length	350	350
Steerer	length	219	219

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	69.5	69.5
Fork offset	58.0	58.0
Trail	63	63
Seat tube angle	72.8	72.8
Effective top tube	609	609
Seat tube	449	397
Standover	658	501
Wheelbase	1105	1080
Bottom bracket height	275	275
Chainstay	450	450
Head tube	130	130

GEARING

	38
18	55

Trek Town & Country

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color	Metallic Red/Wheat Silver	
	Metallic Blue/Metallic Silver	
Fork	Hi-tensile steel, 396mm axle-crown length	
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 36.5mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem	Alloy quill	
Shift levers	Shimano Nexus Revo	
Grips	Dual density	

DRIVETRAIN

Crankset	Alloy 3-piece, 38T	65mm bolt hole circle
Bottom bracket	Cartridge	68 x 127.5 (shell x axle,mm), Square axle
Chain	Z410	1/8", 96 links
Cassette	20T	

WHEELSET

Front wheel	Alloy, nuttled hub, 36°, Alloy rim	573mm ERD
Spokes	14g stainless, 264mm, 3x	
Tire	Bontrager Cruiser, 26 x 2.125, Rubber rim strip	
Rear wheel	Shimano Nexus 3-speed hub, 36°, Alloy rim	573mm ERD
Spokes	14g stainless, 257.5/256.5mm, 3x	
Tire	Bontrager Cruiser, 26 x 2.125, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Alloy	27.2mm outer diameter
Saddle	Cruiser webspring	
Seatpost binder	Alloy w/integral bolt	31.8mm inner diameter
Brakes	no front, Coaster type rear	
Pedals	Platform 9/16" axle	
Additional	Alloy kickstand, Trek cruiser fenders, Trek cruiser chainguard,	

FIT *dimensions in mm, unless specified*

Frame	Size	19	21	17W
Rider height, in.		62.7	65.3	62.7
	cm	159	166	159
Handlebar	width	698	698	698
Handlebar	rise	132	132	132
Stem	length	80	80	80
	angle	25	25	25
Headset spacers		6	6	6
Crank	length	165	165	165
Seatpost	length	350	350	350
Steerer	length	169	229	169

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	69.5	69.0	69.5
Fork offset	58.0	58.0	58.0
Trail	63	66	63
Seat tube angle	72.8	72.0	72.8
Effective top tube	609	632	609
Seat tube	449	533	397
Standover	658		501
Wheelbase	1105	1162	1080
Bottom bracket height	275	275	275
Chainstay	450	450	450
Head tube	130	190	130

GEARING

	38
20	50

Trek Calypso

FRAMESET

Main tubes	Hi-tensile steel	
Stays	Hi-tensile steel	
Color	Baja Blue/Metallic Silver or Black Chrome/Wheat Silver (men and women's)	
	Deep Green (men's)	
	Soft Yellow (women's)	
Fork	Hi-tensile steel, 396mm axle-crown length	
Headset	Semi-cartridge, threaded	25.4/34.0/30.0, 36.5mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem	Alloy quill	
Shift levers	SRAM MRX Plus, right only	
Brake levers	Alloy, direct pull	
Grips	Dual density	

DRIVETRAIN

Rear derailleur	Shimano TX-50	
Crankset	Alloy 3-piece, 38T	65mm bolt hole circle
Bottom bracket	Cartridge	73 x 122.5 (shell x axle,mm), Square axle
Chain	KMC Z51	3/32", 116 links
Cassette	Shimano MF-37 13-34, 7spd	

WHEELSET

Front wheel	Alloy, nuttled hub, 36°, Alloy rim	573mm ERD
Spokes	14g stainless, 264mm, 3x	
Tire	Bontrager Cruiser, 26 x 2.125, Rubber rim strip	
Rear wheel	Alloy, nuttled hub, 36°, Alloy rim	573mm ERD
Spokes	14g stainless, 260/260mm, 3x	
Tire	Bontrager Cruiser, 26 x 2.125, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Alloy	27.2mm outer diameter
Saddle	Cruiser webspring	
Seatpost binder	Alloy w/integral bolt	31.8mm inner diameter
Brakes	Alloy direct pull w/modulator front, Alloy direct pull rear	
Pedals	Platform 9/16" axle	
Additional	Alloy kickstand, Trek cruiser fenders, Trek cruiser chainguard,	

FIT *dimensions in mm, unless specified*

Frame	Size	19	17W
Rider height, in.		63.0	62.9
	cm	160	160
Handlebar	width	698	698
Handlebar	rise	132	132
Stem	length	80	80
	angle	25	25
Headset spacers		6	6
Crank	length	165	165
Seatpost	length	350	350
Steerer	length	169	169

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	69.5	69.5
Fork offset	58.0	58.0
Trail	63	63
Seat tube angle	72.8	72.8
Effective top tube	609	609
Seat tube	449	397
Standover	658	501
Wheelbase	1105	1080
Bottom bracket height	275	275
Chainstay	450	450
Head tube	130	130

GEARING

	38
13	77
15	66
17	59
19	52
22	45
26	38
34	29

Trek Bonnie/Clyde

FRAMESET

Main tubes	Hi-tensile steel	
Stays	Hi-tensile steel	
Color	Matte Metallic Pink (Bonnie)	
	Matte Silver (Clyde)	
Fork	Trek Springer, 376mm axle-crown length	
Headset	Semi-cartridge, threaded	25.4/34.0/30.0, 36.5mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem	Alloy quill	
Shift levers	Shimano Nexus Revo	
Grips	Dual density	

DRIVETRAIN

Crankset	Alloy 3-piece, 38T	65mm bolt hole circle
Bottom bracket	Cartridge	73 x 122.5 (shell x axle,mm), Square axle
Chain	Z410	1/8", 98 links
Cassette	20T	

WHEELSET

Front wheel	Alloy, nuttled hub, 36°, Alloy rim	573mm ERD
Spokes	14g stainless, 264mm, 3x	
Tire	Bontrager Cruiser, 26 x 2.125, Rubber rim strip	
Rear wheel	Shimano Nexus 7speed hub, 36°, Alloy rim	573mm ERD
Spokes	14g stainless, 260/260mm, 3x	
Tire	Bontrager Cruiser, 26 x 2.125, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Alloy	27.2mm outer diameter
Saddle	Cruiser webspring	
Seatpost binder	Alloy w/integral bolt	31.8mm inner diameter
Brakes	no front, Shimano Nexus, coaster type rear	
Pedals	Platform 9/16" axle	
Additional	Alloy kickstand, Trek cruiser fenders, Trek cruiser chainguard,	

FIT *dimensions in mm, unless specified*

Frame	Size	19	17W
Rider height, in.		64.0	64.0
	cm	163	163
Handlebar	width	698	698
Handlebar	rise	132	132
Stem	length	100	100
	angle	25	25
Headset spacers		6	6
Crank	length	165	165
Seatpost	length	350	350
Steerer	length	176	169

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	69.5	69.5
Fork offset	58.0	58.0
Trail	63	63
Seat tube angle	72.8	72.8
Effective top tube	609	609
Seat tube	449	397
Standover	658	501
Wheelbase	1105	1080
Bottom bracket height	275	275
Chainstay	450	450
Head tube	130	130

GEARING

	32
20	42

Trek Cruiser Classic

FRAMESET

Main tubes	Hi-tensile steel	
Stays	Hi-tensile steel	
Color	Metallic Black or Matte Silver (men's) Candy Purple or Misty Blue (women's)	
Fork.	Hi-tensile steel, 396mm axle-crown length	
Headset	Semi-cartridge, threaded	25.4/34.0/30.0, 36.5mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem	Alloy quill	
Grips	Dual density	

DRIVETRAIN

Crankset	Alloy 3-piece, 38T	65mm bolt hole circle
Bottom bracket	Cartridge	68 x 127.5 (shell x axle,mm), Square axle
Chain.	Z410	1/8", 98 links
Cassette.	18T	

WHEELSET

Front wheel.	Alloy, nuttled hub, 36°, Alloy rim	573mm ERD
Spokes	14g stainless, 264mm, 3x	
Tire	Bontrager Cruiser, 26 x 2.125, Rubber rim strip	
Rear wheel	Coaster brake, nuttled hub, 36°, Alloy rim	573mm ERD
Spokes	14g stainless, 260/260mm, 3x	
Tire	Bontrager Cruiser, 26 x 2.125, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost.	Alloy	27.2mm outer diameter
Saddle	Cruiser webspring	
Seatpost binder. . . .	Alloy w/integral bolt	31.8mm inner diameter
Brakes	no front, Coaster type rear	
Pedals	Platform 9/16" axle	
Additional	Alloy kickstand, Trek cruiser fenders, Trek cruiser chainguard,	

FIT *dimensions in mm, unless specified*

Frame	Size	19	21	17W
Rider height, in.		62.7	65.3	62.7
	cm	159	166	159
Handlebar	width	698	698	698
Handlebar	rise	132	132	132
Stem	length	80	80	80
	angle	25	25	25
Headset spacers		6	6	6
Crank	length	165	165	165
Seatpost	length	350	350	350
Steerer	length	169	229	169

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	69.5	69.0	69.5
Fork offset	58.0	58.0	58.0
Trail	63		63
Seat tube angle	72.8	72.0	72.8
Effective top tube	609	632	609
Seat tube	449	533	397
Standover	658		501
Wheelbase	1105	1162	1080
Bottom bracket height	275	275	275
Chainstay	450	450	450
Head tube	130	190	130

GEARING

38
18 55

Trek Cruiser Classic Steel

FRAMESET

Main tubes	Hi-tensile steel	
Stays	Hi-tensile steel	
Color	Metallic Black or Matte Silver (men's)	
	Candy Purple or Misty Blue (women's)	
Fork	Hi-tensile steel, 396mm axle-crown length	
Headset	Semi-cartridge, threaded	25.4/34.0/30.0, 36.5mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem	Alloy quill	
Grips	Dual density	

DRIVETRAIN

Crankset	Alloy 3-piece, 38T	65mm bolt hole circle
Bottom bracket	Cartridge	73 x 122.5 (shell x axle,mm), Square axle
Chain	Z410	1/8", 98 links
Cassette	18T	

WHEELSET

Front wheel	Alloy, nuttled hub, 36°, Alloy rim	573mm ERD
Spokes	14g stainless, 264mm, 3x	
Tire	Bontrager Cruiser, 26 x 2.125, Rubber rim strip	
Rear wheel	Coaster brake, nuttled hub, 36°, Alloy rim	573mm ERD
Spokes	14g stainless, 260/260mm, 3x	
Tire	Bontrager Cruiser, 26 x 2.125, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Alloy	27.2mm outer diameter
Saddle	Cruiser webspring	
Seatpost binder	Alloy w/integral bolt	31.8mm inner diameter
Brakes	no front, Coaster type rear	
Pedals	Platform 9/16" axle	
Additional	Alloy kickstand, Trek chainguard,	

FIT *dimensions in mm, unless specified*

Frame	Size	19	17W
Rider height, in.		63.0	62.9
	cm	160	160
Handlebar	width	698	698
Handlebar	rise	132	132
Stem	length	80	80
	angle	25	25
Headset spacers		6	6
Crank	length	165	165
Seatpost	length	350	350
Steerer	length	169	169

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	69.5	69.5
Fork offset	58.0	58.0
Trail	63	63
Seat tube angle	72.8	72.8
Effective top tube	609	609
Seat tube	449	397
Standover	658	501
Wheelbase	1105	1080
Bottom bracket height	275	275
Chainstay	450	450
Head tube	130	130

GEARING

	38
18	55

Trek Madone SSL

1477?
Bike weight: 15.3 lb/6.95 kg

FRAMESET

Main tubes	OCV 55 Carbon superlight	
Stays	OCV 55 Carbon superlight	
Color	Gloss Black/Blue Pearl Carbon	
Fork	Bontrager Race XXX Lite, 379mm axle-crown length	
Headset	Cane Creek S-6 Aheadset, alloy	25.4/34.0/30.0, mm stack height

CONTROLS

Handlebar	Bontrager Race X Lite	31.8mm clamp diameter
Stem	Bontrager Race XXX Lite	
Shift levers	Shimano Dura-Ace STI	
Brake levers	Integrated brake/shift	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano Dura-Ace	Down pull, Braze-on type attachment
Rear derailleur . . .	Shimano Dura-Ace	
Crankset	Shimano Dura-Ace 53/39	130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain		10 speed, links
Cassette	Shimano Dura-Ace 12-25, 10spd	

WHEELSET

Front wheel	Bontrager Race XXX Lite, 20°	592mm ERD
Spokes	DT Aerolite, ProLock alloy nipples, 286mm, radial	
Tire	Bontrager Pro, folding, 700 x 23c, Velox 16mm rim strip	
Rear wheel	Bontrager Race XXX Lite, 24°	595mm ERD
Spokes	DT Aerolite (New Aero rear drive), ProLock alloy nipples, 291/286mm, 2x/radial	
Tire	Bontrager Pro, folding, 700 x 23c, Velox 16mm rim strip	
Inner tubes		

OTHER

Seatpost	Bontrager Race X Lite	27.2mm outer diameter
Saddle	Bontrager Race XXX Lite	
Seatpost binder . . .	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano Dura-Ace, pads for carbon rim	
Pedals	-not supplied- 9/16" axle	
Additional		

FIT dimensions in mm, unless specified

Frame	Size	50	52	54	56	58	60	62
Rider height, in.		58.1	58.5	58.9	60.2	61.2	62.3	63.2
	cm	148	149	150	153	155	158	160
Handlebar	width							
Stem	length							
	angle							
Headset spacers								
Crank	length							
Seatpost	length							
Steerer	length	99	99	102	119	137.5	156.5	175

GEOMETRY dimensions in mm, unless specified

Head tube angle	72.1	72.5	73.0	73.8	73.7	74.0	73.9
Fork offset	41.0	41.0	41.0	41.0	41.0	41.0	41.0
Trail							
Seat tube angle	75.1	75.0	74.0	73.5	73.0	72.9	72.5
Effective top tube	526	531	546	561	572	582	592
Seat tube	500	520	540	560	580	600	620
Standover	740	755	770	790	808	827	844
Wheelbase	979	980	984	984	991	998	1003
Bottom bracket height	266	266	266	269	268	268	268
Chainstay	408	408	410	410	412	412	412
Head tube	101	101	104	121	140	159	177

GEARING

	39 53
12	86 117
13	79 108
14	74 100
15	69 93
16	64 88
17	61 82
19	54 74
21	49 67
23	45 61 0
25	41 56 0

Trek Madone 5.9 LTD

1479000*15.124
Bike weight: 15.4 lb/6.99 kg

FRAMESET

Main tubes	OCV 110 carbon fiber composite
Stays	OCV 110, carbon fiber composite
Color	Pearl white/ Baja blue (Team) Trek red/ Black pearl carbon
Fork	Bontrager Race XXX Lite, 379mm axle-crown length
Headset	Cane Creek S-6 Aheadset, alloy 25.4/34.0/30.0, 27.1mm stack height

CONTROLS

Handlebar	Bontrager Race X Lite	31.8mm clamp diameter
Stem	Bontrager Race XXX Lite	40.0mm steerer clamp height
Shift levers	Shimano Dura-Ace STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano Dura-Ace	Down pull, Braze-on type attachment
Rear derailleur	Shimano Dura-Ace	
Crankset	Bontrager Race Lite 53/39 w/Giga-X-Pipe	130mm bolt hole circle
Bottom bracket	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano Dura-Ace	10 speed, 108 links
Cassette	Shimano Dura-Ace 12-25, 10spd	

WHEELSET

Front wheel	Bontrager Race XXX Lite, 20°	592mm ERD
Spokes	DT Aerolite nail-head, internal alloy nipples, 286mm, radial	
Tire	Bontrager Race X Lite Pro, folding, 700 x 23c, Velox 16mm rim strip	
Rear wheel	Bontrager Race XXX Lite, 20°	592mm ERD
Spokes	DT New Aero, Aerolite nail-head non-drive side, internal alloy nipples, 291/286mm, 2x/radial	
Tire	Bontrager Race X Lite Pro, folding, 700 x 23c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race XXX Lite	27.2mm outer diameter
Saddle	Bontrager Race X Lite Pro	
Seatpost binder	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano Dura-Ace, pads for carbon rim	
Pedals	-not supplied- 9/16" axle	
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	50	52	54	56	58	60	62
Rider height, in.		67.2	68.9	70.2	71.6	73.0	75.1	76.8
	cm	171	175	178	182	185	191	195
Handlebar	width	380	400	400	420	420	440	440
Stem	length	80	90	100	100	110	120	130
	angle	12	12	12	12	12	12	12
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	170	172.5	172.5	175	175	175
Seatpost	length	250	250	250	250	250	250	250
Steerer	length	204.1	204.1	207.1	227.5	242.6	261.6	280.1

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.1	72.5	73.0	73.8	73.7	74.0	73.9
Fork offset	45.0	45.0	45.0	40.0	40.0	40.0	40.0
Trail							
Seat tube angle	75.1	75.0	74.0	73.5	73.0	72.9	72.5
Effective top tube	526	531	546	561	572	582	592
Seat tube	500	520	540	560	580	600	620
Standover	740	755	770	790	808	827	844
Wheelbase	979	980	984	984	991	998	1003
Bottom bracket height	266	266	266	269	268	268	268
Chainstay	408	408	410	410	412	412	412
Head tube	101	101	104	121	140	159	177

GEARING

	39 53
12	86 117
13	79 108
14	74 100
15	69 93
16	64 88
17	61 82
19	54 74
21	49 67
23	45 61 0
25	41 56 0

Trek Madone 5.9

1472000*15.074
Bike weight: 16.4 lb/7.45 kg

FRAMESET

Main tubes	OCV 110 carbon fiber composite
Stays	OCV 110, carbon fiber composite
Color	Pearl white/ Baja blue (Team) Trek red/ Black pearl carbon
Fork	Bontrager Race XXX Lite, 379mm axle-crown length
Headset	Cane Creek S-2 Aheadset, alloy 25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Race X Lite	31.8mm clamp diameter
Stem	Bontrager Race XXX Lite	40.0mm steerer clamp height
Shift levers	Shimano Dura-Ace STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano Dura-Ace	Down pull, Braze-on type attachment
Rear derailleur	Shimano Dura-Ace	
Crankset	Shimano Dura-Ace 53/39	130mm bolt hole circle
Bottom bracket	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano Dura-Ace	10 speed, 108 links
Cassette	Shimano Dura-Ace 12-25, 10spd	

WHEELSET

Front wheel	Bontrager Race X Lite Aero, 16"	582mm ERD
Spokes	DT New Aero, internal alloy nipples, 281mm, radial	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Bontrager, 17.5mm rim strip	
Rear wheel	Bontrager Race X Lite Aero, 16"	582mm ERD
Spokes	DT New Aero, internal alloy nipples, 288/288mm, 2x	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Bontrager, 17.5mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race XXX Lite	27.2mm outer diameter
Saddle	Bontrager Race X Lite Pro	
Seatpost binder	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano Dura-Ace	
Pedals	-not supplied- 9/16" axle	
Additional		

FIT

dimensions in mm, unless specified

Frame	Size	50	52	54	56	58	60	62
Rider height, in.		67.2	68.9	70.2	71.5	72.9	75.0	76.7
	cm	171	175	178	182	185	191	195
Handlebar	width	380	400	400	420	420	440	440
Stem	length	80	90	100	100	110	120	130
	angle	12	12	12	12	12	12	12
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	170	172.5	172.5	175	175	175
Seatpost	length	250	250	250	250	250	250	250
Steerer	length	203.5	203.5	206.5	223.5	242	261	279.5

GEOMETRY

dimensions in mm, unless specified

Head tube angle	72.1	72.5	73.0	73.8	73.7	74.0	73.9
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail							
Seat tube angle	75.1	75.0	74.0	73.5	73.0	72.9	72.5
Effective top tube	526	531	546	561	572	582	592
Seat tube	500	520	540	560	580	600	620
Standover	740	755	770	790	808	827	844
Wheelbase	979	980	984	984	991	998	1003
Bottom bracket height	266	266	266	269	268	268	268
Chainstay	408	408	410	410	412	412	412
Head tube	101	101	104	121	140	159	177

GEARING

39 53

12	86 117
13	79 108
14	74 100
15	69 93
16	64 88
17	61 82
19	54 74
21	49 67
23	45 61 0
25	41 56 0

Trek Madone SL 5.9 Compact

1475000*15.114
Bike weight: 15.7 lb/7.13 kg

FRAMESET

Main tubes	OCV 110 carbon fiber composite
Stays	OCV 110, carbon fiber composite
Color	Pearl white/ Satin silver (Team)
	Andromeda
Fork	Bontrager Race XXX Lite, 379mm axle-crown length
Headset	Cane Creek S-6 Aheadset, alloy 25.4/34.0/30.0, 27.1mm stack height

CONTROLS

Handlebar	Bontrager Race X Lite	31.8mm clamp diameter
Stem	Bontrager Race XXX Lite	40.0mm steerer clamp height
Shift levers	Shimano Dura-Ace STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano Dura-Ace	Down pull, Braze-on type attachment
Rear derailleur	Shimano Dura-Ace	
Crankset	Bontrager Race X Lite 50/36 w/Giga-X-Pipe	64/104mm bolt hole circle
Bottom bracket	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano Dura-Ace	10 speed, 108 links
Cassette	Shimano Dura-Ace 12-27, 10spd	

WHEELSET

Front wheel	Bontrager Race X Lite, 20°	592mm ERD
Spokes	DT Aerolite nail-head, internal alloy nipples, 286mm, radial	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Bontrager, 17.5mm rim strip	
Rear wheel	Bontrager Race X Lite, 24°	595mm ERD
Spokes	DT New Aero, Aerolite nail-head non-drive side, internal alloy nipples, 291/286mm, 2x/radial	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Bontrager, 17.5mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race XXX Lite	27.2mm outer diameter
Saddle	Bontrager Race X Lite Pro	
Seatpost binder	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano Dura-Ace	
Pedals	-not supplied- 9/16" axle	
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	50	52	54	56	58	60	62
Rider height, in.		67.3	68.9	70.3	71.6	73.0	75.1	76.8
	cm	171	175	179	182	185	191	195
Handlebar	width	380	400	400	420	420	440	440
Stem	length	80	90	100	100	110	120	130
	angle	12	12	12	12	12	12	12
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	170	172.5	172.5	175	175	175
Seatpost	length	250	250	250	250	250	250	250
Steerer	length	204.1	204.1	207.1	227.1	242.6	261.6	280.1

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.1	72.5	73.0	73.8	73.7	74.0	73.9
Fork offset	41.0	41.0	41.0	41.0	41.0	41.0	41.0
Trail							
Seat tube angle	75.1	75.0	74.0	73.5	73.0	72.9	72.5
Effective top tube	526	531	546	561	572	582	592
Seat tube	500	520	540	560	580	600	620
Standover	740	755	770	790	808	827	844
Wheelbase	979	980	984	984	991	998	1003
Bottom bracket height	266	266	266	269	268	268	268
Chainstay	408	408	410	410	412	412	412
Head tube	101	101	104	121	140	159	177

GEARING

	36 50
12	79 110
13	73 102
14	68 94
15	63 88
16	60 83
17	56 78
19	50 70
21	45 63
23	41 58 0
25	38 53 0

Trek Madone 5.9 Compact

1473000*15.074
Bike weight: 18.7 lb/8.49 kg

FRAMESET

Main tubes	OCV 110 carbon fiber composite
Stays	OCV 110, carbon fiber composite
Color	Pearl white/ Baja blue (Team)
	Trek red/ Black pearl carbon
Fork	Bontrager Race XXX Lite, 379mm axle-crown length
Headset	Cane Creek S-2 Aheadset, alloy 25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Race X Lite	31.8mm clamp diameter
Stem	Bontrager Race XXX Lite	40.0mm steerer clamp height
Shift levers	Shimano Dura-Ace STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano Dura-Ace	Down pull, Braze-on type attachment
Rear derailleur	Shimano Dura-Ace	
Crankset	Bontrager Race X Lite 50/36 w/Giga-X-Pipe	64/104mm bolt hole circle
Bottom bracket	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano Dura-Ace	10 speed, 108 links
Cassette	Shimano Dura-Ace 12-27, 10spd	

WHEELSET

Front wheel	Bontrager Race X Lite Aero, 16°	582mm ERD
Spokes	DT New Aero, internal alloy nipples, 281mm, radial	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Bontrager, 17.5mm rim strip	
Rear wheel	Bontrager Race X Lite Aero, 16°	582mm ERD
Spokes	DT New Aero, internal alloy nipples, 288/288mm, 2x	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Bontrager, 17.5mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race XXX Lite	27.2mm outer diameter
Saddle	Bontrager Race X Lite Pro	
Seatpost binder	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano Dura-Ace	
Pedals	-not supplied- 9/16" axle	
Additional	PN 253438 Compact drive derailleur hanger	

FIT *dimensions in mm, unless specified*

Frame	Size	50	52	54	56	58	60	62
Rider height, in.		67.2	68.9	70.2	71.5	72.9	75.0	76.7
	cm	171	175	178	182	185	191	195
Handlebar	width	380	400	400	420	420	440	440
Stem	length	80	90	100	100	110	120	130
	angle	12	12	12	12	12	12	12
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	170	172.5	172.5	175	175	175
Seatpost	length	250	250	250	250	250	250	250
Steerer	length	203.5	203.5	206.5	223.5	242	261	279.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.1	72.5	73.0	73.8	73.7	74.0	73.9
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail							
Seat tube angle	75.1	75.0	74.0	73.5	73.0	72.9	72.5
Effective top tube	526	531	546	561	572	582	592
Seat tube	500	520	540	560	580	600	620
Standover	740	755	770	790	808	827	844
Wheelbase	979	980	984	984	991	998	1003
Bottom bracket height	266	266	266	269	268	268	268
Chainstay	408	408	410	410	412	412	412
Head tube	101	101	104	121	140	159	177

GEARING

	36	50
12	79	110
13	73	102
14	68	94
15	63	88
16	60	83
17	56	78
19	50	70
21	45	63
23	41	58 0
25	38	53 0

Trek Madone SL 5.2 T

1467000*15.104

FRAMESET

Main tubes	OCLEV 120 carbon fiber composite
Stays	OCLEV 120 carbon fiber composite
Color	Pearl white/ Satin silver (Team)
	Platinum silver/ Black pearl carbon
Fork	Bontrager Race XXX Lite, 379mm axle-crown length
Headset	Cane Creek S-2 Aheadset, alloy 25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Race Lite	31.8mm clamp diameter
Stem	Bontrager Race Lite	40.0mm steerer clamp height
Shift levers	Shimano Ultegra STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano Ultegra T	Down pull, Braze-on type attachment
Rear derailleur	Shimano Ultegra GS	
Crankset	Shimano Ultegra 52/39/30	74/130mm bolt hole circle
Bottom bracket	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano Ultegra	10 speed, 108 links
Cassette	Shimano Ultegra 12-25, 10spd	

WHEELSET

Front wheel	Bontrager Race Lite, 20°	592mm ERD
Spokes	DT New Aero, ProLock alloy nipples, 279mm, radial	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Velox 16mm rim strip	
Rear wheel	Bontrager Race Lite, 24°	595mm ERD
Spokes	DT New Aero, T-head drive side, ProLock alloy nipples, 291/293mm, 2x	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race X Lite	27.2mm outer diameter
Saddle	Bontrager Race Lite Luxe	
Seatpost binder	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano Ultegra	
Pedals	-not supplied- 9/16" axle	
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	50	52	54	56	58	60	62
Rider height, in.		67.5	68.8	70.4	71.4	73.1	75.3	76.6
	cm	172	175	179	181	186	191	195
Handlebar	width	380	400	400	420	420	440	440
Stem	length	80	90	100	100	110	120	130
	angle	7	7	7	7	7	7	7
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	170	172.5	172.5	175	175	175
Seatpost	length	250	250	250	250	250	250	250
Steerer	length	203.5	203.5	206.5	226.5	242.0	261.0	279.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.1	72.5	73.0	73.8	73.7	74.0	73.9
Fork offset	41.0	41.0	41.0	41.0	41.0	41.0	41.0
Trail							
Seat tube angle	75.1	75.0	74.0	73.5	73.0	72.9	72.5
Effective top tube	526	531	546	561	572	582	592
Seat tube	500	520	540	560	580	600	620
Standover	740	755	770	790	808	827	844
Wheelbase	979	980	984	984	991	998	1003
Bottom bracket height	266	266	266	269	268	268	268
Chainstay	408	408	410	410	412	412	412
Head tube	101	101	104	121	140	159	177

GEARING

	30	39	52
12	66	86	115
13	61	79	106
14	57	74	98
15	53	69	92
16	50	64	86
17	47	61	81
19	42	54	72
21	38	49	66
23	35	45	60
25	32	41	55

Trek Madone SL 5.2 T

1467000*15.104

FRAMESET

Main tubes	OCV 120 carbon fiber composite	
Stays	OCV 120 carbon fiber composite	
Color	Pearl white/ Satin silver (Team)	
	Platinum silver/ Black pearl carbon	
Fork.	Bontrager Race XXX Lite, 379mm axle-crown length	
Headset	Cane Creek S-2 Aheadset, alloy	25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Race Lite	31.8mm clamp diameter
Stem	Bontrager Race Lite	40.0mm steerer clamp height
Shift levers	Shimano Ultegra STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano Ultegra T	Down pull, Braze-on type attachment
Rear derailleur . . .	Shimano Ultegra GS	
Crankset	Shimano Ultegra 52/39/30	74/130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain.	Shimano Ultegra	10 speed, 108 links
Cassette.	Shimano Ultegra 12-25, 10spd	

WHEELSET

Front wheel.	Bontrager Race Lite, 20°	592mm ERD
Spokes	DT New Aero, ProLock alloy nipples, 279mm, radial	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Velox 16mm rim strip	
Rear wheel	Bontrager Race Lite, 24°	595mm ERD
Spokes	DT New Aero, T-head drive side, ProLock alloy nipples, 291/293mm, 2x	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost.	Bontrager Race X Lite	27.2mm outer diameter
Saddle	Bontrager Race Lite Luxe	
Seatpost binder. . .	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano Ultegra	
Pedals	-not supplied- 9/16" axle	
Additional		

FIT

dimensions in mm, unless specified

Frame	Size	50	52	54	56	58	60	62
Rider height, in.		67.5	68.8	70.4	71.4	73.1	75.3	76.6
	cm	172	175	179	181	186	191	195
Handlebar	width	380	400	400	420	420	440	440
Stem	length	80	90	100	100	110	120	130
	angle	7	7	7	7	7	7	7
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	170	172.5	172.5	175	175	175
Seatpost	length	250	250	250	250	250	250	250
Steerer	length	203.5	203.5	206.5	226.5	242.0	261.0	279.5

GEOMETRY

dimensions in mm, unless specified

Head tube angle	72.1	72.5	73.0	73.8	73.7	74.0	73.9
Fork offset	41.0	41.0	41.0	41.0	41.0	41.0	41.0
Trail							
Seat tube angle	75.1	75.0	74.0	73.5	73.0	72.9	72.5
Effective top tube	526	531	546	561	572	582	592
Seat tube	500	520	540	560	580	600	620
Standover	740	755	770	790	808	827	844
Wheelbase	979	980	984	984	991	998	1003
Bottom bracket height	266	266	266	269	268	268	268
Chainstay	408	408	410	410	412	412	412
Head tube	101	101	104	121	140	159	177

GEARING

	30	39	52
12	66	86	115
13	61	79	106
14	57	74	98
15	53	69	92
16	50	64	86
17	47	61	81
19	42	54	72
21	38	49	66
23	35	45	60
25	32	41	55

Trek

Madone SL 5.2

1466000*15.104
Bike weight: 17.4 lb/7.90 kg

FRAMESET

Main tubes	OCLV 120 carbon fiber composite	
Stays	OCLV 120 carbon fiber composite	
Color	Pearl white/ Satin silver (Team)	
	Platinum silver/ Black pearl carbon	
Fork	Bontrager Race XXX Lite, 379mm axle-crown length	
Headset	Cane Creek S-2 Aheadset, alloy	25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Race Lite	31.8mm clamp diameter
Stem	Bontrager Race Lite	40.0mm steerer clamp height
Shift levers	Shimano Ultegra STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano Ultegra	Down pull, Braze-on type attachment
Rear derailleur . . .	Shimano Ultegra	
Crankset	Shimano Ultegra 53/39	130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano Ultegra	10 speed, 108 links
Cassette	Shimano Ultegra 12-25, 10spd	

WHEELSET

Front wheel	Bontrager Race Lite, 20°	592mm ERD
Spokes	DT New Aero, ProLock alloy nipples, 279mm, radial	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Velox 16mm rim strip	
Rear wheel	Bontrager Race Lite, 24°	595mm ERD
Spokes	DT New Aero, T-head drive side, ProLock alloy nipples, 291/293mm, 2x	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race X Lite	27.2mm outer diameter
Saddle	Bontrager Race Lite Luxe	
Seatpost binder . . .	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano Ultegra	
Pedals	-not supplied- 9/16" axle	
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	50	52	54	56	58	60	62
Rider height, in.		67.5	68.8	70.4	71.4	73.1	75.3	76.6
	cm	172	175	179	181	186	191	195
Handlebar	width	380	400	400	420	420	440	440
Stem	length	80	90	100	100	110	120	130
	angle	7	7	7	7	7	7	7
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	170	172.5	172.5	175	175	175
Seatpost	length	250	250	250	250	250	250	250
Steerer	length	203.5	203.5	206.5	226.5	242.0	261.0	279.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.1	72.5	73.0	73.8	73.7	74.0	73.9
Fork offset	41.0	41.0	41.0	41.0	41.0	41.0	41.0
Trail							
Seat tube angle	75.1	75.0	74.0	73.5	73.0	72.9	72.5
Effective top tube	526	531	546	561	572	582	592
Seat tube	500	520	540	560	580	600	620
Standover	740	755	770	790	808	827	844
Wheelbase	979	980	984	984	991	998	1003
Bottom bracket height	266	266	266	269	268	268	268
Chainstay	408	408	410	410	412	412	412
Head tube	101	101	104	121	140	159	177

GEARING

	39	53
12	86	117
13	79	108
14	74	100
15	69	93
16	64	88
17	61	82
19	54	74
21	49	67
23	45	61 0
25	41	56 0

Trek Madone 5.2 SL WSD T

1467003*15.104

FRAMESET

Main tubes	OCV 120 carbon fiber composite
Stays	OCV 120 carbon fiber composite
Color	Platinum Silver/Midnight Blue
Fork	Bontrager Race XXX Lite, OCLV 110 carbon, 378mm axle-crown length
Headset	Cane Creek S-2 Aheadset, alloy 25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Race	26.0mm clamp diameter
Stem	Bontrager Race	40.0mm steerer clamp height
Shift levers	Shimano Ultegra STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano Ultegra T	Down pull, Braze-on type attachment
Rear derailleur	Shimano Ultegra GS	
Crankset	Shimano Ultegra 52/39/30	74/130mm bolt hole circle
Bottom bracket	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano Ultegra	10 speed, 108 links
Cassette	Shimano Ultegra 12-25, 10spd	

WHEELSET

Front wheel	Bontrager Race Lite, 20°	592mm ERD
Spokes	DT New Aero, ProLock alloy nipples, 279mm, radial	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Velox 16mm rim strip	
Rear wheel	Bontrager Race Lite, 24°	595mm ERD
Spokes	DT New Aero, T-head drive side, ProLock alloy nipples, 291/293mm, 2x	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race X Lite	27.2mm outer diameter
Saddle	Bontrager Race Lite WSD	
Seatpost binder	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano Ultegra	
Pedals	-not supplied-	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	47	51	53	56
Rider height, in.		65.4	67.9	67.9	0.0
	cm	166	172	172	0
Handlebar	width	380	380	380	380
Stem	length	80	100	100	90
	angle	7	7	7	7
Headset spacers		40	40	40	40
Crank	length	165	170	170	170
Seatpost	length	250	250	250	250
Steerer	length	203.5	203.5	206.5	226.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	72.0	72.2	
Fork offset	45.0	45.0	45.0	45.0
Trail	68	62	61	
Seat tube angle	74.7	74.9	73.7	
Effective top tube	505	515	528	
Seat tube	470	510	540	
Standover	719	747	769	
Wheelbase	965	968	971	
Bottom bracket height	269	266	268	
Chainstay	408	410	410	
Head tube	115	110	109	

GEARING

	30	39	52
12	66	86	115
13	61	79	106
14	57	74	98
15	53	69	92
16	50	64	86
17	47	61	81
19	42	54	72
21	38	49	65
23	35	45	60
25	32	41	55

Trek

Madone 5.2 T

1465000*15.054
Bike weight: 19.3 lb/8.76 kg

FRAMESET

Main tubes	OCV 120 carbon fiber composite	
Stays	OCV 120, carbon fiber composite	
Color	Satin Silver	
Fork	Bontrager Race Lite, 370.0mm axle-crown length	
Headset	Cane Creek S-2 Aheadset, alloy	25.4/34.0/30.0, 26.5mm stack height

CONTROLS

Handlebar	Bontrager Race Lite	31.8mm clamp diameter
Stem	Bontrager Race Lite	40.0mm steerer clamp height
Shift levers	Shimano Ultegra STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano Ultegra T	Down pull, Braze-on type attachment
Rear derailleur . . .	Shimano Ultegra GS	
Crankset	Shimano Ultegra 52/42/30	74/130mm bolt hole circle
Bottom bracket . . .	Shimano Ultegra	68 x 118 (shell x axle,mm), Shimano splined axle
Chain	Shimano HG-73	9 speed, 108 links
Cassette	Shimano Ultegra 12-25, 9spd	

WHEELSET

Front wheel	Bontrager Race X Lite, 20°	592mm ERD
Spokes	DT Aerolite nail-head, internal alloy nipples, 286mm, radial	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Bontrager, 17.5mm rim strip	
Rear wheel	Bontrager Race X Lite, 24°	595mm ERD
Spokes	DT New Aero, Aerolite nail-head non-drive side, internal alloy nipples, 291/286mm, 2x/radial	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Bontrager, 17.5mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race X Lite	27.2mm outer diameter
Saddle	Bontrager Race Lite Luxe, Ti rails	
Seatpost binder . . .	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano Ultegra	
Pedals	-not supplied- 9/16" axle	
Additional	2 water bottle mounts	

FIT *dimensions in mm, unless specified*

Frame Size	50	52	54	56	58	60	62
Rider height, in.	66.7	68.2	69.6	71.1	72.6	74.8	76.5
cm	169	173	177	181	185	190	194
Handlebar width	380	400	400	420	420	440	440
Handlebar rise	0						
Stem length	80	90	100	100	110	120	130
angle	7	7	7	7	7	7	7
Headset spacers	40	40	40	40	40	40	40
Crank length	170	170	172.5	172.5	175	175	175
Seatpost length	250	250	250	250	250	250	250
Steerer length	203.5	203.5	203.5	223.5	242.0	261.6	280.1

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.7	72.2	72.7	73.5	73.5	73.8	73.8
Fork offset	45.0	45.0	45.0	40.0	40.0	40.0	40.0
Trail							
Seat tube angle	74.7	74.7	73.7	73.3	72.8	72.8	72.3
Effective top tube	525	531	546	561	572	582	592
Seat tube	500	520	540	560	580	600	620
Standover	743	757	772	791	809	828	846
Wheelbase	979	982	987	986	994	1001	1006
Bottom bracket height	268	268	268	270	270	270	270
Chainstay	408	408	410	410	412	412	412
Head tube	101	101	104	121	140	159	177

GEARING

	30 42 52
12	66 93 115
13	61 85 106
14	57 79 98
15	53 74 92
17	47 65 81
19	42 58 72
21	38 53 66
23	35 48 60
25	32 44 55

Trek Madone 5.2

FRAMESET

Main tubes	OCV 120 carbon fiber composite
Stays	OCV 120, carbon fiber composite
Color	Black pearl carbon
	Pearl white/ Baja blue (Team)
Fork.	Bontrager Race X Lite, OCV 120 carbon, mm axle-crown length
Headset	Cane Creek S-2 Aheadset, alloy 25.4/34.0/30.0, mm stack height

CONTROLS

Handlebar	Bontrager Race Lite	31.8mm clamp diameter
Stem	Bontrager Race Lite	
Shift levers	Shimano Ultegra STI	
Brake levers	Integrated brake/shift	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano Ultegra	Down pull, Braze-on type attachment
Rear derailleur . . .	Shimano Ultegra	
Crankset	Shimano Ultegra 53/39	130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain.		9 speed, links
Cassette.	Shimano Ultegra 12-25, 9spd	

WHEELSET

Front wheel.	Bontrager Race Lite, 20°	592mm ERD
Spokes	DT New Aero, ProLock alloy nipples, 279mm, radial	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Velox 16mm rim strip	
Rear wheel	Bontrager Race Lite, 24°	595mm ERD
Spokes	DT New Aero, T-head drive side, ProLock alloy nipples, 291/293mm, 2x	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Velox 16mm rim strip	
Inner tubes		

OTHER

Seatpost.	Bontrager Race X Lite	27.2mm outer diameter
Saddle	Bontrager Race Lite Luxe, Ti rails	
Seatpost binder. . .	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano Ultegra	
Pedals	-not supplied- 9/16" axle	
Additional		

FIT

dimensions in mm, unless specified

Frame	Size	50	52	54	56	58	60	62
Rider height, in.		41.0	41.4	41.7	42.6	43.1	44.0	44.6
	cm	104	105	106	108	109	112	113
Handlebar	width							
Stem	length							
	angle							
Headset spacers								
Crank	length							
Seatpost	length							
Steerer	length	99	99	102	119	137.5	156.5	175

GEOMETRY

dimensions in mm, unless specified

Head tube angle	72.1	72.5	73.0	73.8	73.7	74.0	73.9
Fork offset	41.0	41.0	41.0	41.0	41.0	41.0	41.0
Trail							
Seat tube angle	75.1	75.0	74.0	73.5	73.0	72.9	72.5
Effective top tube	526	531	546	561	572	582	592
Seat tube	500	520	540	560	580	600	620
Standover	740	755	770	790	808	827	844
Wheelbase	979	980	984	984	991	998	1003
Bottom bracket height	266	266	266	269	268	268	268
Chainstay	408	408	410	410	412	412	412
Head tube	101	101	104	121	140	159	177

GEARING

	39 53
12	86 117
13	79 108
14	74 100
15	69 93
17	61 82
19	54 74
21	49 67
23	45 61
25	41 56 0

FRAMESET

Main tubes	OCV 55 Carbon superlight	
Stays	OCV 55 Carbon superlight	
Color	Pearl white/ Satin silver (Team)	
	Andromeda	
Fork.	Bontrager Race XXX Lite, 379mm axle-crown length	
Headset	Cane Creek S-6 Aheadset, alloy	25.4/34.0/30.0, 27.1mm stack height

CONTROLS

Handlebar	Bontrager Race X Lite	31.8mm clamp diameter
Stem	Bontrager Race XXX Lite	40.0mm steerer clamp height
Shift levers	Shimano Dura-Ace STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano Dura-Ace	Down pull, Braze-on type attachment
Rear derailleur . . .	Shimano Dura-Ace	
Crankset	Shimano Dura-Ace 53/39	130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain.	Shimano Dura-Ace	10 speed, 108 links
Cassette.	Shimano Dura-Ace 12-25, 10spd	

WHEELSET

Front wheel.	Bontrager Race XXX Lite, tubular, 20°	592mm ERD
Spokes	DT Aerolite nail-head, internal alloy nipples, 286mm, radial	
Tire	Bontrager Race X Lite Pro, folding, 700 x 23c, Velox 16mm rim strip	
Rear wheel	Bontrager Race XXX Lite, tubular, 24°	595mm ERD
Spokes	DT New Aero, Aerolite nail-head non-drive side, internal alloy nipples, 291/286mm, 2x/radial	
Tire	Bontrager Race X Lite Pro, folding, 700 x 23c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost.	Bontrager Race XXX Lite	27.2mm outer diameter
Saddle	Bontrager Race X Lite Pro	
Seatpost binder. . .	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano Dura-Ace, pads for carbon rim	
Pedals	-not supplied- 9/16" axle	
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	50	52	54	56	58	60	62
Rider height, in.		61.2	61.9	62.2	63.7	63.9	65.0	65.3
	cm	155	157	158	162	162	165	166
Handlebar	width	380	400	400	420	420	440	440
Stem	length	12	12	12	12	12	12	12
	angle							
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	170	172.5	172.5	178.5	175	175
Seatpost	length	250	250	250	250	250	250	250
Steerer	length	204.1	204.1	207.1	227.1	242.6	261.6	280.1

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.1	72.5	73.0	73.8	73.7	74.0	73.9
Fork offset	45.0	45.0	45.0	40.0	40.0	40.0	40.0
Trail							
Seat tube angle	75.1	75.0	74.0	73.5	73.0	72.9	72.5
Effective top tube	526	531	546	561	572	582	592
Seat tube	500	520	540	560	580	600	620
Standover	740	755	770	790	808	827	844
Wheelbase	979	980	984	984	991	998	1003
Bottom bracket height	266	266	266	269	268	268	268
Chainstay	408	408	410	410	412	412	412
Head tube	101	101	104	121	140	159	177

GEARING

	39 53
12	86 117
13	79 108
14	74 100
15	69 93
16	64 88
17	61 82
19	54 74
21	49 67
23	45 61 0
25	41 56 0

Trek 5.9 Superlight

1476000*15.114

FRAMESET

Main tubes	OCV 110 carbon fiber composite	
Stays	OCV 110, carbon fiber composite	
Color	Pearl white/ Satin silver (Team)	
	Andromeda	
Fork.	Bontrager Race XXX Lite, 379mm axle-crown length	
Headset	Cane Creek S-6 Aheadset, alloy	25.4/34.0/30.0, 27.1mm stack height

CONTROLS

Handlebar	Bontrager Race X Lite	31.8mm clamp diameter
Stem	Bontrager Race XXX Lite	40.0mm steerer clamp height
Shift levers	Shimano Dura-Ace STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano Dura-Ace	Down pull, Braze-on type attachment
Rear derailleur . . .	Shimano Dura-Ace	
Crankset	Shimano Dura-Ace 53/39	130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain.	Shimano Dura-Ace	10 speed, 108 links
Cassette.	Shimano Dura-Ace 12-25, 10spd	

WHEELSET

Front wheel.	Bontrager Race X Lite, 20°	592mm ERD
Spokes	DT Aerolite nail-head, internal alloy nipples, 286mm, radial	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Bontrager, 17.5mm rim strip	
Rear wheel	Bontrager Race X Lite, 24°	595mm ERD
Spokes	DT New Aero, Aerolite nail-head non-drive side, internal alloy nipples, 291/286mm, 2x/radial	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Bontrager, 17.5mm rim strip	
Inner tubes		

OTHER

Seatpost.	Bontrager Race XXX Lite	27.2mm outer diameter
Saddle	Bontrager Race X Lite Pro	
Seatpost binder. . .	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano Dura-Ace	
Pedals	-not supplied- 9/16" axle	
Additional		

FIT *dimensions in mm, unless specified*

	Size	50	52	54	56	58	60	62
Rider height, in.		61.2	61.9	62.2	63.6	63.8	64.9	65.2
	cm	155	157	158	162	162	165	166
Handlebar width		380	400	400	420	420	440	440
Stem length		12	12	12	12	12	12	12
Headset spacers		40	40	40	40	40	40	40
Crank length		170	170	172.5	172.5	178.5	175	175
Seatpost length		250	250	250	250	250	250	250
Steerer length		204.1	204.1	207.1	227.1	242.6	261.6	280.1

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.1	72.5	73.0	73.8	73.7	74.0	73.9
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail							
Seat tube angle	75.1	75.0	74.0	73.5	73.0	72.9	72.5
Effective top tube	526	531	546	561	572	582	592
Seat tube	500	520	540	560	580	600	620
Standover	740	755	770	790	808	827	844
Wheelbase	979	980	984	984	991	998	1003
Bottom bracket height	266	266	266	269	268	268	268
Chainstay	408	408	410	410	412	412	412
Head tube	101	101	104	121	140	159	177

GEARING

	39 53
12	86 117
13	79 108
14	74 100
15	69 93
16	64 88
17	61 82
19	54 74
21	49 67
23	45 61 0
25	41 56 0

Trek 5200 T WSD

1463003*15.084
Bike weight: 19.0 lb/8.63 kg

FRAMESET

Main tubes	OCV 120 carbon fiber composite	
Stays	OCV 120 carbon fiber composite	
Color	Jet Blue/Titanite Black	
Fork	Bontrager Race, 349mm axle-crown length	
Headset	Cane Creek C-1 Aheadset	25.4/34.0/30.0, 26.7mm stack height

CONTROLS

Handlebar	Bontrager Race	26.0mm clamp diameter
Stem	Bontrager Race	40.0mm steerer clamp height
Shift levers	Shimano Ultegra STI, adjustable reach	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano 105 T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur . . .	Shimano Ultegra GS	
Crankset	Bontrager Race Lite 52/42/30 w/Giga-X-Pipe	74/130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano HG-73	9 speed, 108 links
Cassette	SRAM PG970 12-26, 9spd	

WHEELSET

Front wheel	Bontrager Race, 20°	544mm ERD
Spokes	DT New Aero, ProLock brass nipples, 253mm, radial	
Tire	Bontrager Race Lite, folding, 650 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Race, 24°	549mm ERD
Spokes	DT New Aero, ProLock brass nipples, 268/268mm, 2x	
Tire	Bontrager Race Lite, folding, 650 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race X Lite	27.2mm outer diameter
Saddle	Bontrager Select WSD	
Seatpost binder . . .	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano 105	
Pedals	-not supplied- axle	
Additional	see 5000T for 700c wheel parts	

FIT *dimensions in mm, unless specified*

Frame	Size	47	51	54	56
Rider height, in.		63.7	66.4	67.7	69.3
	cm	162	169	172	176
Handlebar	width		380		
Stem	length	80	100	100	90
	angle	17	17	17	17
Headset spacers		40	40	40	40
Crank	length	165	170	170	170
Seatpost	length	250	250	250	250
Steerer	length	217.7	235.2	211.9	226.7

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.5	72.5	72.5	73.8
Fork offset	38.0	38.0	45.0	45.0
Trail	59	59	58	57
Seat tube angle	74.5	74.5	74.0	73.5
Effective top tube	498	505	528	562
Seat tube	470	510	540	560
Standover	709	741	768	789
Wheelbase	945	954	973	991
Bottom bracket height	267	267	266	270
Chainstay	408	408	410	410
Head tube	115	133	109	124

GEARING

	30	42	52
12	61	86	106
13	57	79	98
14	52	73	91
15	49	69	85
17	43	61	75
19	39	54	67
21	35	49	61
23	32	45	55
26	28	40	49

Trek 5000

1462000*15.054
Bike weight: 17.9 lb/8.13 kg

FRAMESET

Main tubes	OCV 120, carbon fiber composite
Stays	OCV 120, carbon fiber composite
Color	Nude Pearl/Baja Blue • Dark silver/white/blue dactal • Nude Pearl/Silver fork Nude Carbon • Dark silver/silver/red decal • Nude Carbon fork
Fork	Bontrager Race Lite, 370.0mm axle-crown length
Headset	Cane Creek C-1 Aheadset 25.4/34.0/30.0, 26.7mm stack height

CONTROLS

Handlebar	Bontrager Race	31.8mm clamp diameter
Stem	Bontrager Race	40.0mm steerer clamp height
Shift levers	Shimano Ultegra STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano 105	Down pull, Braze-on type attachment
Rear derailleur	Shimano Ultegra	
Crankset	Shimano 105 53/39	130mm bolt hole circle
Bottom bracket	Shimano 105	68 x 109.5 (shell x axle,mm), Shimano splined axle
Chain	Shimano HG-73	9 speed, 108 links
Cassette	SRAM PG970 12-26, 9spd	

WHEELSET

Front wheel	Bontrager Race, 20°	593mm ERD
Spokes	DT New Aero, ProLock brass nipples, 280mm, radial	
Tire	Bontrager Race Lite, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Race, 24°	603mm ERD
Spokes	DT New Aero, ProLock brass nipples, 294/294mm, 2x	
Tire	Bontrager Race Lite, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race X Lite	27.2mm outer diameter
Saddle	Bontrager Race, hollow CrMo rails	
Seatpost binder	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano 105	
Pedals	-not supplied- 9/16" axle	
Additional	2 water bottle mounts	

FIT

dimensions in mm, unless specified

Frame	Size	50	52	54	56	58	60	62
Rider height, in.		66.7	68.2	69.6	71.0	72.6	74.7	76.5
	cm	169	173	177	180	184	190	194
Handlebar	width	380	400	400	420	420	440	440
Handlebar	rise	0						
Stem	length	80	90	100	100	110	120	130
	angle	7	7	7	7	7	7	7
Headset spacers		40	40	40	40	40	40	40
Crank	length	170	170	172.5	172.5	175	175	175
Seatpost	length	250	250	250	250	250	250	250
Steerer	length	203.7	203.7	206.7	223.7	242.7	261.7	279.7

GEOMETRY

dimensions in mm, unless specified

Head tube angle	71.7	72.2	72.7	73.5	73.5	73.8	73.8
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail							
Seat tube angle	74.7	74.7	73.7	73.3	72.8	72.8	72.3
Effective top tube	525	531	546	561	572	582	592
Seat tube	500	520	540	560	580	600	620
Standover	743	757	772	791	809	828	846
Wheelbase	979	982	987	986	994	1001	1006
Bottom bracket height	268	268	268	270	270	270	270
Chainstay	408	408	410	410	412	412	412
Head tube	101	101	104	121	140	159	177

GEARING

	39 53
12	86 117
13	79 108
14	74 100
15	69 93
17	61 82
19	54 74
21	49 67
23	45 61
26	40 54 0

Trek 5000 T

1463000*15.054
Bike weight: 17.9 lb/8.13 kg

FRAMESET

Main tubes	OCV 120, carbon fiber composite
Stays	OCV 120, carbon fiber composite
Color	Nude Pearl/Baja Blue • Dark silver/white/blue dactal • Nude Pearl/Silver fork Nude Carbon • Dark silver/silver/red decal • Nude Carbon fork
Fork	Bontrager Race Lite, 370.0mm axle-crown length
Headset	Cane Creek C-1 Aheadset 25.4/34.0/30.0, 26.7mm stack height

CONTROLS

Handlebar	Bontrager Race	31.8mm clamp diameter
Stem	Bontrager Race	40.0mm steerer clamp height
Shift levers	Shimano Ultegra STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano 105 T	Down pull, Braze-on type attachment
Rear derailleur . . .	Shimano Ultegra GS	
Crankset	Shimano Ultegra 52/42/30	74/130mm bolt hole circle
Bottom bracket . . .	Shimano 105	68 x 118 (shell x axle,mm), Shimano splined axle
Chain	Shimano HG-73	9 speed, 108 links
Cassette	SRAM PG970 12-26, 9spd	

WHEELSET

Front wheel	Bontrager Race, 20°	593mm ERD
Spokes	DT New Aero, ProLock brass nipples, 280mm, radial	
Tire	Bontrager Race Lite, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Race, 24°	603mm ERD
Spokes	DT New Aero, ProLock brass nipples, 294/294mm, 2x	
Tire	Bontrager Race Lite, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race X Lite	27.2mm outer diameter
Saddle	Bontrager Race, hollow CrMo rails	
Seatpost binder . . .	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano 105	
Pedals	-not supplied- 9/16" axle	
Additional	2 water bottle mounts	

FIT dimensions in mm, unless specified

Frame Size	50	52	54	56	58	60	62
Rider height, in.	66.7	68.2	69.6	71.0	72.6	74.7	76.5
cm	169	173	177	180	184	190	194
Handlebar width	380	400	400	420	420	440	440
Handlebar rise	0						
Stem length	80	90	100	100	110	120	130
angle	7	7	7	7	7	7	7
Headset spacers	40	40	40	40	40	40	40
Crank length	170	170	170	175	175	175	175
Seatpost length	250	250	250	250	250	250	250
Steerer length	203.7	203.7	206.7	223.7	242.7	261.7	279.7

GEOMETRY dimensions in mm, unless specified

Head tube angle	71.7	72.2	72.7	73.5	73.5	73.8	73.8
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail							
Seat tube angle	74.7	74.7	73.7	73.3	72.8	72.8	72.3
Effective top tube	525	531	546	561	572	582	592
Seat tube	500	520	540	560	580	600	620
Standover	743	757	772	791	809	828	846
Wheelbase	979	982	987	986	994	1001	1006
Bottom bracket height	268	268	268	270	270	270	270
Chainstay	408	408	410	410	412	412	412
Head tube	101	101	104	121	140	159	177

GEARING

	30	42	52
12	66	93	115
13	61	85	106
14	57	79	98
15	53	74	92
17	47	65	81
19	42	58	72
21	38	53	66
23	35	48	60
26	31	43	53

Trek 2300

1448000*15.104
Bike weight: 18.4 lb/8.35 kg

FRAMESET

Main tubes	ZR9000	
Stays	OCLV 120 carbon fiber composite	
Color	Baja Blue/Metallic Charcoal	
Fork	Bontrager Race, 370mm axle-crown length	
Headset	Cane Creek Internal	25.4/34.0/30.0, 8.0mm stack height

CONTROLS

Handlebar	Bontrager Race Lite	31.8mm clamp diameter
Stem	Bontrager Race Lite	40.0mm steerer clamp height
Shift levers	Shimano Ultegra STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano Ultegra	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur . . .	Shimano Ultegra	
Crankset	Shimano Ultegra 53/39	130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano Ultegra	10 speed, 108 links
Cassette	Shimano Ultegra 12-25, 10spd	

WHEELSET

Front wheel	Bontrager Race, 20°	593mm ERD
Spokes	DT New Aero, ProLock brass nipples, 280mm, radial	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Velox 16mm rim strip	
Rear wheel	Bontrager Race, 24°	603mm ERD
Spokes	DT New Aero, ProLock brass nipples, 294/294mm, 2x	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race X Lite	27.2mm outer diameter
Saddle	Bontrager Race Lite Luxe	
Seatpost binder . . .	Alloy w/integral bolt	32.1mm inner diameter
Brakes	Shimano Ultegra	
Pedals	-not supplied-	9/16" axle
Additional		

FIT dimensions in mm, unless specified

Frame	Size	50	52	54	56	58	60	63
Rider height, in.		67.0	68.6	70.3	71.6	73.0	75.1	77.7
	cm	170	174	179	182	185	191	197
Handlebar	width	380	400	400	420	420	440	440
Stem	length	80	90	100	100	110	120	130
	angle	7	7	7	7	7	7	7
Headset spacers		40	40	40	40	40	40	35
Crank	length	170	170	172.5	172.5	175	175	175
Seatpost	length	250	250	250	250	250	250	250
Steerer	length	200.0	200.0	209.0	225.0	245.0	264.0	289.0

GEOMETRY dimensions in mm, unless specified

Head tube angle	72.0	72.5	73.0	73.8	73.8	74.0	74.0
Fork offset							
Trail	60	57	54	53	53	52	52
Seat tube angle	75.0	75.0	74.0	73.5	73.0	73.0	72.5
Effective top tube	521	526	544	560	571	581	601
Seat tube	500	520	540	560	580	600	630
Standover	743	757	772	792	810	829	859
Wheelbase	989	989	993	994	999	1006	1021
Bottom bracket height	266	266	266	268	268	268	270
Chainstay	417	417	417	417	417	417	417
Head tube	116	116	125	141	161	180	210

GEARING

	39 53
12	86 117
13	79 108
14	74 100
15	69 93
16	64 88
17	61 82
19	54 74
21	49 67
23	45 61 0
25	41 56 0

Trek 2300T

1449000*15.104
Bike weight: 18.6 lb/8.44 kg

FRAMESET

Main tubes	ZR9000	
Stays	OCLV 120 carbon fiber composite	
Color	Baja Blue/Metallic Charcoal	
Fork	Bontrager Race, 370mm axle-crown length	
Headset	Cane Creek Internal	25.4/34.0/30.0, 8.0mm stack height

CONTROLS

Handlebar	Bontrager Race Lite	31.8mm clamp diameter
Stem	Bontrager Race Lite	40.0mm steerer clamp height
Shift levers	Shimano Ultegra STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano Ultegra T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur . . .	Shimano Ultegra GS	
Crankset	Shimano Ultegra 52/39/30	74/130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano Ultegra	10 speed, 108 links
Cassette	Shimano Ultegra 12-25, 10spd	

WHEELSET

Front wheel	Bontrager Race, 20"	593mm ERD
Spokes	DT New Aero, ProLock brass nipples, 280mm, radial	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Velox 16mm rim strip	
Rear wheel	Bontrager Race, 24"	603mm ERD
Spokes	DT New Aero, ProLock brass nipples, 294/294mm, 2x	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race X Lite	27.2mm outer diameter
Saddle	Bontrager Race Lite Luxe	
Seatpost binder . . .	Alloy w/integral bolt	32.1mm inner diameter
Brakes	Shimano Ultegra	
Pedals	-not supplied-	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	50	52	54	56	58	60	63
Rider height, in.		67.0	68.6	70.3	71.6	73.0	75.1	77.7
	cm	170	174	179	182	185	191	197
Handlebar	width	380	400	400	420	420	440	440
Stem	length	80	90	100	100	110	120	130
	angle	7	7	7	7	7	7	7
Headset spacers		40	40	40	40	40	40	35
Crank	length	170	170	172.5	172.5	175	175	175
Seatpost	length	250	250	250	250	250	250	250
Steerer	length	200.0	200.0	209.0	225.0	245.0	264.0	289.0

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.0	72.5	73.0	73.8	73.8	74.0	74.0
Fork offset							
Trail	60	57	54	53	53	52	52
Seat tube angle	75.0	75.0	74.0	73.5	73.0	73.0	72.5
Effective top tube	521	526	544	560	571	581	601
Seat tube	500	520	540	560	580	600	630
Standover	743	757	772	792	810	829	859
Wheelbase	989	989	993	994	999	1006	1021
Bottom bracket height	266	266	266	268	268	268	270
Chainstay	417	417	417	417	417	417	417
Head tube	116	116	125	141	161	180	210

GEARING

	30 39 52
12	66 86 115
13	61 79 106
14	57 74 98
15	53 69 92
16	50 64 86
17	47 61 81
19	42 54 72
21	38 49 66
23	35 45 60
25	32 41 55

Trek 2300 WSD T

1449003*15.104

FRAMESET

Main tubes	ZR9000	
Stays	OCLV 120 carbon fiber composite	
Color	Platinum Silver/Neptune Blue	
Fork	Bontrager Race Lite, 344mm axle-crown length	
Headset	Cane Creek Internal	25.4/34.0/30.0, 8.0mm stack height

CONTROLS

Handlebar	Bontrager Race	26.0mm clamp diameter
Stem	Bontrager Race	40.0mm steerer clamp height
Shift levers	Shimano Ultegra STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano Ultegra T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur . . .	Shimano Ultegra GS	
Crankset	Shimano Ultegra 52/39/30	74/130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano Ultegra	10 speed, 108 links
Cassette	Shimano Ultegra 12-25, 10spd	

WHEELSET

Front wheel	Bontrager Race Lite, 20°	544mm ERD
Spokes	DT New Aero, ProLock brass nipples, 253mm, radial	
Tire	Bontrager Race X Lite, folding, 650 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Race Lite, 24°	544mm ERD
Spokes	DT New Aero, T-head drive side, ProLock alloy nipples, 265/260mm, 2x	
Tire	Bontrager Race X Lite, folding, 650 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Race X Lite	27.2mm outer diameter
Saddle	Bontrager Race Lite WSD Luxe	
Seatpost binder . . .	Alloy w/integral bolt	32.1mm inner diameter
Brakes	Shimano Ultegra	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional	see 2300T for 700c wheel sizes	

FIT *dimensions in mm, unless specified*

Frame	Size	43	47	51	54	56
Rider height, in.		63.3	63.7	66.1	67.1	68.8
	cm	161	162	168	170	175
Handlebar	width	380	380	380	380	380
Stem	length	80	80	100	100	90
	angle	17	17	17	17	17
Headset spacers		40	40	40	40	40
Crank	length	165	165	170	170	170
Seatpost	length	250	250	250	250	250
Steerer	length	200.0	209.0	200.0	209.0	225.0

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.5	72.5	72.0	72.5	73.8
Fork offset	35.0	35.0	35.0	45.0	45.0
Trail	58	58	60	57	54
Seat tube angle	76.0	75.0	75.0	74.0	73.5
Effective top tube	485	497	506	527	560
Seat tube	430	470	510	540	560
Standover	683	713	743	772	792
Wheelbase	952	956	977	980	994
Bottom bracket height	265	267	267	266	268
Chainstay	412	412	417	417	417
Head tube	116	125	116	125	141

GEARING

	30 39 52
12	61 80 106
13	57 73 98
14	52 68 91
15	49 64 85
16	46 60 80
17	43 56 75
19	39 50 67
21	35 45 61
23	32 42 55
25	29 38 51

Trek 2000

1430000*15.114

FRAMESET

Main tubes	Alpha SLR aluminum	
Stays	Alpha SLR aluminum	
Color	Metallic black/ Brushed aluminum	
Fork	Carbon, mm axle-crown length	
Headset	Sealed, semi-cartridge	25.4/41.4/30.0, mm stack height

CONTROLS

Handlebar	Bontrager Race	31.8mm clamp diameter
Stem	Bontrager Select	
Shift levers	Shimano Ultegra STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano Ultegra	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur . . .	Shimano Ultegra	
Crankset	Shimano Ultegra 53/39	130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano Ultegra	10 speed, 108 links
Cassette	Shimano Ultegra 12-25, 10spd	

WHEELSET

Front wheel	Bontrager Race, 20°	593mm ERD
Spokes	DT New Aero, ProLock brass nipples, 280mm, radial	
Tire	Bontrager Race Lite, 700 x 23c, Velox 16mm rim strip	
Rear wheel	Bontrager Race, 24°	603mm ERD
Spokes	DT New Aero, ProLock brass nipples, 294/294mm, 2x	
Tire	Bontrager Race Lite, 700 x 23c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race X Lite	27.2mm outer diameter
Saddle	Bontrager Race	
Seatpost binder . . .		31.8mm inner diameter
Brakes	Shimano Ultegra	
Pedals	-not supplied-	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	43	50	52	54	56	58	60	63
Rider height, in.		41.1	40.5	48.5	42.0	42.7	43.4	44.4	45.4
	cm	104	103	123	107	109	110	113	115
Handlebar	width	380	380	400	400	420	420	440	440
Stem	length90 angle7								
Headset spacers		45							
Crank	length	170	170	170	172.5	172.5	175	175	175
Seatpost	length	250							
Steerer	length	139.5	94.5	94.5	102.5	120.5	138	156.5	187

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	71.5	71.5	72.5	73.0	73.0	73.5	74.0
Fork offset	47.0	47.0	47.0	47.0	43.0	43.0	43.0	43.0
Trail	67	64	64	58	59	59	56	53
Seat tube angle	75.0	75.0	75.0	74.5	73.8	73.5	73.5	72.5
Effective top tube	527	521	526	544	560	571	581	601
Seat tube	430	500	520	540	560	580	600	630
Standover	696	740	755	770	790	808	827	856
Wheelbase	1002	1002	1002	1004	1006	1014	1020	1024
Bottom bracket height	266	266	266	266	268	268	268	268
Chainstay	417	417	417	417	417	417	417	417
Head tube	97	97	97	105	123	140	159	189

GEARING

	39 53
12	86 117
13	79 108
14	74 100
15	69 93
16	64 88
17	61 82
19	54 74
21	49 67
23	45 61 0
25	41 56 0

Trek 2000T

1431000*15.114

FRAMESET

Main tubes	Alpha SLR aluminum	
Stays	Alpha SLR aluminum	
Color	Metallic black/ Brushed aluminum	
Fork	Carbon, mm axle-crown length	
Headset	Sealed, semi-cartridge	25.4/41.4/30.0, mm stack height

CONTROLS

Handlebar	Bontrager Race	31.8mm clamp diameter
Stem	Bontrager Select	
Shift levers	Shimano Ultegra STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano Ultegra	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur . . .	Shimano Ultegra GS	
Crankset	Shimano Ultegra 52/42/30	74/130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano Ultegra	10 speed, 108 links
Cassette	Shimano Ultegra 12-25, 10spd	

WHEELSET

Front wheel	Bontrager Race, 20°	593mm ERD
Spokes	DT New Aero, ProLock brass nipples, 280mm, radial	
Tire	Bontrager Race Lite, 700 x 23c, Velox 16mm rim strip	
Rear wheel	Bontrager Race, 24°	603mm ERD
Spokes	DT New Aero, ProLock brass nipples, 294/294mm, 2x	
Tire	Bontrager Race Lite, 700 x 23c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race X Lite	27.2mm outer diameter
Saddle	Bontrager Race	
Seatpost binder . . .		31.8mm inner diameter
Brakes	Shimano Ultegra	
Pedals	-not supplied- 9/16" axle	
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	43	50	52	54	56	58	60	63
Rider height, in.		41.1	40.5	48.5	42.0	42.7	43.4	44.4	45.4
	cm	104	103	123	107	109	110	113	115
Handlebar	width	380	380	400	400	420	420	440	440
Stem	length			90					
	angle			7					
Headset spacers				45					
Crank	length	170	170	170	172.5	172.5	175	175	175
Seatpost	length	250							
Steerer	length	139.5	94.5	94.5	102.5	120.5	138	156.5	187

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	71.5	71.5	72.5	73.0	73.0	73.5	74.0
Fork offset	47.0	47.0	47.0	47.0	43.0	43.0	43.0	43.0
Trail	67	64	64	58	59	59	56	53
Seat tube angle	75.0	75.0	75.0	74.5	73.8	73.5	73.5	72.5
Effective top tube	527	521	526	544	560	571	581	601
Seat tube	430	500	520	540	560	580	600	630
Standover	696	740	755	770	790	808	827	856
Wheelbase	1002	1002	1002	1004	1006	1014	1020	1024
Bottom bracket height	266	266	266	266	268	268	268	268
Chainstay	417	417	417	417	417	417	417	417
Head tube	97	97	97	105	123	140	159	189

GEARING

	30	42	52
12	66	93	115
13	61	85	106
14	57	79	98
15	53	74	92
16	50	69	86
17	47	65	81
19	42	58	72
21	38	53	66
23	35	48	60
25	32	44	55

Trek 2100

1444000*15.104
Bike weight: 20.0 lb/9.08 kg

FRAMESET

Main tubes	Alpha SLR aluminum	
Stays	Alpha SLR aluminum	
Color	Metallic black/ Brushed aluminum	
Fork	Bontrager Race, mm axle-crown length	
Headset	Cane Creek Internal	25.4/34.0/30.0, 8.0mm stack height

CONTROLS

Handlebar	Bontrager Race	31.8mm clamp diameter
Stem	Bontrager Race	40.0mm steerer clamp height
Shift levers	Shimano 105 STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano 105	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur . . .	Shimano 105	
Crankset	Bontrager Race Lite 53/39 w/Giga-X-Pipe	130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano HG-73	9 speed, 108 links
Cassette	SRAM PG970 12-26, 9spd	

WHEELSET

Front wheel	Bontrager Race, 20"	593mm ERD
Spokes	DT New Aero, ProLock brass nipples, 280mm, radial	
Tire	Bontrager Race Lite, folding, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Race, 24"	603mm ERD
Spokes	DT New Aero, ProLock brass nipples, 294/294mm, 2x	
Tire	Bontrager Race Lite, folding, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race X Lite	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .	Alloy w/integral bolt	32.1mm inner diameter
Brakes	Shimano 105	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	50	52	54	56	58	60	63
Rider height, in.		48.3	49.5	51.1	52.2	53.8	55.7	58.1
	cm	123	126	130	133	137	142	147
Handlebar	width	380	400	400	420	420	440	440
Stem	length	80	90	100	100	110	120	130
	angle	7	7	7	7	7	7	7
Headset spacers		40	40	40	40	40	40	35
Crank	length	170	170	172.5	172.5	175	175	175
Seatpost	length	250	250	250	250	250	250	250
Steerer	length	200.0	200.0	209.0	225.0	245.0	264.0	289.0

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.0	72.5	73.0	73.8	73.8	74.0	74.0
Fork offset	46.0	46.0	46.0	46.0	46.0	46.0	46.0
Trail	60	57	54	53	53	52	52
Seat tube angle	75.0	75.0	74.0	73.5	73.0	73.0	72.5
Effective top tube	521	526	544	560	571	581	601
Seat tube	500	520	540	560	580	600	630
Standover	743	757	772	792	810	829	859
Wheelbase	989	989	993	994	999	1006	1021
Bottom bracket height	266	266	266	268	268	268	270
Chainstay	417	417	417	417	417	417	417
Head tube	116	116	125	141	161	180	210

GEARING

	39 53
12	86 117
13	79 108
14	74 100
15	69 93
17	61 82
19	54 74
21	49 67
23	45 61
26	40 54 0

Trek 2100T

1445000*15.104
Bike weight: 20.4 lb/9.26 kg

FRAMESET

Main tubes	Alpha SLR aluminum	
Stays	Alpha SLR aluminum	
Color	Metallic black/ Brushed aluminum	
Fork	Bontrager Race, mm axle-crown length	
Headset	Cane Creek Internal	25.4/34.0/30.0, 8.0mm stack height

CONTROLS

Handlebar	Bontrager Race	31.8mm clamp diameter
Stem	Bontrager Race	40.0mm steerer clamp height
Shift levers	Shimano 105 STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano 105 T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur . . .	Shimano Ultegra GS	
Crankset	Bontrager Race Lite 52/42/30 w/Giga-X-Pipe	74/130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano HG-73	9 speed, 108 links
Cassette	SRAM PG970 12-26, 9spd	

WHEELSET

Front wheel	Bontrager Race, 20°	593mm ERD
Spokes	DT New Aero, ProLock brass nipples, 280mm, radial	
Tire	Bontrager Race Lite, folding, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Race, 24°	603mm ERD
Spokes	DT New Aero, ProLock brass nipples, 294/294mm, 2x	
Tire	Bontrager Race Lite, folding, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race X Lite	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .	Alloy w/integral bolt	32.1mm inner diameter
Brakes	Shimano 105	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

	Size	50	52	54	56	58	60	63
Rider height, in.		48.3	49.5	51.1	52.2	53.8	55.7	58.1
	cm	123	126	130	133	137	142	147
Handlebar	width	380	400	400	420	420	440	440
Stem	length	80	90	100	100	110	120	130
	angle	7	7	7	7	7	7	7
Headset spacers		40	40	40	40	40	40	35
Crank	length	170	170	172.5	172.5	175	175	175
Seatpost	length	250	250	250	250	250	250	250
Steerer	length	200.0	200.0	209.0	225.0	245.0	264.0	289.0

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.0	72.5	73.0	73.8	73.8	74.0	74.0
Fork offset	46.0	46.0	46.0	46.0	46.0	46.0	46.0
Trail	60	57	54	53	53	52	52
Seat tube angle	75.0	75.0	74.0	73.5	73.0	73.0	72.5
Effective top tube	521	526	544	560	571	581	601
Seat tube	500	520	540	560	580	600	630
Standover	743	757	772	792	810	829	859
Wheelbase	989	989	993	994	999	1006	1021
Bottom bracket height	266	266	266	268	268	268	270
Chainstay	417	417	417	417	417	417	417
Head tube	116	116	125	141	161	180	210

GEARING

	30	42	52
12	66	93	115
13	61	85	106
14	57	79	98
15	53	74	92
17	47	65	81
19	42	58	72
21	38	53	66
23	35	48	60
26	31	43	53

Trek 2100 WSD T

1445003*15.104
Bike weight: 19.8 lb/8.99 kg

FRAMESET

Main tubes	Alpha SLR aluminum	
Stays	Alpha SLR aluminum	
Color	Lava Red/Pearl White	
Fork	Bontrager Race, mm axle-crown length	
Headset	Cane Creek Internal	25.4/34.0/30.0, 8.0mm stack height

CONTROLS

Handlebar	Bontrager Race	26.0mm clamp diameter
Stem	Bontrager Race	40.0mm steerer clamp height
Shift levers	Shimano Ultegra STI, adjustable reach	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano 105 T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur . . .	Shimano Ultegra GS	
Crankset	Bontrager Race Lite 52/42/30 w/Giga-X-Pipe	74/130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano HG-73	9 speed, 108 links
Cassette	SRAM PG970 12-26, 9spd	

WHEELSET

Front wheel	Bontrager Race, 20°	544mm ERD
Spokes	DT New Aero, ProLock brass nipples, 253mm, radial	
Tire	Bontrager Race Lite, folding, 650 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Race, 24°	549mm ERD
Spokes	DT New Aero, ProLock brass nipples, 268/268mm, 2x	
Tire	Bontrager Race Lite, folding, 650 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Race X Lite	27.2mm outer diameter
Saddle	Bontrager Select WSD	
Seatpost binder . . .	Alloy w/integral bolt	32.1mm inner diameter
Brakes	Shimano 105	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional	see 1500T for 700c wheel sizes	

FIT *dimensions in mm, unless specified*

Frame	Size	43	47	51	54	56
Rider height, in.		46.2	46.5	48.7	49.6	51.2
	cm	117	118	124	126	130
Handlebar	width	380	380	380	380	380
Stem	length	80	80	100	100	90
	angle	17	17	17	17	17
Headset spacers		40	40	40	40	40
Crank	length	165	165	170	170	170
Seatpost	length	250	250	250	250	250
Steerer	length	200.0	209.0	200.0	209.0	225.0

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.5	72.5	72.0	72.5	73.8
Fork offset	35.0	35.0	35.0	45.0	45.0
Trail	58	58	60	57	54
Seat tube angle	76.0	75.0	75.0	74.0	73.5
Effective top tube	485	497	506	527	560
Seat tube	430	470	510	540	560
Standover	683	713	743	772	792
Wheelbase	952	956	977	980	994
Bottom bracket height	265	267	267	266	268
Chainstay	412	412	417	417	417
Head tube	116	125	116	125	141

GEARING

	30	42	52
12	61	86	106
13	57	79	98
14	52	73	91
15	49	69	85
17	43	60	75
19	39	54	67
21	35	49	61
23	32	45	55
26	28	40	49

Trek 1500

1428000*15.074

FRAMESET

Main tubes	Alpha SLR aluminum	
Stays	Alpha SLR aluminum	
Color	Metallic black/ Brushed aluminum	
Fork	Carbon, mm axle-crown length	
Headset	Sealed, semi-cartridge	25.4/41.4/30.0, mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Select	
Shift levers	Shimano Ultegra STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano 105	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur . . .	Shimano 105	
Crankset	Shimano Ultegra 53/39	130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano Ultegra	10 speed, 108 links
Cassette	Shimano Ultegra 12-25, 10spd	

WHEELSET

Front wheel	Bontrager Select, 20°	593mm ERD
Spokes	DT 14g, ProLock brass nipples, 281mm, radial	
Tire	Bontrager Race Lite, 700 x 23c, Velox 16mm rim strip	
Rear wheel	Bontrager Select, 24°	603mm ERD
Spokes	DT 14g, ProLock brass nipples, 293/294mm, 2x	
Tire	Bontrager Race Lite, 700 x 23c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Carbon	27.2mm outer diameter
Saddle	Bontrager Race	
Seatpost binder . . .		31.8mm inner diameter
Brakes	Shimano Ultegra	
Pedals	-not supplied-	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	43	50	52	54	56	58	60	63
Rider height, in.		41.1	40.5	48.5	42.0	42.7	43.4	44.4	45.4
	cm	104	103	123	107	109	110	113	115
Handlebar	width	380	380	400	400	420	420	440	440
Stem	length90 angle7								
Headset spacers		45							
Crank	length	170	170	170	172.5	172.5	175	175	175
Seatpost	length								
Steerer	length	139.5	94.5	94.5	102.5	120.5	138	156.5	187

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	71.5	71.5	72.5	73.0	73.0	73.5	74.0
Fork offset	47.0	47.0	47.0	47.0	43.0	43.0	43.0	43.0
Trail	67	64	64	58	59	59	56	53
Seat tube angle	75.0	75.0	75.0	74.5	73.8	73.5	73.5	72.5
Effective top tube	527	521	526	544	560	571	581	601
Seat tube	430	500	520	540	560	580	600	630
Standover	696	740	755	770	790	808	827	856
Wheelbase	1002	1002	1002	1004	1006	1014	1020	1024
Bottom bracket height	266	266	266	266	268	268	268	268
Chainstay	417	417	417	417	417	417	417	417
Head tube	97	97	97	105	123	140	159	189

GEARING

	39 53
12	86 117
13	79 108
14	74 100
15	69 93
16	64 88
17	61 82
19	54 74
21	49 67
23	45 61 0
25	41 56 0

Trek 1500T

1428000*15.074
Bike weight: 20.5 lb/9.31 kg

FRAMESET

Main tubes	Alpha SLR aluminum	
Stays	Alpha SLR aluminum	
Color	Metallic black/ Brushed aluminum	
Fork	Carbon, mm axle-crown length	
Headset	Sealed, semi-cartridge	25.4/41.4/30.0, mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Select	
Shift levers	Shimano Ultegra STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano Ultegra T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur . . .	Shimano 105 GS	
Crankset	Shimano Ultegra 52/42/30	74/130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano Ultegra	10 speed, 108 links
Cassette	Shimano Ultegra 12-25, 10spd	

WHEELSET

Front wheel	Bontrager Select, 20°	593mm ERD
Spokes	DT 14g, ProLock brass nipples, 281mm, radial	
Tire	Bontrager Race Lite, 700 x 23c, Velox 16mm rim strip	
Rear wheel	Bontrager Select, 24°	603mm ERD
Spokes	DT 14g, ProLock brass nipples, 293/294mm, 2x	
Tire	Bontrager Race Lite, 700 x 23c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Carbon	27.2mm outer diameter
Saddle	Bontrager Race	
Seatpost binder . . .		31.8mm inner diameter
Brakes	Shimano Ultegra	
Pedals	-not supplied-	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

	Size	43	50	52	54	56	58	60	63
Frame									
Rider height, in.		41.1	40.5	48.5	42.0	42.7	43.4	44.4	45.4
	cm	104	103	123	107	109	110	113	115
Handlebar width		380	380	400	400	420	420	440	440
Stem length ⁹⁰									
Headset spacers		45							
Crank length		170	170	170	172.5	172.5	175	175	175
Seatpost length									
Steerer length		139.5	94.5	94.5	102.5	120.5	138	156.5	187

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	71.5	71.5	72.5	73.0	73.0	73.5	74.0
Fork offset	47.0	47.0	47.0	47.0	43.0	43.0	43.0	43.0
Trail	67	64	64	58	59	59	56	53
Seat tube angle	75.0	75.0	75.0	74.5	73.8	73.5	73.5	72.5
Effective top tube	527	521	526	544	560	571	581	601
Seat tube	430	500	520	540	560	580	600	630
Standover	696	740	755	770	790	808	827	856
Wheelbase	1002	1002	1002	1004	1006	1014	1020	1024
Bottom bracket height	266	266	266	266	268	268	268	268
Chainstay	417	417	417	417	417	417	417	417
Head tube	97	97	97	105	123	140	159	189

GEARING

	30	42	52
12	66	93	115
13	61	85	106
14	57	79	98
15	53	74	92
16	50	69	86
17	47	65	81
19	42	58	72
21	38	53	66
23	35	48	60
25	32	44	55

Trek 1500 WSD T

1442003*15.104
Bike weight: 19.5 lb/8.85 kg

FRAMESET

Main tubes	Alpha SLR aluminum	
Stays	Alpha SLR aluminum	
Color	Sport Blue/Metallic Navy	
Fork	, mm axle-crown length	
Headset		25.4/34.0/30.0, mm stack height

CONTROLS

Handlebar	Bontrager Select	26.0mm clamp diameter
Stem		
Shift levers	Shimano 105 STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano 105 T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur . . .	Shimano Ultegra GS	
Crankset	Bontrager Race 52/42/30	74/130mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe SL	68 x 118 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	SRAM PG950 12-26, 9spd	

WHEELSET

Front wheel	Bontrager Select, 20°	544mm ERD
Spokes	DT 14g, ProLock brass nipples, 254mm, radial	
Tire	Bontrager Select, 650 x 20c, Velox 16mm rim strip	
Rear wheel	Bontrager Select, 24°	549mm ERD
Spokes	DT 14g, ProLock brass nipples, 268/270mm, 2x	
Tire	Bontrager Select, 650 x 20c, Velox 16mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Race	27.2mm outer diameter
Saddle	Bontrager Select WSD	
Seatpost binder . . .		31.9mm inner diameter
Brakes	Alloy dual pivot, cartridge pads	
Pedals	Alloy road, sealed, w/clips and straps	9/16" axle
Additional	see 1500T for 700c wheel sizes	

FIT *dimensions in mm, unless specified*

Frame	Size	43	47	51	54	56
Rider height, in.		38.9	39.1	39.5	40.4	42.6
	cm	99	99	100	103	108
Handlebar	width	380	380	380	380	380
Stem	length					
	angle					
Headset spacers						
Crank	length	165	165	170	170	170
Seatpost	length	250	250	250	250	250
Steerer	length	114	123	114	123	139

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.5	72.5	72.0	72.5	73.8
Fork offset	35.0	35.0	35.0	45.0	45.0
Trail	58	58	60	57	54
Seat tube angle	76.0	75.0	75.0	74.0	73.5
Effective top tube	485	497	506	527	560
Seat tube	430	470	510	540	560
Standover	683	713	743	772	792
Wheelbase	952	956	977	980	994
Bottom bracket height	265	267	267	266	268
Chainstay	412	412	417	417	417
Head tube	116	125	116	125	141

GEARING

	30 42 52
12	61 86 106
13	57 79 98
14	52 73 91
15	49 69 85
17	43 60 75
19	39 54 67
21	35 49 61
23	32 45 55
26	28 40 49

Trek 1400

1426000*15.074

FRAMESET

Main tubes	Alpha SL aluminum	
Stays	Alpha SL aluminum	
Color	Metallic black/ Brushed aluminum	
Fork	Carbon, mm axle-crown length	
Headset	Sealed, semi-cartridge	25.4/41.4/30.0, mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Select	
Shift levers	Shimano 105 STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano 105	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur . . .	Shimano 105	
Crankset	Shimano 105 53/39	130mm bolt hole circle
Bottom bracket . . .	Shimano 105	68 x 109.5 (shell x axle,mm), Shimano splined axle
Chain	Shimano HG-73	9 speed, 108 links
Cassette	Shimano HG50 12-25, 9spd	

WHEELSET

Front wheel	Bontrager Select, 20°	593mm ERD
Spokes	DT 14g, ProLock brass nipples, 281mm, radial	
Tire	Bontrager Race Lite, 700 x 23c, Velox 16mm rim strip	
Rear wheel	Bontrager Select, 24°	603mm ERD
Spokes	DT 14g, ProLock brass nipples, 293/294mm, 2x	
Tire	Bontrager Race Lite, 700 x 23c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Carbon	27.2mm outer diameter
Saddle	Bontrager Race	
Seatpost binder . . .		31.8mm inner diameter
Brakes	Shimano 105	
Pedals	-not supplied-	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	43	50	52	54	56	58	60	63
Rider height, in.		41.1	40.5	48.5	42.0	42.7	43.4	44.4	45.4
	cm	104	103	123	107	109	110	113	115
Handlebar	width	380	380	400	400	420	420	440	440
Stem	length			90					
	angle			7					
Headset spacers				45					
Crank	length	170	170	170	172.5	172.5	175	175	175
Seatpost	length								
Steerer	length	139.5	94.5	94.5	102.5	120.5	138	156.5	187

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	71.5	71.5	72.5	73.0	73.0	73.5	74.0
Fork offset	47.0	47.0	47.0	47.0	43.0	43.0	43.0	43.0
Trail	67	64	64	58	59	59	56	53
Seat tube angle	75.0	75.0	75.0	74.5	73.8	73.5	73.5	72.5
Effective top tube	527	521	526	544	560	571	581	601
Seat tube	430	500	520	540	560	580	600	630
Standover	696	740	755	770	790	808	827	856
Wheelbase	1002	1002	1002	1004	1006	1014	1020	1024
Bottom bracket height	266	266	266	266	268	268	268	268
Chainstay	417	417	417	417	417	417	417	417
Head tube	97	97	97	105	123	140	159	189

GEARING

	39 53
12	86 117
13	79 108
14	74 100
15	69 93
17	61 82
19	54 74
21	49 67
23	45 61
25	41 56 0

Trek 1400T

1427000*15.074

FRAMESET

Main tubes	Alpha SL aluminum	
Stays	Alpha SL aluminum	
Color	Metallic black/ Brushed aluminum	
Fork	Carbon, mm axle-crown length	
Headset	Sealed, semi-cartridge	25.4/41.4/30.0, mm stack height

CONTROLS

Handlebar	Bontrager Select	31.8mm clamp diameter
Stem	Bontrager Select	
Shift levers	Shimano 105 STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano 105 T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur . . .	Shimano 105	
Crankset	Shimano 105 52/42/30	74/130mm bolt hole circle
Bottom bracket . . .	Shimano 105	68 x 109.5 (shell x axle,mm), Shimano splined axle
Chain	Shimano HG-73	9 speed, 108 links
Cassette	Shimano HG50 12-25, 9spd	

WHEELSET

Front wheel	Bontrager Select, 20°	593mm ERD
Spokes	DT 14g, ProLock brass nipples, 281mm, radial	
Tire	Bontrager Race Lite, 700 x 23c, Velox 16mm rim strip	
Rear wheel	Bontrager Select, 24°	603mm ERD
Spokes	DT 14g, ProLock brass nipples, 293/294mm, 2x	
Tire	Bontrager Race Lite, 700 x 23c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Carbon	27.2mm outer diameter
Saddle	Bontrager Race	
Seatpost binder . . .		31.8mm inner diameter
Brakes	Shimano 105	
Pedals	-not supplied-	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	43	50	52	54	56	58	60	63
Rider height, in.		41.1	40.5	48.5	42.0	42.7	43.4	44.4	45.4
	cm	104	103	123	107	109	110	113	115
Handlebar	width	380	380	400	400	420	420	440	440
Stem	length			90					
	angle			7					
Headset spacers				45					
Crank	length	170	170	170	172.5	172.5	175	175	175
Seatpost	length								
Steerer	length	139.5	94.5	94.5	102.5	120.5	138	156.5	187

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	71.5	71.5	72.5	73.0	73.0	73.5	74.0
Fork offset	47.0	47.0	47.0	47.0	43.0	43.0	43.0	43.0
Trail	67	64	64	58	59	59	56	53
Seat tube angle	75.0	75.0	75.0	74.5	73.8	73.5	73.5	72.5
Effective top tube	527	521	526	544	560	571	581	601
Seat tube	430	500	520	540	560	580	600	630
Standover	696	740	755	770	790	808	827	856
Wheelbase	1002	1002	1002	1004	1006	1014	1020	1024
Bottom bracket height	266	266	266	266	268	268	268	268
Chainstay	417	417	417	417	417	417	417	417
Head tube	97	97	97	105	123	140	159	189

GEARING

	30	42	52
12	66	93	115
13	61	85	106
14	57	79	98
15	53	74	92
17	47	65	81
19	42	58	72
21	38	53	66
23	35	48	60
25	32	44	55

Trek 1200 D

FRAMESET

Main tubes	Alpha SL aluminum	
Stays	Alpha SL aluminum	
Color	Metallic black/ Brushed aluminum	
Fork	Bontrager Carbon, 377mm axle-crown length	
Headset	Sealed, semi-cartridge	25.4/41.4/30.0, 36.3mm stack height

CONTROLS

Handlebar	Bontrager Sport	25.4mm clamp diameter
Stem	Bontrager Select	40.0mm steerer clamp height
Shift levers	Shimano Tiagra STI	
Brake levers	Integrated brake/shift	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano Tiagra	Down pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano 105	
Crankset	Bontrager Select 53/39	64/106mm bolt hole circle
Bottom bracket . . .		68 x 108 (shell x axle,mm), Square axle
Chain		9 speed, 108 links
Cassette	SRAM PG950 12-26, 9spd	

WHEELSET

Front wheel	Shimano Tiagra hub, 32°, Alex rim	633.5mm ERD
Spokes	14g, 294mm, 3x	
Tire	Bontrager Select, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Shimano Tiagra hub, 32°, Alex rim	633.5mm ERD
Spokes	14g, 291/293mm, 3x	
Tire	Bontrager Select, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Carbon	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .		31.8mm inner diameter
Brakes	Alloy dual pivot front, Alloy dual pivot rear	
Pedals	Wellgo Road, clipless 9/16" axle	
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	43	50	52	54	56	58	60	63
Rider height, in.		65.1	66.6	67.9	70.5	71.2	73.2	75.4	77.9
	cm	165	169	172	179	181	186	191	198
Handlebar	width	380	380	400	400	420	420	440	440
Stem	length	60	80	90	100	100	110	120	130
	angle	10	17	17	17	17	17	17	17
Headset	spacers	30	30	30	30	30	30	30	30
Crank	length	165	170	170	170	170	175	175	175
Seatpost	length	250	250	250	250	250	250	250	250
Steerer	length	200	200	200	208	226	244	262	293

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	71.5	71.5	72.5	73.0	73.0	73.5	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	67	64	64	58	59	59	56	53
Seat tube angle	75.0	75.0	75.0	74.5	73.8	73.5	73.5	72.5
Effective top tube	527	521	526	544	560	571	581	601
Seat tube	430	500	520	540	560	580	600	630
Standover	696	740	755	770	790	808	827	856
Wheelbase	1002	1002	1002	1004	1006	1014	1020	1024
Bottom bracket height	266	266	266	266	268	268	268	268
Chainstay	417	417	417	417	417	417	417	417
Head tube	97	97	97	105	123	140	159	189

GEARING

	39 53
12	86 117
13	79 108
14	74 100
15	69 93
17	61 82
19	54 74
21	49 67
23	45 61
26	40 54 0

Trek 1200 T

FRAMESET

Main tubes	Alpha SL aluminum	
Stays	Alpha SL aluminum	
Color	Metallic black/ Brushed aluminum	
Fork	Bontrager Carbon, 377mm axle-crown length	
Headset	Sealed, semi-cartridge	25.4/41.4/30.0, 36.3mm stack height

CONTROLS

Handlebar	Bontrager Sport	25.4mm clamp diameter
Stem	Bontrager Select	40.0mm steerer clamp height
Shift levers	Shimano Tiagra STI	
Brake levers	Integrated brake/shift	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano Tiagra	Down pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano 105	
Crankset	Bontrager Select 52/42/30	64/106mm bolt hole circle
Bottom bracket . . .		68 x 118 (shell x axle,mm), Square axle
Chain		9 speed, 108 links
Cassette	SRAM PG950 12-26, 9spd	

WHEELSET

Front wheel	Shimano Tiagra hub, 32°, Alex rim	633.5mm ERD
Spokes	14g, 294mm, 3x	
Tire	Bontrager Select, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Shimano Tiagra hub, 32°, Alex rim	633.5mm ERD
Spokes	14g, 291/293mm, 3x	
Tire	Bontrager Select, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Carbon	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .		31.8mm inner diameter
Brakes	Alloy dual pivot front, Alloy dual pivot rear	
Pedals	Wellgo Road, clipless 9/16" axle	
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	43	50	52	54	56	58	60	63
Rider height, in.		65.1	66.6	67.9	70.5	71.2	73.2	75.4	77.9
	cm	165	169	172	179	181	186	191	198
Handlebar	width	380	380	400	400	420	420	440	440
Stem	length	60	80	90	100	100	110	120	130
	angle	10	17	17	17	17	17	17	17
Headset spacers		30	30	30	30	30	30	30	30
Crank	length	165	170	170	170	170	175	175	175
Seatpost	length	250	250	250	250	250	250	250	250
Steerer	length	200	200	200	208	226	244	262	293

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	71.5	71.5	72.5	73.0	73.0	73.5	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	67	64	64	58	59	59	56	53
Seat tube angle	75.0	75.0	75.0	74.5	73.8	73.5	73.5	72.5
Effective top tube	527	521	526	544	560	571	581	601
Seat tube	430	500	520	540	560	580	600	630
Standover	696	740	755	770	790	808	827	856
Wheelbase	1002	1002	1002	1004	1006	1014	1020	1024
Bottom bracket height	266	266	266	266	268	268	268	268
Chainstay	417	417	417	417	417	417	417	417
Head tube	97	97	97	105	123	140	159	189

GEARING

	30	42	52
12	66	93	115
13	61	85	106
14	57	79	98
15	53	74	92
17	47	65	81
19	42	58	72
21	38	53	66
23	35	48	60
26	31	43	53

Trek 1000 D

FRAMESET

Main tubes	Alpha SL aluminum	
Stays	Alpha SL aluminum	
Color	Metallic Orange/Pearl White	
	Black Chrome/Smooth Silver	
Fork	Bontrager Carbon, 377mm axle-crown length	
Headset	Aheadset, semi-cartridge	25.4/41.4/30.0, 36.3mm stack height

CONTROLS

Handlebar	Bontrager Sport	25.4mm clamp diameter
Stem	Bontrager Select	40.0mm steerer clamp height
Shift levers	Shimano Sora STI	
Brake levers	Integrated brake/shift	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano 2203	Down pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Tiagra	
Crankset	Bontrager Sport 53/39	74/130mm bolt hole circle
Bottom bracket . . .		68 x 110.5 (shell x axle,mm), Square axle
Chain		3/32", 108 links
Cassette	SRAM PG850 12-26, 8spd	

WHEELSET

Front wheel	Alloy, QR hub, 32°, Alex rim	633.5mm ERD
Spokes	14g, 294mm, 3x	
Tire	Bontrager Select, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Alloy, QR hub, 32°, Alex rim	633.5mm ERD
Spokes	14g, 291/293mm, 3x	
Tire	Bontrager Select, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .		31.8mm inner diameter
Brakes	Alloy dual pivot front, Alloy dual pivot rear	
Pedals	Alloy/nylon road, w/clips and straps	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	43	50	52	54	56	58	60	63
Rider height, in.		65.1	66.6	67.9	70.5	71.2	73.2	75.4	77.9
	cm	165	169	172	179	181	186	191	198
Handlebar	width	380	380	400	400	420	420	440	440
Stem	length	60	80	90	100	100	110	120	130
	angle	10	17	17	17	17	17	17	17
Headset spacers		30	30	30	30	30	30	30	30
Crank	length	165	170	170	170	170	175	175	175
Seatpost	length	250	250	250	250	250	250	250	250
Steerer	length	200	200	200	208	226	244	262	293

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	71.5	71.5	72.5	73.0	73.0	73.5	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	67	64	64	58	59	59	56	53
Seat tube angle	75.0	75.0	75.0	74.5	73.8	73.5	73.5	72.5
Effective top tube	527	521	526	544	560	571	581	601
Seat tube	430	500	520	540	560	580	600	630
Standover	696	740	755	770	790	808	827	856
Wheelbase	1002	1002	1002	1004	1006	1014	1020	1024
Bottom bracket height	266	266	266	266	268	268	268	268
Chainstay	417	417	417	417	417	417	417	417
Head tube	97	97	97	105	123	140	159	189

GEARING

	39	53
12	86	117
13	79	108
15	69	93
17	61	82
19	54	74
21	49	67
23	45	61
26	40	54

Trek 1000T

FRAMESET

Main tubes	Alpha SL aluminum	
Stays	Alpha SL aluminum	
Color	Metallic Orange/Pearl White	
	Black Chrome/Smooth Silver	
Fork.	Bontrager Carbon, 377mm axle-crown length	
Headset	Aheadset, semi-cartridge	25.4/41.4/30.0, 36.3mm stack height

CONTROLS

Handlebar	Bontrager Sport	25.4mm clamp diameter
Stem	Bontrager Select	40.0mm steerer clamp height
Shift levers	Shimano Sora STI	
Brake levers	Integrated brake/shift	
Grips		

DRIVETRAIN

Front derailleur . . .	Shimano 2203	Down pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Tiagra	
Crankset	Bontrager Sport 52/42/30	74/130mm bolt hole circle
Bottom bracket . . .		68 x 113 (shell x axle,mm), Square axle
Chain.		3/32", 108 links
Cassette.	SRAM PG850 12-26, 8spd	

WHEELSET

Front wheel.	Alloy, QR hub, 32°, Alex rim	633.5mm ERD
Spokes	14g, 294mm, 3x	
Tire	Bontrager Select, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Alloy, QR hub, 32°, Alex rim	633.5mm ERD
Spokes	14g, 291/293mm, 3x	
Tire	Bontrager Select, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost.	Bontrager Sport	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder. . . .		31.8mm inner diameter
Brakes	Alloy dual pivot front, Alloy dual pivot rear	
Pedals	Alloy/nylon road, w/clips and straps	9/16" axle
Additional		

FIT

dimensions in mm, unless specified

Frame	Size	43	50	52	54	56	58	60	63
Rider height, in.		65.1	66.6	67.9	70.5	71.2	73.2	75.4	77.9
	cm	165	169	172	179	181	186	191	198
Handlebar	width	380	380	400	400	420	420	440	440
Stem	length	60	80	90	100	100	110	120	130
	angle	10	17	17	17	17	17	17	17
Headset spacers		30	30	30	30	30	30	30	30
Crank	length	165	170	170	170	170	175	175	175
Seatpost	length	250	250	250	250	250	250	250	250
Steerer	length	200	200	200	208	226	244	262	293

GEOMETRY

dimensions in mm, unless specified

Head tube angle	71.0	71.5	71.5	72.5	73.0	73.0	73.5	74.0
Fork offset	45.0	45.0	45.0	45.0	45.0	45.0	45.0	45.0
Trail	67	64	64	58	59	59	56	53
Seat tube angle	75.0	75.0	75.0	74.5	73.8	73.5	73.5	72.5
Effective top tube	527	521	526	544	560	571	581	601
Seat tube	430	500	520	540	560	580	600	630
Standover	696	740	755	770	790	808	827	856
Wheelbase	1002	1002	1002	1004	1006	1014	1020	1024
Bottom bracket height	266	266	266	266	268	268	268	268
Chainstay	417	417	417	417	417	417	417	417
Head tube	97	97	97	105	123	140	159	189

GEARING

	30	42	52
12	66	93	115
13	61	85	106
15	53	74	92
17	47	65	81
19	42	58	72
21	38	53	66
23	35	48	60
26	31	43	53

FRAMESET

Main tubes	Alpha SL aluminum	
Stays	Alpha SL aluminum	
Color	Pearl White/ Brushed Aluminum	
Fork	Bontrager Carbon, 330mm axle-crown length	
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 36.3mm stack height

CONTROLS

Handlebar	Bontrager Sport	26.0mm clamp diameter
Stem	Bontrager Select	40.0mm steerer clamp height
Shift levers	Shimano Sora STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano 2203	Down pull, 34.9 mm/ 1 3/8" attachment
Rear derailleur . . .	Shimano Tiagra GS	
Crankset	Bontrager Sport 52/42/30	64/106mm bolt hole circle
Bottom bracket . . .		68 x 113 (shell x axle,mm), Square axle
Chain	Shimano HG-53	3/32", 108 links
Cassette	SRAM PG850 12-26, 8spd	

WHEELSET

Front wheel	Alloy, QR hub, 20°, Alex rim	544mm ERD
Spokes	14g, 267mm, 3x	
Tire	Bontrager Select, 650 x 25c, Velox 16mm rim strip	
Rear wheel	Alloy, QR hub, 24°, Alex rim	549mm ERD
Spokes	14g, 265/268mm, 3x	
Tire	Bontrager Select, 650 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Sport	27.2mm outer diameter
Saddle	Bontrager Select WSD	
Seatpost binder . . .		31.8mm inner diameter
Brakes	Alloy dual pivot front, Alloy dual pivot rear	
Pedals	Alloy/nylon road, w/clips and straps	9/16" axle
Additional	see 1500T for 700c wheel sizes	

FIT *dimensions in mm, unless specified*

Frame	Size	43	47	51	54	56
Rider height, in.		61.6	62.0	64.0	66.0	68.9
	cm	156	158	163	168	175
Handlebar	width	380	380	400	400	400
Stem	length	60	60	80	90	90
	angle	10	10	17	17	17
Headset spacers		30	30	30	30	30
Crank	length	165	165	170	170	170
Seatpost	length	250	250	250	250	250
Steerer	length	209	217	200	208	226

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.5	72.5	72.0	72.5	73.8
Fork offset	35.0	35.0	35.0	45.0	45.0
Trail	58	58	60	57	54
Seat tube angle	76.0	75.0	75.0	74.0	73.5
Effective top tube	485	497	506	527	560
Seat tube	430	470	510	540	560
Standover	683	713	743	772	792
Wheelbase	952	956	977	980	994
Bottom bracket height	265	267	267	266	268
Chainstay	412	412	417	417	417
Head tube	116	125	116	125	141

GEARING

	30	42	52
12	61	86	106
13	57	79	98
15	49	69	85
17	43	60	75
19	39	54	67
21	35	49	61
23	32	45	55
26	28	40	49

Trek 1000 KDR

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color	Team	
Fork	Aluminum, 330mm axle-crown length	
Headset	Aheadset, semi-cartridge	25.4/34.0/30.0, 36.3mm stack height

CONTROLS

Handlebar	Bontrager Sport	26.0mm clamp diameter
Stem	Bontrager Sport	40.0mm steerer clamp height
Shift levers	Shimano Sora STI	
Grips	Bontrager	

DRIVETRAIN

Front derailleur . . .	Shimano 2200	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur . . .	Shimano Tiagra	
Crankset	Bontrager Sport 48/39	64mm bolt hole circle
Bottom bracket . . .	Cartridge	68 x 110.5 (shell x axle,mm), Square axle
Chain	KMC Z51	3/32", 102 links
Cassette	SRAM PG850 12-23, 8spd	

WHEELSET

Front wheel	Alloy, QR hub, 32°, Alex rim	mm ERD
Spokes	14g stainless, 252.5mm, 3x	
Tire, 24 x 1, Velox 16mm rim strip		
Rear wheel	Alloy, QR hub, 32°, Alex rim	mm ERD
Spokes	14g stainless, 250/252.5mm, 3x	
Tire, 24 x 1, Velox 16mm rim strip		
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager	27.2mm outer diameter
Saddle	Bontrager	
Seatpost binder . . .	Alloy w/integral bolt	31.8mm inner diameter
Brakes	Alloy dual pivot, cartridge pads	
Pedals	Alloy platform, clipless adaptable	9/16" axle
Additional	Alloy mid-line brake levers	

FIT *dimensions in mm, unless specified*

Frame	Size	40
Rider height, in.		57.5
	cm	146
Handlebar	width	380
Stem	length	60
	angle	10
Headset spacers		20
Crank	length	150
Seatpost	length	300
Steerer	length	183

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0
Fork offset	40.0
Trail	
Seat tube angle	76.0
Effective top tube	450
Seat tube	345
Standover	
Wheelbase	856
Bottom bracket height	282
Chainstay	385
Head tube	90

GEARING

	39 48
12	80 98
13	74 91
14	68 84
15	64 79
17	56 69
19	50 62
21	46 56
23	42 51

Trek Pilot 5.9

1411000*15.104
Bike weight: 17.2 lb/7.81 kg

FRAMESET

Main tubes	OCV 110 carbon fiber composite	
Stays	OCV VC carbon	
Color	Pearl carbon	
Fork	Bontrager Satellite Plus, 381mm axle-crown length	
Headset	Slimstack	25.4/34.0/30.0, 39.6mm stack height

CONTROLS

Handlebar	Bontrager Race X Lite	31.8mm clamp diameter
Stem	Bontrager Race XXX Lite	40.0mm steerer clamp height
Shift levers	Shimano Dura-Ace STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano Dura-Ace	Down pull, Braze-on type attachment
Rear derailleur . . .	Shimano Dura-Ace	
Crankset	Bontrager Race X Lite 50/36 w/Giga-X-Pipe	64/104mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano Dura-Ace	10 speed, 108 links
Cassette	Shimano Dura-Ace 12-27, 10spd	

WHEELSET

Front wheel	Bontrager Race X Lite , 20°	592mm ERD
Spokes	DT Aerolite nail-head, internal alloy nipples, 286mm, radial	
Tire	Bontrager Race X Lite AC, 700 x 25c, Bontrager, 17.5mm rim strip	
Rear wheel	Bontrager Race X Lite , 24°	595mm ERD
Spokes	DT New Aero, Aerolite nail-head non-drive side, internal alloy nipples, 291/286mm, 2x/radial	
Tire	Bontrager Race X Lite AC, 700 x 25c, Bontrager, 17.5mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race XXX Lite	27.2mm outer diameter
Saddle	Bontrager Race Lite Luxe	
Seatpost binder . . .	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano Ultegra, long reach	
Pedals	-not supplied- axle	
Additional	Buzz-Kill	

FIT *dimensions in mm, unless specified*

Frame	Size	50	52	54	56	58	63
Rider height, in.		66.6	68.7	70.4	71.5	73.2	76.4
	cm	169	174	179	182	186	194
Handlebar	width	380	400	400	420	420	440
Stem	length	80	90	100	100	110	130
	angle	12	12	12	12	12	12
Headset spacers		25	25	25	25	25	25
Crank	length	170	170	172.5	172.5	175	175
Seatpost	length	330	330	330	330	330	330
Steerer	length	220.6	220.6	237.6	250.6	270.6	290.6

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.4	71.9	72.4	72.5	72.6	72.6
Fork offset	50.0	50.0	50.0	45.0	45.0	45.0
Trail	63	59	56	61	60	60
Seat tube angle	74.5	74.8	73.8	73.3	72.7	72.1
Effective top tube	520	531	545	562	570	590
Seat tube	450	470	490	510	530	580
Standover	722	734	751	768	786	824
Wheelbase	985	993	995	1003	1006	1021
Bottom bracket height	277	274	274	276	276	277
Chainstay	413	413	415	415	417	417
Head tube	123	123	140	153	173	193

GEARING

	36 50
12	81 112
13	75 104
14	69 96
15	65 90
16	61 84
17	57 79
19	51 71
21	46 64
23	42 59 0
25	39 54 0

FRAMESET

Main tubes	OCV 110 carbon fiber composite	
Stays	OCV VC carbon	
Color	Black Pearl Carbon	
Fork	Bontrager Satellite Plus, 381390mm axle-crown length	
Headset	Slimstack	25.4/34.0/30.0, 39.6mm stack height

CONTROLS

Handlebar	Bontrager Race X Lite	31.8mm clamp diameter
Stem	Bontrager Race XXX Lite	40.0mm steerer clamp height
Shift levers	Shimano Dura-Ace STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano Dura-Ace	Down pull, Plate style w/34.9mm clamp attachment
Rear derailleur . . .	Shimano Dura-Ace	
Crankset	Bontrager Race X Lite 50/36 w/Giga-X-Pipe	64/104mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano Dura-Ace	10 speed, 108 links
Cassette	Shimano Dura-Ace 12-27, 10spd	

WHEELSET

Front wheel	Bontrager Race X Lite , 20°	592mm ERD
Spokes	DT Aerolite nail-head, internal alloy nipples, 286mm, radial	
Tire	Bontrager Race X Lite AC, 700 x 25c, Bontrager, 17.5mm rim strip	
Rear wheel	Bontrager Race X Lite , 24°	595mm ERD
Spokes	DT New Aero, Aerolite nail-head non-drive side, internal alloy nipples, 291/286mm, 2x/radial	
Tire	Bontrager Race X Lite AC, 700 x 25c, Bontrager, 17.5mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race XXX Lite	27.2mm outer diameter
Saddle	Bontrager Race Lite WSD	
Seatpost binder . . .	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano Ultegra, long reach	
Pedals	-not supplied- 9/16" axle	
Additional	BuzzKill	

FIT*dimensions in mm, unless specified*

Frame	Size	47	50	54	56
Rider height, in.		66.0	67.5	70.5	71.2
	cm	168	172	179	181
Handlebar	width	380	380	380	380
Stem	length	80	90	100	90
	angle	12	12	12	12
Headset spacers		25	25	25	25
Crank	length	170	170	172.5	172.5
Seatpost	length	330	330	330	330
Steerer	length	220.6	220.6	237.6	250.6

GEOMETRY*dimensions in mm, unless specified*

Head tube angle	70.5	71.2	71.4	72.5
Fork offset	50.0	50.0	50.0	45.0
Trail				
Seat tube angle	74.5	74.3	74.0	73.3
Effective top tube	508	517	540	562
Seat tube	430	450	490	510
Standover	712	722	750	768
Wheelbase	980	982	1002	1003
Bottom bracket height	277	278	273	276
Chainstay	413	413	415	415
Head tube	123	123	140	153

GEARING

	36 50
12	81 112
13	75 104
14	69 96
15	65 90
16	61 84
17	57 79
19	51 71
21	46 64
23	42 59 0
25	39 54 0

Trek Pilot 5.2

1409000*15.104
Bike weight: 18.7 lb/8.49 kg

FRAMESET

Main tubes	OCV 120 carbon fiber composite
Stays	OCV VC carbon
Color	Pewter carbon
Fork	Bontrager Satellite Plus, 381mm axle-crown length
Headset	Slimstack 25.4/34.0/30.0, 39.6mm stack height

CONTROLS

Handlebar	Bontrager Race Flat Top	26.0mm clamp diameter
Stem	Bontrager Race	40.0mm steerer clamp height
Shift levers	Shimano Ultegra STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano Ultegra T, attachment
Rear derailleur	Shimano Ultegra GS
Crankset	Shimano Ultegra 52/39/30 74/130mm bolt hole circle
Bottom bracket	(shell x axle,mm), axle
Chain	10 speed, links
Cassette	Shimano Ultegra 12-25, 10spd

WHEELSET

Front wheel	Bontrager Race Lite, 20°	592mm ERD
Spokes	DT New Aero, ProLock alloy nipples, 279mm, radial	
Tire	Bontrager Race X Lite AC, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Race Lite, 24°	595mm ERD
Spokes	DT New Aero, T-head drive side, ProLock alloy nipples, 291/293mm, 2x	
Tire	Bontrager Race X Lite AC, 700 x 25c, Velox 16mm rim strip	
Inner tubes		

OTHER

Seatpost	Bontrager Race X Lite	mm outer diameter
Saddle	Bontrager Race Lite Luxe	
Seatpost binder	Alloy w/integral bolt	mm inner diameter
Brakes	Shimano Ultegra, long reach	
Pedals	-not supplied-	axle
Additional	Buzz-Kill handlebar dampers	

FIT *dimensions in mm, unless specified*

Frame	Size	50	52	54	56	58	63
Rider height, in.		67.0	69.1	70.8	71.9	73.6	76.8
	cm	170	175	180	183	187	195
Handlebar	width	380	400	400	420	420	440
Handlebar	rise	0	0	0	0	0	0
Stem	length	80	90	100	100	110	130
	angle	17	17	17	17	17	17
Headset spacers		25	25	25	25	25	25
Crank	length	170	170	172.5	172.5	175	175
Seatpost	length	330	330	330	330	330	330
Steerer	length	220.6	224.6	237.6	254.6	270.6	290.6

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.4	71.9	72.4	72.5	72.6	72.6
Fork offset	50.0	50.0	50.0	45.0	45.0	45.0
Trail	63	59	56	61	60	60
Seat tube angle	74.5	74.8	73.8	73.3	72.7	72.1
Effective top tube	520	531	545	562	570	590
Seat tube	450	470	490	510	530	580
Standover	722	734	751	768	786	824
Wheelbase	985	993	995	1003	1006	1021
Bottom bracket height	277	274	274	276	276	277
Chainstay	413	413	415	415	417	417
Head tube	123	123	140	153	173	193

GEARING

	30	39	52
12	67	88	117
13	62	81	108
14	58	75	100
15	54	70	93
16	50	66	88
17	48	62	82
19	43	55	74
21	38	50	67
23	35	46	61
25	32	42	56

FRAMESET

Main tubes	OCV 120 carbon fiber composite	
Stays	OCV VC carbon	
Color	Pewter Carbon	
Fork	Bontrager Satellite Plus, 381390mm axle-crown length	
Headset	Slimstack	25.4/34.0/30.0, 39.6mm stack height

CONTROLS

Handlebar	Bontrager Race Flat Top	26.0mm clamp diameter
Stem	Bontrager Race	40.0mm steerer clamp height
Shift levers	Shimano Ultegra STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano Ultegra T	Down pull, Plate style w/34.9mm clamp attachment
Rear derailleur . . .	Shimano Ultegra GS	
Crankset	Shimano Ultegra 52/42/30	74/130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano Ultegra	10 speed, 108 links
Cassette	Shimano Ultegra 12-25, 10spd	

WHEELSET

Front wheel	Bontrager Race Lite, 20°	592mm ERD
Spokes	DT New Aero, ProLock alloy nipples, 279mm, radial	
Tire	Bontrager Race X Lite AC, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Race Lite, 24°	595mm ERD
Spokes	DT New Aero, T-head drive side, ProLock alloy nipples, 291/293mm, 2x	
Tire	Bontrager Race X Lite AC, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race X Lite	27.2mm outer diameter
Saddle	Bontrager Race Lite WSD	
Seatpost binder . . .	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano Ultegra, long reach	
Pedals	-not supplied- 9/16" axle	
Additional	BuzzKill	

FIT *dimensions in mm, unless specified*

Frame	Size	47	50	54	56
Rider height, in.		66.4	67.9	70.9	71.6
	cm	169	173	180	182
Handlebar	width				
Handlebar	rise	0	0	0	0
Stem	length	80	90	100	90
	angle	17	17	17	17
Headset spacers		25	25	25	25
Crank	length	165	170	170	170
Seatpost	length	330	330	330	330
Steerer	length	220.6	220.6	241.6	254.6

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	71.2	71.4	72.5
Fork offset	50.0	50.0	50.0	45.0
Trail				
Seat tube angle	74.5	74.3	74.0	73.3
Effective top tube	508	517	540	562
Seat tube	430	450	490	510
Standover	712	722	750	768
Wheelbase	980	982	1002	1003
Bottom bracket height	277	278	273	276
Chainstay	413	413	415	415
Head tube	123	123	140	153

GEARING

	30 42 52
12	67 94 117
13	62 87 108
14	58 81 100
15	54 75 93
16	50 71 88
17	48 67 82
19	43 60 74
21	38 54 67
23	35 49 61
25	32 45 56

Trek Pilot 5.0

1408000*15.104
Bike weight: 19.1 lb/8.67 kg

FRAMESET

Main tubes	OCV 120 carbon fiber composite
Stays	OCV VC carbon
Color	Blue carbon
Fork	Bontrager Satellite Plus, 381mm axle-crown length
Headset	Slimstack 25.4/34.0/30.0, 39.6mm stack height

CONTROLS

Handlebar	Bontrager Race Flat Top	26.0mm clamp diameter
Stem	Bontrager Race	40.0mm steerer clamp height
Shift levers	Shimano 105 STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano 105 T, attachment	
Rear derailleur	Shimano Dura-Ace GS	
Crankset	Bontrager Race Lite 52/42/30 w/Giga-X-Pipe	74/130mm bolt hole circle
Bottom bracket	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano HG-73	9 speed, 108 links
Cassette	SRAM PG970 12-26, 9spd	

WHEELSET

Front wheel	Bontrager Race, 20°	593mm ERD
Spokes	DT New Aero, ProLock brass nipples, 280mm, radial	
Tire	Bontrager Race X Lite AC, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Race, 24°	603mm ERD
Spokes	DT New Aero, ProLock brass nipples, 294/294mm, 2x	
Tire	Bontrager Race X Lite AC, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race X Lite	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano, long reach front, Shimano 105, long reach rear	
Pedals	-not supplied- axle	
Additional	Buzz-Kill	

FIT *dimensions in mm, unless specified*

Frame	Size	50	52	54	56	58	63
Rider height, in.		67.0	69.1	70.8	71.9	73.6	76.8
	cm	170	175	180	183	187	195
Handlebar	width	380	400	400	420	420	440
Handlebar	rise	0	0	0	0	0	0
Stem	length	80	90	100	100	110	130
	angle	17	17	17	17	17	17
Headset	spacers	25	25	25	25	25	25
Crank	length	170	170	172.5	172.5	175	175
Seatpost	length	330	330	330	330	330	330
Steerer	length	220.6	224.6	237.6	254.6	270.6	290.6

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.4	71.9	72.4	72.5	72.6	72.6
Fork offset	50.0	50.0	50.0	45.0	45.0	45.0
Trail	63	59	56	61	60	60
Seat tube angle	74.5	74.8	73.8	73.3	72.7	72.1
Effective top tube	520	531	545	562	570	590
Seat tube	450	470	490	510	530	580
Standover	722	734	751	768	786	824
Wheelbase	985	993	995	1003	1006	1021
Bottom bracket height	277	274	274	276	276	277
Chainstay	413	413	415	415	417	417
Head tube	123	123	140	153	173	193

GEARING

	30	42	52
12	67	94	117
13	62	87	108
14	58	81	100
15	54	75	93
17	48	67	82
19	43	60	74
21	38	54	67
23	35	49	61
26	31	44	54

FRAMESET

Main tubes	OCV 120 carbon fiber composite	
Stays	OCV VC carbon	
Color	Blue Carbon	
	Bright Silver	
Fork	Bontrager Satellite Plus, 381390mm axle-crown length	
Headset	Slimstack	25.4/34.0/30.0, 39.6mm stack height

CONTROLS

Handlebar	Bontrager Race Flat Top	26.0mm clamp diameter
Stem	Bontrager Race	40.0mm steerer clamp height
Shift levers	Shimano 105 STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano 105 T	Down pull, Plate style w/34.9mm clamp attachment
Rear derailleur . . .	Shimano Dura-Ace GS	
Crankset	Bontrager Race Lite 52/42/30 w/Giga-X-Pipe	74/130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano HG-73	9 speed, 108 links
Cassette	SRAM PG970 12-26, 9spd	

WHEELSET

Front wheel	Bontrager Race, 20°	593mm ERD
Spokes	DT New Aero, ProLock brass nipples, 280mm, radial	
Tire	Bontrager Race X Lite AC, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Race, 24°	603mm ERD
Spokes	DT New Aero, ProLock brass nipples, 294/294mm, 2x	
Tire	Bontrager Race X Lite AC, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Race X Lite	27.2mm outer diameter
Saddle	Bontrager Select WSD	
Seatpost binder . . .	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Shimano 105, long reach front, Shimano 105, long reach rear	
Pedals	-not supplied- 9/16" axle	
Additional	BuzzKill	

FIT*dimensions in mm, unless specified*

Frame	Size	47	50	54	56
Rider height, in.		66.4	67.9	70.9	71.6
	cm	169	173	180	182
Handlebar	width				
Handlebar	rise	0	0	0	0
Stem	length	80	90	100	90
	angle	17	17	17	17
Headset spacers		25	25	25	25
Crank	length	165	170	170	170
Seatpost	length	330	330	330	330
Steerer	length	220.6	220.6	237.6	254.6

GEOMETRY*dimensions in mm, unless specified*

Head tube angle	70.5	71.2	71.4	72.5
Fork offset	50.0	50.0	50.0	45.0
Trail				
Seat tube angle	74.5	74.3	74.0	73.3
Effective top tube	508	517	540	562
Seat tube	430	450	490	510
Standover	712	722	750	768
Wheelbase	980	982	1002	1003
Bottom bracket height	277	278	273	276
Chainstay	413	413	415	415
Head tube	123	123	140	153

GEARING

	30 42 52
12	67 94 117
13	62 87 108
14	58 81 100
15	54 75 93
17	48 67 82
19	43 60 74
21	38 54 67
23	35 49 61
26	31 44 54

Trek Pilot 2.1

1407000*15.104

FRAMESET

Main tubes		ZR9000	
Stays		OCLV 120 carbon fiber composite	
Color		Brushed aluminum	
Fork		Bontrager Satellite Plus, 381mm axle-crown length	
Headset		Cane Creek Internal	25.4/34.0/30.0, 20.6mm stack height

CONTROLS

Handlebar		Bontrager Select Flat Top	26.0mm clamp diameter
Stem		Bontrager Select	41.0mm steerer clamp height
Shift levers		Shimano 105 STI	
Brake levers		Integrated brake/shift	
Grips		Bontrager Gel	

DRIVETRAIN

Front derailleur		Shimano 105 T, Braze-on type w/34.9mm clamp attachment	
Rear derailleur		Shimano 105 GS	
Crankset		Bontrager Race 52/42/30	74/130mm bolt hole circle
Bottom bracket		TruVativ Giga-Pipe SL	68 x 118 (shell x axle,mm), ISIS splined axle
Chain		Shimano HG-53	9 speed, 108 links
Cassette		SRAM PG950 12-26, 9spd	

WHEELSET

Front wheel		Bontrager Select, 20°	593mm ERD
Spokes		DT 14g, ProLock brass nipples, 281mm, radial	
Tire		Bontrager Race Lite, folding, 700 x 25c, Velox 16mm rim strip	
Rear wheel		Bontrager Select, 24°	603mm ERD
Spokes		DT 14g, ProLock brass nipples, 293/294mm, 2x	
Tire		Bontrager Race Lite, folding, 700 x 25c, Velox 16mm rim strip	
Inner tubes		Presta valve, 48mm stem	

OTHER

Seatpost		Bontrager Select	mm outer diameter
Saddle		Bontrager Race Luxe	
Seatpost binder		Alloy w/integral bolt	32.1mm inner diameter
Brakes		Alloy dual pivot, long reach, cartridge pads	
Pedals		Alloy road, sealed, w/clips and straps	axle
Additional			

FIT *dimensions in mm, unless specified*

Frame	Size	50	52	54	56	58	63
Rider height, in.		66.2	68.6	69.9	71.1	72.8	75.9
	cm	168	174	178	181	185	193
Handlebar	width	380	400	400	420	420	440
Handlebar	rise	0	0	0	0	0	0
Stem	length	80	90	100	100	110	130
	angle	17	17	17	17	17	17
Headset spacers		20	20	20	20	20	20
Crank	length	170	170	170	170	175	175
Seatpost	length	330	330	330	330	330	330
Steerer	length	217.6	217.6	234.6	247.6	267.6	287.6

GEOMETRY *dimensions in mm, unless specified*

Head tube angle		71.4	71.9	72.4	72.5	72.6	72.6
Fork offset		50.0	50.0	50.0	45.0	45.0	45.0
Trail		63	59	56	61	60	60
Seat tube angle		74.5	74.8	73.8	73.3	72.7	72.1
Effective top tube		520	531	545	562	570	590
Seat tube		450	470	490	510	530	580
Standover		722	734	751	768	786	824
Wheelbase		985	993	995	1003	1006	1021
Bottom bracket height		277	274	274	276	276	277
Chainstay		413	413	415	415	417	417
Head tube		123	123	140	153	173	193

GEARING

	30 42 52
12	67 94 117
13	62 87 108
14	58 81 100
15	54 75 93
17	48 67 82
19	43 60 74
21	38 54 67
23	35 49 61
26	31 44 54

Trek Pilot WSD 2.1

1407003*15.104

FRAMESET

Main tubes	ZR9000	
Stays	OCLV 120 carbon fiber composite	
Color	Brushed Aluminum	
Fork	, 382mm axle-crown length	
Headset	Cane Creek Internal	25.4/34.0/30.0, 35.6mm stack height

CONTROLS

Handlebar	Bontrager Select Flat Top	26.0mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	Shimano 105 STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano 105 T	Down pull, Plate style w/34.9mm clamp attachment
Rear derailleur . . .	Shimano 105 GS	
Crankset	Bontrager Race 52/42/30	74/130mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe SL	68 x 118 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	SRAM PG950 12-26, 9spd	

WHEELSET

Front wheel	Bontrager Select, 20°	593mm ERD
Spokes	DT 14g, ProLock brass nipples, 281mm, radial	
Tire	Bontrager Race Lite, folding, 700 x 25c, Velox 16mm rim strip	
Rear wheel	Bontrager Select, 24°	603mm ERD
Spokes	DT 14g, ProLock brass nipples, 293/294mm, 2x	
Tire	Bontrager Race Lite, folding, 700 x 25c, Velox 16mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Select	27.2mm outer diameter
Saddle	Bontrager Select WSD	
Seatpost binder . . .	Alloy w/integral bolt	32.1mm inner diameter
Brakes	Alloy dual pivot, long reach, cartridge pads	
Pedals	Alloy road, sealed, w/clips and straps	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	47	50	54	56
Rider height, in.		65.0	67.4	70.4	71.0
	cm	165	171	179	180
Handlebar	width				
Handlebar	rise	0	0	0	0
Stem	length	80	90	100	90
	angle	17	17	17	17
Headset spacers		25	25	25	25
Crank	length	165	170	170	170
Seatpost	length	330	330	330	330
Steerer	length	222.6	222.6	239.6	252.6

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.5	71.2	71.4	72.5
Fork offset	50.0	50.0	50.0	45.0
Trail				
Seat tube angle	74.5	74.3	74.0	73.3
Effective top tube	508	517	540	562
Seat tube	430	450	490	510
Standover	712	722	750	768
Wheelbase	980	982	1002	1003
Bottom bracket height	277	278	273	276
Chainstay	413	413	415	415
Head tube	123	123	140	153

GEARING

	30 42 52
12	61 86 106
13	57 79 98
14	53 74 91
15	49 69 85
17	43 61 75
19	39 54 67
21	35 49 61
23	32 45 56
26	28 40 49

Trek 2300C

1455000*15.114
Bike weight: 21.7 lb/9.85 kg

FRAMESET

Main tubes		ZR9000	
Stays		OCLV 120, carbon fiber composite	
Color		Rage Red	
Fork		Bontrager Satellite Plus, 381mm axle-crown length	
Headset		Cane Creek Internal	25.4/34.0/30.0, 20.6mm stack height

CONTROLS

Handlebar		Bontrager Flat Top	25.4mm clamp diameter
Stem		Bontrager Select	41.0mm steerer clamp height
Shift levers		Shimano Ultegra STI	
Brake levers		Integrated brake/shift	
Grips		Bontrager Gel	

DRIVETRAIN

Front derailleur	...	Shimano Ultegra T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur		Shimano Ultegra GS	
Crankset		Shimano Ultegra 52/39/30	74/130mm bolt hole circle
Bottom bracket		integral axle	68 (shell x axle,mm), Integral axle
Chain		Shimano Ultegra	10 speed, 108 links
Cassette		Shimano Ultegra 12-25, 10spd	

WHEELSET

Front wheel		Bontrager Race, 20°	593mm ERD
Spokes		DT New Aero, ProLock brass nipples, 280mm, radial	
Tire		Bontrager Race Lite HardCase, 700 x 28c, Velox 16mm rim strip	
Rear wheel		Bontrager Race, 24°	603mm ERD
Spokes		DT New Aero, ProLock brass nipples, 294/294mm, 2x	
Tire		Bontrager Race Lite HardCase, 700 x 28c, Velox 16mm rim strip	
Inner tubes		Presta valve, 48mm stem	

OTHER

Seatpost		Bontrager Race X Lite	27.2mm outer diameter
Saddle		Bontrager Race CRZ+	
Seatpost binder		Alloy w/integral bolt	32.1mm inner diameter
Brakes		Shimano Ultegra, long reach	
Pedals		Shimano SPD M520, clipless	9/16" axle
Additional		Cane Creek CrossTop in-line levers, S.P.A. rear shock, BuzzKill	

FIT *dimensions in mm, unless specified*

Frame	Size	50	52	54	56	58	63
Rider height, in.		67.8	69.1	70.0	71.4	72.7	75.3
	cm	172	175	178	181	185	191
Handlebar	width	380	400	400	420	420	440
Handlebar	rise	0	0	0	0	0	0
Stem	length	80	90	90	100	100	110
	angle	25	25	25	25	25	25
Headset	spacers	40	40	40	40	40	40
Crank	length	170	170	172.5	172.5	175	175
Seatpost	length	330	330	330	330	330	330
Steerer	length	237.6	237.6	254.6	267.6	287.6	307.6

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.5	71.5	72.0	72.5	72.5	73.0
Fork offset	50.0	50.0	50.0	45.0	45.0	45.0
Trail	63	63	60	56	62	58
Seat tube angle	75.0	74.5	74.0	73.5	73.0	72.5
Effective top tube	525	530	545	550	570	590
Seat tube	511	516	528	531	548	580
Standover	736	748	758	768	779	818
Wheelbase	1020	1020	1026	1021	1030	1039
Bottom bracket height	266	266	266	266	266	266
Chainstay	435	435	435	435	435	435
Head tube	140	140	157	170	190	210

GEARING

	30	39	52
12	66	86	115
13	61	79	106
14	57	74	98
15	53	69	92
16	50	64	86
17	47	61	81
19	42	54	72
21	38	49	65
23	35	45	60
25	32	41	55

Trek 2100C

1451000*15.114
Bike weight: 22.5 lb/10.22 kg

FRAMESET

Main tubes		ZR9000	
Stays		OCLV 120, carbon fiber composite	
Color		Rage Red	
Fork		Bontrager Satellite Plus, 381mm axle-crown length	
Headset		Cane Creek Internal	25.4/34.0/30.0, 20.6mm stack height

CONTROLS

Handlebar		Bontrager Flat Top	25.4mm clamp diameter
Stem		Alloy direct connect, adjustable rise	40.0mm steerer clamp height
Shift levers		Shimano 105 STI	
Brake levers		Integrated brake/shift	
Grips		Bontrager Gel	

DRIVETRAIN

Front derailleur	...	Shimano 105 T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur		Shimano 105 GS	
Crankset		Bontrager Race 52/42/30	74/130mm bolt hole circle
Bottom bracket		TruVativ Giga-Pipe SL	68 x 118 (shell x axle,mm), ISIS splined axle
Chain		Shimano HG-53	9 speed, 110 links
Cassette		SRAM PG950 12-26, 9spd	

WHEELSET

Front wheel		Bontrager Select, 20°	593mm ERD
Spokes		DT 14g, ProLock brass nipples, 281mm, radial	
Tire		Bontrager Race Lite HardCase, 700 x 28c, Velox 16mm rim strip	
Rear wheel		Bontrager Select, 24°	603mm ERD
Spokes		DT 14g, ProLock brass nipples, 293/294mm, 2x	
Tire		Bontrager Race Lite HardCase, 700 x 28c, Velox 16mm rim strip	
Inner tubes		Presta valve, 48mm stem	

OTHER

Seatpost		Bontrager Select	27.2mm outer diameter
Saddle		Bontrager Race CRZ+	
Seatpost binder		Alloy w/integral bolt	32.1mm inner diameter
Brakes		Alloy dual pivot, long reach, cartridge pads	
Pedals		Shimano SPD M505, clipless	9/16" axle
Additional		Cane Creek CrossTop in-line brake levers, BuzzKill	

FIT *dimensions in mm, unless specified*

Frame	Size	50	52	54	56	58	63
Rider height, in.		69.6	69.6	70.6	70.8	72.3	74.0
	cm	177	177	179	180	184	188
Handlebar	width	380	400	400	420	420	440
Handlebar	rise	0	0	0	0	0	0
Stem	length	105	105	105	105	105	105
	angle	35	35	35	35	35	35
Headset spacers		40	40	40	40	40	40
Crank	length	170	170	170	175	175	175
Seatpost	length	330	330	330	330	330	330
Steerer	length	236.6	236.6	253.6	266.6	286.6	306.6

GEOMETRY *dimensions in mm, unless specified*

Head tube angle		71.5	71.5	72.0	72.5	72.5	73.0
Fork offset		50.0	50.0	50.0	45.0	45.0	45.0
Trail		63	63	60	56	62	58
Seat tube angle		75.0	74.5	74.0	73.5	73.0	72.5
Effective top tube		525	530	545	550	570	590
Seat tube		511	516	528	531	548	580
Standover		736	748	758	768	779	818
Wheelbase		1020	1020	1026	1021	1030	1039
Bottom bracket height		266	266	266	266	266	266
Chainstay		435	435	435	435	435	435
Head tube		140	140	157	170	190	210

GEARING

	30 42 52
12	66 93 115
13	61 85 106
14	57 79 98
15	53 74 92
17	47 65 81
19	42 58 72
21	38 53 65
23	35 48 60
26	31 43 53

Trek 2100 C WSD

1451003*15.114
Bike weight: 21.7 lb/9.85 kg

FRAMESET

Main tubes		ZR9000	
Stays		OCLV 120, carbon fiber composite	
Color		Cumulus Blue	
Fork		Bontrager Satellite Plus, 381385mm axle-crown length	
Rear shock		S.P.A.	
Headset		Cane Creek Internal	25.4/34.0/30.0, 20.6mm stack height

CONTROLS

Handlebar		Bontrager Flat Top	25.4mm clamp diameter
Stem		Alloy direct connect, adjustable rise	40.0mm steerer clamp height
Shift levers		Shimano 105 STI	
Brake levers		Integrated brake/shift	
Grips		Bontrager Gel	

DRIVETRAIN

Front derailleur	...	Shimano 105 T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur		Shimano 105 GS	
Crankset		Bontrager Race 52/42/30	74/130mm bolt hole circle
Bottom bracket		TruVativ Giga-Pipe SL	68 x 118 (shell x axle,mm), ISIS splined axle
Chain		Shimano HG-53	9 speed, 108 links
Cassette		SRAM PG950 12-26, 9spd	

WHEELSET

Front wheel		Bontrager Select, 20°	544mm ERD
Spokes		DT 14g, ProLock brass nipples, 254mm, radial	
Tire		Bontrager Race Lite HardCase, 650 x 25c, Velox 16mm rim strip	
Rear wheel		Bontrager Select, 24°	549mm ERD
Spokes		DT 14g, ProLock brass nipples, 268/270mm, 2x	
Tire		Bontrager Race Lite HardCase, 650 x 25c, Velox 16mm rim strip	
Inner tubes		Presta valve	

OTHER

Seatpost		Bontrager Race	27.2mm outer diameter
Saddle		Bontrager Race CRZ+ WSD	
Seatpost binder		Alloy w/integral bolt	32.1mm inner diameter
Brakes		Alloy dual pivot, long reach, cartridge pads	
Pedals		Shimano SPD M505, clipless	9/16" axle
Additional		Cane Creek CrossTop in-line brake levers, Buzzkill	

FIT *dimensions in mm, unless specified*

Frame	Size	45	50	54
Rider height, in.		68.4	69.0	70.3
	cm	174	175	179
Handlebar	width	380	380	400
Handlebar	rise	0	0	0
Stem	length	105	105	105
	angle	35	35	35
Headset spacers		40	40	40
Crank	length	165	165	170
Seatpost	length	250	330	330
Steerer	length	234.6	234.6	251.6

GEOMETRY *dimensions in mm, unless specified*

Head tube angle		72.0	71.0	71.5
Fork offset		50.0		
Trail		62	66	63
Seat tube angle		75.0	75.0	74.5
Effective top tube		507	515	530
Seat tube		430	495	510
Standover		682	736	759
Wheelbase		994	1015	1021
Bottom bracket height		268	266	266
Chainstay		435	435	435
Head tube		140	140	157

GEARING

	30 42 52
12	61 86 106
13	57 79 98
14	53 74 91
15	49 69 85
17	43 61 75
19	39 54 67
21	35 49 61
23	32 45 56
26	28 40 49

Trek 1200C

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color	Brushed aluminum	
Fork	Bontrager Satellite Plus, 381mm axle-crown length	
Headset	Sealed, semi-cartridge	25.4/34.0/30.0, mm stack height

CONTROLS

Handlebar	Bontrager Flat Top	25.4mm clamp diameter
Stem	Alloy direct connect, adjustable rise	
Shift levers	Shimano Tiagra STI	
Brake levers	Integrated brake/shift	
Grips		

DRIVETRAIN

Front derailleur	Shimano Tiagra T, attachment	
Rear derailleur	Shimano 105 GS	
Crankset	Bontrager Select 52/42/30	74/130mm bolt hole circle
Bottom bracket		(shell x axle,mm), axle
Chain		9 speed, links
Cassette	SRAM PG950 12-26, 9spd	

WHEELSET

Front wheel	Shimano Tiagra hub, °, Alex rim	mm ERD
Spokes	14G stainless, mm, x	
Tire	Bontrager Race Lite HardCase, 700 x 28c, rim strip	
Rear wheel	Shimano Tiagra hub, °, Alex rim	mm ERD
Spokes	14G stainless, mm, x	
Tire	Bontrager Race Lite HardCase, 700 x 28c, rim strip	
Inner tubes		

OTHER

Seatpost	Suspension, alloy	mm outer diameter
Saddle	Bontrager CRZ+	
Seatpost binder		mm inner diameter
Brakes	Alloy dual pivot, long reach front, Alloy dual pivot, long reach rear	
Pedals	Wellgo Road, clipless	axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	50	54	58	63		
Rider height, in.		59.4	60.6	62.1	63.8	0.0	0.0
	cm	151	154	158	162	0	0
Handlebar	width						
Handlebar	rise	0	0	0	0		
Stem	length						
	angle						
Headset	spacers						
Crank	length						
Seatpost	length						
Steerer	length	138	155	188	208		

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.5	72.0	72.5	73.0		
Fork offset	50.0	50.0	50.0	45.0	45.0	45.0
Trail	63	60	62	58		
Seat tube angle	75.0	74.0	73.0	72.5		
Effective top tube	525	545	570	590		
Seat tube	511	528	548	580		
Standover	736	758	779	818		
Wheelbase	1020	1026	1030	1039		
Bottom bracket height	266	266	266	266		
Chainstay	435	435	435	435		
Head tube	140	157	190	210		

GEARING

	30 42 52
12	66 93 115
13	61 85 106
14	57 79 98
15	53 74 92
17	47 65 81
19	42 58 72
21	38 53 65
23	35 48 60
26	31 43 53

Trek Team Time Trial

1478000*15.104
Bike weight: 19.5 lb/8.85 kg

FRAMESET

Main tubes	OCV HC superlight carbon fiber composite	
Stays	OCV 120 carbon fiber composite	
Color	Pearl White/Baja blue	
Fork	Bontrager Race XXX Lite, OCLV 110 carbon, 375mm axle-crown length	
Headset	Cane Creek BL	22.2/30.2/26.4, 30.1mm stack height

CONTROLS

Handlebar	Bontrager Race, bullhorn w/Profile Stryke clipons	26.0mm clamp diameter
Stem	Bontrager Race	40.0mm steerer clamp height
Shift levers	Shimano Dura-Ace, bar-cons	
Brake levers	Cane Creek BL2000K	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano Dura-Ace	Down pull, Braze-on type attachment
Rear derailleur . . .	Shimano Dura-Ace	
Crankset	Shimano Dura-Ace 53/39	130mm bolt hole circle
Bottom bracket . . .	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano Dura-Ace	10 speed, 108 links
Cassette	Shimano Dura-Ace 11-23, 10spd	

WHEELSET

Front wheel	Bontrager Race X Lite Aero, 16"	582mm ERD
Spokes	DT New Aero, internal alloy nipples, 281mm, radial	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Bontrager, 17.5mm rim strip	
Rear wheel	Bontrager Race X Lite Aero, 16"	582mm ERD
Spokes	DT New Aero, internal alloy nipples, 288/288mm, 2x	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Bontrager, 17.5mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager TT	25.0mm outer diameter
Saddle	SSM Aspide Triathlon, gel, Ti rails	
Seatpost binder . . .		mm inner diameter
Brakes	Shimano Dura-Ace	
Pedals	-not supplied-	axle
Additional	stem shim from 1" to 1 1/8"	

FIT *dimensions in mm, unless specified*

Frame	Size	S	M	L
Rider height, in.		60.8	66.4	72.0
	cm	154	169	183
Handlebar	width	420	420	420
Stem	length	70	90	110
	angle	7	7	7
Headset spacers		40	40	40
Crank	length	172.5	175	175
Seatpost	length	120	160	160
Steerer	length	189.1	207.1	219.1

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.0	73.3	73.9
Fork offset	40.0	40.0	40.0
Trail	68	60	56
Seat tube angle	73.6	73.8	73.7
Effective top tube	514	542	578
Seat tube	595	655	705
Standover	768	768	768
Wheelbase	949	967	997
Bottom bracket height	269	266	266
Chainstay	405	405	405
Head tube	83	102	113

GEARING

	39 53
11	94 127
12	86 117
13	79 108
14	74 100
15	69 93
16	64 88
17	61 82
19	54 74
21	49 67 0
23	45 61 0

Trek Equinox 11

1499000*15.015
Bike weight: 19.6 lb/8.90 kg

FRAMESET

Main tubes	OCV HC superlight carbon fiber composite
Stays	OCV 120 carbon fiber composite
Color	Titanite Black
Fork	Bontrager Race XXX Lite, OCV 110 carbon, 375mm axle-crown length
Headset	Cane Creek BL 22.2/30.2/26.4, 30.1mm stack height

CONTROLS

Handlebar	Bontrager Race, bullhorn w/Profile Stryke clipons	26.0mm clamp diameter
Stem	Bontrager Race	40.0mm steerer clamp height
Shift levers	Shimano Dura-Ace, bar-cons	
Brake levers	Cane Creek BL2000K	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur	Shimano Ultegra	Down pull, Braze-on type attachment
Rear derailleur	Shimano Ultegra	
Crankset	Bontrager Race Lite 53/39 w/Giga-X-Pipe	130mm bolt hole circle
Bottom bracket	integral axle	68 (shell x axle,mm), Integral axle
Chain	Shimano Ultegra	10 speed, 108 links
Cassette	Shimano Ultegra 12-25, 10spd	

WHEELSET

Front wheel	Bontrager Race X Lite Aero, 16"	582mm ERD
Spokes	DT New Aero, internal alloy nipples, 281mm, radial	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Bontrager, 17.5mm rim strip	
Rear wheel	Bontrager Race X Lite Aero, 16"	582mm ERD
Spokes	DT New Aero, internal alloy nipples, 288/288mm, 2x	
Tire	Bontrager Race X Lite, folding, 700 x 23c, Bontrager, 17.5mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager TT	25.0mm outer diameter
Saddle	SSM Aspide Triathlon, gel, Ti rails	
Seatpost binder		mm inner diameter
Brakes	Shimano Ultegra	
Pedals	-not supplied- 9/16" axle	
Additional	stem shim from 1" to 1 1/8"	

FIT dimensions in mm, unless specified

Frame	Size	S	M	L
Rider height, in.		60.8	66.4	72.0
	cm	154	169	183
Handlebar	width	420	420	420
Stem	length	70	90	110
	angle	7	7	7
Headset spacers		40	40	40
Crank	length	172.5	175	175
Seatpost	length	120	160	160
Steerer	length	189.1	207.1	219.1

GEOMETRY dimensions in mm, unless specified

Head tube angle	72.0	73.3	73.9
Fork offset	40.0	40.0	40.0
Trail	68	60	56
Seat tube angle	73.6	73.8	73.7
Effective top tube	514	542	578
Seat tube	595	655	705
Standover	768	768	768
Wheelbase	949	967	997
Bottom bracket height	269	266	266
Chainstay	405	405	405
Head tube	83	102	113

GEARING

	39	53
12	86	117
13	79	108
14	74	100
15	69	93
16	64	88
17	61	82
19	54	74
21	49	67
23	45	61
25	41	56

Trek Equinox 9

1497000*15.104
Bike weight: 21.4 lb/9.72 kg

FRAMESET

Main tubes		ZR9000	
Stays		ZR9000	
Color		Trek Red	
Fork		Bontrager Race XXX Lite, OCLV 110 carbon, 355/375mm axle-crown length	
Headset		Cane Creek BL	22.2/30.2/26.4, 30.1mm stack height

CONTROLS

Handlebar		Bontrager Race, bullhorn w/Profile Stryke clipons	26.0mm clamp diameter
Stem		Bontrager Race	40.0mm steerer clamp height
Shift levers		Shimano Dura-Ace, bar-cons	
Brake levers		Cane Creek BL2000K	
Grips		Bontrager Gel	

DRIVETRAIN

Front derailleur	...	Shimano 105	Down pull, Braze-on type attachment
Rear derailleur		Shimano Dura-Ace	
Crankset		Bontrager Race Lite 53/39 w/Giga-X-Pipe	130mm bolt hole circle
Bottom bracket		integral axle	68 (shell x axle,mm), Integral axle
Chain		Shimano HG-73	9 speed, 106 links
Cassette		SRAM PG950 12-26, 9spd	

WHEELSET

Front wheel		Bontrager Race Aero, 16°	525mm ERD
Spokes		DT New Aero, internal alloy nipples, 257mm, radial	
Tire		Bontrager Race X Lite, folding, 650 x 25c, Velox 16mm rim strip	
Rear wheel		Bontrager Race Aero, 16°	525mm ERD
Spokes		DT New Aero, internal alloy nipples, 262/262mm, 2x	
Tire		Bontrager Race X Lite, folding, 650 x 25c, Velox 16mm rim strip	
Inner tubes		Presta valve, 48mm stem	

OTHER

Seatpost		Bontrager TT	27.2mm outer diameter
Saddle		SSM Aspide Triathlon, gel, Ti rails	
Seatpost binder		Alloy w/integral bolt	32.1mm inner diameter
Brakes		Shimano 105	
Pedals		-not supplied- 9/16" axle	
Additional		stem shim 1" to 1 1/8", Bontrager Select Aero 700c on 54-60	

FIT *dimensions in mm, unless specified*

Frame	Size	50	52	54	56	58	60
Rider height, in.		62.8	66.2	68.8	71.1	74.6	78.2
	cm	160	168	175	181	189	199
Handlebar	width	420	420	420	420	420	420
Stem	length	70	80	90	100	110	120
	angle	7	7	7	7	7	7
Headset spacers		40	40	40	40	40	40
Crank	length	170	170	172.5	175	175	175
Seatpost	length	160	160	160	160	160	160
Steerer	length	216.1	236.1	201.1	221.1	241.1	271.1

GEOMETRY *dimensions in mm, unless specified*

Head tube angle		72.5	72.5	73.0	73.0	73.0	73.0
Fork offset		35.0	35.0	40.0	40.0	40.0	40.0
Trail		61	61	61	61	61	61
Seat tube angle		76.0	76.0	76.0	76.0	76.0	76.0
Effective top tube		502	525	545	555	575	600
Seat tube		530	560	590	620	650	690
Standover		714	734	758	782	801	825
Wheelbase		934	958	988	999	1020	1047
Bottom bracket height		266	266	266	266	266	266
Chainstay		380	380	400	400	400	400
Head tube		110	130	95	115	135	165

GEARING

	39 53
12	79 108
13	73 99
14	68 92
15	63 86
17	56 76
19	50 68
21	45 62
23	41 56
26	37 50 0

Trek Equinox 7

1496000*15.104
Bike weight: 21.9 lb/9.94 kg

FRAMESET

Main tubes		ZR9000	
Stays		ZR9000	
Color		Bright Silver	
Fork		Bontrager Race XXX Lite, OCLV 110 carbon, 375mm axle-crown length	
Headset		Cane Creek BL	22.2/30.2/26.4, 30.1mm stack height

CONTROLS

Handlebar		Bontrager Race, bullhorn w/Profile Aerolite clipons	26.0mm clamp diameter
Stem		Bontrager Race	40.0mm steerer clamp height
Shift levers		Shimano Dura-Ace, bar-cons	
Brake levers		Cane Creek BL2000K	
Grips			

DRIVETRAIN

Front derailleur	...	Shimano 105	Down pull, Braze-on type attachment
Rear derailleur		Shimano 105	
Crankset		Bontrager Race 53/39	130mm bolt hole circle
Bottom bracket		TruVativ Giga-Pipe SL	68 x 108 (shell x axle,mm), ISIS splined axle
Chain		Shimano HG-73	9 speed, 106 links
Cassette		SRAM PG950 12-26, 9spd	

WHEELSET

Front wheel		Bontrager Select, 20°	544mm ERD
Spokes		DT 14g, ProLock brass nipples, 254mm, radial	
Tire		Bontrager Select, 650 x 23c, Velox 16mm rim strip	
Rear wheel		Bontrager Select, 24°	549mm ERD
Spokes		DT 14g, ProLock brass nipples, 268/270mm, 2x	
Tire		Bontrager Select, 650 x 23c, Velox 16mm rim strip	
Inner tubes		Presta valve, 48mm stem	

OTHER

Seatpost		Bontrager TT	27.2mm outer diameter
Saddle		SSM Azoto Triathlon, CrMo rails, leather cover	
Seatpost binder		Alloy w/integral bolt	32.1mm inner diameter
Brakes		Alloy dual pivot, cartridge pads	
Pedals		axle	
Additional		stem shim 1" to 1 1/8", Bontrager Select Aero 700c on 54-60	

FIT *dimensions in mm, unless specified*

Frame	Size	50	52	54	56	58	60
Rider height, in.		62.8	66.1	68.8	71.1	74.6	78.2
	cm	159	168	175	181	189	199
Handlebar	width	420	420	420	420	420	420
Stem	length	70	80	90	100	110	120
	angle	7	7	7	7	7	7
Headset spacers		40	40	40	40	40	40
Crank	length	170	170	170	175	175	175
Seatpost	length	160	160	160	160	160	160
Steerer	length	216.1	236.1	201.1	221.1	241.1	271.1

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.5	72.5	73.0	73.0	73.0	73.0
Fork offset	40.0	40.0	40.0	40.0	40.0	40.0
Trail	61	61	61	61	61	61
Seat tube angle	76.0	76.0	76.0	76.0	76.0	76.0
Effective top tube	502	525	545	555	575	600
Seat tube	530	560	590	620	650	690
Standover	714	734	758	782	801	825
Wheelbase	934	958	988	999	1020	1047
Bottom bracket height	266	266	266	266	266	266
Chainstay	380	380	400	400	400	400
Head tube	110	130	95	115	135	165

GEARING

	39 53
12	79 108
13	73 99
14	68 92
15	63 86
17	56 76
19	50 68
21	45 62
23	41 56
26	37 50 0

Trek T2000

1492000*15.084
Bike weight: 35.3 lb/16.03 kg

FRAMESET

Main tubes	ZR9000	
Stays	ZR9000	
Color	Red Flare Pearl	
Fork	Tandem Cro-Moly, 414mm axle-crown length	
Headset	Cane Creek S-6 Aheadset, alloy	25.4/34.0/30.0, 37.1mm stack height

CONTROLS

Handlebar	Bontrager Select/ Race CX	31.8/25.4mm clamp diameter
Stem	Bontrager Race Lite/ Bontrager Tandem, adjustable,	40.0mm steerer clamp height
Shift levers	Shimano Ultegra STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano Ultegra T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur . . .	Shimano Deore XT SGS	
Crankset	Shimano Ultegra Tandem 53/42/30	74/130mm bolt hole circle
Bottom bracket . . .	Shimano Ultegra	68 x 118 (shell x axle,mm), Shimano splined axle
Chain	Shimano HG-73	9 speed, 114/152 (154 on L) links
Cassette	SRAM PG970 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Race Lite Tandem, 24°	575mm ERD
Spokes	DT New Aero, ProLock brass nipples, 281mm, 2x	
Tire	Bontrager Race Lite HardCase, 700 x 28c, Bontrager, 17.5mm rim strip	
Rear wheel	Bontrager Race Lite Tandem, 24°	575mm ERD
Spokes	DT New Aero, ProLock brass nipples, 281/281mm, 2x	
Tire	Bontrager Race Lite HardCase, 700 x 28c, Bontrager, 17.5mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Select, Alloy suspension	27.2mm outer diameter
Saddle	Bontrager Race Lite Luxe/ Race Lite Luxe WSD	
Seatpost binder . . .	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Avid Shorty 6, cantilevers	
Pedals	Alloy road, sealed, w/clips and straps	axle
Additional	Stoker levers, brake hanger	

FIT *dimensions in mm, unless specified*

Frame	Size	54/44	56/45	58/46		
Rider height, in.		71.0	0.0	73.5	0.0	75.0
	cm	180	0	187	0	191
Handlebar	width	440	440	460	460	460
Stem	length	100	170-240	110	170-240	120
	angle	17		17		17
Headset spacers		45		45		45
Crank	length	175	170			
Seatpost	length	330	350	330	350	330
Steerer	length	198.6		228.1		253.1

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.5	73.0	73.0		
Fork offset	55.0	55.0	55.0		
Trail	51	48	48		
Seat tube angle	73.5	73.0	73.0	72.5	73.0
Effective top tube	550	565	575		
Seat tube	520	440	540	450	560
Standover	758	689	779	700	797
Wheelbase	1744		1754		1782
Bottom bracket height	273	273	273	273	273
Chainstay	440	440	440		
Head tube	93	120	145		

GEARING

	30 42 53
11	74 103 130
13	62 87 110
15	54 76 95
17	48 67 84
20	41 57 72
23	35 49 62
26	31 44 55
30	27 38 48
34	24 33 42

Trek T1000

1490000*15.084
Bike weight: 38.3 lb/17.39 kg

FRAMESET

Main tubes	ZR9000	
Stays	ZR9000	
Color	Titanite Black	
Fork	Tandem Cro-Moly, 414mm axle-crown length	
Headset	VP, alloy threadless	25.4/34.0/30.0, 37.2mm stack height

CONTROLS

Handlebar	Bontrager Select/ Race CX	26.0/25.4mm clamp diameter
Stem	Bontrager Race/ Bontrager Tandem, adjustable	40.0mm steerer clamp height
Shift levers	Shimano Tiagra STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano Tiagra T	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur . . .	Shimano Deore XT SGS	
Crankset	Bontrager Select Tandem 52/42/30	74/130mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe SL	68 x 118 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-73	9 speed, 114/152 (154 on L) links
Cassette	SRAM PG970 11-34, 9spd	

WHEELSET

Front wheel	Bontrager Clyde, 48°	604mm ERD
Spokes	DT 14g, ProLock brass nipples, 289mm, 4x	
Tire	Bontrager Race Lite HardCase, 700 x 28c, Velox 22mm rim strip	
Rear wheel	Bontrager Clyde, 48°	604mm ERD
Spokes	DT 14g, ProLock brass nipples, 288/289mm, 4x	
Tire	Bontrager Race Lite HardCase, 700 x 28c, Velox 22mm rim strip	
Inner tubes	Presta valve, 48mm stem	

OTHER

Seatpost	Bontrager Select, Alloy suspension	27.2mm outer diameter
Saddle	Bontrager Race Luxe/ Select WSD	
Seatpost binder . . .	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Avid Shorty 4, cantilevers	
Pedals	Alloy road, sealed, w/clips and straps	axle
Additional	Stoker levers, front brake cable hanger	

FIT *dimensions in mm, unless specified*

Frame	Size	54/44		56/45		58/46	
Rider height, in.		71.0	0.0	73.5	0.0	75.0	0.0
	cm	180	0	187	0	191	0
Handlebar	width	440	440	460	460	460	460
Stem	length	100	170-240	110	170-240	120	170-240
	angle	17		17		17	
Headset spacers		45		45		45	
Crank	length	175	170				
Seatpost	length	330	350	330	350	330	350
Steerer	length	198.7		228.2		253.2	

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	72.5		73.0		73.0	
Fork offset	55.0		55.0		55.0	
Trail	51		48		48	
Seat tube angle	73.5	73.0	73.0	73.0	72.5	73.0
Effective top tube	550		565		575	
Seat tube	520	440	540	450	560	460
Standover	758	689	779	700	797	771
Wheelbase	1744		1754		1782	
Bottom bracket height	273	273	273	273	273	273
Chainstay	440		440		440	
Head tube	93		120		145	

GEARING

	30	42	52
11	74	103	128
13	62	87	108
15	54	76	94
17	48	67	83
20	41	57	70
23	35	49	61
26	31	44	54
30	27	38	47
34	24	33	41

Trek XO-1

1494000*15.124
Bike weight: 22.5 lb/10.22 kg

FRAMESET

Main tubes	Alpha SLR aluminum	
Stays	Alpha SLR aluminum	
Color	Black anodized	
Fork	X-Lite aluminum, 403mm axle-crown length	
Headset	Sealed, semi-cartridge	25.4/34.0/30.0, 36.5mm stack height

CONTROLS

Handlebar	Bontrager Race CX	25.4mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	Shimano 105 STI	
Brake levers	Integrated brake/shift	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano 105	Down pull, Braze-on type w/34.9mm clamp attachment
Rear derailleur . . .	Shimano 105	
Crankset	Bontrager Race 46/38	64/104mm bolt hole circle
Bottom bracket . . .	TruVativ Giga-Pipe SL	68 x 108 (shell x axle,mm), ISIS splined axle
Chain	Shimano HG-53	9 speed, 108 links
Cassette	SRAM PG950 12-26, 9spd	

WHEELSET

Front wheel	Bontrager Select, 20°	593mm ERD
Spokes	DT 14g, ProLock brass nipples, 281mm, radial	
Tire	Bontrager Jones CX, 127tpi, 700 x 32c, Velox 16mm rim strip	
Rear wheel	Bontrager Select, 24°	603mm ERD
Spokes	DT 14g, ProLock brass nipples, 293/294mm, 2x	
Tire	Bontrager Jones CX, 127tpi, 700 x 32c, Velox 16mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Select	27.2mm outer diameter
Saddle	Bontrager Select	
Seatpost binder . . .	Alloy w/integral bolt, cable hanger	31.9mm inner diameter
Brakes	Avid Shorty 4, cantilevers	
Pedals	Shimano SPD M505, clipless	9/16" axle
Additional	Cane Creek CrossTop in-line brake levers, front brake cable hanger	

FIT *dimensions in mm, unless specified*

Frame	Size	50	52	54	56	58
Rider height, in.		66.5	66.8	69.7	70.5	72.6
	cm	169	170	177	179	184
Handlebar	width	400	420	420	440	440
Stem	length	80	80	100	100	110
	angle	10	10	10	10	10
Headset spacers		40	40	40	40	40
Crank	length	170	170	175	175	175
Seatpost	length	250	250	250	250	250
Steerer	length	200.0	200.0	208.0	208.0	226.0

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	71.0	71.5	72.0	72.5
Fork offset	50.0	50.0	45.0	45.0	45.0
Trail	74	74	71	68	64
Seat tube angle	74.5	74.0	73.5	73.0	73.0
Effective top tube	515	525	540	555	565
Seat tube	500	520	540	560	580
Standover	763	775	791	805	824
Wheelbase	999	1004	1009	1014	1021
Bottom bracket height	281	281	281	281	283
Chainstay	430	430	430	430	430
Head tube	97	97	105	105	123

GEARING

	38 46
12	88 106
13	81 98
14	75 91
15	70 85
17	62 75
19	55 67
21	50 61
23	46 55
26	40 49 0

Trek 520

1432000*15.084
Bike weight: 27.0 lb/12.26 kg

FRAMESET

Main tubes	Trek butted Cro-Moly	
Stays	Trek butted Cro-Moly	
Color	Beaujolais	
Fork	Cro-Moly Touring, mm axle-crown length	
Headset	Cane Creek BL	22.2/30.2/26.4, 30.1mm stack height

CONTROLS

Handlebar	Bontrager Select	26.0mm clamp diameter
Stem	Bontrager Select	41.0mm steerer clamp height
Shift levers	Shimano Dura-Ace, bar-cons	
Brake levers	Dia-Compe 287 Aero	
Grips	Bontrager Gel	

DRIVETRAIN

Front derailleur . . .	Shimano 105 T	Down pull, 31.8 mm/ 1 1/4" attachment
Rear derailleur . . .	Shimano Deore LX SGS	
Crankset	Shimano 105 52/42/30	74/130mm bolt hole circle
Bottom bracket . . .	Shimano 105	68 x 118 (shell x axle,mm), Shimano splined axle
Chain	Shimano HG-73	9 speed, 114 links
Cassette	SRAM 7.0 11-32, 9spd	

WHEELSET

Front wheel	Shimano Deore LX hub, 36°, Bontrager Maverick rim	604mm ERD
Spokes	DT 14G stainless, 295mm, 3x	
Tire	Bontrager Race Lite HardCase, 700 x 32c, Velox 19mm rim strip	
Rear wheel	Shimano Deore LX hub, 36°, Bontrager Maverick OSB rim	604mm ERD
Spokes	DT 14G stainless, 292/293mm, 3x	
Tire	Bontrager Race Lite HardCase, 700 x 32c, Velox 22mm rim strip	
Inner tubes	Presta valve	

OTHER

Seatpost	Bontrager Select	27.2mm outer diameter
Saddle	Bontrager Race Luxe	
Seatpost binder . . .	Alloy w/integral bolt	32.1mm inner diameter
Brakes	Avid Single Digit 5, linear pull	
Pedals	Shimano SPD M520, clipless	9/16" axle
Additional	shim for stem to fit 1" steerer	Massload rear rack,

FIT *dimensions in mm, unless specified*

Frame	Size	17	19	21	23	25
Rider height, in.		48.4	49.6	50.8	51.9	55.4
	cm	123	126	129	132	141
Handlebar	width	400	420	420	440	440
Stem	length	80	90	100	100	120
	angle	17	17	17	17	17
Headset spacers		40	40	40	40	35
Crank	length	170	170	170	175	175
Seatpost	length	250	250	250	250	250
Steerer	length	196.1	196.1	196.1	226.1	266.1

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	71.0	71.0	71.0	72.0	72.5
Fork offset	52.0	52.0	52.0	52.0	52.0
Trail	64	64	64	57	54
Seat tube angle	74.0	74.0	73.5	73.0	72.0
Effective top tube	540	545	555	566	590
Seat tube	432	483	533	584	635
Standover	697	727	764	806	852
Wheelbase	1044	1046	1054	1052	1062
Bottom bracket height	268	268	268	268	268
Chainstay	450	450	450	450	450
Head tube	90	90	90	120	165

GEARING

	30	42	52
11	74	103	128
12	68	95	117
14	58	81	100
16	51	71	88
18	45	63	78
21	39	54	67
24	34	47	59
28	29	41	50
32	25	35	44

Trek Mt. Track 220

1580000114
Bike weight: 30.0 lb/13.62 kg

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color	White/Black • Red/Yellow/Black/White decals	
	Metallic Blue/Ball Burnished • Red/Silver/Black/White decals	
	Pearl Blue/Ball Burnished • Blue/Blue/White/Silver decals	
	Metallic Purple • Purple/Purple/White decals	
Fork	SR	80mm travel, 369.4mm axle-crown length
Headset	Steel	25.4/34.0/30.0, 36mm stack height

CONTROLS

Handlebar	Dialed Child, 22.2mm diameter	25.4mm clamp diameter
Stem	Dialed Child, adjustable rise	
Shift levers	SRAM MRX Halfpipe	
Brake levers	Alloy, direct pull, kid's reach	
Grips	Dialed Child, 26mm grip size	

DRIVETRAIN

Front derailleur . . .	Shimano Altus	Down pull, 31.8 mm/ 1 1/4" attachment
Rear derailleur . . .	Shimano C050 MegaRange	
Crankset	Dialed Child, adjustable 127 to 150mm, 40/32/22	Riveted chainrings
Bottom bracket . . .	Cartridge	73 (shell x axle,mm), Square axle
Chain	KMC Z-51	3/32", 104 links
Cassette	Sun Race 13-34, 7spd	

WHEELSET

Front wheel	Alloy, nutted hub, 32°, Aluminum alloy rim	493.8mm ERD
Spokes	14G, 242mm, 2x	
Tire	Bontrager Connection, 24 x 2.0, Rubber rim strip	
Rear wheel	Alloy, nutted hub, 32°, Aluminum alloy rim	493.8mm ERD
Spokes	14g, 239.5/241.5mm, 2x	
Tire	Bontrager Connection, 24 x 2.0, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Steel	27.2mm outer diameter
Saddle	Dialed Child, sized	
Seatpost binder . . .	Quick release	31.8mm inner diameter
Brakes	Alloy direct pull w/modulator front, Alloy direct pull rear	
Pedals	Dialed Child, sized	9/16" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	12B	12G
Rider height, in.		60.1	60.4
	cm	153	153
Handlebar	width	560	560
Handlebar	rise	30	30
Stem	length	70	70
	angle	15	15
Headset spacers		2	2
Crank	length	127	152
Seatpost	length	300	300
Steerer	length	139.5	139.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.0
Fork offset	38.7	38.7
Trail	62	62
Seat tube angle	72.0	72.0
Effective top tube	529	529
Seat tube	290	290
Standover	587	530
Wheelbase	985	985
Bottom bracket height	262	262
Chainstay	409	409
Head tube	105	95

GEARING

	24	34	42
13	44	62	76
15	38	54	66
17	33	47	58
19	30	42	52
22	26	37	45
26	22	31	38
34	17	24	29

Trek

Mt. Track 200

1580000114
Bike weight: 30.0 lb/13.62 kg

FRAMESET

Main tubes	Hi Tensile steel	
Stays	Hi Tensile steel	
Color	White/Black • Red/Yellow/Black/White decals	
	Metallic Blue/Ball Burnished • Red/Silver/Black/White decals	
	Pearl Blue/Ball Burnished • Blue/Blue/White/Silver decals	
	Metallic Purple • Purple/Purple/White decals	
Fork.	High tensile steel, 337mm axle-crown length	
Headset	Steel	25.4/34.0/30.0, 37.5mm stack height

CONTROLS

Handlebar	Dialed Child, 22.2mm diameter	25.4mm clamp diameter
Stem	Dialed Child, adjustable rise	
Shift levers	SRAM MRX	
Brake levers	Alloy, direct pull, kid's reach	
Grips	Dialed Child, 26mm grip size	

DRIVETRAIN

Front derailleur . . .	Shimano TY-22	Down pull, 31.8 mm/ 1 1/4" attachment
Rear derailleur . . .	Shimano Tourney TY-23 GS	
Crankset	Dialed Child, adjustable 127 to 150mm, 38/28T	Riveted chainrings
Bottom bracket . . .	Three-piece semi-sealed	68 (shell x axle,mm), Square axle
Chain.	KMC Z-51	3/32", 100 links
Cassette.	SRAM 14-28, 6spd	

WHEELSET

Front wheel.	Alloy, nuttled hub, 32°, Aluminum alloy rim	493.8mm ERD
Spokes	14G, 241.5mm, 2x	
Tire	Bontrager Connection, 24 x 2.0, Rubber rim strip	
Rear wheel	Alloy, nuttled hub, 32°, Aluminum alloy rim	493.8mm ERD
Spokes	14g, 239.5/241.5mm, 2x	
Tire	Bontrager Connection, 24 x 2.0, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost.	Steel	29.2mm outer diameter
Saddle	Dialed Child, sized	
Seatpost binder. . .	Quick release	31.8mm inner diameter
Brakes	Alloy direct pull w/modulator front, Alloy direct pull rear	
Pedals	Dialed Child, sized 9/16" axle	
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	12B	12G
Rider height, in.		59.3	59.5
	cm	151	151
Handlebar	width	560	560
Handlebar	rise	30	30
Stem	length	70	70
	angle	15	15
Headset spacers		2	2
Crank	length	152	152
Seatpost	length	300	300
Steerer	length	143	143

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.0
Fork offset	45.0	45.0
Trail	62	62
Seat tube angle	72.0	72.0
Effective top tube	529	529
Seat tube	290	290
Standover	587	530
Wheelbase	985	985
Bottom bracket height	262	262
Chainstay	409	409
Head tube	105	95

GEARING

	38
14	64
16	56
18	50
21	43
24	37
28	32

Trek Mt. Track 60

1578600114
Bike weight: 26.0 lb/11.80 kg

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color	White/Silver • Black/White/Silver decals	
	Black/Red • Silver/White decals	
	Pearl White • Blue/Blue/White/Silver decals	
Fork	RST 150E	80mm travel, 319mm axle-crown length
Headset	Steel	25.4/34.0/30.0, 37.5mm stack height

CONTROLS

Handlebar	Dialed Child, 22.2mm diameter	25.4mm clamp diameter
Stem	Dialed Child, adjustable rise	
Shift levers	SRAM MRX, right only	
Brake levers	Alloy, direct pull	
Grips	Dialed Child, 26mm grip size	

DRIVETRAIN

Rear derailleur	Shimano Tourney TY-22 GS	
Crankset	Dialed Child, adjustable 120 to 140mm, 36T, w/chainguard	Riveted chainrings
Bottom bracket	One-piece type	68 (shell x axle,mm), Square axle
Chain	KMC Z-51	3/32", 96 links
Cassette	Sun Race 14-28, 6spd	

WHEELSET

Front wheel	Alloy, nuttled hub, 32°, Aluminum alloy rim	420mm ERD
Spokes	14G, 191.5mm, 2x	
Tire	Bontrager Connection, 20 x 1.95, Rubber rim strip	
Rear wheel	Alloy, nuttled hub, 32°, Aluminum alloy rim	420mm ERD
Spokes	14g, 191/189.5mm, 2x	
Tire	Bontrager Connection, 20 x 1.95, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Steel	29.2mm outer diameter
Saddle	Dialed Child, sized	
Seatpost binder	Quick release, 47mm	31.8mm inner diameter
Brakes	Alloy direct pull w/modulator front, Alloy direct pull rear	
Pedals	Dialed Child, sized 1/2" axle	
Additional	Rear derailleur guard, double chainring guards, kickstand	

FIT *dimensions in mm, unless specified*

Frame	Size	12B	12G
Rider height, in.		57.9	57.9
	cm	147	147
Handlebar	width	540	540
Handlebar	rise	40	40
Stem	length	85	85
	angle	40	40
Headset spacers		35	35
Crank	length	140	140
Seatpost	length	300	300
Steerer	length	138	138

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0	70.0
Fork offset	37.4	37.4
Trail	49	49
Seat tube angle	72.0	72.0
Effective top tube	505	505
Seat tube	260	260
Standover	527	492
Wheelbase	944	944
Bottom bracket height	240	240
Chainstay	359	359
Head tube	100	100

GEARING

	32
14	46
16	40
18	36
21	31
24	27
28	23

Trek

Jet 20

1576000114
Bike weight: 28.6 lb/12.98 kg

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color	Black/Silver • Black/White/Blue decals	
	Red • Black/White/Silver decals	
Fork.	Hi Tensile steel, 284mm axle-crown length	
Headset	Steel	22.2/30.0/27.0, 36.5mm stack height

CONTROLS

Handlebar	Dialed Child, 22.2mm diameter	22.2mm clamp diameter
Stem	Dialed Child, adjustable rise	
Brake levers	Alloy, direct pull, right only	
Grips	Dialed Child, 24mm grip size	

DRIVETRAIN

Crankset	One-piece type, 34T	1 piecemm bolt hole circle
Bottom bracket	One-piece type	(shell x axle,mm), One-piece axle
Chain.	KMC 410	1/8", 84 links
Cassette.	19	

WHEELSET

Front wheel.	Steel hub, 36°, Aluminum alloy rim	420mm ERD
Spokes	14G, 189mm, 3x	
Tire	Cross tread, 20 x 1.95, Rubber rim strip	
Rear wheel	Shimano coaster brake hub, 36°, Aluminum alloy rim	420mm ERD
Spokes	187/187mm, 3x	
Tire	Cross tread, 20 x 1.95, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost.	Steel	29.2mm outer diameter
Saddle	Dialed Child, sized	
Seatpost binder.	Bolt, M6 x 30	35.0mm inner diameter
Brakes.	front, Coaster with direct pull rear	
Pedals	Dialed Child, sized 1/2" axle	
Additional	Kickstand, pads, moto-style fenders	

FIT *dimensions in mm, unless specified*

Frame	Size	9.5B
Rider height, in.		55.6
	cm	141
Handlebar	width	530
Handlebar	rise	150
Stem	length	50
	angle	30
Headset spacers		3
Crank	length	89
Seatpost	length	300
Steerer	length	136.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0
Fork offset	34.0
Trail	67
Seat tube angle	70.0
Effective top tube	488
Seat tube	239
Standover	460
Wheelbase	883
Bottom bracket height	254
Chainstay	372
Head tube	100

GEARING

34
19 36

Trek

Mystic 20

1576001114
Bike weight: 28.6 lb/12.98 kg

FRAMESET

Main tubes	Alpha aluminum	
Stays	Alpha aluminum	
Color	Light Metallic Blue • Blue/Blue/White/Silver decals	
	Light Metallic Purple/Metallic Purple • Purple/Purple/White/Silver decals	
	Metallic Pink • Purple/White decals	
Fork.	Hi Tensile steel, 284mm axle-crown length	
Headset	Steel	22.2/30.0/27.0, 36.5mm stack height

CONTROLS

Handlebar	Dialed Child, 22.2mm diameter	22.2mm clamp diameter
Stem	Dialed Child, adjustable rise	
Brake levers	Alloy, direct pull, right only	
Grips	Dialed Child, 24mm grip size	

DRIVETRAIN

Crankset	One-piece type, 34T	1 piecemm bolt hole circle
Bottom bracket	One-piece type	(shell x axle,mm), One-piece axle
Chain.	KMC 410	1/8", 84 links
Cassette.	20T	

WHEELSET

Front wheel.	Steel hub, 36°, Aluminum alloy rim	420mm ERD
Spokes	14G, 189mm, 3x	
Tire	Cross tread, 20 x 1.95, Rubber rim strip	
Rear wheel	Shimano coaster brake hub, 36°, Aluminum alloy rim	420mm ERD
Spokes	187/187mm, 3x	
Tire	Cross tread, 20 x 1.95, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost.	Steel	29.2mm outer diameter
Saddle	Dialed Child, sized	
Seatpost binder.	Alloy w/integral bolt	35.0mm inner diameter
Brakes	Coaster with direct pull rear	
Pedals	Dialed Child, sized 1/2" axle	
Additional	Kickstand, pads, basket and tassles	

FIT *dimensions in mm, unless specified*

Frame	Size	9.5G
Rider height, in.		55.5
	cm	141
Handlebar	width	530
Handlebar	rise	150
Stem	length	50
	angle	30
Headset spacers		
Crank	length	89
Seatpost	length	300
Steerer	length	137.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0
Fork offset	34.0
Trail	67
Seat tube angle	70.0
Effective top tube	488
Seat tube	239
Standover	410
Wheelbase	883
Bottom bracket height	254
Chainstay	372
Head tube	100

GEARING

34
20 34

Trek

Jet 16

Bike weight: 25.3 lb/11.49 kg

FRAMESET

Main tubes	Hi Tensile steel	
Stays	Hi Tensile steel	
Color	Metallic Blue • Black/White/Silver decals	
	Silver • Black/White/Red decals	
Fork.	Hi Tensile steel, 235mm axle-crown length	
Headset	Steel	22.2/30.0/27.0, 36.5mm stack height

CONTROLS

Handlebar	Dialed Child, 22.2mm diameter	22.2mm clamp diameter
Stem	2 bolt BMX, alloy top	
Grips	Dialed Child, 24mm grip size	

DRIVETRAIN

Crankset	One-piece type, 26T	1 piecemm bolt hole circle
Bottom bracket	One-piece type	68 (shell x axle,mm), One-piece axle
Chain.	KMC 410	1/8", 74 links
Cassette.	20	

WHEELSET

Front wheel.	Steel hub, 28°, Steel rim	319mm ERD
Spokes	14G, 137mm, 2x	
Tire	Cross tread, 16 x 2.125, Rubber rim strip	
Rear wheel	Coaster brake hub, 28°, Steel rim	319mm ERD
Spokes	137mm, 2x	
Tire	Cross tread, 16 x 2.125, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost.	Steel	22.2mm outer diameter
Saddle	Dialed Child, sized	
Seatpost binder. . . .	Bolt, M6 x 30	25.4mm inner diameter
Brakes	Coaster rear	
Pedals	Dialed Child, sized 1/2" axle	
Additional	Training wheels, chainguard, pads, moto-style fenders	

FIT *dimensions in mm, unless specified*

Frame	Size	9B
Rider height, in.		44.7
	cm	113
Handlebar	width	500
Handlebar	rise	130
Stem	length	50
	angle	38
Headset spacers		
Crank	length	92
Seatpost	length	225
Steerer	length	127

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0
Fork offset	34.0
Trail	36
Seat tube angle	70.0
Effective top tube	404
Seat tube	220
Standover	400
Wheelbase	741
Bottom bracket height	196
Chainstay	308
Head tube	90

GEARING

26
20 20

Trek Mystic 16

1574001114
Bike weight: 25.3 lb/11.49 kg

FRAMESET

Main tubes	Hi Tensile steel	
Stays	Hi Tensile steel	
Color	Light Metallic Purple • Pink/Purple/White decals Metallic Magenta • Pink/Purple/Blue decals Light Metallic Pink • Purple/White decals	
Fork.	Hi Tensile steel, 235mm axle-crown length	
Headset	Steel	22.2/30.0/27.0, 36.5mm stack height

CONTROLS

Handlebar	Dialed Child, 22.2mm diameter	22.2mm clamp diameter
Stem	2 bolt BMX, alloy top	
Grips	Dialed Child, 24mm grip size	

DRIVETRAIN

Crankset	One-piece type, 26T	1 piecemm bolt hole circle
Bottom bracket	One-piece type	68 (shell x axle,mm), One-piece axle
Chain.	KMC 410	1/8", 74 links
Cassette.	20T	

WHEELSET

Front wheel.	Steel hub, 28°, Steel rim	319mm ERD
Spokes	14G, 137mm, 2x	
Tire	Cross tread, 16 x 2.125, Rubber rim strip	
Rear wheel	Coaster brake hub, 28°, Steel rim	319mm ERD
Spokes	137mm, 2x	
Tire	Cross tread, 16 x 2.125, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost.	Steel	22.2mm outer diameter
Saddle	Dialed Child, sized	
Seatpost binder. . . .	Bolt, M6 x 30	25.4mm inner diameter
Brakes.	Coaster rear	
Pedals	Dialed Child, sized 1/2" axle	
Additional	Training wheels, chainguard, pads, basket and tassles	

FIT *dimensions in mm, unless specified*

Frame	Size	9G
Rider height, in.		44.7
	cm	113
Handlebar	width	500
Handlebar	rise	130
Stem	length	50
	angle	38
Headset spacers		
Crank	length	92
Seatpost	length	225
Steerer	length	127

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0
Fork offset	34.0
Trail	36
Seat tube angle	70.0
Effective top tube	404
Seat tube	220
Standover	356
Wheelbase	741
Bottom bracket height	196
Chainstay	308
Head tube	90

GEARING

26
20 20

FRAMESET

Main tubes	Hi Tensile steel	
Stays	Hi Tensile steel	
Color	Metallic Red • Black/White/Silver decals	
Fork	Hi Tensile steel, 185mm axle-crown length	
Headset	Steel	22.2/30.0/27.0, 36.5mm stack height

CONTROLS

Handlebar	Dialed Child, 22.2mm diameter	22.2mm clamp diameter
Stem	2 bolt BMX	
Grips	Dialed Child, 24mm grip size	

DRIVETRAIN

Crankset	One-piece type, 24T	1 piecemm bolt hole circle
Bottom bracket	One-piece type, 24tpi	(shell x axle,mm), One-piece axle
Chain	KMC 410	1/8", 58 links
Cassette	20	

WHEELSET

Front wheel	Steel hub, 20°, Steel rim	218mm ERD
Spokes	14G, 83mm, 2x	
Tire	Cross tread, 12.5 x 2.125, Rubber rim strip	
Rear wheel	Coaster brake hub, 20°, Steel rim	218mm ERD
Spokes	83mm, 2x	
Tire	Cross tread, 12.5 x 2.125, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Steel (one piece post and saddle)	22.2mm outer diameter
Saddle	Dialed Child, sized	
Seatpost binder	Bolt, M6 x 30	25.4mm inner diameter
Brakes	Coaster brake rear	
Pedals	Platform 1/2" axle	
Additional	Training wheels, chainguard, pads, and moto-style fenders	

FIT *dimensions in mm, unless specified*

Frame	Size	8
Rider height, in.		35.7
	cm	91
Handlebar	width	460
Handlebar	rise	120
Stem	length	50
	angle	38
Headset spacers		
Crank	length	70
Seatpost	length	250
Steerer	length	125

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0
Fork offset	34.0
Trail	19
Seat tube angle	69.5
Effective top tube	336
Seat tube	200
Standover	356
Wheelbase	605
Bottom bracket height	146
Chainstay	235
Head tube	90

GEARING

24
20 14

Trek Mystic 12

1572001114
Bike weight: 20.9 lb/9.49 kg

FRAMESET

Main tubes	Hi Tensile steel	
Stays	Hi Tensile steel	
Color	Metallic White • Pink/Purple/Silver decals	
	Light Metallic Pink • Purple/White decals	
Fork	Hi Tensile steel, 185mm axle-crown length	
Headset	Steel	22.2/30.0/27.0, 36.5mm stack height

CONTROLS

Handlebar	Dialed Child, 22.2mm diameter	22.2mm clamp diameter
Stem	2 bolt BMX	
Grips	Dialed Child, 24mm grip size	

DRIVETRAIN

Crankset	One-piece type, 24T	1 piecemm bolt hole circle
Bottom bracket	One-piece type	(shell x axle,mm), One-piece axle
Chain	KMC 410	1/8", 58 links
Cassette	20T	

WHEELSET

Front wheel	Steel hub, 20°, Steel rim	218mm ERD
Spokes	14G, 83mm, 2x	
Tire	Cross tread, 12.5 x 2.125, Rubber rim strip	
Rear wheel	Coaster brake hub, 20°, Steel rim	218mm ERD
Spokes, 83mm, 2x		
Tire	Cross tread, 12.5 x 2.125, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Steel (one piece post and saddle)	22.2mm outer diameter
Saddle	Dialed Child, sized	
Seatpost binder	Bolt, M6 x 30	25.4mm inner diameter
Brakes	Coaster brake rear	
Pedals	Dialed Child, sized 1/2" axle	
Additional	Training wheels, chainguard, pads, basket and tassles	

FIT *dimensions in mm, unless specified*

Frame	Size	8G
Rider height, in.		35.7
	cm	91
Handlebar	width	460
Handlebar	rise	120
Stem	length	50
	angle	38
Headset spacers		
Crank	length	70
Seatpost	length	225
Steerer	length	125

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0
Fork offset	34.0
Trail	19
Seat tube angle	69.5
Effective top tube	336
Seat tube	200
Standover	302
Wheelbase	605
Bottom bracket height	146
Chainstay	235
Head tube	90

GEARING

24
20 14

Trek Grommet 12

1570000114
Bike weight: 20.9 lb/9.49 kg

FRAMESET

Main tubes	Hi Tensile steel	
Stays	Hi Tensile steel	
Color	Metallic Red/Silver	
Fork	Hi Tensile steel, 185mm axle-crown length	
Headset	Steel	22.2/30.0/27.0, 36.5mm stack height

CONTROLS

Handlebar	Dialed Child, 15.8mm diameter	22.2mm clamp diameter
Stem	integrated with handlebar	
Grips	Dialed Child, 24mm grip size	

DRIVETRAIN

Crankset	One-piece type, 28T	1 piecemm bolt hole circle
Bottom bracket	One-piece type, 24tpi	68 (shell x axle,mm), axle
Chain	KMC 410	1/8", 60 links
Cassette	19T	

WHEELSET

Front wheel	Steel hub, 20°, Steel rim	218mm ERD
Spokes	14G, 83mm, 2x	
Tire	Cruiser Balloon, 12.5 x 2.125, Rubber rim strip	
Rear wheel	Coaster brake hub, 20°, Steel rim	218mm ERD
Spokes	83mm, 2x	
Tire	Cruiser Balloon, 12.5 x 2.125, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Steel (one piece post and saddle)	25.4mm outer diameter
Saddle	Dialed Child, sized	
Seatpost binder	Bolt, M6 x 30	28.6mm inner diameter
Brakes	Coaster brake rear	
Pedals	Dialed Child, sized 1/2" axle	
Additional	Training wheels, chainguard, beach cruiser fenders	

FIT *dimensions in mm, unless specified*

Frame	Size	8B
Rider height, in.		32.6
	cm	83
Handlebar	width	470
Handlebar	rise	80
Stem	length	50
	angle	48
Headset spacers		20
Crank	length	70
Seatpost	length	225
Steerer	length	124

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0
Fork offset	9.0
Trail	44
Seat tube angle	73.3
Effective top tube	318
Seat tube	223
Standover	372
Wheelbase	585
Bottom bracket height	161
Chainstay	235
Head tube	90

GEARING

28
19 17

Trek

Surfer Girl 12

1570001114
Bike weight: 20.9 lb/9.49 kg

FRAMESET

Main tubes	Hi Tensile steel	
Stays	Hi Tensile steel	
Color	Purple/Silver • Purple/White/Silver decals	
Fork	Hi Tensile steel, 185.0mm axle-crown length	
Headset	Steel	22.2/30.0/27.0, 36.5mm stack height

CONTROLS

Handlebar	Dialed Child, 15.8mm diameter	mm clamp diameter
Stem	integrated with handlebar	
Grips	Dialed Child, 24mm grip size	

DRIVETRAIN

Crankset	One-piece type, 28T	1 piecemm bolt hole circle
Bottom bracket	One-piece type	68 (shell x axle,mm), axle
Chain	KMC 410	1/8", 60 links
Cassette	19T	

WHEELSET

Front wheel	Steel hub, 20°, Steel rim	218mm ERD
Spokes	14G, 83mm, 2x	
Tire	Cruiser Balloon, 12.5 x 2.125, Rubber rim strip	
Rear wheel	Coaster brake hub, 20°, Steel rim	218mm ERD
Spokes	83mm, 2x	
Tire	Cruiser Balloon, 12.5 x 2.125, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Steel (one piece post and saddle)	25.4mm outer diameter
Saddle	Dialed Child, sized	
Seatpost binder	Bolt, M6 x 30	28.6mm inner diameter
Brakes	Coaster brake rear	
Pedals	Dialed Child, sized 1/2" axle	
Additional	Training wheels, chainguard, beach cruiser fenders	

FIT *dimensions in mm, unless specified*

Frame	Size	8G
Rider height, in.		32.8
	cm	83
Handlebar	width	470
Handlebar	rise	80
Stem	length	50
	angle	48
Headset spacers		
Crank	length	70
Seatpost	length	225
Steerer	length	124

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	70.0
Fork offset	9.0
Trail	44
Seat tube angle	73.3
Effective top tube	318
Seat tube	223
Standover	295
Wheelbase	585
Bottom bracket height	161
Chainstay	235
Head tube	90

GEARING

28
19 17

Trek TR30

1516000114
Bike weight: 25.6 lb/11.62 kg

FRAMESET

Main tubes	Cro-Moly top tube and down tube	
Stays	Hi Tensile steel	
Color	Black Chrome • Black/Tan/Cream decals • Black Chrome fork	
Fork	Trek Dirt Cro-Moly, 1 3/8", 282.0mm axle-crown length	
Headset	Aheadset	25.4/34.0/30.0, 28.0mm stack height

CONTROLS

Handlebar	Trek	22.2mm clamp diameter
Stem	Trek BMX, direct connect	51.0mm steerer clamp height
Brake levers	Alloy 2 finger, right only	
Grips	Bontrager, dual density	

DRIVETRAIN

Crankset	DK-A2B tubular Cro-Moly, 44T	mm bolt hole circle
Bottom bracket	DK-A2B sealed Cro-Moly	68 (shell x axle,mm), Square axle
Chain	KMC Z-410	1/8", 90 links
Cassette	16T	

WHEELSET

Front wheel	Trek, alloy hub, 48°, Aluminum alloy rim	420mm ERD
Spokes	14G, 179.5mm, 2x	
Tire	Knobby, 20 x 2.125, Rubber rim strip	
Rear wheel	Trek, alloy hub, 48°, Aluminum alloy rim	420mm ERD
Spokes	14g, 179mm, 2x	
Tire	Knobby, 20 x 2.125, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Steel	25.4mm outer diameter
Saddle	Trek BMX	
Seatpost binder	Alloy w/integral bolt	28.6mm inner diameter
Brakes	front, U-Brake rear	
Pedals	Alloy, Cro-Moly spindles 1/2" axle	
Additional	chain tensioners	

FIT *dimensions in mm, unless specified*

Frame	Size	Pro
Rider height, in.		55.8
	cm	142
Handlebar	width	680
Handlebar	rise	190
Stem	length	25
	angle	0
Headset spacers		15
Crank	length	170
Seatpost	length	300
Steerer	length	190.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	74.5
Fork offset	33.0
Trail	37
Seat tube angle	71.5
Effective top tube	558
Seat tube	284
Standover	578
Wheelbase	956
Bottom bracket height	296
Chainstay	378
Head tube	104

GEARING

44
16 55

Trek TR20

1
Bike weight: 25.9 lb/11.76 kg

FRAMESET

Main tubes	Cro-Moly top tube and down tube	
Stays	Hi Tensile steel	
Color	Matte Black • Dark Gray/Mid Gray/Light Gray decals • Matte Black fork	
Fork	Trek Dirt, 1 3/8" Cro-Moly blades, 282.0mm axle-crown length	
Headset	Aheadset	25.4/34.0/30.0, 23.0mm stack height

CONTROLS

Handlebar	Trek	22.2mm clamp diameter
Stem	Trek BMX, direct connect	51.0mm steerer clamp height
Brake levers	Alloy 2 finger, right only	
Grips	Bontrager, dual density	

DRIVETRAIN

Crankset	Trek 3-piece forged steel, 44T	1 piecemm bolt hole circle
Bottom bracket	One-piece type	68 (shell x axle,mm), Square axle
Chain	KMC Z-410	1/8", 90 links
Cassette	16T	

WHEELSET

Front wheel	Trek, alloy hub, 48°, Aluminum alloy rim	420mm ERD
Spokes	14G, 179.5mm, 2x	
Tire	Knobby, 20 x 2.125, Rubber rim strip	
Rear wheel	Trek, alloy hub, 48°, Aluminum alloy rim	420mm ERD
Spokes	14g, 178.5mm, 2x	
Tire	Knobby, 20 x 2.125, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Steel	25.4mm outer diameter
Saddle	Trek BMX	
Seatpost binder	Alloy w/integral bolt	28.6mm inner diameter
Brakes	front, U-Brake rear	
Pedals	Alloy, Cro-Moly spindles 1/2" axle	
Additional	chain tensioners	

FIT *dimensions in mm, unless specified*

Frame	Size	Pro
Rider height, in.		55.5
	cm	141
Handlebar	width	680
Handlebar	rise	190
Stem	length	25
	angle	0
Headset spacers		15
Crank	length	170
Seatpost	length	300
Steerer	length	185.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	74.5
Fork offset	33.0
Trail	37
Seat tube angle	71.5
Effective top tube	558
Seat tube	284
Standover	578
Wheelbase	956
Bottom bracket height	296
Chainstay	378
Head tube	104

GEARING

44
16 55

Trek TR10

1512000114
Bike weight: 26.1 lb/11.85 kg

FRAMESET

Main tubes	High tensile steel	
Stays	Hi Tensile steel	
Color	Bluegray • Black/Dark Gray/Light Gray decals • Sky Blue fork	
Fork	Trek Dirt, 1 3/8", 282.0mm axle-crown length	
Headset	Aheadset	25.4/34.0/30.0, 23.0mm stack height

CONTROLS

Handlebar	Trek	22.2mm clamp diameter
Stem	Trek BMX	51.0mm steerer clamp height
Brake levers	Alloy 2 finger	
Grips	Bontrager, dual density	

DRIVETRAIN

Crankset	One-piece type, 44T	mm bolt hole circle
Bottom bracket	One-piece type	68 (shell x axle,mm), Square axle
Chain	KMC Z-410	1/8", 90 links
Cassette	16T	

WHEELSET

Front wheel	Steel hub, 48°, Aluminum alloy rim	420mm ERD
Spokes	14G, 179mm, 2x	
Tire	Knobby, 20 x 2.125, Rubber rim strip	
Rear wheel	Steel hub, 48°, Aluminum alloy rim	420mm ERD
Spokes	14g, 189mm, 2x	
Tire	Knobby, 20 x 2.125, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Steel	25.4mm outer diameter
Saddle	Trek BMX	
Seatpost binder	Alloy w/integral bolt	28.6mm inner diameter
Brakes	BMX, caliper type front, U-Brake rear	
Pedals	Platform	1/2" axle
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	Expert
Rider height, in.		50.6
	cm	128
Handlebar	width	610
Handlebar	rise	140
Stem	length	25
	angle	0
Headset spacers		15
Crank	length	170
Seatpost	length	300
Steerer	length	185.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	74.5
Fork offset	33.0
Trail	37
Seat tube angle	71.5
Effective top tube	496
Seat tube	284
Standover	578
Wheelbase	896
Bottom bracket height	296
Chainstay	378
Head tube	104

GEARING

44
16 55

FRAMESET

Main tubes	High tensile steel	
Stays	Hi Tensile steel	
Color	Blood Red • Black/Tan/Cream decals • Blood Red fork	
	Silver • Black/Blue/Light Blue decals • Silver fork	
Fork	Trek Dirt, 1 3/8", 282.0mm axle-crown length	
Headset	Aheadset	25.4/34.0/30.0, 23.0mm stack height

CONTROLS

Handlebar	Trek	22.2mm clamp diameter
Stem	Trek BMX	50.0mm steerer clamp height
Brake levers	Alloy, right only	
Grips	Bontrager, dual density	

DRIVETRAIN

Crankset	One-piece type, 44T	mm bolt hole circle
Bottom bracket	One-piece type	68 (shell x axle,mm), Square axle
Chain	KMC Z-410	1/8", 90 links
Cassette	16T	

WHEELSET

Front wheel	Alloy, nudded hub, 36°, Aluminum alloy rim	420mm ERD
Spokes	14G, 189mm, 2x	
Tire	Knobby, 20 x 1.95, Rubber rim strip	
Rear wheel	Steel hub, 36°, Aluminum alloy rim	420mm ERD
Spokes	14g, 189mm, 2x	
Tire	Knobby, 20 x 1.95, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Steel	25.4mm outer diameter
Saddle	Trek dirt jumper	
Seatpost binder	Alloy w/integral bolt	28.6mm inner diameter
Brakes	front, U-Brake and coaster brake rear	
Pedals	Platform 1/2" axle	
Additional		

FIT *dimensions in mm, unless specified*

Frame	Size	Expert
Rider height, in.		50.6
	cm	128
Handlebar	width	610
Handlebar	rise	140
Stem	length	25
	angle	0
Headset spacers		15
Crank	length	170
Seatpost	length	300
Steerer	length	185.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	74.5
Fork offset	33.0
Trail	37
Seat tube angle	71.5
Effective top tube	496
Seat tube	284
Standover	578
Wheelbase	896
Bottom bracket height	296
Chainstay	378
Head tube	104

GEARING

	42
16	53

Trek Vert 2

1544000114
Bike weight: 26.4 lb/11.99 kg

FRAMESET

Main tubes	Cro-Moly top tube and down tube	
Stays	Hi Tensile steel	
Color	Black Chrome • Black/Tan/Cream decals • Black Chrome fork	
Fork	Cro-Moly 1 3/8" , 282.0mm axle-crown length	
Headset	Steel	25.4/34.0/30.0, 23.0mm stack height

CONTROLS

Handlebar	Trek Freestyle	22.2mm clamp diameter
Stem	Trek BMX, direct connect	51.0mm steerer clamp height
Brake levers	Alloy 2 finger	
Grips	Bontrager dual density	

DRIVETRAIN

Crankset	DK-A2B tubular Cro-Moly, 44T	mm bolt hole circle
Bottom bracket	DK-A2B sealed Cro-Moly	68 (shell x axle,mm), Square axle
Chain	KMC Z-410	1/8", 90 links
Cassette	16T	

WHEELSET

Front wheel	Trek, alloy hub, 48°, Aluminum alloy rim	420mm ERD
Spokes	14G, 179.5mm, 2x	
Tire	Freestyle, 20 x 2.125, Rubber rim strip	
Rear wheel	Trek, alloy hub, 48°, Aluminum alloy rim	420mm ERD
Spokes	14g, 179mm, 2x	
Tire	Freestyle, 20 x 2.125, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Steel	25.4mm outer diameter
Saddle	Trek Freestyle	
Seatpost binder	Alloy w/integral bolt	28.6mm inner diameter
Brakes	U-Brake front, U-Brake rear	
Pedals	Alloy, Cro-Moly spindles 9/16" axle	
Additional	chain tensioners	

FIT *dimensions in mm, unless specified*

Frame	Size	All-around
Rider height, in.		55.4
	cm	141
Handlebar	width	680
Handlebar	rise	190
Stem	length	25
	angle	0
Headset spacers		15
Crank	length	175
Seatpost	length	300
Steerer	length	185.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	75.0
Fork offset	33.0
Trail	35
Seat tube angle	73.5
Effective top tube	538
Seat tube	284
Standover	
Wheelbase	932
Bottom bracket height	296
Chainstay	368
Head tube	104

GEARING

44
16 55

FRAMESET

Main tubes	Hi Tensile steel	
Stays	Hi Tensile steel	
Color	Blood Red • Black/Tan/Cream decals • Blood Red fork Bluegray • Black/Gray/Light Gray decals • Bluegray fork	
Fork	1 3/8" Trek Street, 282.0mm axle-crown length	
Headset	Aheadset	25.4/34.0/30.0, 23.0mm stack height

CONTROLS

Handlebar	BMX	22.2mm clamp diameter
Stem	Trek BMX, direct connect	51.0mm steerer clamp height
Brake levers	Alloy 2 finger	
Grips	Bontrager dual density	

DRIVETRAIN

Crankset	Three-piece, 44T	1 piecemm bolt hole circle
Bottom bracket	One-piece type	68 (shell x axle,mm), Square axle
Chain	KMC Z-410	1/8", 88 links
Cassette	16T	

WHEELSET

Front wheel	Steel hub, 48°, Aluminum alloy rim	420mm ERD
Spokes	14G, 179.5mm, 2x	
Tire	Freestyle, 20 x 2.125, Rubber rim strip	
Rear wheel	Steel hub, 48°, Aluminum alloy rim	420mm ERD
Spokes	14g, 179mm, 2x	
Tire	Freestyle, 20 x 2.125, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Steel	25.4mm outer diameter
Saddle	Trek Freestyle	
Seatpost binder	Alloy w/integral bolt	28.6mm inner diameter
Brakes	U-Brake front, U-Brake rear	
Pedals	Alloy, Cro-Moly spindles 9/16" axle	
Additional	chain tensioners	

FIT *dimensions in mm, unless specified*

Frame	Size	All-around
Rider height, in.		55.4
	cm	141
Handlebar	width	680
Handlebar	rise	190
Stem	length	25
	angle	0
Headset spacers		15
Crank	length	175
Seatpost	length	300
Steerer	length	185.5

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	75.0
Fork offset	33.0
Trail	35
Seat tube angle	73.5
Effective top tube	538
Seat tube	284
Standover	
Wheelbase	932
Bottom bracket height	296
Chainstay	368
Head tube	104

GEARING

44
16 55

Trek Mt. Train 241

FRAMESET

Main tubes Hi Tensile steel
 Stays Hi Tensile steel
 Color Silver/Blue • Black/White/Silver decals

CONTROLS

Handlebar BMX 25.4mm clamp diameter
 Stem Alloy adjustable rise, quick change, quill
 Grips Kraton

DRIVETRAIN

Crankset One-piece type, 42T mm bolt hole circle
 Bottom bracket One-piece type 68 (shell x axle,mm), axle
 Chain KMC Z-51 1/8", 88 links
 Cassette 16T

WHEELSET

Rear wheel Alloy, nitted hub, 36°, Aluminum alloy rim 524mm ERD
 Spokes 14g, 188.5mm, 2x
 Tire Cross tread, 20 x 1.75, Rubber rim strip
 Inner tubes Schraeder valve

OTHER

Seatpost Suspension 25.4mm outer diameter
 Saddle Trek padded
 Seatpost binder . . . Alloy w/integral bolt 28.6mm inner diameter
 Brakes none
 Pedals Platform 1/2" axle
 Additional Handlebar pad, visibility flag

FIT *dimensions in mm, unless specified*

Frame	Size	
Rider height, in.		0.0
	cm	0
Handlebar	width	530
Handlebar	rise	150
Stem	length	85
	angle	5
Headset spacers		
Crank	length	127
Seatpost	length	300
Steerer	length	

GEOMETRY *dimensions in mm, unless specified*

Head tube angle
 Fork offset
 Trail
 Seat tube angle
 Effective top tube
 Seat tube 286
 Standover
 Wheelbase
 Bottom bracket height
 Chainstay
 Head tube

GEARING

42
16 62

Trek Mt. Train 206

FRAMESET

Main tubes Hi Tensile steel
 Stays Hi Tensile steel
 Color Silver/Red • Black/White/Silver decals
 Silver/Pewter • Blue/Silver/White decals

CONTROLS

Handlebar BMX 25.4mm clamp diameter
 Stem Alloy adjustable rise, quick change, quill
 Shift levers SRAM MRX
 Grips Kraton

DRIVETRAIN

Rear derailleur Shimano Tourney TY-22
 Crankset One-piece type, 42T mm bolt hole circle
 Bottom bracket One-piece type 68 (shell x axle,mm), Square axle
 Chain 3/32", 104 links
 Cassette Sun Race 14-28, 6spd

WHEELSET

Rear wheel Alloy, nuttled hub, 36°, Aluminum alloy rim 420mm ERD
 Spokes 14g, 188.5/191mm, 2x
 Tire Cross tread, 20 x 1.75, Rubber rim strip
 Inner tubes Schraeder valve

OTHER

Seatpost Steel 25.4mm outer diameter
 Saddle Trek padded
 Seatpost binder Alloy w/integral bolt 28.6mm inner diameter
 Brakes none
 Pedals Platform 1/2" axle
 Additional Handlebar pad, visibility flag

FIT *dimensions in mm, unless specified*

Frame	Size	12
Rider height, in.		0.0
	cm	0
Handlebar	width	550
Handlebar	rise	150
Stem	length	85
	angle	5
Headset spacers		
Crank	length	127
Seatpost	length	300
Steerer	length	

GEOMETRY *dimensions in mm, unless specified*

Head tube angle
 Fork offset
 Trail
 Seat tube angle
 Effective top tube
 Seat tube 266
 Standover
 Wheelbase
 Bottom bracket height
 Chainstay
 Head tube

GEARING

	42
14	60
16	53
18	47
21	40
24	35
28	30

Trek

Mt. Train 201

FRAMESET

Main tubes	Hi Tensile steel
Stays	Hi Tensile steel
Color	Silver/Blue • Black/White/Silver decals Silver/Yellow • Blue/Black/White decals Silver/Black • Red/White/Silver decals

CONTROLS

Handlebar	BMX	25.4mm clamp diameter
Stem	Alloy adjustable rise, quick change, quill	
Grips	Kraton	

DRIVETRAIN

Crankset	One-piece type, 42T	mm bolt hole circle
Bottom bracket	One-piece type	68 (shell x axle,mm), Square axle
Chain	KMC Z-51	1/8", 88 links
Cassette	16T	

WHEELSET

Rear wheel	Alloy, nitted hub, 36°, Aluminum alloy rim	420mm ERD
Spokes	14g, 188.5/188.5mm, 2x	
Tire	Cross tread, 20 x 1.75, Rubber rim strip	
Inner tubes	Schraeder valve	

OTHER

Seatpost	Steel	25.4mm outer diameter
Saddle	Trek padded	
Seatpost binder	Alloy w/integral bolt	28.6mm inner diameter
Brakes	none	
Pedals	Platform	1/2" axle
Additional	Handlebar pad, visibility flag	

FIT *dimensions in mm, unless specified*

Frame	Size	10.5
Rider height, in.		0.0
	cm	0
Handlebar	width	530
Handlebar	rise	150
Stem	length	85
	angle	5
Headset spacers		
Crank	length	127
Seatpost	length	300
Steerer	length	

GEOMETRY *dimensions in mm, unless specified*

Head tube angle	
Fork offset	
Trail	?
Seat tube angle	
Effective top tube	
Seat tube	266
Standover	
Wheelbase	
Bottom bracket height	
Chainstay	
Head tube	

GEARING

	42
16	53

Trek Trikester

FRAMESET

Main tubes	Steel	
Stays	Steel	
Color	Pearl White/Candy Blue	
	Pearl White/Metallic Pink	
Fork.	Steel, mm axle-crown length	
Headset		22.2/30.0/27.0, mm stack height

CONTROLS

Handlebar	Steel	25.4mm clamp diameter
Stem		
Grips	Dialed Child, 24mm grip size	

WHEELSET

Front wheel.	
Tire, 4.1/3.5-4, Rubber rim strip	
Rear wheel	
Tire, 3.00-8, rim strip	
Inner tubes	Schraeder valve

OTHER

Seatpost.		mm outer diameter
Saddle		
Seatpost binder. . . .		mm inner diameter
Brakes	none	
Pedals	Platform	9/16" axle
Additional	Stem pad	

FIT *dimensions in mm, unless specified*

Frame	Size	
Rider height, in.	0.0	
	cm	0
Handlebar	width	500
Handlebar	rise	65
Stem	length	34
	angle	135
Headset spacers		
Crank	length	102
Seatpost	length	
Steerer	length	

GEOMETRY *dimensions in mm, unless specified*

Head tube angle
Fork offset
Trail
Seat tube angle
Effective top tube
Seat tube
Standover
Wheelbase
Bottom bracket height
Chainstay
Head tube

GEARING